



PRODUCT DATA SHEET

AGRICULTURAL GEAR OIL – TECHNOFLUID ROTAVATOR OIL (SAE 140)

Commercial name : TECHNOFLUID ROTAVATOR GEAR 140

Product Description

- TECHNOFLUID Rotavator Oil is a heavy-duty gear oil specially formulated for rotavators and agricultural implements operating under severe load and shock conditions.
- Manufactured from high-quality base oils and selected extreme pressure (EP) additives to ensure superior protection of gears and bearings.
- Designed to withstand high torque, heavy loads, and continuous field operations.
- Provides excellent lubrication and film strength, ensuring smooth and reliable performance of rotavator gearboxes.
- Suitable for agricultural equipment working in dusty, humid, and high-temperature environments.

Key Performance Benefits

- Excellent extreme pressure properties protect gears against wear, scuffing, and pitting.
- High load-carrying capacity ensures durability of gears under heavy field conditions.
- Strong oil film prevents metal-to-metal contact, extending gearbox life.
- Superior thermal and oxidation stability minimizes oil degradation during prolonged use.
- Effective rust and corrosion protection safeguards internal components during idle periods.
- Reduces noise and vibration, ensuring smoother gearbox operation.
- Helps lower maintenance costs and increase service intervals.

Applications Recommended for use in:

- Rotavator gearboxes
- Power tillers and agricultural gear systems
- Farm implements operating under heavy loads

- Suitable for equipment where **SAE 140** grade gear oil is recommended by the OEM.

Typical Uses

- Agricultural machinery operating under high shock loads and slow to moderate speeds.
- Equipment requiring reliable lubrication in extreme pressure conditions.
- Continuous and seasonal agricultural operations.

Performance Standards

Meets or exceeds requirements for:

- SAE 140 Gear Oil
- IS 1118 (EP Type) (*where applicable*)

Operating Characteristics

- Maintains stable viscosity at high operating temperatures.
- Non-corrosive to common gear metals and compatible with standard seals.
- Ensures dependable performance throughout long working hours in the field.

Typical Characteristics

Characteristics	Test Method	Typical Figures (SAE 140)
Appearance	Visual	Clear & Bright
Colour	ASTM D1500	≤ 3.0
Base Oil Type	—	Mineral
SAE Grade	SAE J306	140
Density @ 15°C, g/ml	ASTM D4052	0.899
Kinematic Viscosity @ 100°C, cSt	ASTM D445	25.0 – 30.0
Kinematic Viscosity @ 40°C, cSt	ASTM D445	400 – 460
Viscosity Index	ASTM D2270	≥ 95
Flash Point (COC), °C	ASTM D92	≥ 230
Pour Point, °C	ASTM D97	-6

Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1b
Rust Prevention	ASTM D665	Pass
Load Carrying / EP Properties	ASTM D2596	Good
Foaming Characteristics	ASTM D892	Pass
Oxidation Stability	ASTM D943	Excellent