



PRODUCT DATA SHEET

CHAIN LUBRICANT – TECHNOFLUID CHAIN OIL

Commercial / Pack Name: CHAIN OIL HT

Product Description

- TECHNOFLUID Chain Oil is a high-performance lubricant specially formulated for lubrication of chains operating under high temperature, heavy load, and continuous service conditions.
- Manufactured from high-quality base oils and advanced additives to provide excellent lubricity, adhesion, and thermal stability.
- Designed to form a strong, tacky lubricating film that resists fling-off and ensures continuous lubrication.
- Provides effective protection against wear, rust, and corrosion, even in demanding operating environments.
- Suitable for both industrial and automotive chain lubrication applications.

Key Performance Benefits

- Excellent adhesion properties ensure the oil stays on chains during high-speed and high-temperature operation.
- Superior thermal and oxidation stability minimizes oil breakdown and residue formation.
- Reduces chain wear, elongation, and friction, extending chain service life.
- Provides effective rust and corrosion protection in humid and wet environments.
- Low evaporation loss helps maintain consistent lubrication over extended periods.
- Minimizes maintenance requirements and downtime.

Applications

- Recommended for lubrication of:
 - Conveyor chains
 - Drive and transmission chains
 - Stenter frames in textile industries
 - Oven and dryer chains
 - Industrial chain drives operating at elevated temperatures
- Suitable for use in textile, food processing (non-food contact), paper, plywood, ceramics, and packaging industries.

Typical Uses

- Chains operating under high temperature and continuous duty cycles.
- Applications requiring strong oil adhesion and minimal fling-off.
- Systems where clean operation and long lubricant life are critical.

Operating Characteristics

- Maintains stable viscosity over a wide operating temperature range.
- Provides consistent lubrication under slow, medium, and high-speed chain operations.
- Compatible with commonly used chain materials and system components.

Typical Specifications

Characteristics	Test Method	Typical Figures
Appearance	Visual	Clear & Bright
Colour	ASTM D1500	≤ 3.0
Base Oil Type	—	Mineral
Additive Type	—	Anti-wear, oxidation inhibitor, tackifier
Density @ 15°C, g/ml	ASTM D4052	0.870
Kinematic Viscosity @ 40°C, cSt	ASTM D445	150 – 220
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14 – 18
Viscosity Index	ASTM D2270	≥ 95
Flash Point (COC), °C	ASTM D92	≥ 230
Pour Point, °C	ASTM D97	-6
Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1a
Oxidation Stability	ASTM D943	Excellent