



PRODUCT DATA SHEET

HYDRAULIC OIL – TECHNOFLUID HYDRAULIC OIL AW (ISO VG 32, 46,68,100,150,220,320 & 460)

Commercial / Pack Name: HYDRAULIC OIL 32 AW

Product Description

- TECHNOFLUID Hydraulic Oil AW is a premium anti-wear hydraulic fluid formulated from high-quality, chemically stable base oils and a balanced additive system.
- Contains anti-wear, anti-oxidant, anti-rust, and anti-foam additives to ensure reliable performance in modern hydraulic systems.
- Designed to provide excellent lubrication and protection to hydraulic pumps, valves, and actuators operating under high pressure and temperature conditions.
- Maintains stable viscosity and film strength over extended service periods.
- Suitable for use in both industrial and mobile hydraulic systems.

Key Performance Benefits

- Excellent anti-wear protection reduces pump and component wear, extending system life.
- Superior oxidation resistance minimizes sludge, varnish, and deposit formation.
- Effective rust and corrosion protection for ferrous and non-ferrous metals.
- Good demulsibility allows rapid separation of water, maintaining system efficiency.
- Low foaming tendency and quick air release ensure smooth, responsive hydraulic operation.
- Helps reduce downtime, maintenance costs, and oil consumption.

Applications

Recommended for high-pressure hydraulic systems operating under moderate to severe conditions.

Suitable for use in:

- Industrial hydraulic presses and machine tools
- Injection molding and plastic processing machines
- Construction and earth-moving equipment
- Material handling systems and forklifts
- Agricultural and mining machinery
- Compatible with vane, piston, and gear type hydraulic pumps.

Typical Uses

- Systems requiring ISO VG 32, 46, 68, 100, 150, 220, 320 & 460 anti-wear hydraulic oils.
- Equipment operating in continuous or intermittent high-load conditions.
- Applications demanding long oil life and consistent hydraulic performance.

Performance Standards Meets or exceeds:

- IS 10522 : 1983 (Reaffirmed)
- Vickers V-104C / Denison HF-0 / HF-1 / HF-2

Operating Characteristics

- Maintains excellent viscosity stability over a wide temperature range.
- Compatible with commonly used hydraulic system seals and elastomers.
- Ensures clean and efficient operation of hydraulic systems.

Typical Characteristics

[illegible]

[illegible]