



PRODUCT DATA SHEET

LUBRICATING OILS – TECHNOFLUID LUBE SERIES

(LUBE 20W-40, ISO VG 100, 150, 220, 320 & 460)

Commercial / Pack Name: LUBE 20W-40 / 100 / 150 / 220 / 320 / 460

Product Description

- TECHNOFLUID LUBE Series lubricating oils are premium-quality general-purpose lubricants formulated from carefully selected high-quality base oils and performance-enhancing additives.
- Designed to provide reliable lubrication, wear protection, and smooth operation across a wide range of industrial and automotive applications.
- Offer excellent lubricity, thermal stability, and oxidation resistance, ensuring long service life and dependable performance.
- Suitable for applications requiring multigrade as well as monograde lubricating oils.
- Available in multiple viscosity grades to meet diverse equipment and operating requirements.

Key Performance Benefits

- Excellent lubricating film strength reduces wear and friction of moving parts.
- Good oxidation and thermal stability minimize sludge and deposit formation.
- Effective rust and corrosion protection for ferrous and non-ferrous components.
- Stable viscosity ensures consistent performance under varying operating conditions.
- Low foaming tendency ensures uninterrupted lubrication.
- Helps extend equipment life and reduce maintenance costs.

Applications

Recommended for lubrication of:

- Industrial machinery and equipment
- Bearings, slides, and guides
- Gearboxes and circulating oil systems (where EP properties are not required)
- Compressors and pumps (as per OEM recommendation)

LUBE 20W-40 is suitable for general automotive and agricultural lubrication requirements.

ISO VG 100, 150, 220, 320 & 460 grades are suitable for industrial lubrication and circulating systems.

Typical Uses

- General-purpose lubrication in industrial plants.
- Equipment operating under moderate load and temperature conditions.
- Applications requiring reliable, economical lubrication solutions.

Operating Characteristics

- Maintains stable viscosity over prolonged operating periods.
- Compatible with commonly used seals, gaskets, and materials.
- Performs reliably in splash, circulation, and manual lubrication systems.

Typical Characteristics

Characteristics	Test Method	LUBE 20W-40	LUBE 100	LUBE 150	LUBE 220	LUBE 320	LUBE 460
Appearance	Visual	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright
Colour	ASTM D1500	Red	≤ 3.0	≤ 3.0	≤ 3.0	≤ 3.0	≤ 3.0
Base Oil Type	—	Mineral	Mineral	Mineral	Mineral	Mineral	Mineral
Density @ 29.5°C, g/ml	ASTM D4052	0.855	0.850	0.850	0.850	0.850	0.850
Kinematic Viscosity @ 40°C, cSt	ASTM D445	130 – 150	100	150	220	320	460
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14 – 16	11.0	14.5	19.0	24.5	30.5
Viscosity Index	ASTM D2270	≥ 95	≥ 95	≥ 95	≥ 95	≥ 95	≥ 95
Flash Point (COC), °C	ASTM D92	≥ 210	≥ 210	≥ 210	≥ 210	≥ 210	≥ 210
Pour Point, °C	ASTM D97	-6	-6	-6	-6	-6	-6

Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1b	1b	1b	1b	1b	1b
Rust Prevention	ASTM D665	Pass	Pass	Pass	Pass	Pass	Pass
Foaming Characteristics	ASTM D892	Pass	Pass	Pass	Pass	Pass	Pass
Oxidation Stability	ASTM D943	Good	Excellent	Excellent	Excellent	Excellent	Excellent