



PRODUCT DATA SHEET

TECHNOFLUID CIRCULATING OIL

Product Description

TECHNOFLUID CIRCULATING OIL is a premium-quality general-purpose industrial lubricating oil formulated for reliable lubrication of bearings, machine components and circulating lubrication systems. It is available in a comprehensive range of ISO viscosity grades to suit different operating conditions and equipment requirements.

The product provides good lubricating performance, rust and corrosion protection, thermal and oxidation stability, good water separation and low foaming tendency. Its clean and stable formulation makes it suitable for continuous circulation and general industrial lubrication where an EP-type lubricant is not specifically required.

Typical Characteristics

Product Type	—	General-Purpose Circulating Oil
Base Oil Type	—	Highly Refined Mineral Base Oil
ISO Viscosity Grades	ISO 3448	VG 32, 46, 68, 100, 150, 220, 320, 460
Appearance	Visual	Clear & Bright
Color	Visual	Water White to Pale Amber
Density @ 15°C	ASTM D4052	Grade dependent

Kinematic Viscosity @ 40°C	ASTM D445	Grade dependent
Kinematic Viscosity @ 100°C	ASTM D445	Grade dependent
Viscosity Index	ASTM D2270	Typically 90–120
Flash Point (COC)	ASTM D92	Typically >180°C
Pour Point	ASTM D97	Grade dependent
Foaming Tendency	ASTM D892	Low
Rust Protection	ASTM D665	Pass / Good
Copper Corrosion	ASTM D130	Typically 1a
Oxidation Stability	—	Good
Water Separability	ASTM D1401	Good

Key Benefits

- - Available in a wide range of ISO VG grades for different operating requirements
- - Good oxidation and thermal stability for dependable service
- - Good rust and corrosion protection of lubricated components
- - Good demulsibility and water-separation characteristics
- - Low foaming tendency for stable circulation
- - Good natural lubricity and film-forming characteristics
- - Suitable for continuous circulation and general-purpose industrial lubrication

- - Helps maintain clean and reliable lubrication systems
- - Good compatibility with commonly used mineral-oil-compatible seals
- - Suitable for a wide range of industrial machinery and components

ISO VG grade reference, kinematic viscosity @ 40°C: VG 32 = 28.8–35.2 cSt; VG 46 = 41.4–50.6 cSt; VG 68 = 61.2–74.8 cSt; VG 100 = 90–110 cSt; VG 150 = 135–165 cSt; VG 220 = 198–242 cSt; VG 320 = 288–352 cSt; VG 460 = 414–506 cSt.

Typical Applications

TECHNOFLUID CIRCULATING OIL is recommended for use in:

- - Circulating lubrication systems
- - Plain and sleeve bearings
- - Roller and other lightly to moderately loaded bearings
- - Machine tools and general machinery
- - Electric motors and generators
- - Gear reducers where a non-EP circulating oil is specified
- - Spindle and machine components requiring suitable ISO viscosity
- - Roller and drive chains where the specified viscosity is appropriate
-

Handling & Storage

- - Store in clean, dry and covered conditions.
- - Keep containers tightly closed when not in use.
- - Protect from moisture, dust and other contamination.
- - Avoid prolonged exposure to direct sunlight and excessive heat.
- - Recommended storage temperature: 5°C to 40°C.

Health & Safety

Avoid prolonged skin contact. Wear appropriate protective equipment during handling. Refer to the latest Safety Data Sheet (SDS) before use.

Disclaimer

The information contained herein is based on current formulation and manufacturing data and is believed to be accurate. Typical values are not to be construed as product specifications and may vary slightly within normal manufacturing tolerances. Users should evaluate the product's suitability for their specific application before use.