



PRODUCT DATA SHEET

TECHNOFLUID GEAR EP 460

Product Description

TECHNOFLUID GEAR EP 460 is a premium quality Extreme Pressure (EP) industrial gear lubricant manufactured from highly refined base oils and advanced sulphur-phosphorus additive technology. It is specially formulated to provide excellent load-carrying capacity, wear protection, oxidation resistance and long service life in enclosed industrial gear systems operating under severe conditions.

Applications

- Enclosed industrial spur gears
- Helical gear drives
- Bevel gear drives
- Worm gear units (where EP oils are recommended)
- Heavy-duty reduction gearboxes
- Cement, steel, mining, sugar, paper and textile industries

Performance Level / Specifications

Suitable for use where the following specifications are required:

- AGMA 9005-F16 (EP)
- DIN 51517 Part 3 (CLP)
- ISO 12925-1 Type CKD
- US Steel 224
- David Brown S1.53.101

Typical Specifications

Characteristics	Test Method	Typical Figures
Appearance	Visual	Clear & Bright
Density @ 29.5°C, g/cm ³	ASTM D4052	0.88
Kinematic Viscosity @ 40°C, cSt	ASTM D445	410 – 460
Flash Point (COC), °C	ASTM D92	230
Pour Point, °C	ASTM D97	-6 Max
Copper Corrosion (3 h @100°C)	ASTM D130	1b
Rust Protection	ASTM D665	Pass
Foaming Characteristics	ASTM D892	Pass

Note: The above characteristics are typical values and may vary slightly within normal manufacturing tolerances.

Key Performance Benefits

- Excellent Extreme Pressure (EP) performance
- Outstanding protection against wear and scuffing
- High load-carrying capability
- Superior oxidation and thermal stability
- Excellent resistance to rust and corrosion
- Good demulsibility for rapid water separation
- Excellent anti-foam characteristics
- Extended oil drain intervals
- Longer gearbox life and reduced maintenance costs

TECHNOFLUID GEAR EP 460 is designed to deliver reliable lubrication and long service life for heavily loaded industrial gear systems operating under demanding conditions.