



PRODUCT DATA SHEET

TECHNOFLUID GIRTH GEAR GREASE

Commercial / Pack Name: GIRTH GEAR GREASE

Product Description

- TECHNOFLUID Girth Gear Grease is a heavy-duty, high-load lubricating grease specially formulated for open girth gears and large slow-speed gear drives.
- Manufactured using high-viscosity base oils, special thickeners, and advanced EP/solid lubricant additives to withstand extreme loads, shock loads, and boundary lubrication conditions.
- Forms a tenacious, adhesive lubricating film that protects gear teeth against wear, pitting, and scuffing.
- Designed to perform reliably in cement, steel, mining, sugar, and power plants under harsh operating environments.

Key Performance Benefits

- Exceptional load-carrying and extreme pressure performance.
- Strong adhesion ensures grease remains on gear teeth during rotation.
- Provides excellent protection against micropitting, scuffing, and wear.
- Good resistance to water washout and contamination.
- Minimizes gear noise and vibration.
- Extends gear life and reduces maintenance downtime.
- Suitable for spray, brush, or manual application systems.

Applications

- Recommended for:
 - Open girth gears of rotary kilns
 - Ball mills and tube mills
 - Dryers and rotary furnaces

- Large open gear drives
 - Suitable for slow-speed, heavily loaded gear systems operating under shock loads and dusty environments.

Typical Characteristics

Characteristics	Test Method	Typical Figures
Appearance	Visual	Smooth, tacky grease
Colour	Visual	Dark Brown / Black
Thickener Type	—	Special Soap / Clay
Base Oil Type	—	High Viscosity Mineral
Solid Lubricants	—	Graphite / MoS ₂ (as applicable)
NLGI Grade	ASTM D217	0 / 1 (Sprayable / Brushable)
Worked Penetration (60 strokes), 0.1 mm	ASTM D217	310 – 370
Base Oil Viscosity @ 40°C, cSt	ASTM D445	≥ 1000
Drop Point, °C	ASTM D2265	Non-melting
Four Ball Weld Load, kg	ASTM D2596	≥ 400
Wear Scar Dia, mm	ASTM D2266	≤ 0.50
FZG Load Stage	DIN 51354	≥ 14
Water Washout @ 79°C, % loss	ASTM D1264	≤ 5
Copper Corrosion (24 hrs @ 100°C)	ASTM D4048	1b
Rust Prevention	ASTM D1743	Pass
Adhesion / Tackiness	In-house	Excellent
Operating Temperature Range, °C	—	-10 to 120

