



## PRODUCT DATA SHEET

### TECHNOFLUID ROLL PERFECT 46 (SOLUBLE)

*Commercial / Pack Name: ROLL PERFECT 46*

#### Product Description

- TECHNOFLUID Roll Perfect 46 (Soluble) is a **high-performance soluble rolling lubricant** specially formulated for **hot and cold rolling mill operations**.
- Designed to provide **excellent lubrication, cooling, and surface finish** during metal rolling processes.
- Forms a **stable emulsion with water**, ensuring consistent performance and long sump life.
- Reduces roll wear, improves strip quality, and minimizes surface defects.
- Suitable for ferrous and non-ferrous rolling applications.

#### Key Performance Benefits

- Excellent **lubricity** reduces roll bite friction and power consumption.
- Superior **cooling characteristics** control roll and strip temperature.
- Stable emulsion ensures **uniform lubrication** across roll surfaces.
- Minimizes roll wear and surface scoring.
- Enhances surface finish and dimensional accuracy.
- Provides good **rust and corrosion protection** to rolls and mill components.
- Low foaming and good hard-water tolerance.

#### Applications Recommended for:

- **Hot rolling mills**
- **Cold rolling mills**
- Bar, rod, and strip rolling operations
  - Suitable for **carbon steel, alloy steel**, and selected non-ferrous metals.
  - Can be used in **recirculating water systems**.

## Typical Characteristics

| Characteristics                       | Test Method   | Typical Figures                     |
|---------------------------------------|---------------|-------------------------------------|
| Appearance<br>(Concentrate)           | Visual        | Clear / Light Amber                 |
| Appearance (5%<br>Emulsion)           | Visual        | Milky White                         |
| Base Fluid Type                       | —             | Mineral Oil Based<br>(Emulsifiable) |
| Emulsion Stability<br>(5% in water)   | IP / In-house | Stable                              |
| Density @ 15°C, g/ml                  | ASTM D4052    | 0.870                               |
| Kinematic Viscosity<br>@ 40°C, cSt    | ASTM D445     | 45 – 50                             |
| pH of 5% Emulsion                     | ASTM D1287    | 8.5 – 9.0                           |
| Refractometer Factor<br>(5% Emulsion) | —             | 4.0 – 5.0                           |
| Flash Point (COC), °C                 | ASTM D92      | ≥ 180                               |
| Pour Point, °C                        | ASTM D97      | -6                                  |
| Copper Corrosion (3<br>hrs @ 100°C)   | ASTM D130     | Pass                                |
| Rust Prevention                       | IP / In-house | Pass                                |
| Foam Tendency                         | ASTM D892     | Low                                 |
| Hard Water Stability                  | In-house      | Good                                |
| Biostability                          | In-house      | Good                                |
| Recommended<br>Dilution Ratio         | —             | 2% – 8%                             |