



PRODUCT DATA SHEET

SCREW AIR COMPRESSOR OIL / AIR COMPRESSOR OIL

Commercial / Pack Name: Screw Compressor Oil 32 / 46 / 68 , Air Compressor Oil 100 / 150 / 220

Product Description

- Premium compressor lubricants formulated from highly refined base oils and advanced additives.
- Designed for rotary screw and reciprocating air compressors.
- Excellent oxidation and thermal stability.
- Low deposit formation for clean compressor operation.
- Superior anti-wear, rust and corrosion protection.

Key Performance Benefits

- Extended oil service life.
- Excellent air release and anti-foam performance.
- Minimizes sludge and varnish.
- Reduces maintenance costs.
- Reliable protection under severe operating conditions.

Applications

- Rotary screw compressors.
- Reciprocating air compressors.
- Industrial compressed air systems.
- Manufacturing, textile, mining and engineering industries.

INDUSTRY PERFORMANCE CHARACTERISTICS

- High oxidation stability
- Excellent thermal stability
- Rapid air release
- Low foaming tendency
- Excellent wear protection
- Long service life

Typical Characteristics

Characteristics	SC 32	SC 46	SC 68	AC 100	AC 150	AC 220
Appearance	Clear	Clear	Clear	Clear	Clear	Clear
Density @29.5°C	0.845	0.850	0.858	0.865	0.870	0.875
K.V @40°C cSt	32	46	68	100	150	220
Viscosity Index	100	100	100	98	98	95
Pour Point °C	-18	-18	-15	-12	-9	-6
Flash Point (COC) °C	210	220	230	235	235	235

