



PRODUCT DATA SHEET

TECHNOFLUID TURBINE OILS

Commercial / Pack Name: ISO VG 32 / 46 / 68 / 100

Product Description

- Premium turbine oils formulated from highly refined base oils and advanced anti-oxidant technology.
- Designed for steam, gas and hydro turbine lubrication systems.
- Excellent oxidation stability and long service life.
- Superior rust, corrosion and foam protection.
- Available in ISO VG 32, 46, 68 and 100 grades.

Key Performance Benefits

- Outstanding oxidation and thermal stability.
- Excellent water separation characteristics.
- Rapid air release and low foaming tendency.
- Reliable rust and corrosion protection.
- Extended oil drain intervals and reduced maintenance.

Applications

- Steam turbines.
- Gas turbines.
- Hydroelectric turbines.
- Industrial circulating lubrication systems.
- Power generation and process industries.

INDUSTRY PERFORMANCE CHARACTERISTICS

- Excellent oxidation stability
- High demulsibility
- Rapid air release
- Low foaming tendency
- Long service life

Typical Characteristics

Characteristics	ISO VG 32	ISO VG 46	ISO VG 68	ISO VG 100
Appearance	Clear	Clear	Clear	Clear
Density @29.5°C	0.845	0.850	0.855	0.865
K.V @40°C cSt	32	46	68	100
Viscosity Index	100	100	100	98
Pour Point °C	-18	-15	-12	-9
Flash Point (COC) °C	210	220	230	240

