



PRODUCT DATA SHEET

TECHNOFLUID SHOCK ABSORBER OIL

Product Description

TECHNOFLUID SHOCK ABSORBER OIL is a premium-quality suspension and shock absorber fluid specially formulated for smooth, consistent and reliable damping performance. It is designed for use in automotive and two-wheeler shock absorbers, telescopic forks and other hydraulic suspension systems where controlled viscosity, good thermal stability and excellent seal compatibility are required.

The product is available in a range of viscosity grades to provide different damping characteristics according to vehicle and suspension requirements. Its formulation provides good oxidation resistance, low foaming tendency, excellent low-temperature fluidity and consistent performance over a wide operating temperature range.

Typical Characteristics

Product Type	—	Shock Absorber / Suspension Fluid
Viscosity Grades	—	2.5W, 5W, 7.5W, 10W, 15W, 20W, 30W
Appearance	Visual	Clear & Bright
Color	Visual	Water White to Pale Amber
Density @ 15°C	ASTM D4052	Typical 0.83–0.87 g/cm ³
Kinematic Viscosity @ 40°C	ASTM D445	Grade dependent

Viscosity @ 100°C	ASTM D445	Grade dependent
Viscosity Index	ASTM D2270	High
Flash Point (COC)	ASTM D92	Typically >150°C
Pour Point	ASTM D97	Low / Grade dependent
Foaming Tendency	ASTM D892	Low
Oxidation Stability	—	Excellent
Rust / Corrosion Protection	—	Good
Seal Compatibility	—	Suitable for commonly used suspension seals

Key Benefits

- - Available in multiple viscosity grades for different damping requirements
- - Smooth and consistent damping performance
- - Excellent viscosity stability over a wide temperature range
- - Good low-temperature fluidity for reliable cold-temperature response
- - Good oxidation and thermal stability
- - Low foaming tendency for consistent damping performance
- - Good anti-wear and corrosion protection for suspension components
- - Good compatibility with commonly used suspension-system seals and materials
- - Suitable for automotive and two-wheeler suspension applications

- - Helps maintain controlled and predictable suspension response

Grade reference: 2.5W (10–15 cSt), 5W (15–20 cSt), 7.5W (20–25 cSt), 10W (30–35 cSt), 15W (45–50 cSt), 20W (60–70 cSt), 30W (90–110 cSt) @ 40°C.

Typical Applications

TECHNOFLUID SHOCK ABSORBER OIL is recommended for use in:

- - Motorcycle and scooter telescopic forks
- - Two-wheeler shock absorbers
- - Automotive shock absorbers
- - Suspension struts and damping units
- - Steering dampers
- - Hydraulic suspension systems
- - Off-road and recreational vehicle suspension systems
- - General-purpose hydraulic damping applications
-

Note: Suspension-oil 'weight' labels can vary between manufacturers; actual kinematic viscosity is the preferred basis for selecting an equivalent fluid.

Handling & Storage

- - Store in clean, dry and covered conditions.
- - Keep containers tightly closed when not in use.
- - Protect from moisture, dust and other contamination.
- - Avoid prolonged exposure to direct sunlight and excessive heat.
- - Recommended storage temperature: 5°C to 40°C.

Health & Safety

Avoid prolonged skin contact. Wear appropriate protective equipment during handling. Refer to the latest Safety Data Sheet (SDS) before use.

Disclaimer

The information contained herein is based on current manufacturing data and is believed to be accurate. Typical values are not to be construed as product specifications and may vary slightly within normal manufacturing tolerances. Users should evaluate the product's suitability for their specific application before use.