## **SEVER STACK SETTINGS AMAZON**

```
Nginx:
server {
    listen 80;
    server_name 13.245.13.44;
    location /static/ {
        alias /home/ubuntu/django-pd/django_ref/static/;
        expires 30d;
    }
    location / {
          proxy_pass http://unix:/home/ubuntu/django-pd/django_ref/app.sock;
          proxy_set_header Host $host;
          proxy_set_header X-Real-IP $remote_addr;
          proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
          proxy_set_header X-Forwarded-Proto $scheme;
          proxy_connect_timeout 400s;
          proxy_send_timeout 400s;
          proxy_read_timeout 400s;
          proxy_cache my_cache;
          proxy_cache_valid 200 302 180m;
          proxy_cache_valid 404 1m;
          proxy_cache_use_stale updating;
     }
}
and
GNU nano 6.2
                                                  /etc/nginx/nginx.conf
user root:
worker_processes auto;
pid /run/nginx.pid;
include /etc/nginx/modules-enabled/*.conf;
events {
    worker_connections 768;
    # multi_accept on;
}
http {
    proxy_cache_path /var/cache/nginx levels=1:2 keys_zone=my_cache:120m max_size=10g
inactive=120m use_temp_path=off;
```

```
##
    # Basic Settings
    ##
    sendfile on;
    tcp_nopush on;
    types_hash_max_size 2048;
    # server_tokens off;
    # server_names_hash_bucket_size 64;
    # server_name_in_redirect off;
    include /etc/nginx/mime.types;
    default_type application/octet-stream;
    ##
    # SSL Settings
    ##
    ssl_protocols TLSv1.1 TLSv1.2 TLSv1.3; # Dropping SSLv3, ref: POODLE
    ssl_prefer_server_ciphers on;
    ##
    # Logging Settings
    access_log /var/log/nginx/access.log;
    error_log /var/log/nginx/error.log;
    ##
    # Gzip Settings
    ##
    gzip on;
    # gzip_vary on;
    # gzip_proxied any;
    # gzip_comp_level 6;
    # gzip_buffers 16 8k;
    # gzip_http_version 1.1;
    # gzip_types text/plain text/css application/json application/javascript text/xml application/xml
application/xml+rss text/javascript;
    ##
    # Virtual Host Configs
    ##
    include /etc/nginx/conf.d/*.conf;
    include /etc/nginx/sites-enabled/*;
Supervisor:
```

}

## program:gunicorn]

directory = /home/ubuntu/django-pd/django\_ref/
command = /home/ubuntu/django-pd/env/bin/gunicorn --workers=2 --bind
unix:/home/ubuntu/django-pd/django\_ref/app.sock django\_ref.wsgi:application --timeout 400
autostart=true
autorestart=true
stderr\_logfile=/var/log/gunicorn/gunicorn.err.log
stdout\_logfile=/var/log/gunicorn/gunicorn.out.log

## *Gunicorn alone (python script)*

workers = 3 bind = 'localhost' port = 8000 timeout = 400 accesslog = '/home/humbulani/django/django\_ref/gunicorn.err.log' errorlog = '/home/humbulani/django/django\_ref/gunicorn.out.log'