

Lesson 8

Topic: Introduction to DAX Basics & Calculated Columns vs. Measures

Prerequisites: Download [DAX_Practice_Data.xlsx](#) file

1. What does DAX stand for?

DAX stands for Data Analysis Expressions.

It's a formula language used in Microsoft tools like Power BI, Excel Power Pivot, and Analysis Services to perform calculations and data analysis on data models.

Quick Overview:

- DAX is similar to Excel formulas but much more powerful for working with relational data.
- It allows you to create:
 - Calculated Columns
 - Measures
 - Calculated Tables

2. Write a DAX formula to sum the Sales column.

To sum the Sales column in DAX, you can write the following formula as a Measure:

DAX

Total Sales = SUM(Sales[Sales])

Explanation:

- Total Sales is the name of the new measure.
- SUM(Sales[Sales]) adds up all the values in the Sales column of the Sales table.

3. What is the difference between a calculated column and a measure?

Difference Between Calculated Column and Measure (DAX)

Calculated Column

- Added as a new column in a table.
- Uses row context (calculates row by row).
- Stored in the data model → uses more memory.
- Good for filtering, grouping, or creating new fields (e.g., Profit = Revenue - Cost).
- Example:
Profit = Sales[Revenue] - Sales[Cost]

Measure

- A formula that calculates a value dynamically (not stored).
- Uses filter context (changes based on visuals/slicers).
- Not stored in model → better performance.
- Good for summarizing data (sum, average, etc.).

4. Use the DIVIDE function to calculate Profit Margin (Profit/Sales).

DAX Measure for Profit Margin:

DAX

Profit Margin = DIVIDE(Sales[Profit], Sales[Sales])

Explanation:

- Sales[Profit]: Your calculated column or field for profit (e.g., Revenue - Cost).
- Sales[Sales]: Total sales amount.
- DIVIDE(x, y) is safer than x / y — it handles division by zero and avoids errors.

5. What does COUNTROWS() do in DAX?

COUNTROWS() in DAX

The COUNTROWS() function counts the number of rows in a table.

Syntax:

DAX

COUNTROWS(table)

Example as a Measure:

DAX

Transaction Count = COUNTROWS(Data_sales)

Use Cases:

- Count how many sales transactions happened.
- Count number of products sold.
- Count how many rows remain after filters are applied in visuals.

With a Filter Example:

DAX

High Sales Count = COUNTROWS(
 FILTER(Sales, Sales[Amount] > 1000)
)

This counts only sales rows where the amount is greater than 1000.

6. Create a measure: Total Profit that subtracts total cost from total sales

DAX Measure: Total Profit

DAX

Total Profit = SUM(Data_sales[Sales]) - SUM(Data_sales[Cost])

Explanation:

- SUM(DAX_Practice_Data[Sales]): Adds all sales values.
 - SUM(DAX_Practice_Data[Cost]): Adds all cost values.
 - The result is the total profit across all rows.
-

🌟 How to Create It:

1. Go to Modeling tab in Power BI.
2. Click New measure.
3. Paste the DAX formula above.
4. Press Enter.

7. Write a measure to calculate Average Sales per Product.

DAX Measure: Average Sales per Product

If each row in your Data_sales table represents one product, you can calculate Average Sales per Product like this:

DAX

Avg Sales per Product = AVERAGE(Data_sales[Sales])

Alternative (if you want total sales ÷ number of products):

If you prefer to manually divide total sales by the number of products, use:

DAX

Avg Sales per Product = DIVIDE(
SUM(Data_sales[Sales]), COUNTROWS(Data_sales))

Both methods are valid — use the second one if you're doing custom logic or want more control.

8. Use IF() to tag products as "High Profit" if Profit > 1000.

DAX Calculated Column: Tag Products as "High Profit"

To tag products as "High Profit" if Profit > 1000, use this formula in a calculated column:

DAX

Profit Category =

IF(Data_sales[Profit] > 1000, "High Profit", "Low Profit")


 Steps to Add in Power BI:

1. Go to the Data view.
 2. Click on New column.
 3. Paste the DAX formula above.
 4. Press Enter.
-

This will create a new column (Profit Category) labeling each row as "High Profit" or "Low Profit" based on the value in the Profit column.

9. What is a circular dependency error in a calculated column?

A circular dependency error happens when a calculated column refers directly or indirectly to itself, creating a loop that DAX can't resolve.

 Example (Problem):

DAX

ColumnA = Data_sales[ColumnB] + 100

ColumnB = Data_sales[ColumnA] + 50

In this case:

- ColumnA depends on ColumnB
 - ColumnB depends on ColumnA
- This creates a circular dependency, and Power BI will throw an error.
-

Error Message:

"A circular dependency was detected: Data_sales[ColumnA],
Data_sales[ColumnB]..."

How to Fix It:

- Avoid mutual references between calculated columns.
 - Try to restructure logic using measures instead of columns.
 - Use intermediate steps that don't depend on each other.
-

Summary (Note format):

- Circular dependency = formula loops back to itself.
- Caused by columns referring to each other.
- DAX can't calculate because it never reaches a final value.

10.Explain row context vs. filter context.

Row Context vs. Filter Context in DAX

Understanding these two concepts is essential for mastering DAX calculations:

Row Context

- ◆ Think of it as: "One row at a time."
- ◆ It applies when you create a calculated column or use iterating functions like SUMX, FILTER, etc.

Example:

DAX

Profit = Data_sales[Sales] - Data_sales[Cost]

This formula runs for each row, using the row's own Sales and Cost.

Filter Context

- ◆ Think of it as: "Which data is visible right now?"
- ◆ It comes from visuals (like slicers, charts) or from DAX functions like CALCULATE().

Example:

DAX

Total Sales = SUM(Data_sales[Sales])

In a report:

- If you apply a filter (e.g., ProductID = 1), DAX recalculates based on only that row's data.
- The visible data is the filter context.

11. Write a measure to calculate YTD Sales using TOTALYTD().

DAX Measure: Year-To-Date (YTD) Sales

To calculate YTD Sales using the TOTALYTD() function, use the following DAX measure:

DAX

YTD Sales =

```
TOTALYTD(  
    SUM(Data_sales[Sales]),  
    Data_sales[Date]  
)
```

Explanation:

- SUM(Data_sales[Sales]): Total sales value.

- Data_sales[Date]: The date column used to track time progression.
- TOTALYTD() accumulates sales from the start of the year up to the current date.

12. Create a dynamic measure that switches between Sales, Profit, and Margin.

DAX: Create a Dynamic Measure to Switch Between Sales, Profit, and Margin

To do this, you'll need two steps:

◆ Step 1: Create a Slicer Table (Disconnected Table)

In Power BI, go to Modeling → New Table and enter:

DAX

CopyEdit

Metric Selector =

```

DATATABLE(
    "Metric", STRING,
    {
        {"Sales"},
        {"Profit"},
        {"Margin"}
    }
)

```

This creates a slicer list with the 3 metric options.

◆ Step 2: Create a Dynamic Measure

DAX

CopyEdit

Selected Metric =

VAR SelectedMetric = SELECTEDVALUE('Metric Selector'[Metric])

RETURN

SWITCH(

 SelectedMetric,

 "Sales", SUM(Data_sales[Sales]),

 "Profit", SUM(Data_sales[Sales]) - SUM(Data_sales[Cost]),

 "Margin", DIVIDE(SUM(Data_sales[Sales]) -
SUM(Data_sales[Cost]), SUM(Data_sales[Sales])),

 BLANK()

)

How It Works:

- SELECTEDVALUE reads the user's slicer choice.
- SWITCH changes the calculation based on the selected metric.

To Use It:

1. Add a slicer to your report from the Metric Selector table.
2. Add a card or chart using the Selected Metric measure.
3. Now users can switch between Sales, Profit, and Margin dynamically!

13.Optimize a slow DAX measure using variables (VAR).

Optimize a Slow DAX Measure Using VAR

Slow DAX (Without VAR):

DAX

Profit Margin =

DIVIDE(

```
SUM(Data_sales[Sales]) - SUM(Data_sales[Cost]),  
SUM(Data_sales[Sales])  
)
```

In this example:

- SUM(Data_sales[Sales]) is calculated twice, which is inefficient.

Optimized DAX Using VAR:

DAX

Optimized Profit Margin =

VAR TotalSales = SUM(Data_sales[Sales])

VAR TotalCost = SUM(Data_sales[Cost])

VAR Profit = TotalSales - TotalCost

RETURN

DIVIDE(Profit, TotalSales)

Why This Is Better:

- Each calculation is done once and reused.
- Improves performance and readability.
- Easier to debug and maintain in large models.

Use VAR when:

- You reuse the same calculation.
- You want clean and readable logic.
- You're working with complex measures or large datasets.

14. Use CALCULATE() to override a filter

Use CALCULATE() to Override a Filter in DAX

The CALCULATE() function in DAX modifies or overrides filter context — it's one of the most powerful and flexible functions in Power BI.

◆ Example Goal:

Show Total Sales for all products, even when a product filter is applied (e.g., from a slicer or visual).

Without CALCULATE() (Respects Filter):

DAX

Total Sales = SUM(Data_sales[Sales])

This will only sum visible rows (affected by filters/slicers).

With CALCULATE() to Override Product Filter:

DAX

All Product Sales =

```
CALCULATE(  
    SUM(Data_sales[Sales]),  
    REMOVEFILTERS(Data_sales[ProductID])  
)
```

Explanation:

- SUM(Data_sales[Sales]): Base calculation.
- REMOVEFILTERS(Data_sales[ProductID]): Ignores any filter on ProductID, so all products are included in the total.

Iterate Filter Override Example:

Filter to only ProductID = 1 (hardcoded):

DAX

Sales for Product 1 =

```
CALCULATE(  
    SUM(Data_sales[Sales]),  
    Data_sales[ProductID] = 1  
)
```

15. Write a measure that returns the highest sales amount

Write a DAX Measure to Return the Highest Sales Amount

You can use the MAX() function to get the highest single sales value from the Sales column.

DAX Measure:

DAX

```
Highest Sales = MAX(Data_sales[Sales])
```

What It Does:

- Scans the Sales column in the Data_sales table.
- Returns the largest sales amount found across all rows.

Example Output:

If your sales values are: 6000, 3000, and 2000,
Highest Sales will return: 6000.