

Phạm Trần Gia Hưng 2331200153

Practice Assignment 2

Save the source code, test cases and related test report as per question number. Make a zip folder of all the solutions and upload in Moodle.

1. You need to develop a software based on Test Driven Development (TDD). The details of the software you need to implement as follows.

The software will generate Personal Numbers. Let assume, the personal number consist of 10-digit number: YYMMDD-XYZC.

- The first six digits represent the date of birth with year, month and day, for example 640823, which is 23rd of August 1964.
- The following three digits, XYZ, is a serial number, where Z represents the person's gender. If the person is a female Z is an even number and odd if the person is male.
- The last digit, C, is a checksum and is calculated in the following manner:
 - Multiply the digits in the date and serial number with 2, 1, 2, 1,...

For example:

6 4 0 8 2 3 – 3 2 3

2 1 2 1 2 1 2 1 2

12, 4, 0, 8, 4, 3, 6, 2, 6

- Add the resulting digits: $1+2+4+0+8+4+3+6+2+6=36$

- If a multiplication result is larger than 10, it becomes the sum of the digits, for example $12 \rightarrow 1+2$

- If the summation [in this case it is 36] is greater than 10, take the last digit from the sum (the 6 in the above example) and subtract it from 10.

In the example it will be $10-6 = 4$, the resulting number is the check sum C.

- If the result is 10 then the checksum C is 0.
- If the result is less than 10, then the checksum C will be the digit itself.

The Personal number class shall have the following methods:

- getDate() should return the date of birth, YYMMDD in some form.
- getYear() only return the year
- getMonth() only return the month
- getSex() return if the person is male of female (returning just Z is not allowed).
- getChecksum() return the checksum digit
- When instantiating a personal number class, give the personal number to the constructor as a parameter.
- It shall not be possible to instantiate an invalid personal number. If the instantiation fails an exception shall be thrown.

You are free to choose the types (integers, strings etc.) for your class by yourself. If needed, you can add more member functions, it is then a

At least you should have the following test cases for a class that represents the personal number:

1. A test case for checking the accuracy of checksum calculation
2. A test case for getDate() method
3. A test case for getYear() method
4. A test case for getMonth() method
5. A test case for getSex() method

You should follow TDD. You should have the following steps in your development:

1. Add a test that fails
2. Make the code work
3. Run the test to see if it passes

4. Modify and revise the code (Refactoring)
60 Points

```
4      public class Q1_PersonalNumberTest {
5
6          @Test
7      ►      public void testChecksumCalculation() {
8              // Test case from assignment example: 640823-3234
9              Q1_PersonalNumber pn1 = new Q1_PersonalNumber("6408233234");
10             assertEquals( expected: 4, pn1.getChecksum());
11
12             Q1_PersonalNumber pn2 = new Q1_PersonalNumber("8505152382");
13             assertEquals( expected: 2, pn2.getChecksum());
14         }
15
16         @Test
17     ►      public void testGetDate() {
18             Q1_PersonalNumber pn = new Q1_PersonalNumber("6408233234");
19             assertEquals( expected: "640823", pn.getDate());
20
21             Q1_PersonalNumber pn2 = new Q1_PersonalNumber("8505152382");
22             assertEquals( expected: "850515", pn2.getDate());
23         }
24
25         @Test
26     ►      public void testGetYear() {
27             Q1_PersonalNumber pn = new Q1_PersonalNumber("6408233234");
28             assertEquals( expected: "64", pn.getYear());
29
30             Q1_PersonalNumber pn2 = new Q1_PersonalNumber("0001010172");
31             assertEquals( expected: "00", pn2.getYear());
32         }
33
34         @Test
35     ►      public void testGetMonth() {
36             Q1_PersonalNumber pn = new Q1_PersonalNumber("6408233234");
37             assertEquals( expected: "08", pn.getMonth());
38
39             Q1_PersonalNumber pn2 = new Q1_PersonalNumber("8512152383");
40             assertEquals( expected: "12", pn2.getMonth());
41         }
42
43         @Test
44     ►      public void testGetSex() {
45             // 3 so Male
46             Q1_PersonalNumber pn1 = new Q1_PersonalNumber("6408233234");
47             assertEquals( expected: "Male", pn1.getSex());
```

```

46     Q1_PersonalNumber pn1 = new Q1_PersonalNumber("6408233234");
47     assertEquals( expected: "Male", pn1.getSex());
48
49     // 8 so Female
50     Q1_PersonalNumber pn2 = new Q1_PersonalNumber("8505152382");
51     assertEquals( expected: "Female", pn2.getSex());
52
53     // 1 so Male
54     Q1_PersonalNumber pn3 = new Q1_PersonalNumber("9203121018");
55     assertEquals( expected: "Male", pn3.getSex());
56 }
57
58 @Test(expected = IllegalArgumentException.class)
59 ▶ > public void testInvalidChecksum() { new Q1_PersonalNumber("6408233235"); }
60
61
62
63 @Test(expected = IllegalArgumentException.class)
64 ▶ > public void testInvalidMonth() { new Q1_PersonalNumber("6413233234"); }
65
66
67
68 @Test(expected = IllegalArgumentException.class)
69 ▶ public void testInvalidDay() {
70     // 32 invalid
71     new Q1_PersonalNumber("6408323234");
72 }
73
74
75 @Test
76 ▶ public void testGetDay() {
77     Q1_PersonalNumber pn = new Q1_PersonalNumber("6408233234");
78     assertEquals( expected: "23", pn.getDay());
79 }
80
81 @Test
82 ▶ public void testGetSerialNumber() {
83     Q1_PersonalNumber pn = new Q1_PersonalNumber("6408233234");
84     assertEquals( expected: "323", pn.getSerialNumber());
85 }
86 }

```

✓ Q1_PersonalNumberTest: 21 ms

- ✓ testChecksumCalculation 9 ms
- ✓ testGetMonth 1 ms
- ✓ testGetDate 7 ms
- ✓ testGetYear 0 ms
- ✓ testInvalidChecksum 3 ms
- ✓ testGetDay 0 ms
- ✓ testGetSex 0 ms
- ✓ testGetSerialNumber 0 ms
- ✓ testInvalidMonth 0 ms
- ✓ testInvalidDay 1 ms

✓ 10 tests passed 10 tests

C:\Users\Admin\.jdk\bin

Process finished with

2. You are given a template for the Currency and Money classes. For these two classes, at first, write test cases for the methods of each class, then you have to add code to the methods of these classes (You need to follow Test Driven Development –TDD).The Bank and Account classes were written by a bad programmer. When you are confident that your Money and Currency classes work as intended, write test cases for the Bank and Account classes and find the bugs.

30 Points

Bug:

Account:

```

44     public void tick() { 5 usages
45         for (TimedPayment tp : timedpayments.values()) {
46             // tp.tick(); tp.tick(); error
47             tp.tick(); //removed duplicate tp.tick() call
48         }
49     }

```

Bank:

```

    else {
        //accountlist.get(accountid); // error gets null
        accountlist.put(accountid, new Q2_Account(accountid, currency));
    }

    public void deposit(String accountid, Q2_Money money) throws Q2_AccountDoesNotExist
    // error inverted logic fix, should throw exception if account not exist
    //if (accountlist.containsKey(accountid)) {
    if (!accountlist.containsKey(accountid)) {
        throw new Q2_AccountDoesNotExistException();
    }

    else {
        Q2_Account account = accountlist.get(accountid);
        //call withdraw, not deposit
        //account.deposit(money);
        account.withdraw(money);
    }

    public void transfer(String fromaccount, String toaccount, Q2_Money amount) throws Q2
    //transfer(fromaccount, this, fromaccount, amount); // fromaccount used twice
    transfer(fromaccount, tobank: this, toaccount, amount);
}

```

- Account test:

```

5  public class Q2_AccountTest {
6      Q2_Currency SEK, DKK; 15 usages
7      Q2_Bank Nordea; no usages
8      Q2_Bank DanskeBank; no usages
9      Q2_Bank SweBank; 7 usages
10     Q2_Account testAccount; 37 usages
11
12     @Before
13     public void setUp() throws Exception {
14         SEK = new Q2_Currency( name: "SEK", rate: 0.15);
15         SweBank = new Q2_Bank( name: "SweBank", SEK);
16         SweBank.openAccount( accountid: "Alice");
17         testAccount = new Q2_Account( name: "Hans", SEK);
18         testAccount.deposit(new Q2_Money( amount: 10000000, SEK));
19
20         SweBank.deposit( accountid: "Alice", new Q2_Money( amount: 1000000, SEK));
21     }
22
23     @Test
24     public void testAddRemoveTimedPayment() {
25         // Test adding a timed payment
26         assertFalse(testAccount.timedPaymentExists( id: "payment1"));
27
28         testAccount.addTimedPayment( id: "payment1", interval: 5, next: 2, new Q2_Money( amount: 1000,
29         assertTrue(testAccount.timedPaymentExists( id: "payment1"));
30
31         // Test removing a timed payment
32         testAccount.removeTimedPayment( id: "payment1");
33         assertFalse(testAccount.timedPaymentExists( id: "payment1"));
34
35         // Test adding multiple payments
36         testAccount.addTimedPayment( id: "payment1", interval: 5, next: 2, new Q2_Money( amount: 1000,
37         testAccount.addTimedPayment( id: "payment2", interval: 3, next: 1, new Q2_Money( amount: 500, S
38         assertTrue(testAccount.timedPaymentExists( id: "payment1"));
39         assertTrue(testAccount.timedPaymentExists( id: "payment2"));
40
41         // Remove one
42         testAccount.removeTimedPayment( id: "payment1");
43         assertFalse(testAccount.timedPaymentExists( id: "payment1"));
44         assertTrue(testAccount.timedPaymentExists( id: "payment2"));
45     }
46
47     @Test
48     public void testTimedPayment() throws Q2_AccountDoesNotExistException {
49         // Add a timed payment that executes after 2 ticks
50         int initialBalance = testAccount.getBalance().getAmount();
51         testAccount.addTimedPayment( id: "payment1", interval: 3, next: 2, new Q2_Money( amount: 1000

```



```
47 @Test
48 public void testTimedPayment() throws Q2_AccountDoesNotExistException {
49     // Add a timed payment that executes after 2 ticks
50     int initialBalance = testAccount.getBalance().getAmount();
51     testAccount.addTimedPayment( id: "payment1", interval: 3, next: 2, new Q2_Money( amount: 1000, S
52
53     // First tick no payment next becomes 1
54     testAccount.tick();
55     assertEquals( message: "Balance should not change on first tick", initialBalance, testAccou
56
57     // Second tick no payment next becomes 0, payment execute after 0)
58     testAccount.tick();
59     assertEquals( message: "Balance should not change on second tick", initialBalance, testAcco
60
61     // Third tick payment executes
62     testAccount.tick();
63     assertEquals( message: "Balance should decrease by 1000 after third tick", expected: initial
64
65     // Fourth tick interval is 3, payment execute again after 3 ticks
66     testAccount.tick();
67     assertEquals( message: "Balance should not change on fourth tick", expected: initialBalance
68 }
69
70 @Test
71 public void testAddWithdraw() {
72     int initial = testAccount.getBalance().getAmount();
73
74     testAccount.deposit(new Q2_Money( amount: 5000, SEK));
75     assertEquals( expected: initial + 5000, testAccount.getBalance().getAmount().intValue());
76
77     testAccount.withdraw(new Q2_Money( amount: 2000, SEK));
78     assertEquals( expected: initial + 5000 - 2000, testAccount.getBalance().getAmount().intValue
79
80     testAccount.deposit(new Q2_Money( amount: 10000, SEK));
81     testAccount.withdraw(new Q2_Money( amount: 3000, SEK));
82     assertEquals( expected: initial + 5000 - 2000 + 10000 - 3000, testAccount.getBalance().getA
83 }
84
85 @Test
86 public void testGetBalance() {
87     assertEquals(Integer.valueOf( 10000000), testAccount.getBalance().getAmount());
88
89     testAccount.deposit(new Q2_Money( amount: 1000, SEK));
90     assertEquals(Integer.valueOf( 10001000), testAccount.getBalance().getAmount());
91
92     testAccount.withdraw(new Q2_Money( amount: 500, SEK));
93     assertEquals(Integer.valueOf( 10000500), testAccount.getBalance().getAmount());
94 }
95 }
```

Process finished with exit code 0

Test Method	Duration
Q2_AccountTest	2 ms
testAddRemoveTimed	2 ms
testGetBalance	0 ms
testTimedPayment	0 ms
testAddWithdraw	0 ms

4 tests passed 4 tests total, 2 ms

C:\Users\Admin\.jdk\ms-17.0.17\bin\java.exe ...

- Bank test:

```

6  ▶▶ public class Q2_BankTest {
7      Q2_Currency SEK, DKK; 25 usages
8      Q2_Bank SweBank, Nordea, DanskeBank; 54 usages
9
10     @Before
11     public void setUp() throws Exception {
12         DKK = new Q2_Currency( name: "DKK", rate: 0.20);
13         SEK = new Q2_Currency( name: "SEK", rate: 0.15);
14         SweBank = new Q2_Bank( name: "SweBank", SEK);
15         Nordea = new Q2_Bank( name: "Nordea", SEK);
16         DanskeBank = new Q2_Bank( name: "DanskeBank", DKK);
17         SweBank.openAccount( accountid: "Ulrika");
18         SweBank.openAccount( accountid: "Bob");
19         Nordea.openAccount( accountid: "Bob");
20         DanskeBank.openAccount( accountid: "Gertrud");
21     }
22
23     @Test
24     ▶ public void testGetName() {
25         assertEquals( expected: "SweBank", SweBank.getName());
26         assertEquals( expected: "Nordea", Nordea.getName());
27         assertEquals( expected: "DanskeBank", DanskeBank.getName());
28     }
29
30     @Test
31     ▶ public void testGetCurrency() {
32         assertEquals(SEK, SweBank.getCurrency());
33         assertEquals(SEK, Nordea.getCurrency());
34         assertEquals(DKK, DanskeBank.getCurrency());
35     }
36
37     @Test
38     ▶ public void testOpenAccount() throws Q2_AccountExistsException,

```

```

38 ▶ ~ public void testOpenAccount() throws Q2_AccountExistsException, Q2_AccountDoesNotExistException {
39     SweBank.openAccount( accountid: "Charlie");
40
41     assertEquals(Integer.valueOf(0), SweBank.getBalance( accountid: "Charlie"));
42
43     ~ try {
44         SweBank.openAccount( accountid: "Ulrika");
45         fail("Should throw AccountExistsException");
46     } catch (Q2_AccountExistsException e) {
47     }
48 }
49
50 @Test
51 ▶ ~ public void testDeposit() throws Q2_AccountDoesNotExistException {
52     SweBank.deposit( accountid: "Ulrika", new Q2_Money( amount: 10000, SEK));
53     assertEquals(Integer.valueOf(10000), SweBank.getBalance( accountid: "Ulrika"));
54
55     SweBank.deposit( accountid: "Ulrika", new Q2_Money( amount: 5000, SEK));
56     assertEquals(Integer.valueOf(15000), SweBank.getBalance( accountid: "Ulrika"));
57
58     // depositing to non existent account
59     ~ try {
60         SweBank.deposit( accountid: "NonExistent", new Q2_Money( amount: 1000, SEK));
61         fail("Should throw AccountDoesNotExistException");
62     } catch (Q2_AccountDoesNotExistException e) {
63     }
64 }
65
66 @Test
67 ▶ ~ public void testWithdraw() throws Q2_AccountDoesNotExistException {
68     SweBank.deposit( accountid: "Bob", new Q2_Money( amount: 10000, SEK));
69     assertEquals(Integer.valueOf(10000), SweBank.getBalance( accountid: "Bob"));
70
71     SweBank.withdraw( accountid: "Bob", new Q2_Money( amount: 3000, SEK));
72     assertEquals(Integer.valueOf(7000), SweBank.getBalance( accountid: "Bob"));
73
74     // depositing to non existent account
75     ~ try {
76         SweBank.withdraw( accountid: "NonExistent", new Q2_Money( amount: 1000, SEK));
77         fail("Should throw AccountDoesNotExistException");
78     } catch (Q2_AccountDoesNotExistException e) {
79     }
80 }
81
82 @Test
83 ▶ ~ public void testGetBalance() throws Q2_AccountDoesNotExistException {
84     SweBank.deposit( accountid: "Ulrika", new Q2_Money( amount: 5000, SEK));
85     assertEquals(Integer.valueOf(5000), SweBank.getBalance( accountid: "Ulrika"));

```

Activate Windows


```

85     assertEquals(Integer.valueOf(1: 5000), SweBank.getBalance( accountid: "Ulrika"));
86
87     try {
88         SweBank.getBalance( accountid: "NonExistent");
89         fail("Should throw AccountDoesNotExistException");
90     } catch (Q2_AccountDoesNotExistException e) {
91     }
92 }
93
94 @Test
95 public void testTransfer() throws Q2_AccountDoesNotExistException {
96     SweBank.deposit( accountid: "Ulrika", new Q2_Money( amount: 10000, SEK));
97     SweBank.deposit( accountid: "Bob", new Q2_Money( amount: 5000, SEK));
98
99     // Transfer Ulrika to Bob same bank
100    SweBank.transfer( fromaccount: "Ulrika", toaccount: "Bob", new Q2_Money( amount: 3000, SEK));
101    assertEquals(Integer.valueOf(1: 7000), SweBank.getBalance( accountid: "Ulrika"));
102    assertEquals(Integer.valueOf(1: 8000), SweBank.getBalance( accountid: "Bob"));
103
104    // Transfer between different banks
105    Nordea.deposit( accountid: "Bob", new Q2_Money( amount: 2000, SEK));
106    SweBank.transfer( fromaccount: "Ulrika", Nordea, toaccount: "Bob", new Q2_Money( amount: 2000, SEK));
107    assertEquals(Integer.valueOf(1: 5000), SweBank.getBalance( accountid: "Ulrika"));
108    assertEquals(Integer.valueOf(1: 4000), Nordea.getBalance( accountid: "Bob"));
109
110    try {
111        SweBank.transfer( fromaccount: "NonExistent", toaccount: "Bob", new Q2_Money( amount: 1000, SEK));
112        fail("Should throw AccountDoesNotExistException");
113    } catch (Q2_AccountDoesNotExistException e) {
114    }
115
116    try {
117        SweBank.transfer( fromaccount: "Ulrika", toaccount: "NonExistent", new Q2_Money( amount: 1000, SEK));
118        fail("Should throw AccountDoesNotExistException");
119    } catch (Q2_AccountDoesNotExistException e) {
120    }
121 }
122
123 @Test
124 public void testTransferSameBank() throws Q2_AccountDoesNotExistException {
125     SweBank.deposit( accountid: "Ulrika", new Q2_Money( amount: 10000, SEK));
126     SweBank.deposit( accountid: "Bob", new Q2_Money( amount: 5000, SEK));
127
128     SweBank.transfer( fromaccount: "Ulrika", toaccount: "Bob", new Q2_Money( amount: 3000, SEK));
129
130     assertEquals(Integer.valueOf(1: 7000), SweBank.getBalance( accountid: "Ulrika"));
131     assertEquals(Integer.valueOf(1: 8000), SweBank.getBalance( accountid: "Bob"));
132 }

```

```

131         assertEquals(Integer.valueOf(8000), SweBank.getBalance(accountid: "Bob"));
132     }
133
134     @Test
135     public void testTimedPayment() throws Q2_AccountDoesNotExistException {
136         SweBank.deposit(accountid: "Ulrika", new Q2_Money(amount: 10000, SEK));
137         SweBank.deposit(accountid: "Bob", new Q2_Money(amount: 5000, SEK));
138
139         // Add timed payment executes after 2 tick
140         SweBank.addTimedPayment(accountid: "Ulrika", payid: "payment1", interval: 3, next: 2, new Q2_Money(amount: 10000, SEK));
141
142         // Tick once no payment
143         SweBank.tick();
144         assertEquals(Integer.valueOf(10000), SweBank.getBalance(accountid: "Ulrika"));
145         assertEquals(Integer.valueOf(5000), SweBank.getBalance(accountid: "Bob"));
146
147         // Tick twice no payment
148         SweBank.tick();
149         assertEquals(Integer.valueOf(10000), SweBank.getBalance(accountid: "Ulrika"));
150         assertEquals(Integer.valueOf(5000), SweBank.getBalance(accountid: "Bob"));
151
152         // Tick three times payment execute
153         SweBank.tick();
154         assertEquals(Integer.valueOf(9000), SweBank.getBalance(accountid: "Ulrika"));
155         assertEquals(Integer.valueOf(6000), SweBank.getBalance(accountid: "Bob"));
156
157         // Remove timed payment
158         SweBank.removeTimedPayment(accountid: "Ulrika", id: "payment1");
159
160         int ulrikaBalance = SweBank.getBalance(accountid: "Ulrika");
161         int bobBalance = SweBank.getBalance(accountid: "Bob");
162
163         // Tick again no change since payment removed
164         SweBank.tick();
165         assertEquals(ulrikaBalance, SweBank.getBalance(accountid: "Ulrika").intValue());
166         assertEquals(bobBalance, SweBank.getBalance(accountid: "Bob").intValue());
167     }
168 }

```

Q2_BankTest	3 ms	9 tests passed 9 tests total, 3 ms
testOpenAccount	2 ms	C:\Users\Admin\.jdk\ms-17.0.17\bin
testTransferSameBa	0 ms	Process finished with exit code 0
testGetName	0 ms	
testWithdraw	0 ms	
testGetBalance	0 ms	
testTimedPayment	1 ms	
testDeposit	0 ms	
testGetCurrency	0 ms	
testTransfer	0 ms	

-Currency test

```
6  ✓ public class Q2_CurrencyTest {
7      Q2_Currency SEK, DKK, NOK, EUR; 17 usages
8
9      @Before
10     public void setUp() throws Exception {
11         // Setup currencies with exchange rates
12         SEK = new Q2_Currency( name: "SEK", rate: 0.15);
13         DKK = new Q2_Currency( name: "DKK", rate: 0.20);
14         EUR = new Q2_Currency( name: "EUR", rate: 1.5);
15     }
16
17     @Test
18     ✓ public void testGetName() {
19         assertEquals( expected: "SEK", SEK.getName());
20         assertEquals( expected: "DKK", DKK.getName());
21         assertEquals( expected: "EUR", EUR.getName());
22     }
23
24     @Test
25     ✓ public void testGetRate() {
26         assertEquals(Double.valueOf( d: 0.15), SEK.getRate());
27         assertEquals(Double.valueOf( d: 0.20), DKK.getRate());
28         assertEquals(Double.valueOf( d: 1.5), EUR.getRate());
29     }
30
31     @Test
32     ✓ public void testSetRate() {
33         // Test new rate SEK
34         SEK.setRate(0.18);
35         assertEquals(Double.valueOf( d: 0.18), SEK.getRate());
36
37         // Test new rate EUR
38         EUR.setRate(1.8);
39         assertEquals(Double.valueOf( d: 1.8), EUR.getRate());
```

```

37 // Test new rate EUR
38 EUR.setRate(1.8);
39 assertEquals(Double.valueOf(1.8), EUR.getRate());
40
41 // Reset
42 SEK.setRate(0.15);
43 EUR.setRate(1.5);
44 }
45
46 @Test
47 public void testGlobalValue() {
48     // SEK rate = 0.15
49     assertEquals(Integer.valueOf(15), SEK.universalValue(100));
50
51     // DKK rate = 0.20
52     assertEquals(Integer.valueOf(20), DKK.universalValue(100));
53
54     // EUR rate = 1.5
55     assertEquals(Integer.valueOf(150), EUR.universalValue(100));
56
57     assertEquals(Integer.valueOf(30), SEK.universalValue(200));
58
59     assertEquals(Integer.valueOf(3), SEK.universalValue(20));
60
61     assertEquals(Integer.valueOf(0), SEK.universalValue(0));
62 }
63
64 @Test
65 public void testValueInThisCurrency() {
66     // 100 SEK = 15 universal (100 * 0.15)
67     // 15 universal in DKK = 15 / 0.20 = 75
68     assertEquals(Integer.valueOf(75), DKK.valueInThisCurrency(100, SEK));
69
70     // 100 DKK = 20 universal (100 * 0.20)
71     // 20 universal in SEK = 20 / 0.15 = 133
72     assertEquals(Integer.valueOf(133), SEK.valueInThisCurrency(100, DKK));
73
74     // 100 SEK = 15 universal
75     // 15 universal in EUR = 15 / 1.5 = 10
76     assertEquals(Integer.valueOf(10), EUR.valueInThisCurrency(100, SEK));
77
78     // 100 EUR = 150 universal
79     // 150 universal in SEK = 150 / 0.15 = 1000
80     assertEquals(Integer.valueOf(1000), SEK.valueInThisCurrency(100, EUR));
81
82     // Test same currency
83     assertEquals(Integer.valueOf(100), SEK.valueInThisCurrency(100, SEK));

```

Activate Windows
Go to Settings to activate Windows.


```

64      @Test
65      public void testValueInThisCurrency() {
66          // 100 SEK = 15 universal (100 * 0.15)
67          // 15 universal in DKK = 15 / 0.20 = 75
68          assertEquals(Integer.valueOf(75), DKK.valueInThisCurrency(amount: 100, SEK));
69
70          // 100 DKK = 20 universal (100 * 0.20)
71          // 20 universal in SEK = 20 / 0.15 = 133
72          assertEquals(Integer.valueOf(133), SEK.valueInThisCurrency(amount: 100, DKK));
73
74          // 100 SEK = 15 universal
75          // 15 universal in EUR = 15 / 1.5 = 10
76          assertEquals(Integer.valueOf(10), EUR.valueInThisCurrency(amount: 100, SEK));
77
78          // 100 EUR = 150 universal
79          // 150 universal in SEK = 150 / 0.15 = 1000
80          assertEquals(Integer.valueOf(1000), SEK.valueInThisCurrency(amount: 100, EUR));
81
82          // Test same currency
83          assertEquals(Integer.valueOf(100), SEK.valueInThisCurrency(amount: 100, SEK));
84
85          // Test 0
86          assertEquals(Integer.valueOf(0), DKK.valueInThisCurrency(amount: 0, SEK));
87      }
88
89  }

```

✓ Q2_CurrencyTest	1 ms	✓ 5 tests passed 5 tests total, 1 ms
✓ testGlobalValue	1 ms	C:\Users\Admin\.jdk\ms-17.0.17\bin\java.exe ...
✓ testGetName	0 ms	
✓ testGetRate	0 ms	
✓ testValueInThisCurrency	0 ms	Process finished with exit code 0
✓ testSetRate	0 ms	

-Money test:

```

6 ►► public class Q2_MoneyTest {
7     Q2_Currency SEK, DKK, EUR; 9 usages
8     Q2_Money SEK100, EUR10, SEK200, EUR20, SEK0, EUR0, SEKn100; 14 usages
9
10    @Before
11    public void setUp() throws Exception {
12        SEK = new Q2_Currency( name: "SEK", rate: 0.15);
13        DKK = new Q2_Currency( name: "DKK", rate: 0.20);
14        EUR = new Q2_Currency( name: "EUR", rate: 1.5);
15        SEK100 = new Q2_Money( amount: 10000, SEK);
16        EUR10 = new Q2_Money( amount: 1000, EUR);
17        SEK200 = new Q2_Money( amount: 20000, SEK);
18        EUR20 = new Q2_Money( amount: 2000, EUR);
19        SEK0 = new Q2_Money( amount: 0, SEK);
20        EUR0 = new Q2_Money( amount: 0, EUR);
21        SEKn100 = new Q2_Money( amount: -10000, SEK);
22    }
23
24    @Test
25    ► public void testGetAmount() {
26        assertEquals(Integer.valueOf(10000), SEK100.getAmount());
27        assertEquals(Integer.valueOf(1000), EUR10.getAmount());
28        assertEquals(Integer.valueOf(0), SEK0.getAmount());
29        assertEquals(Integer.valueOf(-10000), SEKn100.getAmount());
30    }
31
32    @Test
33    ► public void testGetCurrency() {
34        assertEquals(SEK, SEK100.getCurrency());
35        assertEquals(EUR, EUR10.getCurrency());
36    }
37
38    @Test
39    ► public void testToString() {
40        assertEquals( expected: "100.0 SEK", SEK100.toString());
41        assertEquals( expected: "10.0 EUR", EUR10.toString());
42        assertEquals( expected: "0.0 SEK", SEK0.toString());
43    }
44
45    @Test
46    ► public void testUniversalValue() {
47        assertEquals(Integer.valueOf(1500), SEK100.universalValue());
48        assertEquals(Integer.valueOf(1500), EUR10.universalValue());
49    }
50
51    @Test
52    ► public void testEquals() {
53        assertTrue(SEK100.equals(EUR10));

```

Act
Get

```

45     @Test
46     public void testUniversalValue() {
47         assertEquals(Integer.valueOf(1500), SEK100.universalValue());
48         assertEquals(Integer.valueOf(1500), EUR10.universalValue());
49     }
50
51     @Test
52     public void testEquals() {
53         assertTrue(SEK100.equals(EUR10));
54         assertFalse(SEK100.equals(SEK200));
55         assertTrue(SEK0.equals(EUR0));
56     }
57
58     @Test
59     public void testAdd() {
60         Q2_Money result = SEK100.add(EUR10);
61         // EUR10 = 1500 universal, convert to SEK: 1500/0.15 = 10000
62         // SEK100 + EUR10 (SEK) = 10000 + 10000
63         assertEquals(Integer.valueOf(20000), result.getAmount());
64         assertEquals(SEK, result.getCurrency());
65     }
66
67     @Test
68     public void testSub() {
69         Q2_Money result = SEK200.sub(EUR10);
70         // EUR10 = 1500 universal, convert to SEK: 1500/0.15 = 10000
71         // SEK200 - EUR10 (SEK) = 20000 - 10000
72         assertEquals(Integer.valueOf(10000), result.getAmount());
73         assertEquals(SEK, result.getCurrency());
74     }
75
76     @Test
77     public void testIsZero() {
78         assertTrue(SEK0.isZero());
79         assertTrue(EUR0.isZero());
80         assertFalse(SEK100.isZero());
81         assertFalse(SEKn100.isZero());
82     }
83
84     @Test
85     public void testNegate() {
86         Q2_Money negated = SEK100.negate();
87         assertEquals(Integer.valueOf(-10000), negated.getAmount());
88         assertEquals(SEK, negated.getCurrency());
89
90         Q2_Money doubleNegated = negated.negate();
91         assertEquals(Integer.valueOf(10000), doubleNegated.getAmount());
92     }

```

```
76     @Test
77     public void testIsZero() {
78         assertTrue(SEK0.isZero());
79         assertTrue(EUR0.isZero());
80         assertFalse(SEK100.isZero());
81         assertFalse(SEKn100.isZero());
82     }
83
84     @Test
85     public void testNegate() {
86         Q2_Money negated = SEK100.negate();
87         assertEquals(Integer.valueOf(-10000), negated.getAmount());
88         assertEquals(SEK, negated.getCurrency());
89
90         Q2_Money doubleNegated = negated.negate();
91         assertEquals(Integer.valueOf(10000), doubleNegated.getAmount());
92     }
93
94     @Test
95     public void testCompareTo() {
96         assertEquals(expected: 0, SEK100.compareTo(EUR10));
97         assertTrue(condition: SEK100.compareTo(SEK200) < 0);
98         assertTrue(condition: SEK200.compareTo(SEK100) > 0);
99         assertTrue(condition: SEKn100.compareTo(SEK100) < 0);
100     }
101 }
102
```

Test Method	Duration
Q2_MoneyTest	9 ms
testAdd	1 ms
testSub	0 ms
testToString	8 ms
testCompareTo	0 ms
testUniversalValue	0 ms
testGetAmount	0 ms
testEquals	0 ms
testIsZero	0 ms
testNegate	0 ms

10 tests passed

C:\Users\Admin\

Process finished

Bonus Points

3. A parking garage has a number of parking spaces for vehicles. The parking garage must keep track of the vehicles that are currently parked there so that it can report the number of parking spaces available and the current value. A parking garage must provide publicly available functions that are called when a vehicle enters and exits the garage. It can throw exceptions if there is insufficient available space in the garage, if a vehicle tries to enter that is already in the garage, or if a car that is not in the garage tries to exit.

Additionally, the garage must provide publicly available functions that report the total capacity of the garage, the number of available spaces in the garage, and the total money collected. The parking fee is assessed when a vehicle enters the parking garage.

Currently, there are three distinct types of vehicles: cars, low-emission cars, and cargo trucks. Every vehicle has a license number consisting of letters and/or numbers and the number of parking spaces it occupies. Cars have a passenger capacity (i.e., the number of passengers). Trucks have a gross vehicle weight it can transport. Cars take up one space, while trucks take up a number of spaces that is their gross weight divided by 10,000. Cars are charged a rate of \$8, low-emission cars are charged half that rate, and trucks are charged \$10 per 10,000 pounds of gross weight. Develop a software based on TDD to solve the above problem.

60 Points

```

1  > import ...
4
5  ▶▶ public class Q3_ParkingGarageTest {
6      private Q3_ParkingGarage garage; 62 usages
7      private Q3_Car car1; 10 usages
8      private Q3_Car car2; 3 usages
9      private Q3_LowEmissionCar eco1; 5 usages
10     private Q3_Truck truck1; 7 usages
11     private Q3_Truck truck2; 3 usages
12
13     ⚡ @Before
14     ▶ public void setUp() {
15         // Create garage with 10 spaces
16         garage = new Q3_ParkingGarage( totalCapacity: 10);
17
18         // Create test vehicles
19         car1 = new Q3_Car( licenseNumber: "ABC123", passengerCapacity: 5);
20         car2 = new Q3_Car( licenseNumber: "DEF456", passengerCapacity: 4);
21         eco1 = new Q3_LowEmissionCar( licenseNumber: "ENDFIELD001", passengerCapacity: 4);
22         truck1 = new Q3_Truck( licenseNumber: "TOMORROW002", grossWeight: 25000); // 3 spaces
23         truck2 = new Q3_Truck( licenseNumber: "SOMETHING003", grossWeight: 50000); // 5 spaces
24     }
25
26     @Test
27     ▶ public void testCarEntry() throws Exception {
28         garage.enter(car1);
29
30         assertEquals( expected: 9, garage.getAvailableSpaces());
31         assertEquals( expected: 1, garage.getNumberOfVehicles());
32         assertEquals( expected: 8.0, garage.getTotalRevenue(), delta: 0.01);
33         assertTrue(garage.isVehicleParked( licenseNumber: "ABC123"));
34     }
35
36     @Test
37     ▶ public void testLowEmissionCarFee() throws Exception {
38         garage.enter(eco1);
39
40         assertEquals( expected: 9, garage.getAvailableSpaces());
41         assertEquals( expected: 4.0, garage.getTotalRevenue(), delta: 0.01);
42     }
43
44     @Test
45     ▶ public void testTruckSpaceCalculation() throws Exception {
46         // Truck 25000 lbs take 3 spaces, 2,5 round up
47         garage.enter(truck1);
48
49         assertEquals( expected: 7, garage.getAvailableSpaces()); // 10 - 3
50         assertEquals( expected: 3, truck1.getSpacesRequired());

```

```

49     assertEquals( expected: 7, garage.getAvailableSpaces()); // 10 - 3
50     assertEquals( expected: 3, truck1.getSpacesRequired());
51 }
52
53 @Test
54 ▶ ▼ public void testTruckFeeCalculation() throws Exception {
55     // Truck with 25000lbs: (25000/10000) * 10 = 25
56     garage.enter(truck1);
57     assertEquals( expected: 25.0, garage.getTotalRevenue(), delta: 0.01);
58
59     // Truck with 50000 lbs: (50000/10000) * 10 = 50
60     Q3_ParkingGarage garage2 = new Q3_ParkingGarage( totalCapacity: 10);
61     garage2.enter(truck2);
62     assertEquals( expected: 50.0, garage2.getTotalRevenue(), delta: 0.01);
63 }
64
65 @Test(expected = Q3_InsufficientSpaceException.class)
66 ▶ ▼ public void testInsufficientSpace() throws Exception {
67     // Fill garage to 9 space
68     garage.enter(car1); // 1
69     garage.enter(car2); // 1
70     garage.enter(eco1); // 1
71     garage.enter(new Q3_Car( licenseNumber: "CAR3", passengerCapacity: 5)); // 1
72     garage.enter(new Q3_Car( licenseNumber: "CAR4", passengerCapacity: 5)); // 1
73     garage.enter(new Q3_Car( licenseNumber: "CAR5", passengerCapacity: 5)); // 1
74     garage.enter(new Q3_Car( licenseNumber: "CAR6", passengerCapacity: 5)); // 1
75     garage.enter(new Q3_Car( licenseNumber: "CAR7", passengerCapacity: 5)); // 1
76     garage.enter(new Q3_Car( licenseNumber: "CAR8", passengerCapacity: 5)); // 1
77
78     assertEquals( expected: 1, garage.getAvailableSpaces());
79
80     // Try truck that need 3, fail
81     garage.enter(truck1);
82 }
83
84 @Test(expected = Q3_VehicleAlreadyParkedException.class)
85 ▶ ▼ public void testDuplicateEntry() throws Exception {
86     garage.enter(car1);
87     garage.enter(car1); // throw exception
88 }
89
90 @Test
91 ▶ ▼ public void testVehicleExit() throws Exception {
92     garage.enter(car1);
93     garage.enter(car2);
94
95     assertEquals( expected: 8, garage.getAvailableSpaces());

```

Activate
Go to Setti

```

91 ▶ public void testVehicleExit() throws Exception {
92     garage.enter(car1);
93     garage.enter(car2);
94
95     assertEquals( expected: 8, garage.getAvailableSpaces());
96     assertEquals( expected: 2, garage.getNumberOfVehicles());
97
98     // Exit car1
99     garage.exit( licenseNumber: "ABC123");
100
101     assertEquals( expected: 9, garage.getAvailableSpaces());
102     assertEquals( expected: 1, garage.getNumberOfVehicles());
103     assertFalse(garage.isVehicleParked( licenseNumber: "ABC123"));
104     assertTrue(garage.isVehicleParked( licenseNumber: "DEF456"));
105
106     // Revenue not change on exit
107     assertEquals( expected: 16.0, garage.getTotalRevenue(), delta: 0.01);
108 }
109
110 @Test(expected = Q3_VehicleNotParkedException.class)
111 ▶ public void testExitNonExistentVehicle() throws Exception {
112     garage.exit( licenseNumber: "lolllol");
113 }
114
115 @Test
116 ▶ public void testTotalRevenue() throws Exception {
117     double expectedRevenue = 0.0;
118     assertEquals(expectedRevenue, garage.getTotalRevenue(), delta: 0.01);
119
120     garage.enter(car1);
121     expectedRevenue += 8.0;
122     assertEquals(expectedRevenue, garage.getTotalRevenue(), delta: 0.01);
123
124     garage.enter(eco1);
125     expectedRevenue += 4.0;
126     assertEquals(expectedRevenue, garage.getTotalRevenue(), delta: 0.01);
127
128     garage.enter(truck1);
129     expectedRevenue += 25.0;
130     assertEquals(expectedRevenue, garage.getTotalRevenue(), delta: 0.01);
131
132     // Exit not change revenue
133     garage.exit( licenseNumber: "ABC123");
134     assertEquals(expectedRevenue, garage.getTotalRevenue(), delta: 0.01);
135 }
136
137 @Test
138 ▶ public void testMultipleVehicleTypes() throws Exception {
139     garage.enter(car1); // 1 space, 8
140     garage.enter(eco1); // 1 space, 4

```

Activa
Go to S

