CUSTOMER (https://access.redhat.com/)
PORTAL



# How to exclude crond from audit logs

**SOLUTION VERIFIED** - Updated November 17 2015 at 1:57 PM - English ▼ ()

### Environment

- Red Hat Enterprise Linux 5
- Red Hat Enterprise Linux 6
- Red Hat Enterprise Linux 7

#### Issue

- How can we disable all the extra PAM-related crond messages from filling up /var/log/audit/audit.log?
- Auditd logs show at least 6 events audit.log every time cron runs a job. In my case that's every 5 minutes cause that's what I have set sar to.

```
type=USER ACCT msg=audit(1336941301.016:10008): user pid=27266 uid=0
auid=4294967295 msg='PAM: accounting acct="root" : exe="/usr/sbin/crond"
(hostname=?, addr=?, terminal=cron res=success)'
type=CRED ACQ msg=audit(1336941301.016:10009): user pid=27266 uid=0
auid=4294967295 msg='PAM: setcred acct="root" : exe="/usr/sbin/crond"
(hostname=?, addr=?, terminal=cron res=success)'
type=L0GIN msg=audit(1336941301.016:10010): login pid=27266 uid=0 old
auid=4294967295 new auid=0 old ses=4294967295 new ses=1542
type=USER START msg=audit(1336941301.046:10011): user pid=27266 uid=0 auid=0
msg='PAM: session open acct="root" : exe="/usr/sbin/crond" (hostname=?, addr=?,
terminal=cron res=success)'
type=CRED_DISP msg=audit(1336941301.076:10012): user pid=27266 uid=0 auid=0
msg='PAM: setcred acct="root" : exe="/usr/sbin/crond" (hostname=?, addr=?,
terminal=cron res=success)'
type=USER END msg=audit(1336941301.076:10013): user pid=27266 uid=0 auid=0
msg='PAM: session close acct="root" : exe="/usr/sbin/crond" (hostname=?, addr=?,
terminal=cron res=success)'
```

we use cookies on our websites to deliver our online services. Details about how we use cookies and how you may disable them are set out in our Privacy Statement (//www.redhat.com/en/about/privacy-policy#cookies). By using this website you agree to our use of cookies.



 Add an audit rule like the following to minimize audit events triggered by crond executing CUSTOMER(https://access.redhat.com/)
 cron jobs

PORTAL



```
-A never,user -F subj_type=crond_t
```

- Notes:
  - This does not work in RHEL 5 (there are no other options there)
  - This does not work if SELinux is disabled (as it relies on filtering by the SELinux context type of the crond process)
  - If unable to add the rule, crond-triggered audit events can be minimized by combining cron jobs, e.g., with the following 3 jobs:

```
*/4 * * * * somecommand

*/4 * * * * another-command

*/4 * * * some-other-command
```

In RHEL 6, that's going to generate 18 audit events every 4 minutes Instead, they could be combined into a single line that would only generate 6 events every 4 minutes, e.g.:

```
*/4 * * * * somecommand; another-command; some-other-command
```

## Private Notes (Red Hat Internal)



- RHEL6 Bugzilla: https://bugzilla.redhat.com/show\_bug.cgi?id=634303 (https://bugzilla.redhat.com/show\_bug.cgi?id=634303)
  - errata released: http://rhn.redhat.com/errata/RHSA-2011-0542.html (http://rhn.redhat.com/errata/RHSA-2011-0542.html)
- RHEL5 Bugzilla: https://bugzilla.redhat.com/show\_bug.cgi?id=667405 (private)
  - no errata

We use cookies on our websites to deliver our online services. Details about how we use cookies and



how you may disable them are set out in our Privacy Statement (//www.redhat.com/en/about/privacy-spokies). By using this website you agree to our use of cookies.



Product(s) Red Hat Enterprise Ling M FtB work of the Prise - linux)
PORTAL



Component audit (/components/audit) Category Configure (/category/configure)

Tags audit (/tags/audit) rhel\_5 (/tags/rhel\_5) rhel\_6 (/tags/rhel\_6) rhel\_7 (/taxonomy/tags/rhel7) selinux (/tags/selinux)

This solution is part of Red Hat's fast-track publication program, providing a huge library of solutions that Red Hat engineers have created while supporting our customers. To give you the knowledge you need the instant it becomes available, these articles may be presented in a raw and unedited form.

#### People who viewed this solution also viewed

auid doesn't display user id while connected via ssh

Solution - May 17, 2012

Why running /etc/init.d/crond status displays "crond dead but pid file exists"?

Solution - Jun 6, 2013

How to change time stamp recorded in the audit log to normal format?

Solution - Sep 22, 2015

We use cookies on our websites to deliver our online services. Details about how we use cookies and how you may disable them are set out in our Privacy Statement (//www.redhat.com/en/about/privacy-policy#cookies). By using this website you agree to our use of cookies.



01518226 (/support/cases/#/case/01518226) - rhn-support-rahranja CUSTOMER (https://access.redhat.com/)
01541823 (/support/cases/#/case/01541823) - rhn-support-ryamamot
01070692 (/support/cases/#/case/01070692) - rhn-support-fjayalat
01446757 (/support/cases/#/case/01446757) - rhn-support-nparmar
01460306 (/support/cases/#/case/01460306) - rhn-support-jiazhang
01624116 (/support/cases/#/case/01624116) - rhn-support-santony
01588167 (/support/cases/#/case/01588167) - rhn-support-santony
01942310 (/support/cases/#/case/01942310) - rhn-support-ryamamot
01737326 (/support/cases/#/case/01737326) - rhn-support-dbodnarc
01983959 (/support/cases/#/case/01983959) - rhn-support-mezhu

Show More

### Comments

Privacy Statement (http://www.redhat.com/en/about/privacy-policy)

Customer Portal Terms of Use
(https://access.redhat.com/help/terms/)

All Policies and Guidelines
(http://www.redhat.com/en/about/all-policies-guidelines)

Copyright © 2018 Red Hat, Inc.

We use cookies on our websites to deliver our online services. Details about how we use cookies and how you may disable them are set out in our Privacy Statement (//www.redhat.com/en/about/privacy-policy#cookies). By using this website you agree to our use of cookies.

