Instability of Flow In Magnetic Nozzle

Hunt Feng

University of Saskatchewan

June 26, 2023

Outline of Presentation

Outline of Presentation

## Instability of Plasma Flow

- The instability of plasma flow refers to the tendency of a plasma system to deviate from a stable, equilibrium state and exhibit perturbations or fluctuations in its behavior. [1]

To investigate instability, we assume oscillating perturbed quantities , $\tilde{n}, \tilde{v} \sim \exp(-i\omega t)$.

1. If $\text{Im}(\omega) > 0$, then it is unstable flow since the perturbations grow exponential in time, $\exp(\text{Im}(\omega)t)$.

2. If $\text{Im}(\omega) <= 0$, then it is stable flow since the perturbations decay/unchanged in time.

Magnetic Nozzle

- A magnetic nozzle is a device that uses a magnetic field to shape and control the flow of charged particles in a plasma propulsion system.
- Instabilities may affect magnetic nozzle operation and the resulting thrust. [4]

(a) Simplified representation of magnetic nozzle.

(b) A simplified magnetic field of magnetic nozzle.

Figure 1: Simplified representation of magnetic nozzle. Length is normalized.

Governing Equations

The nondimensionalized governing equations for the plasma flow in magnetic nozzle are

Cons. of Den.
$$\frac{\partial n}{\partial t} + n\frac{\partial v}{\partial z} + v\frac{\partial n}{\partial z} - nv\frac{\partial_z B}{B} = 0 \qquad (1)$$

Cons. of Mom.
$$n\frac{\partial v}{\partial t} + nv\frac{\partial v}{\partial z} = -\frac{\partial n}{\partial z} \qquad (2)$$

where n, v are density and velocity, respectively.
The equilibrium quantities n_0, v_0 must satify the condition,

$$\frac{\partial}{\partial z}\left(\frac{n_0 v_0}{B}\right) = 0 \qquad (3)$$

$$v_0\frac{\partial v_0}{\partial z} = -\frac{1}{n_0}\frac{\partial n_0}{\partial z} \qquad (4)$$

Figure 2: Velocity if normalized to sound speed. There are 4 different cases for velocity profile, subsonic, supersonic, accelerating and decelerating case.

Polynomial Eigenvalue Problem

By linearizing the governing equations, and assume oscillating perturbed quantities, $\tilde{n}, \tilde{v} \sim \exp(-i\omega t)$. We can derive the following equation,

$$
\begin{aligned}
&\omega^2 \tilde{v} \\
&+ 2i\omega \left(v_0 \frac{\partial}{\partial z} + \frac{\partial v_0}{\partial z} \right) \tilde{v} \\
&+ \left[(1 - v_0^2)\frac{\partial^2}{\partial z^2} - \left(3v_0 + \frac{1}{v_0} \right) \frac{\partial v_0}{\partial z} \frac{\partial}{\partial z} \right. \\
&\left. - \left(1 - \frac{1}{v_0^2} \right) \left(\frac{\partial v_0}{\partial z} \right)^2 - \left(v_0 + \frac{1}{v_0} \right) \frac{\partial^2 v_0}{\partial z^2} \right] \tilde{v} = 0
\end{aligned}
\tag{5}
$$

It is a polynomial eigenvalue problem.

Outline of Presentation

Spectral Method

Eq.(5) can be reformulate as

$$\begin{bmatrix} 0 & 1 \\ \hat{M} & \hat{N} \end{bmatrix} \begin{bmatrix} \tilde{v} \\ \omega\tilde{v} \end{bmatrix} = \omega \begin{bmatrix} \tilde{v} \\ \omega\tilde{v} \end{bmatrix} \qquad (6)$$

where the operators $\hat{M}$ and $\hat{N}$ are defined as

$$\begin{aligned}
\hat{M} = &- \left[(1 - v_0^2)\frac{\partial^2}{\partial z^2} - \left(3v_0 + \frac{1}{v_0} \right) \frac{\partial v_0}{\partial z} \frac{\partial}{\partial z} \right. \\
&\left. - \left(1 - \frac{1}{v_0^2} \right) \left(\frac{\partial v_0}{\partial z} \right)^2 - \left(v_0 + \frac{1}{v_0} \right) \frac{\partial^2 v_0}{\partial z^2} \right] \\
\hat{N} = &- 2i \left(v_0 \frac{\partial}{\partial z} + \frac{\partial v_0}{\partial z} \right)
\end{aligned}$$

Then by discretizing operators $\hat{M}, \hat{N}$, this becomes an algebraic eigenvalue problem.

Spectral Pollution

- All modes of Eq.(5) with $v_0 = $ const are stable.
- Yet all discretization show unstable modes.


(a) Unfiltered eigenvalues.

(b) First few unfiltered eigenfunctions.

Figure 3: Finite difference discretization was used. Spurious modes occurs regardless of the resolution.

Filtering Spurious Modes

(a) Filtered eigenvalues.

(b) First few filtered eigenfunctions.

Figure 4: The spurious modes are changing under different resolution. We can filter them by convergence test.

Outline of Presentation

Existence of Singularity

Figure 5: Dirichlet boundary conditions are set at the two ends, all eigenfunctions are squeezed to the singular point.

Interesting Connection to Black Hole

- The sonic horizon is an exact sonic analogue of black hole horizon. [5]
- A quasi-1D fluid flow is ruled by [2]

$$\frac{\partial}{\partial t}(\rho A) + \frac{\partial}{\partial x}(\rho A v) = 0 \qquad (7)$$

$$\frac{\partial}{\partial t}(\rho A v) + \frac{\partial}{\partial x}[(\rho v^2 + p)A] = 0 \qquad (8)$$

$$\frac{\partial}{\partial t}\left(\frac{\rho v^2}{2} - \frac{p}{1-\gamma}A\right) + \frac{\partial}{\partial x}\left[\left(\frac{\rho v^2}{2} - \frac{\gamma}{1-\gamma}A\right)Av\right] = 0 \qquad (9)$$

In [2, 3], the acoustic analogue of tortoise coordinate is used to transform the above to Schrödinger-type equation,

$$x^* = c_{s0}\int [c_s(x)(1 - M(x)^2)]^{-1}dx$$

where c_{s0} denotes the stagnation speed of sound, $c_s = \mathrm{d}p/\mathrm{d}\rho$ is the local speed of sound and $M(x) = v(x)/c_s(x)$ is the Mach number.

Shooting Method

- Shooting method is employed.
- Initial values are obtained by expanding solution at the singularity.


Figure 6: The solutions crosses the singular point smoothly. All modes are stable.

Outline of Presentation

Future Work

- Investigate and interpret the instability of an accelerating flow with non-zero left boundary. See Fig.7
- Compare results to analytically solvable problems with similar configuration.

Figure 7: What is the physical interpretation of "non-zero" boundary value? How do we interpret these eigenvalues?

📄 F. F. Chen.
Introduction to Plasma Physics and Controlled Fusion.
Springer International Publishing, Cham, 2016.

📄 R. da Rocha.
Black hole acoustics in the minimal geometric deformation of a de
Laval nozzle.
The European Physical Journal C, 77(5):355, 5 2017.
[Online; accessed 2023-03-02].

📄 H. Furuhashi, Y. Nambu, and H. Saida.
Simulation of an acoustic black hole in a Laval nozzle.
Class. Quantum Grav., 23(17):5417–5438, Sept. 2006.

📄 I. D. Kaganovich, A. Smolyakov, Y. Raitses, E. Ahedo, I. G. Mikellides, B. Jorns, F. Taccogna, R. Gueroult, S. Tsikata, A. Bourdon, J.-P. Boeuf, M. Keidar, A. T. Powis, M. Merino, M. Cappelli, K. Hara, J. A. Carlsson, N. J. Fisch, P. Chabert, I. Schweigert, T. Lafleur, K. Matyash, A. V. Khrabrov, R. W. Boswell, and A. Fruchtman.
Physics of E × B discharges relevant to plasma propulsion and similar technologies.
*Physics of Plasmas*, 27(12):120601, 12 2020.

📄 W. Unruh.
Sonic analogue of black holes and the effects of high frequencies on black hole evaporation.
*Physical review. D, Particles and fields*, 51(6):2827–2838, 1995.

Outline of Presentation

(a) Dirichlet boundary, all modes are stable.

(b) Fixed-open boundary, all modes are stable.

Figure 8: Showing the first 5 eigenvalues. In the Dirichlet boundary case, all methods are close to the exact eigenvalues. Meanwhile, finite-difference method has higher accuracy than finite-element method in fixed-open case.

Constant Velocity Case - Supersonic

(a) Dirichlet boundary, filtered modes are stable.

(b) Fixed-open boundary, all modes are unstable.

Figure 9: Showing the first 5 eigenvalues. In the Dirichlet boundary case, all methods are close to the exact eigenvalues. Meanwhile, finite-difference method has higher accuracy than finite-element method in fixed-open case.

Subsonic Case

(a) Dirichlet boundary, all modes are stable.

(b) The ground mode is unstable, other modes are stable.

Figure 10: Showing the first 5 modes. It suggests that the subsonic flow in magnetic nozzle is stable.

Supersonic Case

(a) Dirichlet boundary, filtered modes are stable.

(b) Fixed-open boundary, all modes are unstable.

Figure 11: This suggests that the supersonic flow is stable if the boundary is Dirichlet and unstable if the boundary is left-fixed-right-open.

Accelerating Case

Figure 12: All modes are stable.