

CSCI 127: Introduction to Computer Science



hunter.cuny.edu/csci

Today's Topics



- Recap: Logical Expressions & Circuits
- Design: Cropping Images
- Accessing Formatted Data

Today's Topics



- **Recap: Logical Expressions & Circuits**
- Design: Cropping Images
- Accessing Formatted Data

Recap: Logical Operators

and

in1		in2	returns:
False	and	False	False
False	and	True	False
True	and	False	False
True	and	True	True


or

in1		in2	returns:
False	or	False	False
False	or	True	True
True	or	False	True
True	or	True	True

not

	in1	returns:
not	False	True
not	True	False

Logical Operators & Circuits




- Each logical operator (and, or, & not) can be used to join together expressions.


Example: in1 and in2

- Each logical operator (and, or, & not) has a corresponding logical circuit that can be used to join together inputs.

Examples: Logical Circuit





Examples: Logical Circuit



$(in1 \text{ and } in2) \text{ and } in3$

More Circuit Examples

Examples from last lecture:



Draw a circuit that corresponds to each logical expression:

- `not(in1 or in2)`
- `(in1 or in2) and (in1 or in3)`
- `(not(in1 and not in2)) or (in1 and (in2 and in3))`

Today's Topics



- Recap: Logical Expressions & Circuits
- **Design: Cropping Images**
- Accessing Formatted Data
- CS Survey: Astrophysics and astropy

Group Work: Design Question

From Final Exam, Fall 2017, V4, #6.



Design an algorithm that reads in an image and displays the lower left corner of the image.

Group Work: Design Question

From Final Exam, Fall 2017, V4, #6.



Design an algorithm that reads in an image and displays the lower left corner of the image.

Input:

Output:

Process:

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

How to approach this:

- Create a “To Do” list of what your program has to accomplish.

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

How to approach this:

- Create a “To Do” list of what your program has to accomplish.
- Read through the problem, and break it into “To Do” items.

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

How to approach this:

- Create a “To Do” list of what your program has to accomplish.
- Read through the problem, and break it into “To Do” items.
- Don't worry if you don't know how to do all the items you write down.

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

How to approach this:

- Create a “To Do” list of what your program has to accomplish.
- Read through the problem, and break it into “To Do” items.
- Don’t worry if you don’t know how to do all the items you write down.
- Example:

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

How to approach this:

- Create a “To Do” list of what your program has to accomplish.
- Read through the problem, and break it into “To Do” items.
- Don’t worry if you don’t know how to do all the items you write down.
- Example:
 - ① Import libraries.

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

How to approach this:

- Create a “To Do” list of what your program has to accomplish.
- Read through the problem, and break it into “To Do” items.
- Don’t worry if you don’t know how to do all the items you write down.
- Example:
 - ① Import libraries.
 - ② Ask user for an image name.

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

How to approach this:

- Create a “To Do” list of what your program has to accomplish.
- Read through the problem, and break it into “To Do” items.
- Don’t worry if you don’t know how to do all the items you write down.
- Example:
 - ① Import libraries.
 - ② Ask user for an image name.
 - ③ Read in image.

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

How to approach this:

- Create a “To Do” list of what your program has to accomplish.
- Read through the problem, and break it into “To Do” items.
- Don’t worry if you don’t know how to do all the items you write down.
- Example:
 - ① Import libraries.
 - ② Ask user for an image name.
 - ③ Read in image.
 - ④ Figure out size of image.

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

How to approach this:

- Create a “To Do” list of what your program has to accomplish.
- Read through the problem, and break it into “To Do” items.
- Don’t worry if you don’t know how to do all the items you write down.
- Example:
 - 1 Import libraries.
 - 2 Ask user for an image name.
 - 3 Read in image.
 - 4 Figure out size of image.
 - 5 Make a new image that’s half the height and half the width.

Group Work: Design Question

Design a program that asks the user for an image and then display the upper left quarter of the image. (First, design the pseudocode, and if time, expand to a Python program.)

How to approach this:

- Create a “To Do” list of what your program has to accomplish.
- Read through the problem, and break it into “To Do” items.
- Don’t worry if you don’t know how to do all the items you write down.
- Example:
 - 1 Import libraries.
 - 2 Ask user for an image name.
 - 3 Read in image.
 - 4 Figure out size of image.
 - 5 Make a new image that’s half the height and half the width.
 - 6 Display the new image.

Group Work: Design Question



- 1 Import libraries.

Group Work: Design Question



- 1 Import libraries.

```
import matplotlib.pyplot as plt  
import numpy as np
```


Group Work: Design Question



- ① Import libraries.

```
import matplotlib.pyplot as plt  
import numpy as np
```
- ② Ask user for an image name.

Group Work: Design Question



- ① Import libraries.

```
import matplotlib.pyplot as plt  
import numpy as np
```

- ② Ask user for an image name.

```
inF = input("Enter file name: ")
```

Group Work: Design Question



- ① Import libraries.

```
import matplotlib.pyplot as plt  
import numpy as np
```
- ② Ask user for an image name.

```
inF = input("Enter file name: ")
```
- ③ Read in image.

Group Work: Design Question



- 1 Import libraries.

```
import matplotlib.pyplot as plt  
import numpy as np
```

- 2 Ask user for an image name.

```
inF = input("Enter file name: ")
```

- 3 Read in image.

```
img = plt.imread(inF) #Read in image from inF
```

Group Work: Design Question



- ① Import libraries.

```
import matplotlib.pyplot as plt  
import numpy as np
```
- ② Ask user for an image name.

```
inF = input("Enter file name: ")
```
- ③ Read in image.

```
img = plt.imread(inF) #Read in image from inF
```
- ④ Figure out size of image.

Group Work: Design Question



- ① Import libraries.

```
import matplotlib.pyplot as plt  
import numpy as np
```
- ② Ask user for an image name.

```
inF = input("Enter file name: ")
```
- ③ Read in image.

```
img = plt.imread(inF) #Read in image from inF
```
- ④ Figure out size of image.

```
height = img.shape[0] #Get height  
width = img.shape[1] #Get width
```

Group Work: Design Question



- ① Import libraries.

```
import matplotlib.pyplot as plt  
import numpy as np
```
- ② Ask user for an image name.

```
inF = input("Enter file name: ")
```
- ③ Read in image.

```
img = plt.imread(inF) #Read in image from inF
```
- ④ Figure out size of image.

```
height = img.shape[0] #Get height  
width = img.shape[1] #Get width
```
- ⑤ Make a new image that's half the height and half the width.

Group Work: Design Question



- ① Import libraries.

```
import matplotlib.pyplot as plt  
import numpy as np
```
- ② Ask user for an image name.

```
inF = input("Enter file name: ")
```
- ③ Read in image.

```
img = plt.imread(inF) #Read in image from inF
```
- ④ Figure out size of image.

```
height = img.shape[0] #Get height  
width = img.shape[1] #Get width
```
- ⑤ Make a new image that's half the height and half the width.

```
img2 = img[height//2:, :width//2] #Crop to lower left corner
```


Group Work: Design Question



- ① Import libraries.

```
import matplotlib.pyplot as plt  
import numpy as np
```
- ② Ask user for an image name.

```
inF = input("Enter file name: ")
```
- ③ Read in image.

```
img = plt.imread(inF) #Read in image from inF
```
- ④ Figure out size of image.

```
height = img.shape[0] #Get height  
width = img.shape[1] #Get width
```
- ⑤ Make a new image that's half the height and half the width.

```
img2 = img[height//2:, :width//2] #Crop to lower left corner
```
- ⑥ Display the new image.

```
plt.imshow(img2) #Load our new image into pyplot  
plt.show() #Show the image
```

Today's Topics



- Recap: Logical Expressions & Circuits
- Design: Cropping Images
- **Accessing Formatted Data**
- CS Survey: Astrophysics and astropy

Structured Data

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- Common to have data structured in a spread sheet.

Structured Data

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- Common to have data structured in a spread sheet.
- In the example above, we have the first line that says “Undergraduate”.

Structured Data

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- Common to have data structured in a spread sheet.
- In the example above, we have the first line that says “Undergraduate”.
- Next line has the titles for the columns.

Structured Data

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- Common to have data structured in a spread sheet.
- In the example above, we have the first line that says “Undergraduate”.
- Next line has the titles for the columns.
- Subsequent lines have a college and attributes about the college.

Structured Data

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- Common to have data structured in a spread sheet.
- In the example above, we have the first line that says “Undergraduate”.
- Next line has the titles for the columns.
- Subsequent lines have a college and attributes about the college.
- Python has several ways to read in such data.

Structured Data


Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- Common to have data structured in a spread sheet.
- In the example above, we have the first line that says “Undergraduate”.
- Next line has the titles for the columns.
- Subsequent lines have a college and attributes about the college.
- Python has several ways to read in such data.
- We will use the popular Python Data Analysis Library (**Pandas**).

Structured Data

pandas

$$y_{it} = \beta' x_{it} + \mu_i + \epsilon_{it}$$




- We will use the popular Python Data Analysis Library (**Pandas**).

Structured Data

pandas

$$y_{it} = \beta' x_{it} + \mu_i + \epsilon_{it}$$




- We will use the popular Python Data Analysis Library (**Pandas**).
- Open source and freely available (part of anaconda distribution).

Structured Data

pandas

$$y_{it} = \beta' x_{it} + \mu_i + \epsilon_{it}$$




- We will use the popular Python Data Analysis Library (**Pandas**).
- Open source and freely available (part of anaconda distribution).
- See Lab 1 for directions on downloading it to your home machine.

Structured Data

pandas

$$y_{it} = \beta' x_{it} + \mu_i + \epsilon_{it}$$




- We will use the popular Python Data Analysis Library (**Pandas**).
- Open source and freely available (part of anaconda distribution).
- See Lab 1 for directions on downloading it to your home machine.
- If you can't install on your computer, it is supported in <https://repl.it/>

Structured Data

pandas

$$y_{it} = \beta' x_{it} + \mu_i + \epsilon_{it}$$



- We will use the popular Python Data Analysis Library (**Pandas**).
- Open source and freely available (part of anaconda distribution).
- See Lab 1 for directions on downloading it to your home machine.
- If you can't install on your computer, it is supported in <https://repl.it/>
- To use, add to the top of your program:

```
import pandas as pd
```

CSV Files

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- Excel .xls files have much extra formatting.

CSV Files

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- Excel .xls files have much extra formatting.
- The text file version is called **CSV** for comma separated values.

CSV Files

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- Excel .xls files have much extra formatting.
- The text file version is called **CSV** for comma separated values.
- Each row is a line in the file.

CSV Files

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- Excel .xls files have much extra formatting.
- The text file version is called **CSV** for comma separated values.
- Each row is a line in the file.
- Columns are separated by commas on each line.

CSV Files

Source: https://en.wikipedia.org/wiki/Demographics_of_New_York_City,
All population figures are consistent with present-day boundaries.
First census after the consolidation of the five boroughs,

```
Year,Manhattan,Brooklyn,Queens,Bronx,Staten Island>Total
1698,4937,2017,,727,7681
1771,21863,3623,,2847,28423
1790,33131,4549,6159,1781,3827,49447
1800,60515,5740,6642,1755,4563,79215
1810,96373,8303,7444,2267,5347,119734
1820,123706,11187,8246,2782,6135,152056
1830,202589,20535,9049,3023,7082,242278
1840,312710,47613,14480,5346,10965,391114
1850,515547,138882,18593,8032,15061,696115
1860,813669,279122,32903,23593,25492,1174779
1870,942292,419921,45468,37393,33029,1478103
1880,1164673,599495,56559,51980,38991,1911698
1890,1441216,838547,87050,88908,51693,2507414
1900,1850093,1166582,152999,200507,67021,3437202
1910,2331542,1634351,284041,430980,85969,4766883
1920,2284103,2018356,469042,732016,116531,5620048
1930,1867312,2560401,1079129,1265258,158346,6930446
1940,1889924,2698285,1297634,1394711,174441,7454995
1950,1960101,2738175,1550849,1451277,191555,7891957
1960,1698281,2627319,1809578,1424815,221991,7781984
1970,1539233,2602012,1986473,1471701,295443,7894862
1980,1428285,2230936,1891325,1168972,352121,7071639
1990,1487536,2300664,1951598,1203789,378977,7322564
2000,1537195,2465326,2229379,1332650,443728,8008278
2010,1585873,2504700,2230722,1385108,468730,8175133
2015,1644518,2636735,2339150,1455444,474558,8550405
```

nycHistPop.csv

Reading in CSV Files

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- To read in a CSV file: `myVar = pd.read_csv("myFile.csv")`

Reading in CSV Files

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- To read in a CSV file: `myVar = pd.read_csv("myFile.csv")`
- Pandas has its own type, **DataFrame**, that is perfect for holding a sheet of data.

Reading in CSV Files

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- To read in a CSV file: `myVar = pd.read_csv("myFile.csv")`
- Pandas has its own type, **DataFrame**, that is perfect for holding a sheet of data.
- Often abbreviated: `df`.

Reading in CSV Files

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

- To read in a CSV file: `myVar = pd.read_csv("myFile.csv")`
- Pandas has its own type, **DataFrame**, that is perfect for holding a sheet of data.
- Often abbreviated: `df`.
- It also has **Series**, that is perfect for holding a row or column of data.

Example: Reading in CSV Files

```
Source: https://en.wikipedia.org/wiki/Demographics_of_New_York_City,,,,,
All population figures are consistent with present-day boundaries,,,,,,
First census after the consolidation of the five boroughs,,,,,,
,,,,,
,,,,,
Year,Manhattan,Brooklyn,Queens,Bronx,Staten Island>Total
1698,4937,2017,,,727,7681
1771,21883,3623,,,2847,28423
1790,33131,45049,6159,1781,3827,49447
1800,40515,5740,6642,1755,4563,79215
1810,96373,40203,7444,2267,5347,119734
1820,123706,11187,8246,2782,6135,152056
1830,202589,20535,9049,3023,7082,242278
1840,312710,47613,14480,3344,10965,391114
1850,515547,138882,18593,8032,15061,696115
1860,813649,279122,32963,23593,25492,1174779
1870,942292,419921,45468,37393,33829,1470183
1880,1164673,599495,56559,51980,38991,1911690
1890,1441216,838547,87050,88908,51692,2507414
1900,1650093,1146582,152899,200507,67021,3437202
1910,2331542,1634351,284041,430980,85969,4768883
1920,2284103,2018296,469042,732018,116531,5420048
1930,1867312,2560461,1079129,1262558,159346,690446
1940,1889924,2698285,1297634,1394711,174441,7454995
1950,1940101,2738075,1500849,1452177,191555,78921957
1960,1698281,2627319,1809578,1424815,221993,7781984
1970,1539233,2602012,1986473,1471701,295443,7894862
1980,1428285,2230936,1801325,1168872,352121,7071439
1990,1487536,2300644,1951598,1203789,378977,7322564
2000,1537195,2465326,2229379,1332650,443728,8008278
2010,1494873,2504790,2230722,1385108,448735,81751123
2015,1644518,2636735,2339150,1455444,476558,8550405
```

nycHistPop.csv

In Lab 6

Example: Reading in CSV Files

```
import matplotlib.pyplot as plt
import pandas as pd
```

```
Source: https://en.wikipedia.org/wiki/Demographics_of_New_York_City,,,,,
All population figures are consistent with present-day boundaries,,,,,,
First census after the consolidation of the five boroughs,,,,,,
,,,,,
,,,,,
Year,Manhattan,Brooklyn,Queens,Bronx,Staten Island>Total
1698,4937,2017,,,727,7681
1771,21883,3623,,,2847,28423
1790,33131,4548,6159,1781,3827,49447
1800,60515,5740,6642,1755,4563,79215
1810,96373,8023,7444,2267,5347,119734
1820,123706,11187,8246,2782,6135,152056
1830,202589,20535,9049,3023,7082,242278
1840,312710,47613,14480,3344,10965,391114
1850,515547,138882,18593,8032,15061,696115
1860,813649,279122,32963,23593,25492,1174779
1870,942292,419921,45468,37393,33829,1470183
1880,1164673,599495,56559,51980,38991,1911698
1890,1441216,838547,87050,88908,51692,2507414
1900,1650093,1146582,152899,200507,67021,3437202
1910,2331542,1634351,284041,430980,85969,4766883
1920,2284103,2018296,469042,732018,116511,3420048
1930,1867312,2580461,1079129,1262558,159346,6930446
1940,1889924,2698285,1297634,1394711,174441,7454995
1950,1940101,2738275,1500849,1452177,191555,7893197
1960,1698281,2627319,1809578,1424815,221993,7781984
1970,1539233,2602012,1986473,1471701,295443,7894862
1980,1428285,2230936,1891325,1168872,352121,7071439
1990,1487536,2300644,1951598,1203789,378977,7322564
2000,1537195,2465326,2229379,1332650,443728,8008278
2010,1494873,2504790,2230722,1385108,448730,8175123
2015,1644518,2636735,2339150,1455444,476558,8550405
```

nycHistPop.csv

In Lab 6

Example: Reading in CSV Files

```
import matplotlib.pyplot as plt
import pandas as pd
```

```
pop = pd.read_csv("nycHistPop.csv",skiprows=5)
```

```
Source: https://en.wikipedia.org/wiki/Demographics_of_New_York_City,,,,,
All population figures are consistent with present-day boundaries,,,,,,
First census after the consolidation of the five boroughs,,,,,,
,,,,,
,,,,,
Year,Manhattan,Brooklyn,Queens,Bronx,Staten Island>Total
1698,4937,2017,,,727,7681
1771,21863,3623,,,2847,28423
1790,30131,4548,6159,1781,3827,49447
1800,40515,5740,6642,1755,4563,79215
1810,96373,8003,7444,2267,5347,119734
1820,123706,11187,8246,2782,6135,152056
1830,202589,20535,9049,3023,7082,242278
1840,312710,47613,14480,3344,10965,391114
1850,515547,138882,18593,8032,15061,696115
1860,813649,279122,32963,23593,25492,1174779
1870,942292,419921,45468,37393,33829,1470183
1880,1164673,599495,56559,51980,38991,1911690
1890,1441216,838547,87050,88908,51692,2507414
1900,1650093,1146582,152899,200507,67021,24372702
1910,2331542,1634351,284041,430980,85969,4766883
1920,2284103,2018264,469042,732016,116511,5620048
1930,1867312,2560461,1079129,1265258,159346,4590446
1940,1889924,2698285,1297634,1394711,174441,7454995
1950,1940101,2738075,1500849,1451277,191555,78991957
1960,1698281,2627319,1809578,1624815,221993,7781984
1970,1539233,2602012,1986473,1471701,295443,7894862
1980,1428285,2230936,1801325,1168872,352121,7071639
1990,1487536,2300644,1951598,1203789,378977,7322564
2000,1537195,2465326,2229379,1332650,443728,8006278
2010,1494873,2504790,2230722,1385108,448730,81751123
2015,1644518,2636735,2339150,1455444,476558,8550405
```

nycHistPop.csv

In Lab 6

Example: Reading in CSV Files

```
import matplotlib.pyplot as plt
import pandas as pd
```

```
pop = pd.read_csv("nycHistPop.csv", skiprows=5)
```

```
pop.plot(x="Year")
plt.show()
```

```
Source: https://en.wikipedia.org/wiki/Demographics_of_New_York_City,,,,,
All population figures are consistent with present-day boundaries,,,,,,
First census after the consolidation of the five boroughs,,,,,,
,,,,,
,,,,,
Year,Manhattan,Brooklyn,Queens,Bronx,Staten Island>Total
1698,4937,2017,,,727,7681
1771,21863,3623,,,2847,28423
1790,30131,4549,6159,1781,3827,49447
1800,40515,5740,6642,1755,4563,79215
1810,96373,9303,7444,2267,5347,119734
1820,123706,11187,8246,2782,6135,152056
1830,202589,20535,9049,3023,7082,242278
1840,312710,47613,14480,5344,10965,391114
1850,515547,138882,18593,8032,15061,696115
1860,813649,279122,32963,23593,25492,1174779
1870,942292,419921,45468,37393,33829,1470193
1880,1164673,599495,56559,51980,38991,1911690
1890,1441216,838547,87050,88908,51692,2507414
1900,1650093,1146582,152899,200507,67021,2437202
1910,2331542,1634351,284041,430980,85969,4766883
1920,2284103,2018264,469042,732016,116511,5620048
1930,1867312,2560461,1079129,1265258,159346,4590446
1940,1889924,2698285,1297634,1394711,174441,7454995
1950,1940101,2738075,1550849,1451277,191505,78991957
1960,1698281,2627319,1809578,1624815,221993,7781984
1970,1539233,2602012,1986473,1471701,295443,7894862
1980,1428285,2230936,1801325,1168872,352121,7071639
1990,1487536,2300644,1951598,1203789,378977,7322564
2000,1537195,2465326,2229379,1332650,443728,8006278
2010,1494873,2504760,2230722,1385108,448730,81751123
2015,1644518,2636735,2339150,1455444,476558,8550405
```

nycHistPop.csv

In Lab 6

Example: Reading in CSV Files

```
import matplotlib.pyplot as plt
import pandas as pd
```

```
pop = pd.read_csv("nycHistPop.csv", skiprows=5)
```


```
pop.plot(x="Year")
plt.show()
```

Source: https://en.wikipedia.org/wiki/Demographics_of_New_York_City,.....
All population figures are consistent with present-day boundaries.....
First census after the consolidation of the five boroughs.....


```
Year,Manhattan,Brooklyn,Queens,Bronx,Staten Island,Total
1698,4937,2017,,,727,7681
1771,21863,3623,,,2847,28423
1790,33131,4548,6159,1781,3827,49447
1800,40515,5740,6642,1755,4563,79215
1810,96373,9303,7444,2267,5347,119734
1820,123706,11187,8246,2782,6135,152056
1830,202589,20535,9049,3023,7082,242278
1840,312710,47613,14480,5344,10965,391114
1850,515547,138882,18593,8032,15061,696115
1860,813649,279122,32963,23593,25492,1174779
1870,942292,419921,45468,37393,33829,1470183
1880,1164673,599495,56559,51980,38991,1911698
1890,1441216,838547,87050,88908,51692,2507414
1900,1650093,1146582,152899,200507,67021,3437202
1910,2331542,1634351,284041,430989,85969,4768883
1920,2284103,2018256,469042,732016,116511,5620048
1930,1867312,2560451,1079129,1265588,159346,6906446
1940,1889924,2698285,1297634,1394711,174441,7454995
1950,1940101,2738275,1505049,1452177,291559,7892957
1960,1698281,2627319,1809578,1624815,221993,7781984
1970,1539233,2602012,1986473,1471701,295443,7094862
1980,1428285,2230936,1801325,1164872,352121,7071439
1990,1487536,2300644,1951598,1203789,378977,7322564
2000,1537195,2465326,2229379,1326450,443728,8006278
2010,1484873,2504760,2230722,1385108,468730,8175123
2015,1644518,2636735,2339155,1455444,476558,8550405
```

nycHistPop.csv

In Lab 6




Series in Pandas




- Series can store a column or row of a DataFrame.

Series in Pandas



- Series can store a column or row of a DataFrame.
- Example: `pop["Manhattan"]` is the Series corresponding to the column of Manhattan data.


Series in Pandas



- Series can store a column or row of a DataFrame.
- Example: `pop["Manhattan"]` is the Series corresponding to the column of Manhattan data.
- Example:

```
print("The largest number living in the Bronx is",  
pop["Bronx"].max())
```

Challenge:




Predict what the following will do:

- `print("Queens:", pop["Queens"].min())`
- `print("S I:", pop["Staten Island"].mean())`
- `print("S I:", pop["Staten Island"].std())`
- `pop.plot.bar(x="Year")`
- `pop.plot.scatter(x="Brooklyn", y= "Total")`
- `pop["Fraction"] = pop["Bronx"]/pop["Total"]`

Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`



Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".



Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".
- `print("S I:", pop["Staten Island"].mean())`



Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".
- `print("S I:", pop["Staten Island"].mean())`
Average of values in the column "Staten Island".



Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".
- `print("S I:", pop["Staten Island"].mean())`
Average of values in the column "Staten Island".
- `print("S I :", pop["Staten Island"].std())`



Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".
- `print("S I:", pop["Staten Island"].mean())`
Average of values in the column "Staten Island".
- `print("S I :", pop["Staten Island"].std())`
Standard deviation of values in the column "Staten Island".



Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".
- `print("S I:", pop["Staten Island"].mean())`
Average of values in the column "Staten Island".
- `print("S I :", pop["Staten Island"].std())`
Standard deviation of values in the column "Staten Island".
- `pop.plot.bar(x="Year")`



Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".
- `print("S I:", pop["Staten Island"].mean())`
Average of values in the column "Staten Island".
- `print("S I :", pop["Staten Island"].std())`
Standard deviation of values in the column "Staten Island".
- `pop.plot.bar(x="Year")`
Bar chart with x-axis "Year".



Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".
- `print("S I:", pop["Staten Island"].mean())`
Average of values in the column "Staten Island".
- `print("S I :", pop["Staten Island"].std())`
Standard deviation of values in the column "Staten Island".
- `pop.plot.bar(x="Year")`
Bar chart with x-axis "Year".
- `pop.plot.scatter(x="Brooklyn", y="Total")`



Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".
- `print("S I:", pop["Staten Island"].mean())`
Average of values in the column "Staten Island".
- `print("S I :", pop["Staten Island"].std())`
Standard deviation of values in the column "Staten Island".
- `pop.plot.bar(x="Year")`
Bar chart with x-axis "Year".
- `pop.plot.scatter(x="Brooklyn", y="Total")`
Scatter plot of Brooklyn versus Total values.



Solutions

Predict what the following will do:


- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".
- `print("S I:", pop["Staten Island"].mean())`
Average of values in the column "Staten Island".
- `print("S I :", pop["Staten Island"].std())`
Standard deviation of values in the column "Staten Island".
- `pop.plot.bar(x="Year")`
Bar chart with x-axis "Year".
- `pop.plot.scatter(x="Brooklyn", y= "Total")`
Scatter plot of Brooklyn versus Total values.
- `pop["Fraction"] = pop["Bronx"]/pop["Total"]`



Solutions

Predict what the following will do:

- `print("Queens:", pop["Queens"].min())`
Minimum value in the column with label "Queens".
- `print("S I:", pop["Staten Island"].mean())`
Average of values in the column "Staten Island".
- `print("S I :", pop["Staten Island"].std())`
Standard deviation of values in the column "Staten Island".
- `pop.plot.bar(x="Year")`
Bar chart with x-axis "Year".
- `pop.plot.scatter(x="Brooklyn", y="Total")`
Scatter plot of Brooklyn versus Total values.
- `pop["Fraction"] = pop["Bronx"]/pop["Total"]`
New column with the fraction of population that lives in the Bronx.



Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,800	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

`cunyF2016.csv`

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,800	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

`cunyF2016.csv`

Solution:

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,800	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

`cunyF2016.csv`

Solution:

- 1 *Include pandas & pyplot libraries.*

Challenge:

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,800	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

cunyF2016.csv

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Solution:

- 1 *Include `pandas` & `pyplot` libraries.*
- 2 *Read in the CSV file.*

Challenge:

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,800	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

cunyF2016.csv

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Solution:

- 1 *Include `pandas` & `pyplot` libraries.*
- 2 *Read in the CSV file.*
- 3 *Set up a scatter plot.*

Challenge:

Undergraduate			
College	Full-time	Part-time	Total
Baruch	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,831	2,843	12,674
Lehman	6,800	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

cunyF2016.csv

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Solution:

- 1 *Include `pandas` & `pyplot` libraries.*
- 2 *Read in the CSV file.*
- 3 *Set up a scatter plot.*
- 4 *Display plot.*

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Borough	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,851	2,943	12,814
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

`cunyF2016.csv`

Solution:

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Borough	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,851	2,943	12,874
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

`cunyF2016.csv`

Solution:

- 1 Include *pandas* & *pyplot* libraries.

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Borough	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,851	2,943	12,874
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

`cunyF2016.csv`

Solution:

- 1 *Include pandas & pyplot libraries.*
`import matplotlib.pyplot as plt`
`import pandas as pd`

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Borough	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,851	2,943	12,874
Lehman	8,600	4,720	13,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

`cunyF2016.csv`

Solution:

- 1 *Include pandas & pyplot libraries.*
`import matplotlib.pyplot as plt`
`import pandas as pd`
- 2 *Read in the CSV file.*

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Borough	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,851	2,943	12,874
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Statens Island	9,584	2,948	12,532
York	5,066	3,192	8,258

`cunyF2016.csv`

Solution:

- 1 *Include pandas & pyplot libraries.*

```
import matplotlib.pyplot as plt  
import pandas as pd
```

- 2 *Read in the CSV file.*

```
pop=pd.read_csv("cunyF2016.csv",skiprows=1)
```

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Borough	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	9,851	2,943	12,874
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

`cunyF2016.csv`

Solution:

- 1 *Include pandas & pyplot libraries.*
`import matplotlib.pyplot as plt`
`import pandas as pd`
- 2 *Read in the CSV file.*
`pop=pd.read_csv("cunyF2016.csv",skiprows=1)`
- 3 *Set up a scatter plot.*

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Borough	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,590	16,723
John Jay	9,851	2,943	12,674
Lehman	6,600	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,066	3,192	8,258

`cunyF2016.csv`

Solution:

- 1 *Include pandas & pyplot libraries.*
`import matplotlib.pyplot as plt`
`import pandas as pd`
- 2 *Read in the CSV file.*
`pop=pd.read_csv("cunyF2016.csv",skiprows=1)`
- 3 *Set up a scatter plot.*
`pop.plot.scatter(x="Full-time",y="Part-time")`

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Borough	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,590	16,723
John Jay	8,851	2,943	12,674
Lehman	8,690	4,720	11,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,086	3,192	8,258

`cunyF2016.csv`

Solution:

- 1 *Include pandas & pyplot libraries.*
`import matplotlib.pyplot as plt`
`import pandas as pd`
- 2 *Read in the CSV file.*
`pop=pd.read_csv("cunyF2016.csv",skiprows=1)`
- 3 *Set up a scatter plot.*
`pop.plot.scatter(x="Full-time",y="Part-time")`
- 4 *Display plot.*

Challenge:

Write a complete Python program that reads in the file, `cunyF2016.csv`, and produces a scatter plot of full-time versus part-time enrollment.

Undergraduate			
College	Full-time	Part-time	Total
Borough	11,288	3,922	15,210
Brooklyn	10,198	4,208	14,406
City	10,067	3,250	13,317
Hunter	12,223	4,500	16,723
John Jay	8,851	2,943	12,674
Lehman	8,600	4,720	13,320
Medgar Evers	4,760	2,059	6,819
NYCCT	10,912	6,370	17,282
Queens	11,693	4,633	16,326
Staten Island	9,584	2,948	12,532
York	5,086	3,192	8,258

`cunyF2016.csv`

Solution:

- 1 *Include pandas & pyplot libraries.*
`import matplotlib.pyplot as plt`
`import pandas as pd`
- 2 *Read in the CSV file.*
`pop=pd.read_csv("cunyF2016.csv",skiprows=1)`
- 3 *Set up a scatter plot.*
`pop.plot.scatter(x="Full-time",y="Part-time")`
- 4 *Display plot.*
`plt.show()`

groupby()

Sometimes you have **recurring values in a column** and you want to examine the data for a particular value.

Rain in Australia				
Date	Location	MinTemp	MaxTemp	Rainfall
12/1/08	Albury	13.4	22.9	0.6
5/22/15	BadgenysCree	11	15.6	1.6
3/17/11	BadgenysCree	18.1	25.8	16.6
7/27/10	Cobar	5.3	17.2	0
9/5/10	Moree	12.1	19.8	23.4
1/23/12	CoffsHarbour	20	24.4	28
7/15/11	Moree	2.8	19	0
1/28/10	Newcastle	22.2	28	0
12/2/15	Moree	20.1	32	4.8
* * *				

AustraliaRain.csv

groupby()

Sometimes you have **recurring values in a column** and you want to examine the data for a particular value.

For example, to find the average rainfall at each location:

Rain in Australia				
Date	Location	MinTemp	MaxTemp	Rainfall
12/1/08	Albury	13.4	22.9	0.6
5/22/15	BadgenysCree	11	15.6	1.6
3/17/11	BadgenysCree	18.1	25.8	16.6
7/27/10	Cobar	5.3	17.2	0
9/5/10	Moree	12.1	19.8	23.4
1/23/12	CoffsHarbour	20	24.4	28
7/15/11	Moree	2.8	19	0
1/28/10	Newcastle	22.2	28	0
12/2/15	Moree	20.1	32	4.8
* * *				

AustraliaRain.csv

groupby()

Sometimes you have **recurring values in a column** and you want to examine the data for a particular value.

For example, to find the average rainfall at each location:

Rain in Australia				
Date	Location	MinTemp	MaxTemp	Rainfall
12/1/08	Albury	13.4	22.9	0.6
5/22/15	BadgenysCree	11	15.6	1.6
3/17/11	BadgenysCree	18.1	25.8	16.6
7/27/10	Cobar	5.3	17.2	0
9/5/10	Moree	12.1	19.8	23.4
1/23/12	CoffsHarbour	20	24.4	28
7/15/11	Moree	2.8	19	0
1/28/10	Newcastle	22.2	28	0
12/2/15	Moree	20.1	32	4.8
* * *				

AustraliaRain.csv

- 1 *Import libraries.*
`import pandas as pd`

groupby()

Sometimes you have **recurring values in a column** and you want to examine the data for a particular value.

For example, to find the average rainfall at each location:

Rain in Australia				
Date	Location	MinTemp	MaxTemp	Rainfall
12/1/08	Albury	13.4	22.9	0.6
5/22/15	BadgenysCree	11	15.6	1.6
3/17/11	BadgenysCree	18.1	25.8	16.6
7/27/10	Cobar	5.3	17.2	0
9/5/10	Moree	12.1	19.8	23.4
1/23/12	CoffsHarbour	20	24.4	28
7/15/11	Moree	2.8	19	0
1/28/10	Newcastle	22.2	28	0
12/2/15	Moree	20.1	32	4.8
...				

AustraliaRain.csv

- 1 *Import libraries.*
`import pandas as pd`
- 2 *Read in the CSV file.*
`rain =
pd.read_csv("AustraliaRain.csv", skiprows=1)`

groupby()

Sometimes you have **recurring values in a column** and you want to examine the data for a particular value.

For example, to find the average rainfall at each location:

Rain in Australia				
Date	Location	MinTemp	MaxTemp	Rainfall
12/1/08	Albury	13.4	22.9	0.6
5/22/15	BadgenysCree	11	15.6	1.6
3/17/11	BadgenysCree	18.1	25.8	16.6
7/27/10	Cobar	5.3	17.2	0
9/5/10	Moree	12.1	19.8	23.4
1/23/12	CoffsHarbour	20	24.4	28
7/15/11	Moree	2.8	19	0
1/28/10	Newcastle	22.2	28	0
12/2/15	Moree	20.1	32	4.8
...				

AustraliaRain.csv

- 1 *Import libraries.*
`import pandas as pd`
- 2 *Read in the CSV file.*
`rain =
pd.read_csv("AustraliaRain.csv", skiprows=1)`
- 3 *Group the data by location.*
`groupAvg =
rain.groupby("Location")`

groupby()

Sometimes you have **recurring values in a column** and you want to examine the data for a particular value.

For example, to find the average rainfall at each location:

Rain in Australia				
Date	Location	MinTemp	MaxTemp	Rainfall
12/1/08	Albury	13.4	22.9	0.6
5/22/15	BadgenysCree	11	15.6	1.6
3/17/11	BadgenysCree	18.1	25.8	16.6
7/27/10	Cobar	5.3	17.2	0
9/5/10	Moree	12.1	19.8	23.4
1/23/12	CoffsHarbour	20	24.4	28
7/15/11	Moree	2.8	19	0
1/28/10	Newcastle	22.2	28	0
12/2/15	Moree	20.1	32	4.8
* * *				

AustraliaRain.csv

- 1 *Import libraries.*
`import pandas as pd`
- 2 *Read in the CSV file.*
`rain =
pd.read_csv("AustraliaRain.csv", skiprows=1)`
- 3 *Group the data by location.*
`groupAvg =
rain.groupby("Location")`
- 4 *Print the average rainfall at each location.*
`print(groupAvg["Rainfall"].mean())`

groupby()

Rain in Australia				
Date	Location	MinTemp	MaxTemp	Rainfall
12/1/08	Albury	13.4	22.9	0.6
5/22/15	BadgerysCree	11	15.6	1.6
3/17/11	BadgerysCree	18.1	25.8	16.6
7/27/10	Cobar	5.3	17.2	0
9/5/10	Moree	12.1	19.8	23.4
1/23/12	CoffsHarbour	20	24.4	28
7/15/11	Moree	2.8	19	0
1/28/10	Newcastle	22.2	28	0
12/2/15	Moree	20.1	32	4.8
...				

AustraliaRain.csv

Adelaide	1.572185
Albany	2.255073
Albury	1.925710
AliceSprings	0.869355
BadgerysCreek	2.207925
Ballarat	1.688830
Bendigo	1.621452
Brisbane	3.160536
Cairns	5.765317
Canberra	1.735038
Cobar	1.129262
CoffsHarbour	5.054592
Darlington	2.148554

Sometimes you have **recurring values in a column** and you want to examine the data for a particular value.

For example, to find the average rainfall at each location:

- 1 *Import libraries.*
`import pandas as pd`
- 2 *Read in the CSV file.*
`rain =
pd.read_csv("AustraliaRain.csv", skiprows=1)`
- 3 *Group the data by location.*
`groupAvg =
rain.groupby("Location")`
- 4 *Print the average rainfall at each location.*
`print(groupAvg["Rainfall"].mean())`

get_group()

Sometimes you have **recurring values in a column** and you want to examine the data for a particular value.

For example, to find the average rainfall at one location, e.g. Albury:

Rain in Australia				
Date	Location	MinTemp	MaxTemp	Rainfall
12/1/08	Albury	13.4	22.9	0.6
6/22/15	BadgersCree	11	15.6	1.6
3/17/11	BadgersCree	18.1	25.8	16.6
7/27/10	Cobar	5.3	17.2	0
9/5/10	Moree	12.1	19.8	23.6
1/23/12	CoffinHarbour	20	24.4	20
7/15/11	Moree	2.8	19	0
1/28/10	Newcastle	22.2	28	0
12/9/15	Moree	20.1	32	4.6
...				

AustraliaRain.csv

```
1.9257104647275156
```

get_group()

Sometimes you have **recurring values in a column** and you want to examine the data for a particular value.

For example, to find the average rainfall at one location, e.g. Albury:

Rain in Australia				
Date	Location	MinTemp	MaxTemp	Rainfall
12/1/08	Albury	13.4	22.9	0.6
5/22/15	BadgersCree	11	15.6	1.6
3/17/11	BadgersCree	18.1	25.8	16.6
7/27/10	Cobar	5.3	17.2	0
9/3/10	Moree	12.1	19.8	23.6
1/23/12	CoffinHarbour	20	24.4	20
7/15/11	Moree	2.8	19	0
1/28/10	Newcastle	22.2	28	0
12/9/15	Moree	20.1	32	4.6
...				

AustraliaRain.csv

```
1.9257104647275156
```

- 1 *Import libraries.*
`import pandas as pd`
- 2 *Read in the CSV file.*
`rain =
pd.read_csv("AustraliaRain.csv", skiprows=1)`
- 3 *Group the data by location get data for group Albury.*
`AlburyAvg =
rain.groupby("Location").get_group("Albury")`

get_group()

Sometimes you have **recurring values in a column** and you want to examine the data for a particular value.

For example, to find the average rainfall at one location, e.g. Albury:

Rain in Australia				
Date	Location	MinTemp	MaxTemp	Rainfall
12/1/08	Albury	13.4	22.9	0.6
5/22/15	BadgersCree	11	15.6	1.6
3/17/11	BadgersCree	18.1	25.8	16.6
7/27/10	Cobar	5.3	17.2	0
9/30/10	Moree	12.1	19.8	23.6
1/23/12	CoffinHarbour	20	24.4	20
7/15/11	Moree	2.8	19	0
1/28/10	Newcastle	22.2	28	0
12/01/15	Moree	20.1	32	4.6
...				

AustraliaRain.csv

1.9257104647275156

- 1 *Import libraries.*
`import pandas as pd`
- 2 *Read in the CSV file.*
`rain =
pd.read_csv("AustraliaRain.csv", skiprows=1)`
- 3 **Group the data by location get data for group Albury.**
`AlburyAvg =
rain.groupby("Location").get_group("Albury")`
- 4 *Print the average rainfall in Albury.*
`print(AlburyAvg["Rainfall"].mean())`

Design Challenge

Stars						
Temperature (K)	Luminosity(L/L _o)	Radius(R/R _o)	Absolute magnitude(M _v)	Star type	Star color	Spectral Class
3068	0.0024	0.17	16.12	Brown Dwarf	Red	M
25000	0.056	0.0084	10.58	White Dwarf	Blue White	B
2650	0.00069	0.11	17.45	Brown Dwarf	Red	M
11790	0.00015	0.011	12.59	White Dwarf	Yellowish White	F
15276	1136	7.2	-1.97	Main Sequence	Blue-white	B
5800	0.81	0.9	5.05	Main Sequence	yellow-white	F
16500	0.013	0.014	11.89	White Dwarf	Blue White	B
3192	0.00362	0.1967	13.53	Red Dwarf	Red	M
6380	1.35	0.98	2.93	Main Sequence	yellow-white	F
3834	272000	1183	-9.2	Hypergiant	Red	M

- Design an algorithm that:
 - ▶ Prints the luminosity of the brightest star.
 - ▶ Prints the temperature of the coldest star.
 - ▶ Prints the average radius of a Hypergiant.

Design Challenge - Solution

Stars						
Temperature (K)	Luminosity(L/L _o)	Radius(R/R _o)	Absolute magnitude(M _v)	Star type	Star color	Spectral Class
3068	0.0024	0.17	16.12	Brown Dwarf	Red	M
25000	0.056	0.0084	10.58	White Dwarf	Blue White	B
2650	0.00069	0.11	17.45	Brown Dwarf	Red	M
11790	0.00015	0.011	12.59	White Dwarf	Yellowish White	F
15276	1136	7.2	-1.97	Main Sequence	Blue-white	B
5800	0.81	0.9	5.05	Main Sequence	yellow-white	F
16500	0.013	0.014	11.89	White Dwarf	Blue White	B
3192	0.00362	0.1967	13.53	Red Dwarf	Red	M
6380	1.35	0.98	2.93	Main Sequence	yellow-white	F
3834	272000	1183	-9.2	Hypergiant	Red	M

- **Libraries:** pandas

Design Challenge - Solution

Stars						
Temperature (K)	Luminosity(L/L _o)	Radius(R/R _o)	Absolute magnitude(M _v)	Star type	Star color	Spectral Class
3068	0.0024	0.17	16.12	Brown Dwarf	Red	M
25000	0.056	0.0084	10.58	White Dwarf	Blue White	B
2650	0.00069	0.11	17.45	Brown Dwarf	Red	M
11790	0.00015	0.011	12.59	White Dwarf	Yellowish White	F
15276	1136	7.2	-1.97	Main Sequence	Blue-white	B
5800	0.81	0.9	5.05	Main Sequence	yellow-white	F
16500	0.013	0.014	11.89	White Dwarf	Blue White	B
3192	0.00362	0.1967	13.53	Red Dwarf	Red	M
6380	1.35	0.98	2.93	Main Sequence	yellow-white	F
3834	272000	1183	-9.2	Hypergiant	Red	M

- **Libraries:** pandas
- **Process:**
 - ▶ Print **max** of '**Luminosity**' column

Design Challenge - Solution

Stars						
Temperature (K)	Luminosity(L/L _o)	Radius(R/R _o)	Absolute magnitude(M _v)	Star type	Star color	Spectral Class
3068	0.0024	0.17	16.12	Brown Dwarf	Red	M
25000	0.056	0.0084	10.58	White Dwarf	Blue White	B
2650	0.00069	0.11	17.45	Brown Dwarf	Red	M
11790	0.00015	0.011	12.59	White Dwarf	Yellowish White	F
15276	1136	7.2	-1.97	Main Sequence	Blue-white	B
5800	0.81	0.9	5.05	Main Sequence	yellow-white	F
16500	0.013	0.014	11.89	White Dwarf	Blue White	B
3192	0.00362	0.1967	13.53	Red Dwarf	Red	M
6380	1.35	0.98	2.93	Main Sequence	yellow-white	F
3834	272000	1183	-9.2	Hypergiant	Red	M

- **Libraries:** pandas
- **Process:**
 - ▶ Print **max** of '**Luminosity**' column
 - ▶ Print **min** of '**Temperature**' column

Design Challenge - Solution

Stars						
Temperature (K)	Luminosity(L/L _o)	Radius(R/R _o)	Absolute magnitude(M _v)	Star type	Star color	Spectral Class
3068	0.0024	0.17	16.12	Brown Dwarf	Red	M
25000	0.056	0.0084	10.58	White Dwarf	Blue White	B
2650	0.00069	0.11	17.45	Brown Dwarf	Red	M
11790	0.00015	0.011	12.59	White Dwarf	Yellowish White	F
15276	1136	7.2	-1.97	Main Sequence	Blue-white	B
5800	0.81	0.9	5.05	Main Sequence	yellow-white	F
16500	0.013	0.014	11.89	White Dwarf	Blue White	B
3192	0.00362	0.1967	13.53	Red Dwarf	Red	M
6380	1.35	0.98	2.93	Main Sequence	yellow-white	F
3834	272000	1183	-9.2	Hypergiant	Red	M

- **Libraries:** pandas
- **Process:**
 - ▶ Print **max** of '**Luminosity**' column
 - ▶ Print **min** of '**Temperature**' column
 - ▶ **groupby** '**Star Type**' and take **averages**, then print **max** of '**Radius**' column

Design Challenge - Solution

Stars						
Temperature (K)	Luminosity(L/L _o)	Radius(R/R _o)	Absolute magnitude(M _v)	Star type	Star color	Spectral Class
3068	0.0024	0.17	16.12	Brown Dwarf	Red	M
25000	0.056	0.0084	10.58	White Dwarf	Blue White	B
2650	0.00069	0.11	17.45	Brown Dwarf	Red	M
11790	0.00015	0.011	12.59	White Dwarf	Yellowish White	F
15276	1136	7.2	-1.97	Main Sequence	Blue-white	B
5800	0.81	0.9	5.05	Main Sequence	yellow-white	F
16500	0.013	0.014	11.89	White Dwarf	Blue White	B
3192	0.00362	0.1967	13.53	Red Dwarf	Red	M
6380	1.35	0.98	2.93	Main Sequence	yellow-white	F
3834	272000	1183	-9.2	Hypergiant	Red	M

- **Libraries:** pandas
- **Process:**
 - ▶ Print **max** of '**Luminosity**' column
 - ▶ Print **min** of '**Temperature**' column
 - ▶ **groupby** '**Star Type**' and take **averages**, then print **max** of '**Radius**' column
 - ▶ OR **groupby** '**Star Type**' and **get group** '**Hypergiant**' to print **average** '**Radius**'

Design Challenge - Code

- **Libraries:** pandas

```
import pandas as pd  
stars = pd.read_csv("Stars.csv")
```

Design Challenge - Code

- **Libraries:** pandas

```
import pandas as pd  
stars = pd.read_csv("Stars.csv")
```

- **Process:**

- ▶ Print **max** of '**Luminosity**' column

```
print(stars["Luminosity(L/Lo)"].max())
```

Design Challenge - Code

- **Libraries:** pandas

```
import pandas as pd
stars = pd.read_csv("Stars.csv")
```

- **Process:**

- ▶ Print **max** of '**Luminosity**' column

```
print(stars["Luminosity(L/Lo)"].max())
```

- ▶ Prints **min** of '**Temperature**' column and store it in temp variable

```
print( stars["Temperature (K)"].min())
```

Design Challenge - Code

- **Libraries:** pandas

```
import pandas as pd
stars = pd.read_csv("Stars.csv")
```

- **Process:**

- ▶ Print **max** of '**Luminosity**' column

```
print(stars["Luminosity(L/Lo)"].max())
```

- ▶ Prints **min** of '**Temperature**' column and store it in temp variable

```
print( stars["Temperature (K)"].min())
```

- ▶ **groupby** '**Star Type**' and take **averages**, then print **max of 'Radius'** column

```
print(stars.groupby("Star type")\
.mean()["Radius(R/Ro)"].max())
```

Design Challenge - Code

- **Libraries:** pandas

```
import pandas as pd  
stars = pd.read_csv("Stars.csv")
```

- **Process:**

- ▶ Print **max** of '**Luminosity**' column

```
print(stars["Luminosity(L/Lo)"].max())
```

- ▶ Prints **min** of '**Temperature**' column and store it in temp variable

```
print( stars["Temperature (K)"].min())
```

- ▶ OR **groupby** '**Star Type**' and **get group** '**Hypergiant**' to print **average** '**Radius**'

```
print(stars.groupby("Star type")\  
.get_group("Hypergiant").mean()["Radius(R/Ro)"])
```

Recap

- Recap: Logical Expressions & Circuits



Recap

- Recap: Logical Expressions & Circuits
- Accessing Formatted Data:
 - ▶ Pandas library has elegant solutions for accessing & analyzing structured data.

pandas



$y_i = \beta^T x_i + \mu_i + \epsilon_i$

Recap


- Recap: Logical Expressions & Circuits
- Accessing Formatted Data:
 - ▶ Pandas library has elegant solutions for accessing & analyzing structured data.
 - ▶ Can manipulate individual columns or rows ('Series').



Recap


pandas

$y_i = \beta_0 x_{i0} + \beta_1 x_{i1} + \epsilon_i$



- Recap: Logical Expressions & Circuits
- Accessing Formatted Data:
 - ▶ Pandas library has elegant solutions for accessing & analyzing structured data.
 - ▶ Can manipulate individual columns or rows ('Series').
 - ▶ Has useful functions for the entire sheet ('DataFrame') such as plotting.

Practice Quiz & Final Questions



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - ▶ write as much you can for 60 seconds;
 - ▶ followed by answer; and
 - ▶ repeat.
- Past exams are on the webpage (under [Final Exam Information](#)).
- We're starting with Fall 2019, Version 2.

Lecture Slips & Writing Boards



- Hand your lecture slip to a UTA.
- Return writing boards as you leave.