### CSci 127: Introduction to Computer Science



hunter.cuny.edu/csci

## Two Dimensional Array Slicing

```
import numpy as np
2
 numRows = 6
 numCols = 6
 a = np. zeros ((numRows, numCols))
 #create a table with 6 rows and 6 columns,
 #each element is initialized to be zero.
 #Do not forget parentheses around
 #numRows, numCols.
```

2 / 64

# Two Dimensional Array Slicing: II

CSci 127 (Hunter)

```
for i in range(numRows):
      for j in range(numCols):
          a[i, j] = i*10 + j
10
  #range(numRows) returns [0, 1, 2, 3, 4, 5],
11
  #where outer loop variable i chooses from.
12
 #When i is 0, run
13
       for j in range(numCols):
14
           a[i, j] = i*10 + j
  #
15
 #When i is 1, run
16
       for j in range(numCols):
17
           a[i, j] = i*10 + j
18
  #The last round of i is 5.
19
```

Lecture 7

25 Oct 2022

3 / 64

# Two Dimensional Array Slicing: III

```
for i in range(numRows):
      for j in range(numCols):
21
          print ("%3i"%(a[i, j]), end="")
22
          #"%3i"%(a[i, j]) prints a[i, j] --
23
          #element of a at ith row and
24
          #jth column -- as an 3-digit int.
25
          #"%3i" is a place holder and is
26
             filled by a[i, j].
          #If a[i, j] does not have 3 digits,
27
          #pad space(s) to the left.
28
          #end="" print w/o a new line.
29
30
```

print () #print a new line after each row ... 31 CSci 127 (Hunter) Lecture 7 25 Oct 2022

## Two Dimensional Array Slicing: III

print (a[0, 3:5])

row	0	1	2	3	4	5	
0	0	1	2	3	4	5	
1	10	11	12	13	14	15	
2	20	21	22	23	24	25	
3	30	31	2 12 22 32 42 52	33	34	35	
4	40	41	42	43	44	45	
5	50	51	52	53	54	55	

## Two Dimensional Array Slicing: III

print(a[0, 3:5])

<ul><li>COI</li></ul>							\ \ (	JOI I						
row	0	1	2	3	4	5	row		0	1	2	3	4	5
0	0	1	2	3	4	5		0	0	1	2	(3	4	5
1	10	11	12	13	14	15		1	10	11	12	13	14	15
2	20	21	22	23	24	25		2	20	21	22	23	24	25
3	30	31	32	33	34	35		3	30	31	32	33	34	35
4	40	41	42	43	44	45		4	40	41	42	43	44	45
5	50	51	52	53	54	55		5	50	51	52	53	54	55

\_ col |

print

[3. 4.]

# Two Dimensional Array Slicing: IV

print (a[4:, 4:])

row	0	1	2	3	4	5
0	0	1	2	3	4	5
1	10	11	12	13	14	15
2	20	21	22	23	24	25
3	30	31	32	33	34	35
4	40	41	42	43	44	45
5	50	51	2 12 22 32 42 52	53	54	55

# Two Dimensional Array Slicing: IV

print (a[4:, 4:])

row	0	1	2	3	4	5		row	0	1	2	3	4	5
0	0	1	2	3	4	5	_	0	0	1	2	3	4	5
1	10	11	12	13	14	15		1	10	11	12	13	14	15
2	20	21	22	23	24	25		2	20	21	22	23	24	25
3	30	31	32	33	34	35		3	30	31	32	33	34	35
4	40	41	42	43	44	45		4	40	41	42	43	44	45
5	50	51	52	53	54	55		5	50	51	52	53	54	55

∕ col │

#### Print out

```
[[44. 45.]
[54. 55.]]
```

∕ col

## Two Dimensional Array Slicing: V

print (a[:, 2])

row	0	1	2	3	4	5
0	0	1	2	3	4	5
1	10	11	12	13	14	15
2	20	21	22	23	4 14 24 34 44 54	25
3	30	31	32	33	34	35
4	40	41	42	43	44	45
5	50	51	52	53	54	55

CSci 127 (Hunter)

# Two Dimensional Array Slicing: V

print (a[:, 2])

r	ow	0	1	2	3	4	5	row	0	1	2	3	4	5
-	0	0	1	2	3	4	5	0	0	1	2	3	4	5
	1	10	11	12	13	14	15	1	10	11	12	13	14	15
	2	20	21	22	23	24	25	2	20	21	22	23	24	25
	3	30	31	32	33	34	35	3	30	31	32	33	34	35
	4	40	41	42	43	44	45	4	40	41	<b>4</b> 2	43	44	45
	5	50	51	52	53	54	55	5	50	51	52	53	54	55

Print out

CSci 127 (Hunter)

[ 2. 12. 22. 32. 42. 52.]

## Two Dimensional Array Slicing: VI

print (a[2::2, ::2])

```
0
   10
                13
                    14
   20
       21
            22
                23
                    24
                        25
3
   30
       31
                33
           32
                    34
                        35
   40
       41
           42
                43
                    44
                        45
       51
            52
   50
                53
                    54
                        55
```

CSci 127 (Hunter)

# Two Dimensional Array Slicing: VI

<sub>5</sub> print (a[2::2, ::2])

	0	1	2	3	4	5		0	1	2	3	4	5
0	0	1	2	3	4	5	0	0	1	2	3	4	5
1	10	11	12	13	14	15	1	10	11	12	13	14	15
2	20	21	22	23	24	25	2	20	21	22	23	24	25
3	30	31	32	33	34	35				32			
4	40	41	42	43	44	45	4	40	41	42	43	44	45
5	50	51	52	53	54	55	5	50	51	52	53	54	55

### print

```
[[20. 22. 24.]
[40. 42. 44.]]
```

8 / 64

## Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

CSci 127 (Hunter)

## Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data


### Image and Array

```
import matplotlib.pyplot as plt
 import numpy as np
3
 height= 20
 width = 30
6
 #An image is an array with height, width and
 |#depth 3 for r(ed) g(reen) b(lue)
 img = np.zeros((height, width, 3))
 img[:height//2, :width//2, 0] = 1
 #which does this statement do? Same as
 |\#img[:height//2, :width//2] = [1,0,0]
```

# Image and Array: II

```
img[height//2:, :width//2, 1] = 1
  #which does this statement do? Same as
 |\#img[height//2:, :width//2] = [0,1,0]
16
  img[:height//2:2, width//2:, 2] = 1
17
  #What does this statement do?
18
19
  img[height//2:, width//2::2] = [1, 1, 0]
20
  #What does this statement do?
21
22
  plt.imshow(img)
 plt.show()
```

### output for the above program



13 / 64

Crop an image to select the top quarter (upper left corner)



```
import matplotlib.pyplot as plt
 import numpy as np
3
 img = plt.imread("csBridge.png")
 height = img.shape[0]
 |width = img.shape[1]
 |img2 = img[0:height//2, 0:width//2, :]
 #img2 is top left of img. Same as
 \#img2 = img[:height//2, :width//2].
 plt.imshow(img2)
```

12

plt.show()

plt.imsave("top\_left\_csBridge=png", = img2) = -> QCC 127 (Hunter) Lecture 7 25 Oct 2022 15 / 64


```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```




```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



• How would you select the lower left corner?

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



• How would you select the lower left corner? img2 = img[height//2:, :width//2]

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner?
   img2 = img[height//2:, :width//2]
- How would you select the upper right corner?

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[:height//2, width//2:]

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```




- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[:height//2, width//2:]
- How would you select the lower right corner?

18 / 64

CSci 127 (Hunter) Lecture 7 25 Oct 2022

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[:height//2, width//2:]
- How would you select the lower right corner? img2 = img[height//2:, width//2:]

## Today's Topics




- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

### Modularity



### Modularity



 Functions are a way to break code into pieces, that can be easily reused.

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- Naming conventions same as variables

22 / 64

```
#Name: your name here
#Date: October 2017
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- Naming conventions same as variables
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:

22 / 64

#### **Functions**

```
#Name: your name here
#Date: October 2017
This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- Naming conventions same as variables
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")

#### **Functions**

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- Naming conventions same as variables
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions,

#### **Functions**

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- Naming conventions same as variables
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.

## "Hello, World!" with Functions

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
      says hello to the world!
def main():
     print("Hello, World!")
if __name__ == "__main__":
     main()
```

# Python Tutor

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```


(Demo with pythonTutor)

CSci 127 (Hunter) Lecture 7 25 Oct 2022 24 / 64

# functions - modules - packages




# functions - modules - packages



CSci 127 (Hunter) Lecture 7 25 Oct 2022 26 / 64

# functions - modules - packages



# Stand-alone program



CSci 127 (Hunter) Lecture 7 25 Oct 2022 28 / 64

# Challenge:

Predict what the code will do:

```
def totalWithTax(food,tip):
     total = 0
2
     tax = 0.1
3
     total = food + food * tax
4
    total = total + tip
5
    return(total)
6
7
 lunch = float(input('Enter lunch total: '))
 1Tip = float(input('Enter lunch tip: '))
 print('Lunch total is', 1Total)
```

CSci 127 (Hunter) Lecture 7 25 Oct 2022 29 / 64

# totalWithTax function: continued

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.1
    total = food + food * tax
    total = total + tip
    return(total)
```

Omit code to calculate lunch total...

```
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip: '))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

CSci 127 (Hunter) Lecture 7 25 Oct 2022 30 / 64

#### Scope

```
def eight():
    x = 5+3
    print(x)

def nine():
    x = "nine"
    print(x)
```

 You can have multiple functions.

CSci 127 (Hunter) Lecture 7 25 Oct 2022 31 / 64

#### Scope

```
def eight():
    x = 5+3
    print(x)

def nine():
    x = "nine"
    print(x)
```

- You can have multiple functions.
- Each function defines the scope of its local variables

#### Scope


```
def eight():
    x = 5+3
    print(x)

def nine():
    x = "nine"
    print(x)
```

- You can have multiple functions.
- Each function defines the scope of its local variables
- A variable defined inside a function is **local**, i.e. defined only inside that function.


CSci 127 (Hunter) Lecture 7 25 Oct 2022 31 / 64

#### Local Data?



CSci 127 (Hunter) Lecture 7 25 Oct 2022 32 / 64

### Function Example: burger



Function name: burger (like a variable name, no space is allowed) Input:

- bread: representing for bread layermeat: representing for meat layer
- vegetable: representing for vegetable layer

Return: a hamburger

CSci 127 (Hunter)



Lecture 7


# Burger function definition

Pseudocode of burger function.

```
def burger(bread, meat, veg):
   pick a bread, put on top
   put meat
   put vegetable
   put a bread at the bottom

return the burger made
```

# Call burger function



Functions can have input parameters.

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
    print('Lunch total is', lTotal)
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner total: '))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)

lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)

dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)

lunch = float(input('Enter lunch total: '))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)
dinner= float(input('Enter dinner total: '))
dTotal = totalWithTax(driner, dTip)
print('Dinner total is', if or dinner total: '))
dTotal = totalWithTax(driner, dTip)
print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner total: '))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters

```
def totalWithTax(food,tip):
    total = 0
                        Formal Parameters
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', [[otal)
                           Actual Parameters
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal = totalWithTax dinner, dTip
print('Dinner total is', grotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters.

```
def totalWithTax(food,tip):
    total = 0
                        Formal Parameters
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', [[otal)
                           Actual Parameters
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal = totalWithTax dinner, dTip
print('Dinner total is', grotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters.
- Functions can also return
   values to where it was called.

#### Challenge:

Circle the actual parameters and underline the formal parameters:

```
def prob4():
    verse = "jam tomorrow and jam yesterday,"
    print("The rule is.")
    c = mystery(verse)
    w = enigma(verse.c)
    print(c,w)
def mystery(v):
    print(v)
    c = v.count("jam")
    return(c)
def enigma(v,c):
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
prob4()
```

#### Challenge:

Circle the actual parameters and underline the formal parameters:

```
def prob4():
    verse "jam tomorrow and jam yesterday,"
    print("The rule is,")
    c = hystery (verse)
    w = enigma (verse,c)
                                   *Actual
    print(c,w)
                                   Parameters
def mystery(v):
    print(v)
    c = v.count(fiam
    return(c)
                                     Formal
def enigma(v,c):
                                      Parameters
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
prob4()
```

#### Challenge: Predict what the code will do: def prob4(): verse = "jam tomorrow and jam yesterday, 2 ш print("The rule is,") 3 c = mystery(verse) 4 w = enigma(verse,c) 5 print(c,w) 6 def mystery(v): print (v) c = v.count("jam") 9 return(c) 10 def enigma(v,c):

Lecture 7

25 Oct 2022

CSci 127 (Hunter)

# Challenge: Predict what the code will do: def prob4(): verse = "jam tomorrow and jam yesterday," print("The rule is,") c = mystery(verse) w = enigma(verse,c) print(c,w)

Lecture 7

25 Oct 2022

41 / 64

```
Omit code of function mystery.
```

CSci 127 (Hunter)

```
def enigma(v,c):
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
    prob4()
```

# Python Tutor

```
def probd():
    verse = 'jam tomorrow and jam yesterday,"
    print('The rule is,")
    c = mystery(verse):
    w = enigma(verse,c)
    print(c),w
    def mystery(v):
        print('D)
    c = v.count('jam')
    return(c)
    def enigma(v,c)
    print('D)
    print('D)
```

prob4()

(Demo with pythonTutor)

CSci 127 (Hunter) Lecture 7 25 Oct 2022 42 / 64

# Challenge: Predict what the code will do:

```
# From "Teaching with Python" by John Zelle
 def happy():
      print("Happy Birthday to you!")
3
4
  def sing(P):
     happy()
6
     happy()
7
      print ("Happy Birthday dear " + P + "!")
8
```

#### Challenge:

#### Fill in the missing code:

```
def monthString(monthNum):
    Takes as input a number, monthNum, and
    returns the corresponding month name as a string.
    Example: monthString(1) returns "January".
    Assumes that input is an integer ranging from 1 to 12
    monthString = ""
     ********************************
    ### FTLL TN YOUR CODE HERE
                                    ###
    ### Other than your name above, ###
    ### this is the only section
                                    ###
    ### you change in this program. ###
    *************
    return(monthString)
def main():
    n = int(input('Enter the number of the month: '))
    mString = monthString(n)
    print('The month is', mString)
```

#### **IDLE**

mString = monthString(n) print('The month is', mString)

#### def monthString(monthNum): Takes as input a number, monthNum, and returns the corresponding month name as a string. Example: monthString(1) returns "January". Assumes that input is an integer ranging from 1 to 12 monthString = "" \*\*\*\*\*\*\*\*\*\*\*\*\*\* (Demo with IDLE) ### FILL IN YOUR CODE HERE ### ### Other than your name above, ### ### this is the only section ### ### you change in this program. ### \*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\* return(monthString) def main(): n = int(input('Enter the number of the month: '))

CSci 127 (Hunter) Lecture 7 25 Oct 2022 45 / 64

 Used to collaborate on and share code, documents, etc.



CSci 127 (Hunter) Lecture 7 25 Oct 2022 46 / 64



Octocat

- Used to collaborate on and share code, documents, etc.
- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.



- Used to collaborate on and share code, documents, etc.
- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.



- Used to collaborate on and share code, documents, etc.
- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.
- Github provides hosting for repositories ('repos') of code.

#### Github



- Used to collaborate on and share code, documents, etc.
- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.
- Github provides hosting for repositories ('repos') of code.
- Also convenient place to host websites (i.e. huntercsci127.github.io).

#### Github



- Used to collaborate on and share code, documents, etc.
- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.
- Github provides hosting for repositories ('repos') of code.
- Also convenient place to host websites (i.e. huntercsci127.github.io).
- In Lab6 you set up github accounts to copy ('clone') documents from the class repo. (More in future courses.)

46 / 64

```
#Name: your name here
#Date: October 2017
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

 Functions are a way to break code into pieces, that can be easily reused.

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if name == " main ":
```

main()

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if name == " main ":
```

main()

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")

```
#Name: your name here
#Date: October 2017
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions,

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.

# Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

Luminosity(L/Lo)	Radius(R/Ro)	Absolute magnitude(Mv)	Star type	Star color	Spectral Class				
0.0024	0.17	16.12	Brown Dwarf	Red	M				
0.056	0.0084	10.58	White Dwarf	Blue White	В				
0.00069	0.11	17.45	Brown Dwarf	Red	M				
0.00015	0.011	12.59	White Dwarf	Yellowish White	F				
1136	7.2	-1.97	Main Sequence	Blue-white	В				
0.81	0.9	5.05	Main Sequence	yellow-white	F				
0.013	0.014	11.89	White Dwarf	Blue White	В				
0.00362	0.1967	13.53	Red Dwarf	Red	М				
1.35	0.98	2.93	Main Sequence	yellow-white	F				
272000	1183	-9.2	Hypergiant	Red	M				
	0.0024 0.056 0.00069 0.00015 1136 0.81 0.013	0.0024 0.17 0.056 0.0084 0.00069 0.11 0.00015 0.011 1136 7.2 0.81 0.9 0.013 0.014 0.00362 0.1967 1.35 0.98	0.0024 0.17 16.12 0.056 0.0084 10.58 0.0069 0.11 17.45 0.00015 0.011 12.59 1136 7.2 1.97 0.81 0.9 5.05 0.013 0.014 11.89 0.0052 0.1567 13.53 0.98 2.93	0.056 0.084 10.58 White Dwarf 0.00069 0.11 17.45 Brown Dwarf 0.00015 0.011 12.59 White Dwarf 1136 7.2 -1.97 Main Sequence 0.81 0.9 5.05 Main Sequence 0.013 0.014 11.89 White Dwarf 0.00362 0.1967 13.53 Red Dwarf 1.135 0.98 2.93 Main Sequence	0.0024         0.17         16.12 Brown Dwarf         Red           0.055         0.0084         10.58 White Dwarf         Blue White           0.00090         0.11         17.45 Brown Dwarf         Red           0.00015         0.011         12.59 White Dwarf         Yellowish White           1136         7.2         -1.97 Main Sequence         Blue-white           0.81         0.9         5.05 Main Sequence         Blue-white           0.013         0.014         11.89 White Dwarf         Blue White           0.0362         0.1967         13.53 Red Dwarf         Red           1.35         0.98         2.93 Main Sequence         yellow-white				

• Libraries: pandas

Stars									
Temperature (K)	Luminosity(L/Lo)	Radius(R/Ro)	Absolute magnitude(Mv)	Star type	Star color	Spectral Class			
3068	0.0024	0.17	16.12	Brown Dwarf	Red	M			
25000	0.056	0.0084	10.58	White Dwarf	Blue White	В			
2650	0.00069	0.11	17.45	Brown Dwarf	Red	M			
11790	0.00015	0.011	12.59	White Dwarf	Yellowish White	F			
15276	1136	7.2	-1.97	Main Sequence	Blue-white	В			
5800	0.81	0.9	5.05	Main Sequence	yellow-white	F			
16500	0.013	0.014	11.89	White Dwarf	Blue White	В			
3192	0.00362	0.1967	13.53	Red Dwarf	Red	М			
6380	1.35	0.98	2.93	Main Sequence	yellow-white	F			
3834	272000	1183	-9.2	Hypergiant	Red	M			

• Libraries: pandas

Process:

► Print max of 'Luminosity' column

Stars									
Temperature (K)	Luminosity(L/Lo)	Radius(R/Ro)	Absolute magnitude(Mv)	Star type	Star color	Spectral Class			
3068	0.0024	0.17	16.12	Brown Dwarf	Red	M			
25000	0.056	0.0084	10.58	White Dwarf	Blue White	В			
2650	0.00069	0.11	17.45	Brown Dwarf	Red	M			
11790	0.00015	0.011	12.59	White Dwarf	Yellowish White	F			
15276	1136	7.2	-1.97	Main Sequence	Blue-white	В			
5800	0.81	0.9	5.05	Main Sequence	yellow-white	F			
16500	0.013	0.014	11.89	White Dwarf	Blue White	В			
3192	0.00362	0.1967	13.53	Red Dwarf	Red	M			
6380	1.35	0.98	2.93	Main Sequence	yellow-white	F			
3834	272000	1183	-9.2	Hypergiant	Red	M			

- Libraries: pandas
- Process:
  - ▶ Print max of 'Luminosity' column
  - ► Print min of 'Temperature' column

Stars									
Temperature (K)	Luminosity(L/Lo)	Radius(R/Ro)	Absolute magnitude(Mv)	Star type	Star color	Spectral Class			
3068	0.0024	0.17	16.12	Brown Dwarf	Red	M			
25000	0.056	0.0084	10.58	White Dwarf	Blue White	В			
2650	0.00069	0.11	17.45	Brown Dwarf	Red	M			
11790	0.00015	0.011	12.59	White Dwarf	Yellowish White	F			
15276	1136	7.2	-1.97	Main Sequence	Blue-white	В			
5800	0.81	0.9	5.05	Main Sequence	yellow-white	F			
16500	0.013	0.014	11.89	White Dwarf	Blue White	В			
3192	0.00362	0.1967	13.53	Red Dwarf	Red	M			
6380	1.35	0.98	2.93	Main Sequence	yellow-white	F			
3834	272000	1183	-9.2	Hypergiant	Red	M			

- Libraries: pandas
- Process:
  - ► Print max of 'Luminosity' column
  - ► Print min of 'Temperature' column
  - groupby 'Star Type' and get group 'Hypergiant' to print average 'Radius'

## Design Challenge - Code

• Libraries: pandas
import pandas as pd
stars = pd.read\_csv('Stars.csv')

## Design Challenge - Code

Libraries: pandas
import pandas as pd
stars = pd.read\_csv('Stars.csv')

- Process:
  - ► Print max of 'Luminosity' column

```
print (stars['Luminosity(L/Lo)'].max())
```

## Design Challenge - Code

Libraries: pandas
import pandas as pd
stars = pd.read\_csv('Stars.csv')

- Process:
  - ► Print max of 'Luminosity' column

```
print (stars['Luminosity(L/Lo)'].max())
```

- ▶ Prints min of 'Temperature' column and store it in temp variable
  - print (stars['Temperature(K)'].min())

 groupby 'Star Type' and get a group of Hypergiant, then print average of 'Radius' column for this group.



Freely available source of data.



- Freely available source of data.
- Maintained by the NYC data analytics team.



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.
- Will use pandas, pyplot & folium libraries to analyze, visualize and map the data.



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.
- Will use pandas, pyplot & folium libraries to analyze, visualize and map the data.
- Lab 7 covers accessing and downloading NYC OpenData datasets.




ne Data About v Learr

#### Film Permits


Permits are generally required when asserting the exclusive use of city property, like a sidewalk, a street, or a park. See http://www1.nyc.gov/site/mome/permits/when-permit-required.page

EventID :	EventType :	StartDateTi	EndDateTime :	EnteredOn ↓ :	EventAg :	ParkingHeld :	Borou
455063	Shooting Permit	12/06/2018 07:00	12/06/2018 09:00	12/05/2018 12:36	Mayor's Offic	STARR AVENUE b	Queens
454967	Shooting Permit	12/06/2018 07:00	12/06/2018 05:00	12/04/2018 09:11	Mayor's Offic	EAGLE STREET be	Brooklyn
454941	Shooting Permit	12/06/2018 07:00	12/06/2018 07:00	12/04/2018 05:44	Mayor's Offic	SOUTH OXFORD	Brooklyn
454920	Shooting Permit	12/06/2018 10:00	12/06/2018 11:59	12/04/2018 03:28	Mayor's Offic	13 AVENUE betw	Queens
454914	Shooting Permit	12/06/2018 08:00	12/06/2018 11:00	12/04/2018 03:05	Mayor's Offic	ELDERT STREET b	Brooklyn
454909	Shooting Permit	12/05/2018 08:00	12/05/2018 06:00	12/04/2018 02:45	Mayor's Offic	ELDERT STREET b	Brooklyn
454905	Shooting Permit	12/06/2018 07:00	12/06/2018 10:00	12/04/2018 02:17	Mayor's Offic	35 STREET betwe	Queens

CSci 127 (Hunter) Lecture 7 25 Oct 2022



• What's the most popular street for filming?



- What's the most popular street for filming?
- What's the most popular borough?

25 Oct 2022

54 / 64



- What's the most popular street for filming?
- What's the most popular borough?
- How many TV episodes were filmed?



Download the data as a CSV file and store on your computer.

4 0 1 4 4 5 1 4 5 1 5 5



- Download the data as a CSV file and store on your computer.
- Python program:

4 D > 4 A > 4 B > 4 B > -

90 Q



- Download the data as a CSV file and store on your computer.
- Python program:

```
#CSci 127 Teaching Staff
#March 2019
#OpenData Film Permits

#Import pandas for reading and analyzing CSV data:
import pandas as pd
csvFile = "filmPermits.csv"  #Name of the CSV file
tickets = pd.read_csv(csvFile)#Read in the file to a dataframe
print(tickets)  #Print out the dataframe
```

4 D > 4 P > 4 P > 4 P > B

900



- Download the data as a CSV file and store on your computer.
- Python program:

```
#CSci 127 Teaching Staff
#March 2019
#OpenData Film Permits

#Import pandas for reading and analyzing CSV data:
import pandas as pd
csvFile = "filmPermits.csv"  #Name of the CSV file
tickets = pd.read_csv(csvFile)#Read in the file to a dataframe
print(tickets)  #Print out the dataframe
print(tickets["ParkingHeld"])  #Print out streets (multiple times)
```

4 D > 4 P > 4 P > 4 P > B

900



- Download the data as a CSV file and store on your computer.
- Python program:


4 D > 4 P > 4 P > 4 P > B

90 Q



- Download the data as a CSV file and store on your computer.
- Python program:

4 D > 4 P > 4 P > 4 P > B



#### Can approach the other questions in the same way:

- What's the most popular street for filming?
- What's the most popular borough?
- How many TV episodes were filmed?

60 / 64





• **Functions** are a way to break code into pieces, that can be easily reused.





- **Functions** are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:





- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
   Example: print("Hello", "World")





- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
   Example: print("Hello", "World")
- Can write, or define your own functions,

## Recap





- **Functions** are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
  - Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.

### Recap






- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
   Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.
- Accessing Formatted Data: NYC OpenData

### Practice Quiz & Final Questions

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!
def main():
    print("Hello, World!")
if __name__ = "__main__":
    main()
```

```
def totalkiting (Tool, 120)
total a 975 Formal Parameters
total = 975 Formal Parameters
total = 1004 | 1004 | 1004
total = 1004 | 1004 | 1004
total = 1004 | 1004 | 1004
total = 1004 | 1004
total = 1004 | 1004
total = 1004
tota
```



• Since you must pass the final exam to pass the course, we end every lecture with final exam review.

### Practice Quiz & Final Questions

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!
def main():
    print("Hello, World!")
if __name__ = "__main__":
    main()
```

```
der totalkithe (Ood, (ED)
total = 0
Formal Parameters
tax = 0.000 = food * tax
total = total * tip
return(cotal)
lunch = (Sout(roput("inter lunch total; '))
litip = floot((roput("inter lunch total; '))
direct = lunch (lunch ("inter lunch total; '))
direct = lunch (lunch ("inter lunch total; '))
direct = totalkithou("inter lunch total; ')
direct = totalkithou("inter lunch total; ')
direct = totalkithou("inter lunch total; ')
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
  - write as much you can for 60 seconds;
  - ▶ followed by answer; and
  - ► repeat.

### Practice Quiz & Final Questions

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
says hello to the world!
def main():
    print("Hello, World!")
if __name__ = "__main__":
    main()
```

```
sef total at the continuous conti
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
  - write as much you can for 60 seconds;
  - followed by answer; and
  - ▶ repeat.
- Past exams are on the webpage (under Final Exam Information).
- Theme: Functions!
   Starting with Spring 19 V3, #4(b).



Before next lecture, don't forget to:

Work on this week's Online Lab

CSci 127 (Hunter) Lecture 7 25 Oct 2022 63 / 64



Before next lecture, don't forget to:

- Work on this week's Online Lab
- Schedule an appointment to take the Quiz in lab 1001G Hunter North

CSci 127 (Hunter) Lecture 7 25 Oct 2022 63 / 64



#### Before next lecture, don't forget to:

- Work on this week's Online Lab
- Schedule an appointment to take the Quiz in lab 1001G Hunter North
- If you haven't already, schedule an appointment to take the Code Review (one every week) in lab 1001G Hunter North

CSci 127 (Hunter) Lecture 7 25 Oct 2022 63 / 64



#### Before next lecture, don't forget to:

- Work on this week's Online Lab
- Schedule an appointment to take the Quiz in lab 1001G Hunter North
- If you haven't already, schedule an appointment to take the Code Review (one every week) in lab 1001G Hunter North
- Submit this week's 5 programming assignments (programs 31-35)



#### Before next lecture, don't forget to:

- Work on this week's Online Lab
- Schedule an appointment to take the Quiz in lab 1001G Hunter North
- If you haven't already, schedule an appointment to take the Code Review (one every week) in lab 1001G Hunter North
- Submit this week's 5 programming assignments (programs 31-35)
- If you need help, schedule an appointment for Tutoring in lab 1001G 11:30am-5:30pm



#### Before next lecture, don't forget to:

- Work on this week's Online Lab
- Schedule an appointment to take the Quiz in lab 1001G Hunter North
- If you haven't already, schedule an appointment to take the Code Review (one every week) in lab 1001G Hunter North
- Submit this week's 5 programming assignments (programs 31-35)
- If you need help, schedule an appointment for Tutoring in lab 1001G 11:30am-5:30pm
- Take the Lecture Preview on Blackboard on Monday (or no later than 10:15am on Tuesday)

# Lecture Slips & Writing Boards



- Hand your lecture slip to a UTA.
- Return writing boards as you leave.

CSci 127 (Hunter) Lecture 7 25 Oct 2022 64 / 64