CSci 127: Introduction to Computer Science



hunter.cuny.edu/csci

Frequently Asked Questions

From lecture slips & email

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must:*

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN);*

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN);*

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!);*

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!); Submit programming assignments to Gradescope (approx. 5 per lab)*

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!); Submit programming assignments to Gradescope (approx. 5 per lab)*
- Can I work ahead?

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!); Submit programming assignments to Gradescope (approx. 5 per lab)*
- Can I work ahead?
  Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. Start right away (after Lab1 you can submit the first 5 problems)

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!); Submit programming assignments to Gradescope (approx. 5 per lab)*
- Can I work ahead?
  Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. Start right away (after Lab1 you can submit the first 5 problems)
- When is the midterm?

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!); Submit programming assignments to Gradescope (approx. 5 per lab)*
- Can I work ahead?
  Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. Start right away (after Lab1 you can submit the first 5 problems)
- When is the midterm?
  There is no midterm. Instead there's required weekly quizzes and daily programming assignments.

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!); Submit programming assignments to Gradescope (approx. 5 per lab)*
- Can I work ahead?
  Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. Start right away (after Lab1 you can submit the first 5 problems)
- When is the midterm?
  There is no midterm. Instead there's required weekly quizzes and daily programming assignments.
- I missed class. Do you need documentation?

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!); Submit programming assignments to Gradescope (approx. 5 per lab)*
- Can I work ahead?
  Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. Start right away (after Lab1 you can submit the first 5 problems)
- When is the midterm?
  There is no midterm. Instead there's required weekly quizzes and daily programming assignments.
- I missed class. Do you need documentation?
  No, but If you will miss ≥ 3 *weeks (*$> 20\%$*), see us about taking this in a future term.*

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!); Submit programming assignments to Gradescope (approx. 5 per lab)*
- Can I work ahead?
  Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. Start right away (after Lab1 you can submit the first 5 problems)
- When is the midterm?
  There is no midterm. Instead there's required weekly quizzes and daily programming assignments.
- I missed class. Do you need documentation?
  No, but If you will miss ≥ 3 *weeks (*$> 20\%$*), see us about taking this in a future term.*
- I have not received any emails from this course.

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!); Submit programming assignments to Gradescope (approx. 5 per lab)*
- Can I work ahead?
  Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. Start right away (after Lab1 you can submit the first 5 problems)
- When is the midterm?
  There is no midterm. Instead there's required weekly quizzes and daily programming assignments.
- I missed class. Do you need documentation?
  No, but If you will miss ≥ 3 *weeks (*$> 20\%$*), see us about taking this in a future term.*
- I have not received any emails from this course.
  That is a big problem! *We send tons of important information through email. Please update your email on Blackboard to one you check regularly.*

Frequently Asked Questions

From lecture slips & email

- Am I only responsible for reading the weekly Lab?
  No. *Each week you must: Take a lecture preview (available Mondays); Come to lecture (Tuesday 9:45-11 118 HN); Take a Quiz and Code Review (self-scheduled, 1001E HN); Read the weekly lab (online, see Course Outline on* **course website**, *find it on Blackboard!!!); Submit programming assignments to Gradescope (approx. 5 per lab)*
- Can I work ahead?
  Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. Start right away (after Lab1 you can submit the first 5 problems)
- When is the midterm?
  There is no midterm. Instead there's required weekly quizzes and daily programming assignments.
- I missed class. Do you need documentation?
  No, but If you will miss ≥ 3 *weeks (*$> 20\%$*), see us about taking this in a future term.*
- I have not received any emails from this course.
  That is a big problem! *We send tons of important information through email. Please update your email on Blackboard to one you check regularly.*

Today's Topics

- **For-loops**
- `range()`
- Variables
- Characters
- Strings
- CS Survey (Dr. Sakas, Computational Linguistics)

In Pairs or Triples...

Some review and some novel challenges:

```
1  #Predict what will be printed:
2  for i in range(4):
3      print('The world turned upside down')
4  for j in [0,1,2,3,4,5]:
5      print(j)
6  for count in range(6):
7      print(count)
8  for color in ['red', 'green', 'blue']:
9      print(color)
10 for i in range(2):
11     for j in range(2):
12         print('Look around,')
13     print('How lucky we are to be alive!')
```

Python Tutor

```
1  #Predict what will be printed:
2  for i in range(4):
3      print('The world turned upside down')
4  for j in [0,1,2,3,4,5]:
5      print(j)
6  for count in range(6):
7      print(count)
8  for color in ['red', 'green', 'blue']:
9      print(color)
10 for i in range(2):
11     for j in range(2):
12         print('Look around,')
13     print('How lucky we are to be alive!')
```

(Demo with pythonTutor)

for-loop



How to Think Like CS, §4.5

```
for  i in list:
     statement1
     statement2
     statement3
```

for-loop



How to Think Like CS, §4.5

```
for  i in list:
     statement1
     statement2
     statement3
```

where `list` is a list of items:

- stated explicitly (e.g. [1,2,3]) or
- generated by a function, e.g. `range()`.

Today's Topics

- For-loops
- **range()**
- Variables
- Characters
- Strings
- CS Survey (Dr. Sakas, Computational Linguistics)

More on `range()`:

```
1  #Predict what will be printed:
2
3  for num in [2,4,6,8,10]:
4      print(num)
5
6  sum = 0
7  for x in range(0,12,2):
8      print(x)
9      sum = sum + x
10
11 print(sum)
12
13 for c in "ABCD":
14     print(c)
```

Python Tutor

```
1  #Predict what will be printed:
2
3  for num in [2,4,6,8,10]:
4      print(num)
5
6  sum = 0
7  for x in range(0,12,2):
8      print(x)
9      sum = sum + x
10
11 print(sum)
12
13 for c in "ABCD":
14     print(c)
```

(Demo with pythonTutor)

range()

Simplest version:

- `range(stop)`

`range()`

Simplest version:

- `range(stop)`
- Produces a list: [0,1,2,3,...,stop-1]

range()

Simplest version:

- `range(stop)`
- Produces a list: [0,1,2,3,...,stop-1]
- For example, if you want the the list [0,1,2,3,...,100], you would write:

range()

Simplest version:

- `range(stop)`
- Produces a list: [0,1,2,3,...,stop-1]
- For example, if you want the the list [0,1,2,3,...,100], you would write:

```
range(101)
```

`range()`

What if you wanted to start somewhere else:

`range()`

What if you wanted to start somewhere else:

- `range(start, stop)`

`range()`

What if you wanted to start somewhere else:

- `range(start, stop)`
- Produces a list:
  [start,start+1,...,stop-1]

range()

What if you wanted to start somewhere else:

- `range(start, stop)`
- Produces a list:
  [start,start+1,...,stop-1]
- For example, if you want the the list
  [10,11,...,20]
  you would write:

range()

What if you wanted to start somewhere else:

- `range(start, stop)`
- Produces a list:
  [start,start+1,...,stop-1]
- For example, if you want the the list
  [10,11,...,20]
  you would write:

```
range(10,21)
```

`range()`

What if you wanted to count by twos, or some other number:

range()

What if you wanted to count by twos, or some other number:

- `range(start, stop, step)`

range()

What if you wanted to count by twos, or some other number:

- `range(start, stop, step)`
- Produces a list:
  [start,start+step,start+2*step...,last]
  (where last is the largest start+k*step less than stop)

range()

What if you wanted to count by twos, or some other number:

- `range(start, stop, step)`
- Produces a list:
  [start,start+step,start+2*step...,last]
  (where last is the largest start+k*step less than stop)
- For example, if you want the the list
  [5,10,...,50]
  you would write:

range()

What if you wanted to count by twos, or some other number:

- `range(start, stop, step)`
- Produces a list:
  [start,start+step,start+2*step...,last]
  (where last is the largest start+k*step less than stop)
- For example, if you want the the list
  [5,10,...,50]
  you would write:

  ```
  range(5,51,5)
  ```

In summary: range()

The three versions:

In summary: range()

The three versions:

- `range(stop)`

In summary: range()

The three versions:

- `range(stop)`
- `range(start, stop)`

In summary: range()

The three versions:

- `range(stop)`
- `range(start, stop)`
- `range(start, stop, step)`

Today's Topics

- For-loops
- `range()`
- **Variables**
- Characters
- Strings
- CS Survey (Dr. Sakas, Computational Linguistics)

Variables

- A **variable** is a reserved memory location for storing a value.

Variables

- A **variable** is a reserved memory location for storing a value.
- Different kinds, or **types**, of values need different amounts of space:
  - **int**: integer or whole numbers

Variables

- A **variable** is a reserved memory location for storing a value.
- Different kinds, or **types**, of values need different amounts of space:
  - **int**: integer or whole numbers
  - **float**: floating point or real numbers

Variables

- A **variable** is a reserved memory location for storing a value.
- Different kinds, or **types**, of values need different amounts of space:
  - **int**: integer or whole numbers
  - **float**: floating point or real numbers
  - **string**: sequence of characters

Variables

- A **variable** is a reserved memory location for storing a value.
- Different kinds, or **types**, of values need different amounts of space:
  - **int**: integer or whole numbers
  - **float**: floating point or real numbers
  - **string**: sequence of characters
  - **list**: a sequence of items

Variables

- A **variable** is a reserved memory location for storing a value.
- Different kinds, or **types**, of values need different amounts of space:
  - **int**: integer or whole numbers
  - **float**: floating point or real numbers
  - **string**: sequence of characters
  - **list**: a sequence of items
    e.g. `[3, 1, 4, 5, 9]` or `['violet','purple','indigo']`

Variables

- A **variable** is a reserved memory location for storing a value.
- Different kinds, or **types**, of values need different amounts of space:
  - **int**: integer or whole numbers
  - **float**: floating point or real numbers
  - **string**: sequence of characters
  - **list**: a sequence of items
    e.g. `[3, 1, 4, 5, 9]` or `['violet','purple','indigo']`
  - **class variables**: for complex objects, like turtles.
- In Python (unlike other languages) you don't need to specify the type; it is deduced by its value.

Variable Names

- There's some rules about valid names for variables.

Variable Names

- There's some rules about valid names for variables.
- Can use the underscore ('_'), upper and lower case letters.

Variable Names

- There's some rules about valid names for variables.
- Can use the underscore ('_'), upper and lower case letters.
- Can also use numbers, just can't start a name with a number.

Variable Names

- There's some rules about valid names for variables.
- Can use the underscore ('_'), upper and lower case letters.
- Can also use numbers, just can't start a name with a number.
- Can't use symbols (like '+' or '*') since used for arithmetic.

Variable Names

- There's some rules about valid names for variables.
- Can use the underscore ('_'), upper and lower case letters.
- Can also use numbers, just can't start a name with a number.
- Can't use symbols (like '+' or '*') since used for arithmetic.
- Can't use some words that Python has reserved for itself (e.g. `for`).
  (List of reserved words in *Think CS*, §2.5.)

Today's Topics

- For-loops
- `range()`
- Variables
- **Characters**
- Strings
- CS Survey (Dr. Sakas, Computational Linguistics)

Standardized Code for Characters

American Standard Code for Information Interchange (ASCII), 1960.

Standardized Code for Characters

American Standard Code for Information Interchange (ASCII), 1960.

(New version called: Unicode).

Standardized Code for Characters

American Standard Code for Information Interchange (ASCII), 1960.

(New version called: Unicode).

ASCII TABLE

Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char
0	0	[NULL]	32	20	[SPACE]	64	40	@	96	60	`
1	1	[START OF HEADING]	33	21	!	65	41	A	97	61	a
2	2	[START OF TEXT]	34	22	"	66	42	B	98	62	b
3	3	[END OF TEXT]	35	23	#	67	43	C	99	63	c
4	4	[END OF TRANSMISSION]	36	24	$	68	44	D	100	64	d
5	5	[ENQUIRY]	37	25	%	69	45	E	101	65	e
6	6	[ACKNOWLEDGE]	38	26	&	70	46	F	102	66	f
7	7	[BELL]	39	27	'	71	47	G	103	67	g
8	8	[BACKSPACE]	40	28	(	72	48	H	104	68	h
9	9	[HORIZONTAL TAB]	41	29	)	73	49	I	105	69	i
10	A	[LINE FEED]	42	2A	*	74	4A	J	106	6A	j
11	B	[VERTICAL TAB]	43	2B	+	75	4B	K	107	6B	k
12	C	[FORM FEED]	44	2C	,	76	4C	L	108	6C	l
13	D	[CARRIAGE RETURN]	45	2D	-	77	4D	M	109	6D	m
14	E	[SHIFT OUT]	46	2E	.	78	4E	N	110	6E	n
15	F	[SHIFT IN]	47	2F	/	79	4F	O	111	6F	o
16	10	[DATA LINK ESCAPE]	48	30	0	80	50	P	112	70	p
17	11	[DEVICE CONTROL 1]	49	31	1	81	51	Q	113	71	q
18	12	[DEVICE CONTROL 2]	50	32	2	82	52	R	114	72	r
19	13	[DEVICE CONTROL 3]	51	33	3	83	53	S	115	73	s
20	14	[DEVICE CONTROL 4]	52	34	4	84	54	T	116	74	t
21	15	[NEGATIVE ACKNOWLEDGE]	53	35	5	85	55	U	117	75	u
22	16	[SYNCHRONOUS IDLE]	54	36	6	86	56	V	118	76	v
23	17	[ENG OF TRANS. BLOCK]	55	37	7	87	57	W	119	77	w
24	18	[CANCEL]	56	38	8	88	58	X	120	78	x
25	19	[END OF MEDIUM]	57	39	9	89	59	Y	121	79	y
26	1A	[SUBSTITUTE]	58	3A	:	90	5A	Z	122	7A	z
27	1B	[ESCAPE]	59	3B	;	91	5B	[	123	7B	{
28	1C	[FILE SEPARATOR]	60	3C	<	92	5C	\	124	7C	|
29	1D	[GROUP SEPARATOR]	61	3D	=	93	5D	]	125	7D	}
30	1E	[RECORD SEPARATOR]	62	3E	>	94	5E	^	126	7E	~
31	1F	[UNIT SEPARATOR]	63	3F	?	95	5F	_	127	7F	[DEL]

(wiki)

Converting from Character to Code:

(There is an ASCII table on the back of today's lecture slip.)

ASCII TABLE

Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char
0	0	[NULL]	32	20	[SPACE]	64	40	@	96	60	`
1	1	[START OF HEADING]	33	21	!	65	41	A	97	61	a
2	2	[START OF TEXT]	34	22	"	66	42	B	98	62	b
3	3	[END OF TEXT]	35	23	#	67	43	C	99	63	c
4	4	[END OF TRANSMISSION]	36	24	$	68	44	D	100	64	d
5	5	[ENQUIRY]	37	25	%	69	45	E	101	65	e
6	6	[ACKNOWLEDGE]	38	26	&	70	46	F	102	66	f
7	7	[BELL]	39	27	'	71	47	G	103	67	g
8	8	[BACKSPACE]	40	28	(	72	48	H	104	68	h
9	9	[HORIZONTAL TAB]	41	29	)	73	49	I	105	69	i
10	A	[LINE FEED]	42	2A	*	74	4A	J	106	6A	j
11	B	[VERTICAL TAB]	43	2B	+	75	4B	K	107	6B	k
12	C	[FORM FEED]	44	2C	,	76	4C	L	108	6C	l
13	D	[CARRIAGE RETURN]	45	2D	-	77	4D	M	109	6D	m
14	E	[SHIFT OUT]	46	2E	.	78	4E	N	110	6E	n
15	F	[SHIFT IN]	47	2F	/	79	4F	O	111	6F	o
16	10	[DATA LINK ESCAPE]	48	30	0	80	50	P	112	70	p
17	11	[DEVICE CONTROL 1]	49	31	1	81	51	Q	113	71	q
18	12	[DEVICE CONTROL 2]	50	32	2	82	52	R	114	72	r
19	13	[DEVICE CONTROL 3]	51	33	3	83	53	S	115	73	s
20	14	[DEVICE CONTROL 4]	52	34	4	84	54	T	116	74	t
21	15	[NEGATIVE ACKNOWLEDGE]	53	35	5	85	55	U	117	75	u
22	16	[SYNCHRONOUS IDLE]	54	36	6	86	56	V	118	76	v
23	17	[END OF TRANS. BLOCK]	55	37	7	87	57	W	119	77	w
24	18	[CANCEL]	56	38	8	88	58	X	120	78	x
25	19	[END OF MEDIUM]	57	39	9	89	59	Y	121	79	y
26	1A	[SUBSTITUTE]	58	3A	:	90	5A	Z	122	7A	z
27	1B	[ESCAPE]	59	3B	;	91	5B	[	123	7B	{
28	1C	[FILE SEPARATOR]	60	3C	<	92	5C	\	124	7C	|
29	1D	[GROUP SEPARATOR]	61	3D	=	93	5D	]	125	7D	}
30	1E	[RECORD SEPARATOR]	62	3E	>	94	5E	^	126	7E	~
31	1F	[UNIT SEPARATOR]	63	3F	?	95	5F	_	127	7F	[DEL]

Converting from Character to Code:

(There is an ASCII table on the back of today's lecture slip.)



ASCII TABLE

Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char
0	0	[NULL]	32	20	[SPACE]	64	40	@	96	60	`
1	1	[START OF HEADING]	33	21	!	65	41	A	97	61	a
2	2	[START OF TEXT]	34	22	"	66	42	B	98	62	b
3	3	[END OF TEXT]	35	23	#	67	43	C	99	63	c
4	4	[END OF TRANSMISSION]	36	24	$	68	44	D	100	64	d
5	5	[ENQUIRY]	37	25	%	69	45	E	101	65	e
6	6	[ACKNOWLEDGE]	38	26	&	70	46	F	102	66	f
7	7	[BELL]	39	27	'	71	47	G	103	67	g
8	8	[BACKSPACE]	40	28	(	72	48	H	104	68	h
9	9	[HORIZONTAL TAB]	41	29	)	73	49	I	105	69	i
10	A	[LINE FEED]	42	2A	*	74	4A	J	106	6A	j
11	B	[VERTICAL TAB]	43	2B	+	75	4B	K	107	6B	k
12	C	[FORM FEED]	44	2C	,	76	4C	L	108	6C	l
13	D	[CARRIAGE RETURN]	45	2D	-	77	4D	M	109	6D	m
14	E	[SHIFT OUT]	46	2E	.	78	4E	N	110	6E	n
15	F	[SHIFT IN]	47	2F	/	79	4F	O	111	6F	o
16	10	[DATA LINK ESCAPE]	48	30	0	80	50	P	112	70	p
17	11	[DEVICE CONTROL 1]	49	31	1	81	51	Q	113	71	q
18	12	[DEVICE CONTROL 2]	50	32	2	82	52	R	114	72	r
19	13	[DEVICE CONTROL 3]	51	33	3	83	53	S	115	73	s
20	14	[DEVICE CONTROL 4]	52	34	4	84	54	T	116	74	t
21	15	[NEGATIVE ACKNOWLEDGE]	53	35	5	85	55	U	117	75	u
22	16	[SYNCHRONOUS IDLE]	54	36	6	86	56	V	118	76	v
23	17	[END OF TRANS. BLOCK]	55	37	7	87	57	W	119	77	w
24	18	[CANCEL]	56	38	8	88	58	X	120	78	x
25	19	[END OF MEDIUM]	57	39	9	89	59	Y	121	79	y
26	1A	[SUBSTITUTE]	58	3A	:	90	5A	Z	122	7A	z
27	1B	[ESCAPE]	59	3B	;	91	5B	[	123	7B	{
28	1C	[FILE SEPARATOR]	60	3C	<	92	5C	\	124	7C	|
29	1D	[GROUP SEPARATOR]	61	3D	=	93	5D	]	125	7D	}
30	1E	[RECORD SEPARATOR]	62	3E	>	94	5E	^	126	7E	~
31	1F	[UNIT SEPARATOR]	63	3F	?	95	5F	_	127	7F	[DEL]

- `ord(c)`: returns Unicode (ASCII) of the character.

Converting from Character to Code:

(There is an ASCII table on the back of today's lecture slip.)



ASCII TABLE

Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char
0	0	[NULL]	32	20	[SPACE]	64	40	@	96	60	`
1	1	[START OF HEADING]	33	21	!	65	41	A	97	61	a
2	2	[START OF TEXT]	34	22	"	66	42	B	98	62	b
3	3	[END OF TEXT]	35	23	#	67	43	C	99	63	c
4	4	[END OF TRANSMISSION]	36	24	$	68	44	D	100	64	d
5	5	[ENQUIRY]	37	25	%	69	45	E	101	65	e
6	6	[ACKNOWLEDGE]	38	26	&	70	46	F	102	66	f
7	7	[BELL]	39	27	'	71	47	G	103	67	g
8	8	[BACKSPACE]	40	28	(	72	48	H	104	68	h
9	9	[HORIZONTAL TAB]	41	29	)	73	49	I	105	69	i
10	A	[LINE FEED]	42	2A	*	74	4A	J	106	6A	j
11	B	[VERTICAL TAB]	43	2B	+	75	4B	K	107	6B	k
12	C	[FORM FEED]	44	2C	,	76	4C	L	108	6C	l
13	D	[CARRIAGE RETURN]	45	2D	-	77	4D	M	109	6D	m
14	E	[SHIFT OUT]	46	2E	.	78	4E	N	110	6E	n
15	F	[SHIFT IN]	47	2F	/	79	4F	O	111	6F	o
16	10	[DATA LINK ESCAPE]	48	30	0	80	50	P	112	70	p
17	11	[DEVICE CONTROL 1]	49	31	1	81	51	Q	113	71	q
18	12	[DEVICE CONTROL 2]	50	32	2	82	52	R	114	72	r
19	13	[DEVICE CONTROL 3]	51	33	3	83	53	S	115	73	s
20	14	[DEVICE CONTROL 4]	52	34	4	84	54	T	116	74	t
21	15	[NEGATIVE ACKNOWLEDGE]	53	35	5	85	55	U	117	75	u
22	16	[SYNCHRONOUS IDLE]	54	36	6	86	56	V	118	76	v
23	17	[END OF TRANS. BLOCK]	55	37	7	87	57	W	119	77	w
24	18	[CANCEL]	56	38	8	88	58	X	120	78	x
25	19	[END OF MEDIUM]	57	39	9	89	59	Y	121	79	y
26	1A	[SUBSTITUTE]	58	3A	:	90	5A	Z	122	7A	z
27	1B	[ESCAPE]	59	3B	;	91	5B	[	123	7B	{
28	1C	[FILE SEPARATOR]	60	3C	<	92	5C	\	124	7C	|
29	1D	[GROUP SEPARATOR]	61	3D	=	93	5D	]	125	7D	}
30	1E	[RECORD SEPARATOR]	62	3E	>	94	5E	^	126	7E	~
31	1F	[UNIT SEPARATOR]	63	3F	?	95	5F	_	127	7F	[DEL]

- `ord(c)`: returns Unicode (ASCII) of the character.
- Example: `ord('a')` returns 97.

Converting from Character to Code:

(There is an ASCII table on the back of today's lecture slip.)



ASCII TABLE

Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char
0	0	[NULL]	32	20	[SPACE]	64	40	@	96	60	`
1	1	[START OF HEADING]	33	21	!	65	41	A	97	61	a
2	2	[START OF TEXT]	34	22	"	66	42	B	98	62	b
3	3	[END OF TEXT]	35	23	#	67	43	C	99	63	c
4	4	[END OF TRANSMISSION]	36	24	$	68	44	D	100	64	d
5	5	[ENQUIRY]	37	25	%	69	45	E	101	65	e
6	6	[ACKNOWLEDGE]	38	26	&	70	46	F	102	66	f
7	7	[BELL]	39	27	'	71	47	G	103	67	g
8	8	[BACKSPACE]	40	28	(	72	48	H	104	68	h
9	9	[HORIZONTAL TAB]	41	29	)	73	49	I	105	69	i
10	A	[LINE FEED]	42	2A	*	74	4A	J	106	6A	j
11	B	[VERTICAL TAB]	43	2B	+	75	4B	K	107	6B	k
12	C	[FORM FEED]	44	2C	,	76	4C	L	108	6C	l
13	D	[CARRIAGE RETURN]	45	2D	-	77	4D	M	109	6D	m
14	E	[SHIFT OUT]	46	2E	.	78	4E	N	110	6E	n
15	F	[SHIFT IN]	47	2F	/	79	4F	O	111	6F	o
16	10	[DATA LINK ESCAPE]	48	30	0	80	50	P	112	70	p
17	11	[DEVICE CONTROL 1]	49	31	1	81	51	Q	113	71	q
18	12	[DEVICE CONTROL 2]	50	32	2	82	52	R	114	72	r
19	13	[DEVICE CONTROL 3]	51	33	3	83	53	S	115	73	s
20	14	[DEVICE CONTROL 4]	52	34	4	84	54	T	116	74	t
21	15	[NEGATIVE ACKNOWLEDGE]	53	35	5	85	55	U	117	75	u
22	16	[SYNCHRONOUS IDLE]	54	36	6	86	56	V	118	76	v
23	17	[END OF TRANS. BLOCK]	55	37	7	87	57	W	119	77	w
24	18	[CANCEL]	56	38	8	88	58	X	120	78	x
25	19	[END OF MEDIUM]	57	39	9	89	59	Y	121	79	y
26	1A	[SUBSTITUTE]	58	3A	:	90	5A	Z	122	7A	z
27	1B	[ESCAPE]	59	3B	;	91	5B	[	123	7B	{
28	1C	[FILE SEPARATOR]	60	3C	<	92	5C	\	124	7C	|
29	1D	[GROUP SEPARATOR]	61	3D	=	93	5D	]	125	7D	}
30	1E	[RECORD SEPARATOR]	62	3E	>	94	5E	^	126	7E	~
31	1F	[UNIT SEPARATOR]	63	3F	?	95	5F	_	127	7F	[DEL]

- `ord(c)`: returns Unicode (ASCII) of the character.
- Example: `ord('a')` returns 97.
- `chr(x)`: returns the character whose Unicode is x.

Converting from Character to Code:

(There is an ASCII table on the back of today's lecture slip.)



ASCII TABLE

Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char
0	0	[NULL]	32	20	[SPACE]	64	40	@	96	60	`
1	1	[START OF HEADING]	33	21	!	65	41	A	97	61	a
2	2	[START OF TEXT]	34	22	"	66	42	B	98	62	b
3	3	[END OF TEXT]	35	23	#	67	43	C	99	63	c
4	4	[END OF TRANSMISSION]	36	24	$	68	44	D	100	64	d
5	5	[ENQUIRY]	37	25	%	69	45	E	101	65	e
6	6	[ACKNOWLEDGE]	38	26	&	70	46	F	102	66	f
7	7	[BELL]	39	27	'	71	47	G	103	67	g
8	8	[BACKSPACE]	40	28	(	72	48	H	104	68	h
9	9	[HORIZONTAL TAB]	41	29	)	73	49	I	105	69	i
10	A	[LINE FEED]	42	2A	*	74	4A	J	106	6A	j
11	B	[VERTICAL TAB]	43	2B	+	75	4B	K	107	6B	k
12	C	[FORM FEED]	44	2C	,	76	4C	L	108	6C	l
13	D	[CARRIAGE RETURN]	45	2D	-	77	4D	M	109	6D	m
14	E	[SHIFT OUT]	46	2E	.	78	4E	N	110	6E	n
15	F	[SHIFT IN]	47	2F	/	79	4F	O	111	6F	o
16	10	[DATA LINK ESCAPE]	48	30	0	80	50	P	112	70	p
17	11	[DEVICE CONTROL 1]	49	31	1	81	51	Q	113	71	q
18	12	[DEVICE CONTROL 2]	50	32	2	82	52	R	114	72	r
19	13	[DEVICE CONTROL 3]	51	33	3	83	53	S	115	73	s
20	14	[DEVICE CONTROL 4]	52	34	4	84	54	T	116	74	t
21	15	[NEGATIVE ACKNOWLEDGE]	53	35	5	85	55	U	117	75	u
22	16	[SYNCHRONOUS IDLE]	54	36	6	86	56	V	118	76	v
23	17	[END OF TRANS. BLOCK]	55	37	7	87	57	W	119	77	w
24	18	[CANCEL]	56	38	8	88	58	X	120	78	x
25	19	[END OF MEDIUM]	57	39	9	89	59	Y	121	79	y
26	1A	[SUBSTITUTE]	58	3A	:	90	5A	Z	122	7A	z
27	1B	[ESCAPE]	59	3B	;	91	5B	[	123	7B	{
28	1C	[FILE SEPARATOR]	60	3C	<	92	5C	\	124	7C	|
29	1D	[GROUP SEPARATOR]	61	3D	=	93	5D	]	125	7D	}
30	1E	[RECORD SEPARATOR]	62	3E	>	94	5E	^	126	7E	~
31	1F	[UNIT SEPARATOR]	63	3F	?	95	5F	_	127	7F	[DEL]

- `ord(c)`: returns Unicode (ASCII) of the character.
- Example: `ord('a')` returns 97.
- `chr(x)`: returns the character whose Unicode is x.
- Example: `chr(97)` returns 'a'.

Converting from Character to Code:

(There is an ASCII table on the back of today's lecture slip.)



ASCII TABLE

Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char
0	0	[NULL]	32	20	[SPACE]	64	40	@	96	60	`
1	1	[START OF HEADING]	33	21	!	65	41	A	97	61	a
2	2	[START OF TEXT]	34	22	"	66	42	B	98	62	b
3	3	[END OF TEXT]	35	23	#	67	43	C	99	63	c
4	4	[END OF TRANSMISSION]	36	24	$	68	44	D	100	64	d
5	5	[ENQUIRY]	37	25	%	69	45	E	101	65	e
6	6	[ACKNOWLEDGE]	38	26	&	70	46	F	102	66	f
7	7	[BELL]	39	27	'	71	47	G	103	67	g
8	8	[BACKSPACE]	40	28	(	72	48	H	104	68	h
9	9	[HORIZONTAL TAB]	41	29	)	73	49	I	105	69	i
10	A	[LINE FEED]	42	2A	*	74	4A	J	106	6A	j
11	B	[VERTICAL TAB]	43	2B	+	75	4B	K	107	6B	k
12	C	[FORM FEED]	44	2C	,	76	4C	L	108	6C	l
13	D	[CARRIAGE RETURN]	45	2D	-	77	4D	M	109	6D	m
14	E	[SHIFT OUT]	46	2E	.	78	4E	N	110	6E	n
15	F	[SHIFT IN]	47	2F	/	79	4F	O	111	6F	o
16	10	[DATA LINK ESCAPE]	48	30	0	80	50	P	112	70	p
17	11	[DEVICE CONTROL 1]	49	31	1	81	51	Q	113	71	q
18	12	[DEVICE CONTROL 2]	50	32	2	82	52	R	114	72	r
19	13	[DEVICE CONTROL 3]	51	33	3	83	53	S	115	73	s
20	14	[DEVICE CONTROL 4]	52	34	4	84	54	T	116	74	t
21	15	[NEGATIVE ACKNOWLEDGE]	53	35	5	85	55	U	117	75	u
22	16	[SYNCHRONOUS IDLE]	54	36	6	86	56	V	118	76	v
23	17	[END OF TRANS. BLOCK]	55	37	7	87	57	W	119	77	w
24	18	[CANCEL]	56	38	8	88	58	X	120	78	x
25	19	[END OF MEDIUM]	57	39	9	89	59	Y	121	79	y
26	1A	[SUBSTITUTE]	58	3A	:	90	5A	Z	122	7A	z
27	1B	[ESCAPE]	59	3B	;	91	5B	[	123	7B	{
28	1C	[FILE SEPARATOR]	60	3C	<	92	5C	\	124	7C	|
29	1D	[GROUP SEPARATOR]	61	3D	=	93	5D	]	125	7D	}
30	1E	[RECORD SEPARATOR]	62	3E	>	94	5E	^	126	7E	~
31	1F	[UNIT SEPARATOR]	63	3F	?	95	5F	_	127	7F	[DEL]

- `ord(c)`: returns Unicode (ASCII) of the character.
- Example: `ord('a')` returns 97.
- `chr(x)`: returns the character whose Unicode is x.
- Example: `chr(97)` returns 'a'.
- What is `chr(33)`?

In Pairs or Triples...

Some review and some novel challenges:

```
1  #Predict what will be printed:
2
3  for c in range(65,90):
4      print(chr(c))
5
6  message = "I love Python"
7  newMessage = ""
8  for c in message:
9      print(ord(c))   #Print the Unicode of each number
10     print(chr(ord(c)+1))    #Print the next character
11     newMessage = newMessage + chr(ord(c)+1) #add to the new message
12 print("The coded message is", newMessage)
13
14 word = "zebra"
15 codedWord = ""
16 for ch in word:
17     offset = ord(ch) - ord('a') + 1 #how many letters past 'a'
18     wrap = offset % 26  #if larger than 26, wrap back to 0
19     newChar = chr(ord('a') + wrap)  #compute the new letter
20     print(wrap, chr(ord('a') + wrap))    #print the wrap & new lett
21     codedWord = codedWord + newChar #add the newChar to the coded w
22
23 print("The coded word (with wrap) is", codedWord)
```

Python Tutor

```
#Predict what will be printed:

for c in range(65,90):
    print(chr(c))

message = "I love Python"
newMessage = ""
for c in message:
    print(ord(c))   #Print the Unicode of each number
    print(chr(ord(c)+1))    #Print the next character
    newMessage = newMessage + chr(ord(c)+1) #add to the new message
print("The coded message is", newMessage)

word = "zebra"
codedWord = ""
for ch in word:
    offset = ord(ch) - ord('a') + 1 #how many letters past 'a'
    wrap = offset % 26  #if larger than 26, wrap back to 0
    newChar = chr(ord('a') + wrap)  #compute the new letter
    print(wrap, chr(ord('a') + wrap))    #print the wrap & new lett
    codedWord = codedWord + newChar #add the newChar to the coded w

print("The coded word (with wrap) is", codedWord)
```

(Demo with `pythonTutor`)

User Input

Covered in detail in Lab 2:

```
1  mess = input('Please enter a message: ')
2  print("You entered", mess)
```

(Demo with `pythonTutor`)

Side Note: '+' for numbers and strings

- `x = 3 + 5` stores the number 8 in memory location `x`.

Side Note: '+' for numbers and strings

- `x = 3 + 5` stores the number 8 in memory location `x`.
- `x = x + 1` increases `x` by 1.

Side Note: '+' for numbers and strings

- `x = 3 + 5` stores the number 8 in memory location `x`.
- `x = x + 1` increases `x` by 1.
- `s = "hi" + "Mom"` stores `"hiMom"` in memory locations `s`.

Side Note: '+' for numbers and strings

- `x = 3 + 5` stores the number 8 in memory location `x`.
- `x = x + 1` increases `x` by 1.
- `s = "hi" + "Mom"` stores `"hiMom"` in memory locations `s`.
- `s = s + "A"` adds the letter `"A"` to the end of the strings `s`.

Today's Topics

- For-loops
- `range()`
- Variables
- Characters
- **Strings**
- CS Survey (Dr. Sakas, Computational Linguistics)

More on Strings: String Methods

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called `s`, that stores the string: `"FridaysSaturdaysSundays"`

More on Strings: String Methods

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called `s`, that stores the string: `"FridaysSaturdaysSundays"`
- There are many useful functions for strings (more in Lab 2).

More on Strings: String Methods

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called `s`, that stores the string: `"FridaysSaturdaysSundays"`
- There are many useful functions for strings (more in Lab 2).
- `s.count(x)` will count the number of times the pattern, `x`, appears in s.

More on Strings: String Methods

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called `s`, that stores the string: `"FridaysSaturdaysSundays"`
- There are many useful functions for strings (more in Lab 2).
- `s.count(x)` will count the number of times the pattern, `x`, appears in s.
  - `s.count("s")` counts the number of lower case `s` that occurs.

More on Strings: String Methods

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called `s`, that stores the string: `"FridaysSaturdaysSundays"`
- There are many useful functions for strings (more in Lab 2).
- `s.count(x)` will count the number of times the pattern, `x`, appears in s.
  - `s.count("s")` counts the number of lower case `s` that occurs.
  - `num = s.count("s")` stores the result in the variable `num`, for later.

More on Strings: String Methods

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called `s`, that stores the string: `"FridaysSaturdaysSundays"`
- There are many useful functions for strings (more in Lab 2).
- `s.count(x)` will count the number of times the pattern, `x`, appears in s.
  - `s.count("s")` counts the number of lower case `s` that occurs.
  - `num = s.count("s")` stores the result in the variable `num`, for later.
  - What would `print(s.count("sS"))` output?

More on Strings: String Methods

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called `s`, that stores the string: `"FridaysSaturdaysSundays"`
- There are many useful functions for strings (more in Lab 2).
- `s.count(x)` will count the number of times the pattern, `x`, appears in s.
  - `s.count("s")` counts the number of lower case `s` that occurs.
  - `num = s.count("s")` stores the result in the variable `num`, for later.
  - What would `print(s.count("sS"))` output?
  - What about:

    ```
    mess = "10 20 21 9 101 35"
    mults = mess.count("0 ")
    print(mults)
    ```

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[0]` is

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[0]` is `'F'`.

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[1]` is

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[1]` is `'r'`.

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[-1]` is

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[-1]` is `'s'`.

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[3:6]` is

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[3:6]` is `'day'`.

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[:3]` is

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[:3]` is `'Fri'`.

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[:-1]` is

More on Strings: Indexing & Substrings

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	...	16	17	18	19	20	21	22
F	r	i	d	a	y	s	S	a	...	S	u	n	d	a	y	s
												...	-4	-3	-2	-1

- `s[:-1]` is 'FridaysSaturdaysSunday'.
  (no trailing 's' at the end)

More on Strings: Splits

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- `split()` divides a string into a list.

More on Strings: Splits

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- `split()` divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

More on Strings: Splits

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- `split()` divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

"Friday~~s~~Saturday~~s~~Sunday"

More on Strings: Splits

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- `split()` divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

```
"FridaysSaturdaysSunday"
days = ['Friday', 'Saturday', 'Sunday']
```

More on Strings: Splits

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- `split()` divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

```
"FridaysSaturdaysSunday"
days = ['Friday', 'Saturday', 'Sunday']
```

- Different delimiters give different lists:

More on Strings: Splits

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- `split()` divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

```
"FridaysSaturdaysSunday"
days = ['Friday', 'Saturday', 'Sunday']
```

- Different delimiters give different lists:

```
days = s[:-1].split("day")
```

More on Strings: Splits

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- `split()` divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

```
"FridayXSaturdayXSunday"
days = ['Friday', 'Saturday', 'Sunday']
```

- Different delimiters give different lists:

```
days = s[:-1].split("day")
"FridaysSaturdaysSunday"
```

More on Strings: Splits

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- `split()` divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

```
"FridayXSaturdayXSunday"
days = ['Friday', 'Saturday', 'Sunday']
```

- Different delimiters give different lists:

```
days = s[:-1].split("day")
"FridaysSaturdaysSunday"
days = ['Fri', 'sSatur', 'sSun']
```

Today's Topics

- For-loops
- `range()`
- Variables
- Characters
- Strings
- **CS Survey (Dr. Sakas, Computational Linguistics)**

CS Survey: Prof. Sakas, Computational Computational Linguistics



Language is Hard for Computers

Learning Language is Easy for my 3-year-old twins

CSCI 12700 Guest Bullet Talk

William Gregory Sakas

HUNTER
The City University of New York

M.A./Ph.D. Program in Linguistics
@ The City University of New York

CS Survey: Prof. Sakas, Computational Computational Linguistics



Language is Hard

- *Buffalo buffalo, Buffalo buffalo buffalo, buffalo, Buffalo buffalo*
- *Someone shot the servant of the actress who was on the balcony.* **Who was on the balcony?**
- *Who do you think Mary kissed?*
- *Who do you think* ***that*** *Mary kissed?*
- *Who do you think bought a radio?*
- ***** *Who do you think* ***that*** *bought a radio?*

CS Survey: Prof. Sakas, Computational Computational Linguistics



So how to explain language?

Treat Language as a **scientific field - like Physics.**

Example: A scientific principle about sentences:

Given <p> = [α [H β]],
where α = edge(*Spec's*) β then:
the head H of <p> is inert after the phase is completed, triggering no further grammatical operations.

Language is complex!!!
Understanding how language works is hard!!!

Unless you're 3.

CS Survey: Prof. Sakas, Computational Computational Linguistics

Linguistic experts!

Lecture Slip

Linguistic experts!

Design a program that **counts** the number of plural nouns in a **list** of nouns. Think about:

- what the input is,
- what the output is, and
- how you can determine if a noun is plural.

Note: To simplify the problem, assume all plural nouns end in "s".

Recap

- On lecture slip, write down a topic you wish we had spent more time (and why).

```
#Predict what will be printed:
for i in range(4):
    print('The world turned upside down')
for j in [0,1,2,3,4,5]:
    print(j)
for count in range(6):
    print(count)
for color in ['red', 'green', 'blue']:
    print(color)
for i in range(2):
    for j in range(2):
        print('Look around,')
    print('How lucky we are to be alive!')
```

Recap

- On lecture slip, write down a topic you wish we had spent more time (and why).
- In Python, we introduced:

```
#Predict what will be printed:
for i in range(4):
    print('The world turned upside down')
for j in [0,1,2,3,4,5]:
    print(j)
for count in range(6):
    print(count)
for color in ['red', 'green', 'blue']:
    print(color)
for i in range(2):
    for j in range(2):
        print('Look around,')
    print('How lucky we are to be alive!')
```

Recap

```
#Predict what will be printed:
for i in range(4):
    print('The world turned upside down')
for j in [0,1,2,3,4,5]:
    print(j)
for count in range(6):
    print(count)
for color in ['red', 'green', 'blue']:
    print(color)
for i in range(2):
    for j in range(2):
        print('Look around,')
    print('How lucky we are to be alive!')
```

- On lecture slip, write down a topic you wish we had spent more time (and why).
- In Python, we introduced:
  - For-loops

Recap

```
#Predict what will be printed:
for i in range(4):
    print('The world turned upside down')
for j in [0,1,2,3,4,5]:
    print(j)
for count in range(6):
    print(count)
for color in ['red', 'green', 'blue']:
    print(color)
for i in range(2):
    for j in range(2):
        print('Look around,')
    print('How lucky we are to be alive!')
```

- On lecture slip, write down a topic you wish we had spent more time (and why).
- In Python, we introduced:
  - For-loops
  - `range()`

Recap

```
#Predict what will be printed:
for i in range(4):
    print('The world turned upside down')
for j in [0,1,2,3,4,5]:
    print(j)
for count in range(6):
    print(count)
for color in ['red', 'green', 'blue']:
    print(color)
for i in range(2):
    for j in range(2):
        print('Look around,')
    print('How lucky we are to be alive!')
```

- On lecture slip, write down a topic you wish we had spent more time (and why).
- In Python, we introduced:
  - For-loops
  - `range()`
  - Variables: ints and strings

Recap

```
#Predict what will be printed:
for i in range(4):
    print('The world turned upside down')
for j in [0,1,2,3,4,5]:
    print(j)
for count in range(6):
    print(count)
for color in ['red', 'green', 'blue']:
    print(color)
for i in range(2):
    for j in range(2):
        print('Look around,')
    print('How lucky we are to be alive!')
```

- On lecture slip, write down a topic you wish we had spent more time (and why).
- In Python, we introduced:
  - For-loops
  - `range()`
  - Variables: ints and strings
  - Some arithmetic

Recap

```
#Predict what will be printed:
for i in range(4):
    print('The world turned upside down')
for j in [0,1,2,3,4,5]:
    print(j)
for count in range(6):
    print(count)
for color in ['red', 'green', 'blue']:
    print(color)
for i in range(2):
    for j in range(2):
        print('Look around,')
    print('How lucky we are to be alive!')
```

- On lecture slip, write down a topic you wish we had spent more time (and why).
- In Python, we introduced:
  - For-loops
  - `range()`
  - Variables: ints and strings
  - Some arithmetic
  - String concatenation

Recap

```
#Predict what will be printed:
for i in range(4):
    print('The world turned upside down')
for j in [0,1,2,3,4,5]:
    print(j)
for count in range(6):
    print(count)
for color in ['red', 'green', 'blue']:
    print(color)
for i in range(2):
    for j in range(2):
        print('Look around,')
    print('How lucky we are to be alive!')
```

- On lecture slip, write down a topic you wish we had spent more time (and why).
- In Python, we introduced:
  - For-loops
  - `range()`
  - Variables: ints and strings
  - Some arithmetic
  - String concatenation
  - Functions: `ord()` and `char()`

Recap

```
1  #Predict what will be printed:
2  for i in range(4):
3      print('The world turned upside down')
4  for j in [0,1,2,3,4,5]:
5      print(j)
6  for count in range(6):
7      print(count)
8  for color in ['red', 'green', 'blue']:
9      print(color)
10 for i in range(2):
11     for j in range(2):
12         print('Look around,')
13     print('How lucky we are to be alive!')
```

- On lecture slip, write down a topic you wish we had spent more time (and why).
- In Python, we introduced:
  - For-loops
  - `range()`
  - Variables: ints and strings
  - Some arithmetic
  - String concatenation
  - Functions: `ord()` and `char()`
  - String Manipulation

Recap

```
#Predict what will be printed:
for i in range(4):
    print('The world turned upside down')
for j in [0,1,2,3,4,5]:
    print(j)
for count in range(6):
    print(count)
for color in ['red', 'green', 'blue']:
    print(color)
for i in range(2):
    for j in range(2):
        print('Look around,')
    print('How lucky we are to be alive!')
```

- On lecture slip, write down a topic you wish we had spent more time (and why).
- In Python, we introduced:
  - For-loops
  - `range()`
  - Variables: ints and strings
  - Some arithmetic
  - String concatenation
  - Functions: `ord()` and `char()`
  - String Manipulation
- Pass your lecture slips to the end of the rows for the UTA's to collect.

Practice Quiz & Final Questions



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.

Practice Quiz & Final Questions



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).

Practice Quiz & Final Questions



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:

Practice Quiz & Final Questions



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
  - write as much you can for 60 seconds;

Practice Quiz & Final Questions



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
  - write as much you can for 60 seconds;
  - followed by answer; and

Practice Quiz & Final Questions



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
  - write as much you can for 60 seconds;
  - followed by answer; and
  - repeat.

Practice Quiz & Final Questions



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
  - write as much you can for 60 seconds;
  - followed by answer; and
  - repeat.
- Past exams are on the webpage (under Final Exam Information).

Practice Quiz & Final Questions



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
  - write as much you can for 60 seconds;
  - followed by answer; and
  - repeat.
- Past exams are on the webpage (under Final Exam Information).
- We're starting with Spring 2018, Mock Exam.

Writing Boards



- Return writing boards as you leave...