CSci 127: Introduction to Computer Science



hunter.cuny.edu/csci

From email

From email

From email

• How do I know the height and width of an image?

From email

• How do I know the height and width of an image?

When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.

From email

• How do I know the height and width of an image?

When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.

We will start with that today.

From email

• How do I know the height and width of an image?

When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.

We will start with that today.

• Why are we looking at NYC historical population and CUNY enrollment data?

From email

• How do I know the height and width of an image?

When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.

We will start with that today.

• Why are we looking at NYC historical population and CUNY enrollment data? We are showing you how to access and analyze data. The tools we are exploring can be applied to many different datasets.

From email

• How do I know the height and width of an image?

When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.

We will start with that today.

• Why are we looking at NYC historical population and CUNY enrollment data? We are showing you how to access and analyze data. The tools we are exploring can be applied to many different datasets. We will explore many more in the coming weeks!

From email

- How do I know the height and width of an image?
 - When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.
 - We will start with that today.
- Why are we looking at NYC historical population and CUNY enrollment data? We are showing you how to access and analyze data. The tools we are exploring can be applied to many different datasets.
 - We will explore many more in the coming weeks!
- What is the difference between [] and ()?

From email

• How do I know the height and width of an image?

When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.

We will start with that today.

- Why are we looking at NYC historical population and CUNY enrollment data? We are showing you how to access and analyze data. The tools we are exploring can be applied to many different datasets.

 We will explore many more in the coming weeks!
- What is the difference between [] and ()? Parenthesis () generally follow function names, e.g. print(). You may also find them in mathematical and boolean expressions, e.g. (x == 2*(y+3)) and (x < 10)

From email

• How do I know the height and width of an image?

When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.

We will start with that today.

- Why are we looking at NYC historical population and CUNY enrollment data? We are showing you how to access and analyze data. The tools we are exploring can be applied to many different datasets.
 - We will explore many more in the coming weeks!
- What is the difference between [] and ()?

Parenthesis () generally follow function names, e.g. print().

You may also find them in mathematical and boolean expressions,

e.g.
$$(x == 2*(y+3))$$
 and $(x < 10)$

We use square brackets [] to index or slice,

i.e. take a piece, of a string, list or numpy array: my_string[2:5]

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

Crop an image to select the top quarter (upper left corner)



```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = imq.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(imq2)
plt.show()
```

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```




```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



8 / 54

CSci 127 (Hunter) Lecture 7 22 March 2022

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



• How would you select the lower left corner?

9 / 54

CSci 127 (Hunter) Lecture 7 22 March 2022

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```




• How would you select the lower left corner? img2 = img[height//2:, :width//2]

9 / 54

CSci 127 (Hunter) Lecture 7 22 March 2022


```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner?

22 March 2022


```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[:height//2, width//2:]


22 March 2022

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[:height//2, width//2:]
- How would you select the lower right corner?

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```




- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[:height//2, width//2:]
- How would you select the lower right corner? img2 = img[height//2:, width//2:]

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data


Scripts



Modularity



Modularity



 Functions are a way to break code into pieces, that can be easily reused.

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
      says hello to the world!
def main():
     print("Hello, World!")
if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.

14 / 54

Lecture 7

```
#Name: your name here
#Date: October 2017
This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- Naming conventions same as variables

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- Naming conventions same as variables
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- Naming conventions same as variables
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- Naming conventions same as variables
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions,

Functions

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- Naming conventions same as variables
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.

"Hello, World!" with Functions

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
#
      says hello to the world!
def main():
     print("Hello, World!")
if __name__ == "__main__":
     main()
```

Python Tutor

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

(Demo with pythonTutor)

22 March 2022


16 / 54

CSci 127 (Hunter) Lecture 7


functions - modules - packages



functions - modules - packages



functions - modules - packages



CSci 127 (Hunter) Lecture 7 22 March 2022 19/54

Stand-alone program



CSci 127 (Hunter) Lecture 7 22 March 2022 20 / 54

Predict what the code will do:

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
ITotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

Python Tutor

```
def totalWithTax(food,tip):
total = 0
tax = 0.8875
total = food + food * tax
total = total + tip
return(total)
lunch = floot(input('inter lunch total: '))
lTip= floot(input('inter lunch tip: '))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)
dimen= floot(input('finter dimene tipa'))
divided = totalWithTax(lunch, lTip)
print('Lunch (input('finter dimene tipa'))
dfotal = totalWithTax(dinner, dTip)
dfotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

(Demo with pythonTutor)

Scope

```
def eight():
    x = 5+3
    print(x)

def nine():
    x = "nine"
    print(x)
```

 You can have multiple functions.

Scope

```
def eight():
    x = 5+3
    print(x)
def nine():
    x = "nine"
    print(x)
```

- You can have multiple functions.
- Each function defines the scope of its local variables


Scope

```
def eight():
    x = 5+3
    print(x)

def nine():
    x = "nine"
    print(x)
```

- You can have multiple functions.
- Each function defines the scope of its local variables
- A variable defined inside a function is **local**, i.e. defined only inside that function.

Local Data?



CSci 127 (Hunter) Lecture 7 22 March 2022 24/54

 Functions can have input parameters.

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)
dinner= float(input('Enter dinner total: '))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)

lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)

dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).

```
def totalWithTax(food,tip):
    total = 0
tax = 0.0875
total = food + food * tax
    total = total + tip
    return(total)

lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)

dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)

lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('lunch total is', lTotal)

dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters

```
def totalWithTax(food,tip):
    total = 0
                        Formal Parameters
    tax = 0.0875
    total = food + food * tax
    total = total + tip
   return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', [[otal)
                           Actual Parameters
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal = totalWithTax dinner, dTip
print('Dinner total is', grocal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters.

```
def totalWithTax(food,tip):
    total = 0
                        Formal Parameters
    tax = 0.0875
    total = food + food * tax
    total = total + tip
   return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', [[otal)
                           Actual Parameters
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal = totalWithTax dinner, dTip
print('Dinner total is', grocal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition. and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters.
- Functions can also return **values** to where it was called.

Circle the actual parameters and underline the formal parameters:

```
def prob4():
    verse = "jam tomorrow and jam yesterday,"
    print("The rule is.")
    c = mystery(verse)
    w = enigma(verse.c)
    print(c,w)
def mystery(v):
    print(v)
    c = v.count("jam")
    return(c)
def enigma(v,c):
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
prob4()
```

Circle the actual parameters and underline the formal parameters:

```
def prob4():
    verse "jam tomorrow and jam yesterday,"
    print("The rule is,")
    c = hystery (verse)
    w = enigma (verse,c)
                                   *Actual
    print(c,w)
                                   Parameters
def mystery(v):
    print(v)
    c = v.count(fiam
    return(c)
                                     Formal
def enigma(v,c):
                                      Parameters
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
prob4()
```

Predict what the code will do:

```
def prob4():
    verse = "jam tomorrow and jam yesterday,"
    print("The rule is,")
    c = mystery(verse)
    w = enigma(verse,c)
    print(c,w)
def mystery(v):
    print(v)
    c = v.count("jam")
    return(c)
def enigma(v,c):
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
prob4()
```

Python Tutor

```
def probé():
    verse = "jam tomorrow and jam yesterday,"
    print("The rule is,")
    c = mystery(verse)
    w = enigma(verse,c)
    print(")
    print(")
    c = v.count("jam")
    return(c)
    def enigma(v,c)
    print(")
    print(")
    print(")
    print(")
    print(")
    print(")
    print(")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
```

prob4()

(Demo with pythonTutor)

30 / 54

CSci 127 (Hunter) Lecture 7 22 March 2022

Predict what the code will do:

```
#Greet loop example

def greetLoop(person):
    print("Greetings")
    for i in range(5):
        print("Hello", person)

greetLoop("Thomas")
```

```
# From "Teaching with Python" by John Zelle

def happy():
    print("Happy Birthday to you!")

def sing(P):
    happy()
    happy()
    print("Happy Birthday dear " + P + "!")
    happy()

sing("Fred")
sing("Thomas")
sing("Hunter")
```

Python Tutor

```
#Greet loop example
 def greetLoop(person):
      print("Greetings")
     for i in range(5):
          print("Hello", person)
 greetLoop("Thomas")
# From "Teaching with Python" by John Zelle
def happy():
   print("Happy Birthday to you!")
def sing(P):
   happy()
   happy()
   print("Happy Birthday dear " + P + "!")
   happy()
sing("Fred")
sing("Thomas")
sing("Hunter")
```

(Demo with pythonTutor)

Fill in the missing code:

```
def monthString(monthNum):
    Takes as input a number, monthNum, and
    returns the corresponding month name as a string.
    Example: monthString(1) returns "January".
    Assumes that input is an integer ranging from 1 to 12
    monthString = ""
     ********************************
    ### FTLL TN YOUR CODE HERE
                                    ###
    ### Other than your name above, ###
    ### this is the only section
                                    ###
    ### you change in this program. ###
    *************
    return(monthString)
def main():
    n = int(input('Enter the number of the month: '))
    mString = monthString(n)
    print('The month is', mString)
```

IDLE

def main():

n = int(input('Enter the number of the month: '))
mString = monthString(n)
print('The month is', mString)

CSci 127 (Hunter) Lecture 7 22 March 2022 34 / 54

 Used to collaborate on and share code, documents, etc.



CSci 127 (Hunter) Lecture 7 22 March 2022 35 / 54



Octocat

- Used to collaborate on and share code, documents, etc.
- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.



- Used to collaborate on and share code, documents, etc.
- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.



 Used to collaborate on and share code, documents, etc.

- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.
- Github provides hosting for repositories ('repos') of code.



 Used to collaborate on and share code, documents, etc.

- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.
- Github provides hosting for repositories ('repos') of code.
- Also convenient place to host websites (i.e. huntercsci127.github.io).



Octocat

- Used to collaborate on and share code, documents, etc.
- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.
- Github provides hosting for repositories ('repos') of code.
- Also convenient place to host websites (i.e. huntercsci127.github.io).
- In Lab6 you set up github accounts to copy ('clone') documents from the class repo. (More in future courses.)

Recap: Functions

```
#Name: your name here
#Date: October 2017
This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

 Functions are a way to break code into pieces, that can be easily reused.

Recap: Functions

```
#Name: your name here
#Date: October 2017
This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
```

main()

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:

Recap: Functions

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
```

main()

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")

Recap: Functions

```
#Name: your name here
#Date: October 2017
This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions,

Recap: Functions

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

CSci 127 (Hunter) Lecture 7 22 March 2022 37/54



Freely available source of data.

CSci 127 (Hunter) Lecture 7 22 March 2022 38 / 54



- Freely available source of data.
- Maintained by the NYC data analytics team.

CSci 127 (Hunter) Lecture 7 22 March 2022 38 / 54



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.

CSci 127 (Hunter) Lecture 7 22 March 2022 38 / 54



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.
- Will use pandas, pyplot & folium libraries to analyze, visualize and map the data.



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.
- Will use pandas, pyplot & folium libraries to analyze, visualize and map the data.
- Lab 7 covers accessing and downloading NYC OpenData datasets.



Home Data About V Learn

Film Permits

Permits are generally required when asserting the exclusive use of city property, like a sidewalk, a street, or a park. See http://www1.nyc.gov/site/mome/permits/when-permit-required.page


EventID :	EventType :	StartDateTi	EndDateTime :	EnteredOn ↓ :	EventAg :	ParkingHeld :	Borou
455063	Shooting Permit	12/06/2018 07:00	12/06/2018 09:00	12/05/2018 12:36	Mayor's Offic	STARR AVENUE b	Queens
454967	Shooting Permit	12/06/2018 07:00	12/06/2018 05:00	12/04/2018 09:11	Mayor's Offic	EAGLE STREET be	Brooklyn
454941	Shooting Permit	12/06/2018 07:00	12/06/2018 07:00	12/04/2018 05:44	Mayor's Offic	SOUTH OXFORD	Brooklyn
454920	Shooting Permit	12/06/2018 10:00	12/06/2018 11:59	12/04/2018 03:28	Mayor's Offic	13 AVENUE betw	Queens
454914	Shooting Permit	12/06/2018 08:00	12/06/2018 11:00	12/04/2018 03:05	Mayor's Offic	ELDERT STREET b	Brooklyn
454909	Shooting Permit	12/05/2018 08:00	12/05/2018 06:00	12/04/2018 02:45	Mayor's Offic	ELDERT STREET b	Brooklyn
454905	Shooting Permit	12/06/2018 07:00	12/06/2018 10:00	12/04/2018 02:17	Mayor's Offic	35 STREET betwe	Queens



• What's the most popular street for filming?



- What's the most popular street for filming?
- What's the most popular borough?



- What's the most popular street for filming?
- What's the most popular borough?
- How many TV episodes were filmed?



Download the data as a CSV file and store on your computer.



- Download the data as a CSV file and store on your computer.
- Python program:



- Download the data as a CSV file and store on your computer.
- Python program:

#CSci 127 Teachina Staff

```
#March 2019
#OpenData Film Permits

#Import pandas for reading and analyzing CSV data:
import pandas as pd
csvFile = "filmPermits.csv"  #Name of the CSV file
tickets = pd.read_csv(csvFile)#Read in the file to a dataframe
print(tickets)  #Print out the dataframe
```



- Download the data as a CSV file and store on your computer.
- Python program:



- Download the data as a CSV file and store on your computer.
- Python program:

#CSci 127 Teachina Staff




- Download the data as a CSV file and store on your computer.
- Python program:

```
#CSci 127 Teaching Staff
#March 2019
#OpenData Film Permits

#Import pandas for reading and analyzing CSV data:
import pandas as pd
csvFile = "filmPermits.csv"  #Name of the CSV file
tickets = pd.read_csv(csvFile)#Read in the file to a dataframe
print(tickets)  #Print out the dataframe
print(tickets["ParkingHeld"])  #Print out streets (multiple times)
print(tickets["ParkingHeld"].value_counts())  #Print out streets & number of times used
print(tickets["ParkingHeld"].value_counts()[:10])  #Print 10 most popular
```

4 D > 4 A > 4 B > 4 B > B

90 Q




Can approach the other questions in the same way:

- What's the most popular street for filming?
- What's the most popular borough?
- How many TV episodes were filmed?

46 / 54

MY HOBBY: EMBEDDING NP-COMPLETE PROBLEMS IN RESTAURANT ORDERS





CSci 127 (Hunter) Lecture 7 22 March 2022 47/54

MY HOBBY: Embedding NP-complete problems in restaurant orders



Possible solutions:


CSci 127 (Hunter) Lecture 7 22 March 2022 48/54

MY HOBBY: Embedding NP-complete problems in restaurant orders



- Possible solutions:
 - ▶ 7 orders of mixed fruit, or

MY HOBBY: EMBEDDING NP-COMPLETE PROBLEMS IN RESTAURANT ORDERS



- Possible solutions:
 - ▶ 7 orders of mixed fruit, or
 - ▶ 2 orders hot wings, 1 order mixed fruit, and 1 sampler plate.


MY HOBBY: Embedding NP-complete problems in restaurant orders



- Possible solutions:
 - ▶ 7 orders of mixed fruit, or
 - ▶ 2 orders hot wings, 1 order mixed fruit, and 1 sampler plate.
- Input: List of items with prices and amount to be spent.

CSci 127 (Hunter) Lecture 7 22 March 2022 48 / 54

MY HOBBY: Embedding NP-complete problems in restaurant orders



- Possible solutions:
 - ▶ 7 orders of mixed fruit, or
 - ▶ 2 orders hot wings, 1 order mixed fruit, and 1 sampler plate.
- Input: List of items with prices and amount to be spent.
- Output: An order that totals to the amount or empty list if none.

MY HOBBY: EMBEDDING NP-COMPLETE PROBLEMS IN RESTAURANT ORDERS CHOTCHKIES RESTAURANT WE'D LIKE EXACTLY \$15: 05 ~ APPETIZERS~



- Possible solutions:
 - 7 orders of mixed fruit. or
 - ▶ 2 orders hot wings, 1 order mixed fruit, and 1 sampler plate.
- **Input:** List of items with prices and amount to be spent.
- **Output:** An order that totals to the amount or empty list if none.
- Possible algorithms: For each item on the list, divide total by price. If no remainder, return a list of that item. Repeat with two items, trying 1 of the first, 2 of the first, etc. Repeat with three items, etc.

MY HOBBY: EMBEDDING NP-COMPLETE PROBLEMS IN RESTAURANT ORDERS CHOTCHKIES RESTAURANT WE'D LIKE EXACTLY \$15: 05 ~ APPETIZERS~ ... EXACTLY? UHV ... FRENCH FRIES 2.75 LISTEN T HAVE SIX OTHER SIDE SALAD 3.35 - AG FAST AS POSSIBLE OF COURSE. WANT HOT WINGS 3.55 SOMETHING ON TRAVELING SALESMAN? MOZZAREJIA STICKS 4.20 5.80 SAMPLER PLATE → SANDWICHES
→

- Possible solutions:
 - ▶ 7 orders of mixed fruit, or
 - ▶ 2 orders hot wings, 1 order mixed fruit, and 1 sampler plate.
- Input: List of items with prices and amount to be spent.
- Output: An order that totals to the amount or empty list if none.
- Possible algorithms: For each item on the list, divide total by price. If no remainder, return a list of that item. Repeat with two items, trying 1 of the first, 2 of the first, etc. Repeat with three items, etc.
- "NP-Complete" problem: possible answers can be checked quickly, but not known how to compute quickly.
 CSci 127 (Hunter)
 Lecture 7
 22 March 2022
 48/54





• **Functions** are a way to break code into pieces, that can be easily reused.





- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:





- **Functions** are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 Example: print("Hello", "World")





- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 Example: print("Hello", "World")
- Can write, or define your own functions,





- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.





- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.
- Accessing Formatted Data: NYC OpenData


Practice Quiz & Final Questions

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

```
def total#thfac Took.tip)
total = 8 s Formal Parameters
total = 8 s Formal Parameters
total = food + food * too
total = food + food * too
total = food + food * too
total = total * tip
return(total)
IIIG = floot(input('pitcal.meat.(ip' '))
IIIG = floot(input('pitcal.meat.(ip' '))
Floot(input('pitcal.meat.(ip' '))
Floot(input('pitcal.meat.(ip' '))
flootal = total#thfac@input('))
flootal = total#thfac@input(')
flootal = total#thfac@i
```



• Since you must pass the final exam to pass the course, we end every lecture with final exam review.

Practice Quiz & Final Questions

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```


```
der totalkithen (Ood, IID)

total = 0

Formal Parameters

total = 0

total =
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - ▶ followed by answer; and
 - ► repeat.

Practice Quiz & Final Questions

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
     says hello to the world!
def main():
     print("Hello, World!")
if __name__ == "__main__":
     main()
```

```
def totalWithTax food.tip):
    total - 8
                        Formal Parameters
    tax - 0.0875
    total = food + food * tax
    total - total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal - totalWithTax(lunch, lTip)
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', arotal)
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - followed by answer; and
 - repeat.
- Past exams are on the webpage (under Final Exam Information).
- Theme: Functions! Starting with Spring 19 V3, #4(b).



Before next lecture, don't forget to:

Work on this week's Online Lab

CSci 127 (Hunter) Lecture 7 22 March 2022 51/54



Before next lecture, don't forget to:

- Work on this week's Online Lab
- Schedule an appointment to take the Quiz in lab 1001E Hunter North

CSci 127 (Hunter) Lecture 7 22 March 2022 51 / 54



- Work on this week's Online Lab
- Schedule an appointment to take the Quiz in lab 1001E Hunter North
- If you haven't already, schedule an appointment to take the Code Review (one every two weeks) in lab 1001E Hunter North



- Work on this week's Online Lab
- Schedule an appointment to take the Quiz in lab 1001E Hunter North
- If you haven't already, schedule an appointment to take the Code Review (one every two weeks) in lab 1001E Hunter North
- Submit this week's 5 programming assignments (programs 31-35)



- Work on this week's Online Lab
- Schedule an appointment to take the Quiz in lab 1001E Hunter North
- If you haven't already, schedule an appointment to take the Code Review (one every two weeks) in lab 1001E Hunter North
- Submit this week's 5 programming assignments (programs 31-35)
- If you need help, schedule an appointment for Tutoring in lab 1001E 11am-5pm



- Work on this week's Online Lab
- Schedule an appointment to take the Quiz in lab 1001E Hunter North
- If you haven't already, schedule an appointment to take the Code Review (one every two weeks) in lab 1001E Hunter North
- Submit this week's 5 programming assignments (programs 31-35)
- If you need help, schedule an appointment for Tutoring in lab 1001E 11am-5pm
- Take the Lecture Preview on Blackboard on Monday (or no later than 10am on Tuesday)

Lecture Slips & Writing Boards



- Hand your lecture slip to a UTA.
- Return writing boards as you leave.

CSci 127 (Hunter) Lecture 7 22 March 2022 52 / 54