

CSci 127: Introduction to Computer Science



hunter.cuny.edu/csci

- This lecture will be recorded

Teacher Evaluation

- Please take a moment to fill out the **Teacher Evaluations**

Teacher Evaluation

- Please take a moment to fill out the **Teacher Evaluations**
- Your chance to provide feedback!

Teacher Evaluation

- Please take a moment to fill out the **Teacher Evaluations**
- Your chance to provide feedback!
- Responses are **completely anonymous**.

Teacher Evaluation

- Please take a moment to fill out the **Teacher Evaluations**
- Your chance to provide feedback!
- Responses are **completely anonymous**.
- Smartphone: www.hunter.cuny.edu/mobilete

Teacher Evaluation

- Please take a moment to fill out the **Teacher Evaluations**
- Your chance to provide feedback!
- Responses are **completely anonymous**.
- Smartphone: www.hunter.cuny.edu/mobilete
- Computer: www.hunter.cuny.edu/te

Teacher Evaluation

- Please take a moment to fill out the **Teacher Evaluations**
- Your chance to provide feedback!
- Responses are **completely anonymous**.
- Smartphone: www.hunter.cuny.edu/mobilete
- Computer: www.hunter.cuny.edu/te

Announcements

- **Final Exam Wednesday 12 June**

Announcements

- **Final Exam Wednesday 12 June**
- **Tuesday 11 July we will have an IN-PERSON Mock Exam**

Announcements

- **Final Exam Wednesday 12 June**
- **Tuesday 11 July we will have an IN-PERSON Mock Exam**
 - ▶ Room 1001E Hunter North


Announcements

- **Final Exam Wednesday 12 June**
- **Tuesday 11 July we will have an IN-PERSON Mock Exam**
 - ▶ Room 1001E Hunter North
 - ▶ Only 1.35 hours for the Mock, 2 hours for the real exam.

Announcements

- **Final Exam Wednesday 12 June**
- **Tuesday 11 July we will have an IN-PERSON Mock Exam**
 - ▶ Room 1001E Hunter North
 - ▶ Only 1.35 hours for the Mock, 2 hours for the real exam.
 - ▶ Just a practice run, this WILL NOT be the same as the real exam, and it will not be graded.

CSci 127: Introduction to Computer Science



hunter.cuny.edu/csci

Frequently Asked Questions

- What's the best way to study for the final exam?

Frequently Asked Questions

- What's the best way to study for the final exam?

The final exam problems are variations on the homework, quizzes, lecture examples, and lecture previews.

Frequently Asked Questions

- What's the best way to study for the final exam?

The final exam problems are variations on the homework, quizzes, lecture examples, and lecture previews.

Past exams (and answer keys) are on-line. Do 7-10 previous exams: allow 1 hour (half time) and work through , grade yourself, update note sheet, and repeat.

Frequently Asked Questions

- What's the best way to study for the final exam?

The final exam problems are variations on the homework, quizzes, lecture examples, and lecture previews.

Past exams (and answer keys) are on-line. Do 7-10 previous exams: allow 1 hour (half time) and work through , grade yourself, update note sheet, and repeat.

- I'm worried about my grade. Should I do Credit/NoCredit?

Frequently Asked Questions

- What's the best way to study for the final exam?

The final exam problems are variations on the homework, quizzes, lecture examples, and lecture previews.

Past exams (and answer keys) are on-line. Do 7-10 previous exams: allow 1 hour (half time) and work through , grade yourself, update note sheet, and repeat.

- I'm worried about my grade. Should I do Credit/NoCredit?

It's fine with us, but check with your advisor to make sure it's accepted for your program of study.

Frequently Asked Questions

- What's the best way to study for the final exam?

The final exam problems are variations on the homework, quizzes, lecture examples, and lecture previews.

Past exams (and answer keys) are on-line. Do 7-10 previous exams: allow 1 hour (half time) and work through , grade yourself, update note sheet, and repeat.

- I'm worried about my grade. Should I do Credit/NoCredit?

It's fine with us, but check with your advisor to make sure it's accepted for your program of study.

- Why do you care about cheating?

Frequently Asked Questions

- What's the best way to study for the final exam?

The final exam problems are variations on the homework, quizzes, lecture examples, and lecture previews.

Past exams (and answer keys) are on-line. Do 7-10 previous exams: allow 1 hour (half time) and work through , grade yourself, update note sheet, and repeat.

- I'm worried about my grade. Should I do Credit/NoCredit?

It's fine with us, but check with your advisor to make sure it's accepted for your program of study.

- Why do you care about cheating?

First: it gives unfair advantage & is immoral.

Frequently Asked Questions

- What's the best way to study for the final exam?

The final exam problems are variations on the homework, quizzes, lecture examples, and lecture previews.

Past exams (and answer keys) are on-line. Do 7-10 previous exams: allow 1 hour (half time) and work through , grade yourself, update note sheet, and repeat.

- I'm worried about my grade. Should I do Credit/NoCredit?

It's fine with us, but check with your advisor to make sure it's accepted for your program of study.

- Why do you care about cheating?

First: it gives unfair advantage & is immoral.

Second: it degrades the quality of our students.

Frequently Asked Questions

- What's the best way to study for the final exam?

The final exam problems are variations on the homework, quizzes, lecture examples, and lecture previews.

Past exams (and answer keys) are on-line. Do 7-10 previous exams: allow 1 hour (half time) and work through , grade yourself, update note sheet, and repeat.

- I'm worried about my grade. Should I do Credit/NoCredit?

It's fine with us, but check with your advisor to make sure it's accepted for your program of study.

- Why do you care about cheating?

First: it gives unfair advantage & is immoral.

Second: it degrades the quality of our students.

Third: it's a standard question on faculty references.

Frequently Asked Questions

- What's the best way to study for the final exam?

The final exam problems are variations on the homework, quizzes, lecture examples, and lecture previews.

Past exams (and answer keys) are on-line. Do 7-10 previous exams: allow 1 hour (half time) and work through , grade yourself, update note sheet, and repeat.

- I'm worried about my grade. Should I do Credit/NoCredit?

It's fine with us, but check with your advisor to make sure it's accepted for your program of study.

- Why do you care about cheating?

First: it gives unfair advantage & is immoral.

Second: it degrades the quality of our students.

Third: it's a standard question on faculty references.

Industry & graduate schools hate it: don't want someone who falsifies work.

Today's Topics

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

- Recap: I/O & Definite Loops in C++
- Conditionals in C++
- Indefinite Loops in C++
- Recap: C++ & Python

Today's Topics

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

- Recap: I/O & Definite Loops in C++
- Conditionals in C++
- Indefinite Loops in C++
- Recap: C++ & Python

Recap: Basic Form & I/O in C++

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables:

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: `int num;`
- Many types available:

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: `int num;`
- Many types available:
`int, float, char, ...`

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;
- Many types available:
int, float, char, ...
- To print:

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;
- Many types available:
int, float, char, ...
- To print: cout << "Hello!!";

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;
- Many types available:
int, float, char, ...
- To print: cout << "Hello!!";
- To get input:

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;
- Many types available:
int, float, char, ...
- To print: cout << "Hello!!";
- To get input: cin >> num;

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;
- Many types available:
int, float, char, ...
- To print: cout << "Hello!!";
- To get input: cin >> num;
- To use those I/O functions:

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;
- Many types available:
int, float, char, ...
- To print: cout << "Hello!!";
- To get input: cin >> num;
- To use those I/O functions:
`#include <iostream>
using namespace std;`

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;
- Many types available:
int, float, char, ...
- To print: cout << "Hello!!";
- To get input: cin >> num;
- To use those I/O functions:
`#include <iostream>
using namespace std;`
- Definite loops:

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;
- Many types available:
int, float, char, ...
- To print: cout << "Hello!!";
- To get input: cin >> num;
- To use those I/O functions:
`#include <iostream>
using namespace std;`
- Definite loops:
`for (i = 0; i < 10; i++) {...}`

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;
- Many types available:
int, float, char, ...
- To print: cout << "Hello!!";
- To get input: cin >> num;
- To use those I/O functions:

```
#include <iostream>
using namespace std;
```
- Definite loops:

```
for (i = 0; i < 10; i++) {...}
```
- Blocks of code uses '{' and '}'.

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Recap: Basic Form & I/O in C++

- Efficient for systems programming.
- Programs are organized in functions.
- Must declare variables: int num;
- Many types available:
int, float, char, ...
- To print: cout << "Hello!!";
- To get input: cin >> num;
- To use those I/O functions:

```
#include <iostream>
using namespace std;
```
- Definite loops:

```
for (i = 0; i < 10; i++) {...}
```
- Blocks of code uses '{' and '}'.
- Commands generally end in ';'.

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

Today's Topics

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

- Recap: I/O & Definite Loops in C++
- **Conditionals in C++**
- Indefinite Loops in C++
- Recap: C++ & Python

Challenge:

Predict what the following pieces of code will do:

```
//Demonstrates conditionals
#include <iostream>
using namespace std;

int main ()
{
    int yearBorn;
    cout << "Enter year born: ";
    cin >> yearBorn;
    if (yearBorn < 1946)
    {
        cout << "Greatest Generation";
    }
    else if (yearBorn <= 1964)
    {
        cout << "Baby Boomer";
    }
    else if (yearBorn <= 1984)
    {
        cout << "Generation X";
    }
    else if (yearBorn <= 2004)
    {
        cout << "Millennial";
    }
    else
    {
        cout << "TBD";
    }

    return 0;
}
```

```
using namespace std;

int main ()
{
    string conditions = "blowing snow";
    int winds = 100;
    float visibility = 0.2;

    if ( (winds > 35) && (visibility < 0.25) )
        (conditions == "blowing snow") ||
        (conditions == "heavy snow") )
    cout << "Blizzard!\n";

    string origin = "South Pacific";

    if (winds > 74)
        cout << "Major storm, called a ";
    if ((origin == "Indian Ocean")
        ||(origin == "South Pacific"))
        cout << "cyclone.\n";
    else if (origin == "North Pacific")
        cout << "typhoon.\n";
    else
        cout << "hurricane.\n";
```

C++ Demo

```
//Demonstrates conditionals
#include <iostream>
using namespace std;

int main ()
{
    int yearBorn;
    cout << "Enter year born: ";
    cin >> yearBorn;
    if (yearBorn < 1946)
    {
        cout << "Greatest Generation";
    }
    else if (yearBorn <= 1964)
    {
        cout << "Baby Boomer";
    }
    else if (yearBorn <= 1984)
    {
        cout << "Generation X";
    }
    else if (yearBorn <= 2004)
    {
        cout << "Millennial";
    }
    else
    {
        cout << "TBD";
    }

    return 0;
}
```

(Demo with [onlinedgdb](#))

Conditionals

General format:

```
//Demonstrates conditionals
#include <iostream>
using namespace std;

int main ()
{
    int yearBorn;
    cout << "Enter year born: ";
    cin >> yearBorn;
    if (yearBorn < 1946)
    {
        cout << "Greatest Generation";
    }
    else if (yearBorn <= 1964)
    {
        cout << "Baby Boomer";
    }
    else if (yearBorn <= 1984)
    {
        cout << "Generation X";
    }
    else if (yearBorn <= 2004)
    {
        cout << "Millennial";
    }
    else
    {
        cout << "TBD";
    }
    return 0;
}
```

```
if ( logical expression )
{
    command1;
    ...
}

else if ( logical expression )
{
    command1;
    ...
}

else
{
    command1;
    ...
}
```

Logical Operators in C++

Very similar, just different names: `&&`, `||`, and `!`:

Logical Operators in C++

Very similar, just different names: `&&`, `||`, and `!`:

and (`&&`)

in1	in2	<i>returns:</i>
False	<code>&&</code>	False
False	<code>&&</code>	True
True	<code>&&</code>	False
True	<code>&&</code>	True

Logical Operators in C++

Very similar, just different names: `&&`, `||`, and `!`:

and (`&&`)

in1		in2	<i>returns:</i>
False	<code>&&</code>	False	False
False	<code>&&</code>	True	False
True	<code>&&</code>	False	False
True	<code>&&</code>	True	True

or (`||`)

in1		in2	<i>returns:</i>
False	<code> </code>	False	False
False	<code> </code>	True	True
True	<code> </code>	False	True
True	<code> </code>	True	True

Logical Operators in C++

Very similar, just different names: `&&`, `||`, and `!`:

and (`&&`)

in1		in2	<i>returns:</i>
False	<code>&&</code>	False	False
False	<code>&&</code>	True	False
True	<code>&&</code>	False	False
True	<code>&&</code>	True	True

not (`!`)

	in1	<i>returns:</i>
!	False	True
!	True	False

in1		in2	<i>returns:</i>
False	<code> </code>	False	False
False	<code> </code>	True	True
True	<code> </code>	False	True
True	<code> </code>	True	True

Today's Topics

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

- Recap: I/O & Definite Loops in C++
- Conditionals in C++
- **Indefinite Loops in C++**
- Recap: C++ & Python

Challenge:

Predict what the following pieces of code will do:

```
//While Growth Example
#include <iostream>
using namespace std;

int main ()
{
    int population = 100;
    int year = 0;
    cout << "Year\tPopulation\n";
    while(population < 1000)
    {
        cout << year << "\t\t" << population << "\n";
        population = population * 2;
        year++;
    }
    return 0;
}
```

C++ Demo

```
//While Growth Example
#include <iostream>
using namespace std;

int main ()
{
    int population = 100;
    int year = 0;
    cout << "Year\tPopulation\n";
    while(population < 1000)
    {
        cout << year << "\t\t" << population << "\n";
        population = population * 2;
        year++;
    }
    return 0;
}
```

(Demo with onlinegdb)

Indefinite Loops: while

```
///While Growth Example
#include <iostream>
using namespace std;

int main ()
{
    int population = 100;
    int year = 0;
    cout << "Year\tPopulation\n";
    while(population < 1000)
    {
        cout << year << "\t\t" << population << "\n";
        population = population * 2;
        year++;
    }
    return 0;
}
```

General format:

```
while ( logical expression )
{
    command1;
    command2;
    command3;
    ...
}
```

Challenge:

Predict what the following piece of code will do:

```
//Demonstrates loops
#include <iostream>
using namespace std;

int main ()
{
    int num;
    cout << "Enter an even number: ";
    cin >> num;
    while (num % 2 != 0)
    {
        cout << "\nThat's odd!\n";
        cout << "Enter an even number: ";
        cin >> num;
    }
    cout << "You entered: "
        << num << ".\n";
    return 0;
}
```

C++ Demo

```
//Demonstrates loops
#include <iostream>
using namespace std;

int main ()
{
    int num;
    cout << "Enter an even number: ";
    cin >> num;
    while (num % 2 != 0)
    {
        cout << "\nThat's odd!\n";
        cout << "Enter an even number: ";
        cin >> num;
    }
    cout << "You entered: "
        << num << ".\n";
    return 0;
}
```

(Demo with onlinegdb)

Indefinite Loops: while

```
//Demonstrates loops
#include <iostream>
using namespace std;

int main ()
{
    int num;
    cout << "Enter an even number: ";
    cin >> num;
    while (num % 2 != 0)
    {
        cout << "\nThat's odd!\n";
        cout << "Enter an even number: ";
        cin >> num;
    }
    cout << "You entered: "
        << num << ".\n";
    return 0;
}
```

General format:

```
while ( logical expression )
{
    command1;
    command2;
    command3;
    ...
}
```

Challenge:

Predict what the following pieces of code will do:

```
//Demonstrates do-while loops
#include <iostream>
using namespace std;

int main ()
{
    int num;
    do
    {
        cout << "Enter an even number: ";
        cin >> num;
    } while (num % 2 != 0);

    cout << "You entered: "
        << num << ".\n";
    return 0;
}
```

C++ Demo

```
//Demonstrates do-while loops
#include <iostream>
using namespace std;

int main ()
{
    int num;
    do
    {
        cout << "Enter an even number: ";
        cin >> num;
    } while (num % 2 != 0);

    cout << "You entered: "
        << num << ".\n";
    return 0;
}
```

(Demo with onlinegdb)

Indefinite Loops: do-while

```
//Demonstrates do-while loops
#include <iostream>
using namespace std;

int main ()
{
    int num;
    do
    {
        cout << "Enter an even number: ";
        cin >> num;
    } while (num % 2 != 0);

    cout << "You entered: "
        << num << ".\n";
    return 0;
}
```

General format:

```
do
{
    command1;
    command2;
    command3;
    ...
} while ( logical expression );
```

Today's Topics

```
//Another C++ program, demonstrating I/O & arithmetic
#include <iostream>
using namespace std;

int main ()
{
    float kg, lbs;
    cout << "Enter kg: ";
    cin >> kg;
    lbs = kg * 2.2;
    cout << endl << "Lbs: " << lbs << "\n\n";
    return 0;
}
```

- Recap: I/O & Definite Loops in C++
- Conditionals in C++
- Indefinite Loops in C++
- **Recap: C++ & Python**

Recap: C++ Control Structures

- I/O:

```
//Another C++ program; Demonstrates loops
#include <iostream>
using namespace std;

int main ()
{
    int i,j;
    for (i = 0; i < 4; i++)
    {
        cout << "The world turned upside down...\n";
    }

    for (j = 10; j > 0; j--)
    {
        cout << j << " ";
    }
    cout << "Blast off!!" << endl;
    return 0;
}
```

Recap: C++ Control Structures

- I/O: `cin >> ...;`

```
//Another C++ program; Demonstrates loops
#include <iostream>
using namespace std;

int main ()
{
    int i,j;
    for (i = 0; i < 4; i++)
    {
        cout << "The world turned upside down...\n";
    }

    for (j = 10; j > 0; j--)
    {
        cout << j << " ";
    }
    cout << "Blast off!!" << endl;
}

return 0;
}
```

Recap: C++ Control Structures

- I/O: `cin >> ...;` & `cout << ...;`

```
//Another C++ program; Demonstrates loops
#include <iostream>
using namespace std;

int main ()
{
    int i,j;
    for (i = 0; i < 4; i++)
    {
        cout << "The world turned upside down...\n";
    }

    for (j = 10; j > 0; j--)
    {
        cout << j << " ";
    }
    cout << "Blast off!!" << endl;
    return 0;
}
```

Recap: C++ Control Structures

- I/O: `cin >> ...;` & `cout << ...;`
- Definite loops:

```
//Another C++ program; Demonstrates loops
#include <iostream>
using namespace std;

int main ()
{
    int i,j;
    for (i = 0; i < 4; i++)
    {
        cout << "The world turned upside down...\n";
    }

    for (j = 10; j > 0; j--)
    {
        cout << j << " ";
    }
    cout << "Blast off!!" << endl;
    return 0;
}
```

Recap: C++ Control Structures

- I/O: `cin >> ...; & cout << ...;`

- Definite loops:

```
for (i = 0; i < 10; i++)  
{  
    ...  
}
```

```
//Another C++ program; Demonstrates loops  
#include <iostream>  
using namespace std;  
  
int main ()  
{  
    int i,j;  
    for (i = 0; i < 4; i++)  
    {  
        cout << "The world turned upside down...\n";  
    }  
  
    for (j = 10; j > 0; j--)  
    {  
        cout << j << " ";  
    }  
    cout << "Blast off!!" << endl;  
    return 0;  
}
```

Recap: C++ Control Structures

- I/O: `cin >> ...;` & `cout << ...;`

- Definite loops:

```
for (i = 0; i < 10; i++)  
{  
    ...  
}
```

- Conditionals:

```
/*Another C++ program; Demonstrates loops  
#include <iostream>  
using namespace std;  
  
int main ()  
{  
    int i,j;  
    for (i = 0; i < 4; i++)  
    {  
        cout << "The world turned upside down...\n";  
    }  
  
    for (j = 10; j > 0; j--)  
    {  
        cout << j << " ";  
    }  
    cout << "Blast off!!" << endl;  
    return 0;  
}
```

Recap: C++ Control Structures

- I/O: `cin >> ...;` & `cout << ...;`

- Definite loops:

```
for (i = 0; i < 10; i++)  
{  
    ...  
}  
...
```

- Conditionals:

```
if (logical expression)  
{  
    ...  
}  
else  
{  
    ...  
}
```

```
/*Another C++ program; Demonstrates loops  
#include <iostream>  
using namespace std;  
  
int main ()  
{  
    int i,j;  
    for (i = 0; i < 4; i++)  
    {  
        cout << "The world turned upside down...\n";  
    }  
  
    for (j = 10; j > 0; j--)  
    {  
        cout << j << " ";  
    }  
    cout << "Blast off!!" << endl;  
    return 0;  
}
```

Recap: C++ Control Structures

- I/O: `cin >> ...;` & `cout << ...;`

- Definite loops:

```
for (i = 0; i < 10; i++)  
{  
    ...  
}  
...
```

- Conditionals:

```
if (logical expression)  
{  
    ...  
}  
else  
{  
    ...  
}
```

```
/*Another C++ program; Demonstrates loops  
#include <iostream>  
using namespace std;  
  
int main ()  
{  
    int i,j;  
    for (i = 0; i < 4; i++)  
    {  
        cout << "The world turned upside down...\n";  
    }  
  
    for (j = 10; j > 0; j--)  
    {  
        cout << j << " ";  
    }  
    cout << "Blast off!!" << endl;  
    return 0;  
}
```

- Indefinite loops:

Recap: C++ Control Structures

- I/O: `cin >> ...;` & `cout << ...;`

- Definite loops:

```
for (i = 0; i < 10; i++)  
{  
    ...  
}  
...
```

- Conditionals:

```
if (logical expression)  
{  
    ...  
}  
else  
{  
    ...  
}
```

```
/*Another C++ program; Demonstrates loops  
#include <iostream>  
using namespace std;  
  
int main ()  
{  
    int i,j;  
    for (i = 0; i < 4; i++)  
    {  
        cout << "The world turned upside down...\n";  
    }  
  
    for (j = 10; j > 0; j--)  
    {  
        cout << j << " ";  
    }  
    cout << "Blast off!!" << endl;  
}  
return 0;  
}
```

- Indefinite loops:

```
while (logical expression)  
{  
    ...  
}
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in C++:

```
for i in range(2017, 2000, -2):
    print("Year is", i)
```

- Rewrite this program in Python:

```
#include <iostream>
using namespace std;
int main()
{
    for (int i = 1; i < 50; i++)
    {
        cout << i << endl;
    }
    return 0;
}
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in C++:

```
for i in range(2017, 2000, -2):  
    print("Year is", i)
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in C++:

```
for i in range(2017, 2000, -2):
    print("Year is", i)

#include <iostream>
using namespace std;
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in C++:

```
for i in range(2017, 2000, -2):
    print("Year is", i)
```

```
#include <iostream>
using namespace std;
int main()
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in C++:

```
for i in range(2017, 2000, -2):  
    print("Year is", i)
```

```
#include <iostream>  
using namespace std;  
int main()  
{
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in C++:

```
for i in range(2017, 2000, -2):
    print("Year is", i)
```

```
#include <iostream>
using namespace std;
int main()
{
    for (int i = 2017; i > 2000; i=i-2)
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in C++:

```
for i in range(2017, 2000, -2):
    print("Year is", i)
```

```
#include <iostream>
using namespace std;
int main()
{
    for (int i = 2017; i > 2000; i=i-2)
    {
        cout << "Year is " << i << endl;
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in C++:

```
for i in range(2017, 2000, -2):
    print("Year is", i)

#include <iostream>
using namespace std;
int main()
{
    for (int i = 2017; i > 2000; i=i-2)
    {
        cout << "Year is " << i << endl;
    }
    return 0;
}
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in Python:

```
#include <iostream>
using namespace std;
int main()
{
    for (int i = 1; i < 50; i++)
    {
        cout << i << endl;
    }
    return 0;
}
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in Python:

```
#include <iostream>
using namespace std;
int main()
{
    for (int i = 1; i < 50; i++)
    {
        cout << i << endl;
    }
    return 0;
}
```

```
for i in range(1, 50):
```

Challenge: Definite Loops in Python & C++

- Rewrite this program in Python:

```
#include <iostream>
using namespace std;
int main()
{
    for (int i = 1; i < 50; i++)
    {
        cout << i << endl;
    }
    return 0;
}

for i in range(1, 50):
    print(i)
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

- *Write a C++ program that asks the user the number of times they plan to ride transit this week. Your program should then print if it is cheaper to buy single ride metro cards or 7-day unlimited card.
(The 7-day card is \$33.00, and the cost of single ride, with bonus, is \$2.75).*

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")  year = 2016
```

```
if TRUE and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

```
year = 2016
if TRUE and \
    (not FALSE or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

```
year = 2016
if TRUE and \
    (TRUE or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

```
year = 2016
if TRUE and \
    (TRUE or FALSE):
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

```
year = 2016
if TRUE and \
    (TRUE or FALSE):
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

```
year = 2016
if TRUE and \
    (TRUE):
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

```
year = 2016
if TRUE:
    print("Leap!!")
print("Year")
```

Challenge: Conditionals in Python & C++

- *Python: what is the output?*

```
year = 2016
if year % 4 == 0 and \
    (not (year % 100 == 0) or (year % 400 == 0)):
    print("Leap!!")
print("Year")
```

```
year = 2016
if TRUE:
    print("Leap!!")
print("Year")
```

Prints: Leap!
Year

Challenge: Conditionals in Python & C++

- Your program should then print if it is cheaper to buy single ride metro cards (\$2.75 per ride) or 7-day unlimited card (\$33.00).

```
#include <iostream>
using namespace std;
```

Challenge: Conditionals in Python & C++

- Your program should then print if it is cheaper to buy single ride metro cards (\$2.75 per ride) or 7-day unlimited card (\$33.00).

```
#include <iostream>
using namespace std;
int main()
```

Challenge: Conditionals in Python & C++

- Your program should then print if it is cheaper to buy single ride metro cards (\$2.75 per ride) or 7-day unlimited card (\$33.00).

```
#include <iostream>
using namespace std;
int main()
{
    int rides;
```

Challenge: Conditionals in Python & C++

- Your program should then print if it is cheaper to buy single ride metro cards (\$2.75 per ride) or 7-day unlimited card (\$33.00).

```
#include <iostream>
using namespace std;
int main()
{
    int rides;
    cout << "Enter number of rides:";
```

Challenge: Conditionals in Python & C++

- Your program should then print if it is cheaper to buy single ride metro cards (\$2.75 per ride) or 7-day unlimited card (\$33.00).

```
#include <iostream>
using namespace std;
int main()
{
    int rides;
    cout << "Enter number of rides:";
    cin >> rides;
```

Challenge: Conditionals in Python & C++

- Your program should then print if it is cheaper to buy single ride metro cards (\$2.75 per ride) or 7-day unlimited card (\$33.00).

```
#include <iostream>
using namespace std;
int main()
{
    int rides;
    cout << "Enter number of rides:";
    cin >> rides;
    if (2.75 * rides < 33.00)
```

Challenge: Conditionals in Python & C++

- Your program should then print if it is cheaper to buy single ride metro cards (\$2.75 per ride) or 7-day unlimited card (\$33.00).

```
#include <iostream>
using namespace std;
int main()
{
    int rides;
    cout << "Enter number of rides:";
    cin >> rides;
    if (2.75 * rides < 33.00)
    {
        cout << "Cheaper to buy single ride metro cards.\n";
    }
}
```

Challenge: Conditionals in Python & C++

- Your program should then print if it is cheaper to buy single ride metro cards (\$2.75 per ride) or 7-day unlimited card (\$33.00).

```
#include <iostream>
using namespace std;
int main()
{
    int rides;
    cout << "Enter number of rides:";
    cin >> rides;
    if (2.75 * rides < 33.00)
    {
        cout << "Cheaper to buy single ride metro cards.\n";
    }
    else
```

Challenge: Conditionals in Python & C++

- Your program should then print if it is cheaper to buy single ride metro cards (\$2.75 per ride) or 7-day unlimited card (\$33.00).

```
#include <iostream>
using namespace std;
int main()
{
    int rides;
    cout << "Enter number of rides:";
    cin >> rides;
    if (2.75 * rides < 33.00)
    {
        cout << "Cheaper to buy single ride metro cards.\n";
    }
    else
    {
        cout << "Cheaper to buy 7-day unlimited card.\n";
    }
}
```

Challenge: Conditionals in Python & C++

- Your program should then print if it is cheaper to buy single ride metro cards (\$2.75 per ride) or 7-day unlimited card (\$33.00).

```
#include <iostream>
using namespace std;
int main()
{
    int rides;
    cout << "Enter number of rides:";
    cin >> rides;
    if (2.75 * rides < 33.00)
    {
        cout << "Cheaper to buy single ride metro cards.\n";
    }
    else
    {
        cout << "Cheaper to buy 7-day unlimited card.\n";
    }
    return 0;
}
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.
- Write C++ code that repeatedly prompts until an odd number is entered.

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")  
print("You entered: ", s)
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")  
print("You entered: ", s)
```

- Write C++ code that repeatedly prompts until an odd number is entered.

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")  
print("You entered: ", s)
```

- Write C++ code that repeatedly prompts until an odd number is entered.

```
#include <iostream>  
using namespace std;
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")  
print("You entered: ", s)
```

- Write C++ code that repeatedly prompts until an odd number is entered.

```
#include <iostream>  
using namespace std;  
int main()
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")  
print("You entered: ", s)
```

- Write C++ code that repeatedly prompts until an odd number is entered.

```
#include <iostream>  
using namespace std;  
int main()  
{  
    int num = 0;
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")  
print("You entered: ", s)
```

- Write C++ code that repeatedly prompts until an odd number is entered.

```
#include <iostream>  
using namespace std;  
int main()  
{  
    int num = 0;  
    while (num % 2 == 0)
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")  
print("You entered: ", s)
```

- Write C++ code that repeatedly prompts until an odd number is entered.

```
#include <iostream>  
using namespace std;  
int main()  
{  
    int num = 0;  
    while (num % 2 == 0)  
    {  
        cout << "Enter an odd number:";
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")  
print("You entered: ", s)
```

- Write C++ code that repeatedly prompts until an odd number is entered.

```
#include <iostream>  
using namespace std;  
int main()  
{  
    int num = 0;  
    while (num % 2 == 0)  
    {  
        cout << "Enter an odd number:";  
        cin >> num;
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")  
print("You entered: ", s)
```

- Write C++ code that repeatedly prompts until an odd number is entered.

```
#include <iostream>  
using namespace std;  
int main()  
{  
    int num = 0;  
    while (num % 2 == 0)  
    {  
        cout << "Enter an odd number:";  
        cin >> num;  
    }
```

Challenge: Indefinite Loops in Python & C++

- Write Python code that repeatedly prompts for a non-empty string.

```
s = ""  
while s == "":  
    s = input("Enter a non-empty string: ")  
print("You entered: ", s)
```

- Write C++ code that repeatedly prompts until an odd number is entered.

```
#include <iostream>  
using namespace std;  
int main()  
{  
    int num = 0;  
    while (num % 2 == 0)  
    {  
        cout << "Enter an odd number:";  
        cin >> num;  
    }  
    return 0;  
}
```

Weekly Reminders!



Before next lecture, don't forget to:

- Read and work through Lab 13!

Weekly Reminders!



Before next lecture, don't forget to:

- Read and work through Lab 13!
- Batch 11 is due Monday, July 10th

Weekly Reminders!



Before next lecture, don't forget to:

- Read and work through Lab 13!
- Batch 11 is due Monday, July 10th
- If you need help, please email cscisummer23@gmail.com with questions or Friday tutoring :)

Weekly Reminders!



Before next lecture, don't forget to:

- Read and work through Lab 13!
- Batch 11 is due Monday, July 10th
- If you need help, please email cscisummer23@gmail.com with questions or Friday tutoring :)