

Row:	Seat:

MOCK FINAL EXAM  
 CSci 127: Introduction to Computer Science  
 Hunter College, City University of New York  
 May 16, 2023

## Exam Rules

- Show all your work. Your grade will be based on the work shown.
- The exam is closed book and closed notes with the exception of an 8 1/2" x 11" piece of paper filled with notes, programs, etc.
- When taking the exam, you may have with you pens and pencils, and your note sheet.
- You may not use a computer, calculator, tablet, phone, earbuds, or other electronic device.
- **Do not open this exam until instructed to do so.**

*Hunter College regards acts of academic dishonesty (e.g., plagiarism, cheating on examinations, obtaining unfair advantage, and falsification of records and official documents) as serious offenses against the values of intellectual honesty. The College is committed to enforcing the CUNY Policy on Academic Integrity and will pursue cases of academic dishonesty according to the Hunter College Academic Integrity Procedures.*

I understand that all cases of academic dishonesty will be reported to the Dean of Students and will result in sanctions.									
Name:									
EMPLID:									
Email:									
Signature:									

# ASCII TABLE

Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char
0	0	[NULL]	32	20	[SPACE]	64	40	@	96	60	,
1	1	[START OF HEADING]	33	21	!	65	41	A	97	61	a
2	2	[START OF TEXT]	34	22	"	66	42	B	98	62	b
3	3	[END OF TEXT]	35	23	#	67	43	C	99	63	c
4	4	[END OF TRANSMISSION]	36	24	\$	68	44	D	100	64	d
5	5	[ENQUIRY]	37	25	%	69	45	E	101	65	e
6	6	[ACKNOWLEDGE]	38	26	&	70	46	F	102	66	f
7	7	[BELL]	39	27	'	71	47	G	103	67	g
8	8	[BACKSPACE]	40	28	(	72	48	H	104	68	h
9	9	[HORIZONTAL TAB]	41	29	)	73	49	I	105	69	i
10	A	[LINE FEED]	42	2A	*	74	4A	J	106	6A	j
11	B	[VERTICAL TAB]	43	2B	+	75	4B	K	107	6B	k
12	C	[FORM FEED]	44	2C	,	76	4C	L	108	6C	l
13	D	[CARRIAGE RETURN]	45	2D	-	77	4D	M	109	6D	m
14	E	[SHIFT OUT]	46	2E	.	78	4E	N	110	6E	n
15	F	[SHIFT IN]	47	2F	/	79	4F	O	111	6F	o
16	10	[DATA LINK ESCAPE]	48	30	0	80	50	P	112	70	p
17	11	[DEVICE CONTROL 1]	49	31	1	81	51	Q	113	71	q
18	12	[DEVICE CONTROL 2]	50	32	2	82	52	R	114	72	r
19	13	[DEVICE CONTROL 3]	51	33	3	83	53	S	115	73	s
20	14	[DEVICE CONTROL 4]	52	34	4	84	54	T	116	74	t
21	15	[NEGATIVE ACKNOWLEDGE]	53	35	5	85	55	U	117	75	u
22	16	[SYNCHRONOUS IDLE]	54	36	6	86	56	V	118	76	v
23	17	[ENG OF TRANS. BLOCK]	55	37	7	87	57	W	119	77	w
24	18	[CANCEL]	56	38	8	88	58	X	120	78	x
25	19	[END OF MEDIUM]	57	39	9	89	59	Y	121	79	y
26	1A	[SUBSTITUTE]	58	3A	:	90	5A	Z	122	7A	z
27	1B	[ESCAPE]	59	3B	;	91	5B	[	123	7B	{
28	1C	[FILE SEPARATOR]	60	3C	<	92	5C	\	124	7C	
29	1D	[GROUP SEPARATOR]	61	3D	=	93	5D	]	125	7D	}
30	1E	[RECORD SEPARATOR]	62	3E	>	94	5E	^	126	7E	~
31	1F	[UNIT SEPARATOR]	63	3F	?	95	5F	_	127	7F	[DEL]

(Image from wikipedia commons)

1. (a) Fill in the code below to produce the Output on the right:

```
seasons = "Spring,Summer,Autumn,Winter"
```

```
i. autumn_winter = seasons.split(",")[2:]  
for s in autumn_winter:  
    print(s.lower())
```

**Output:**

autumn  
winter

```
ii. spring_autumn = seasons.split(",")[:2]  
for s in spring_autumn:  
    print(s.upper())
```

**Output:**

SPRING  
AUTUMN

- (b) Consider the following shell commands:

```
$ pwd  
/usr/student  
$ ls  
hello.csv grades.csv test.py hello.py
```

- i. What is the output for:

```
$ mkdir data  
$ mv *.csv data  
$ cd data  
$ ls
```

**Output:**

hello.csv grades.csv

- ii. What is the output for:

```
$ cd ../  
$ ls -l | grep hello | wc -l
```

**Output:**

2

- iii. What is the output for:

```
$ ls | grep test
```

**Output:**

test.py

2. (a) Select the color corresponding to the rgb values below:

i. `rgb = (65, 65, 65)`

☐ black      ☐ red      ☐ white      ☒ gray      ☐ blue

ii. `rgb = "#0000AB"`

☐ black      ☐ red      ☐ white      ☐ gray      ☒ blue

iii. `rgb = (255, 255, 255)`

☐ black      ☐ red      ☒ white      ☐ gray      ☐ blue

iv. What is the binary number equivalent of decimal number 54?

Decimal 54 = Binary

**Answer: 110110**

v. What is the Decimal number equivalent to Hexadecimal 2F?

Hexadecimal 2F = Decimal

**Answer: 47**

(b) Given the list `fruits` below, fill in the code to produce the Output on the right:

`fruits = ["orange", "banana", "apple", "cherry", "strawberry"]`

```

for i in range(  ):
    i. for j in range(  ):
        print(fruits[j], end=" ")

```

**Output:**

```

o b a c s
o b a c s

```

```

ii. for j in range( , ,  ):
    print(fruits[j], end=" ")

```

**Output:**

```

e e y


```

```

import numpy as np
import matplotlib.pyplot as plt
iii. img = np.ones( (10,10,3) )
    img[ , ,  ] = 0
    plt.imshow(img)
    plt.show()

```

**Output:**



3. (a) What is the value (True/False):

in1 = False

i. in2 = True

out = not in1 and in2

☒ True

☐ False

in1 = True

ii. in2 = True

in3 = False

out = not (in1 and not in2) or in3

☒ True

☐ False

in1 = True


iii. in2 = False

in3 = not in1 or not in2

out = not in1 and in3

☐ True

☒ False



iv.

in1 = False

in2 = False


in3 = False

☐ True

☒ False

(b) Draw a circuit that implements the logical expression:

$(\text{in1 or not in2}) \text{ and } ((\text{in1 and in2}) \text{ or not in3})$



4. Consider the following functions:

```
def hello(chris, amy):  
    amanda = 0  
    for num in chris:  
        if frog(num, amy):  
            amanda += 2  
  
    return amanda
```

```
def frog(a, b):  
    return a > b  
  
def main():  
    mylist = [1, 6, 5, -3, 7]  
    print(hello(mylist, 2))
```

(a) What are the formal parameters for `frog()`?

a, b

(b) What are the actual parameters for `hello()`?

mylist, 2

(c) How many calls are made to `frog()` after calling `main()`?

5

(d) What is the output after calling `main()`?

i. **Output:**

6

5. Design an algorithm that asks the user for the name of a text file containing a grid of numbers and loads it into a 2D array of integers (think like an image without the color channel), then outputs the index (row, col) of the LARGEST number in the array.

**Libraries:**

**numpy**

**Input:**

**the input file**

**Output:**

**the index of the largest number**

**Design Pattern:**

☐ Search

☐ Find Min

☒ Find Max

☐ Find All

**Principal Mechanisms (select all that apply):**

☐ Single Loop

☒ Nested Loop

☒ Conditional (if/else) statement

☒ Indexing / Slicing

☐ `split()`

☐ `groupby()`

**Process (as a concise and precise LIST OF STEPS / pseudocode):**

(Assume libraries have already been imported.)

**Answer:**

- (a) Ask the user for input file name
- (b) Load the data into a numpy array, call it `grid`
- (c) Set variables `maxRow` and `maxCol` to 0
- (d) Use a nested loop to consider every number in the grid, looping through rows in the outer loop and columns in the inner loop
- (e) If the current number (`grid[currentRow, currentColumn]`) is greater than the number at `grid[maxRow, maxCol]`, set `maxRow` to the current row and set `maxCol` to the current column
- (f) Return `maxRow` and `maxCol`

6. Consider the `medalcount.csv` dataset that reports the medal count for skating at the 2014 Winter Olympics. A snapshot is given in the image below:

Country	Gold	Silver	Bronze
Canada	0	3	0
Italy	0	0	1
Germany	0	0	1
Japan	1	0	0
Kazakhstan	0	0	1
Russia	3	1	1
South Korea	0	1	0
United States	1	0	1

Fill in the Python program below:

#Import the libraries for data frames.

```
import pandas as pd
```

#Read input data into data frame:

```
df = pd.read_csv("medalcount.csv")
```

#Create a new column that has a total medal count for each country

```
df["Total"] = df["Gold"] + df["Silver"] + df["Bronze"]
```



7. Write a **complete Python program** that prompts the user for the name of an .png (image) file and prints the fraction of pixels that are grayscale, or a shade of gray. Recall that a pixel is a shade of gray if the red, green, and blue values are all equal.

**Answer:**

---

```
#Import the packages for images and arrays:
import matplotlib.pyplot as plt
import numpy as np

#Ask user for image name and read into img:
inImg = input("Enter input image: ")
img = plt.imread(inImg)

#Get height and width:
height = img.shape[0]
width = img.shape[1]

#Initialize counter:
count = 0

#Loop through all the pixels:
for row in range(height):
    for col in range(width):

#Increase the count if the current pixel's red, green, and blue values are equal:
        if img[row,col,0] == img[row,col,1] == img[row,col,2]:
            count = count + 1

#Compute and print fraction:
totalPixelCount = height*width
fractionGray = count/totalPixelCount
print("Fraction gray is", fractionGray)
```

---

8. (a) What does the MIPS program below print:

**Output:**

ABCDE

- (b) Modify the program to print out the string "abc". Shade in the box for each line that needs to be changed and rewrite the instruction next to it.

☒ ADDI \$sp, \$sp, -6      Answer: ADDI \$sp, \$sp, -4

☐ ADDI \$s3, \$zero, 1

☒ ADDI \$t0, \$zero, 65      Answer: ADDI \$t0, \$zero, 97 #(a)

☒ ADDI \$s2, \$zero, 5      Answer: ADDI \$s2, \$zero, 3

☐ SETUP: SB \$t0, 0(\$sp)

☐ ADDI \$sp, \$sp, 1

☐ SUB \$s2, \$s2, \$s3

☐ ADDI \$t0, \$t0, 1

☐ BEQ \$s2, \$zero, DONE

☐ J SETUP

☐ DONE: ADDI \$t0, \$zero, 0

☐ SB \$t0, 0(\$sp) # Add null to stack

☒ ADDI \$sp, \$sp, -5      Answer: ADDI \$sp, \$sp, -3

☐ ADDI \$v0, \$zero, 4 # 4 is for print string

☐ ADDI \$a0, \$sp, 0 # Set \$a0 to stack pointer

☐ syscall # Print to the log

9. Fill in the C++ programs below to produce the Output on the right.

---

(a)	<pre>#include &lt;iostream&gt; using namespace std; int main(){     for( int i = 100; i &lt; 500; i+=100 ){         cout &lt;&lt; i*2 &lt;&lt; endl;     }     return 0; }</pre>	<b>Output:</b> 200 400 600 800
-----	--	--

---

(b)	<pre>#include &lt;iostream&gt; using namespace std; int main(){     int count = 200;     int num = 100;     while( count &gt;= 50 &amp;&amp; num &gt;= 90 ){         cout &lt;&lt; count &lt;&lt; " " &lt;&lt; num &lt;&lt; endl;         count -= 50;         num -= 5;     }     return 0; }</pre>	<b>Output:</b> 200 100 150 95 100 90
-----	--	---

---

(c)	<pre>#include &lt;iostream&gt; using namespace std; int main(){     for( int i = 0; i &lt; 5; i++ ){         cout &lt;&lt; "Hello" &lt;&lt; endl;     }     return 0; }</pre>	<b>Output:</b> Hello Hello Hello Hello Hello
-----	---	---

---

10. (a) Translate the following python program into a **complete C++ program**:

```
for i in range(97,113,3):
    for j in range(i,60,-4):
        print(i," ",j)
```

**Answer:**

---

```
#include <iostream>
using namespace std;

int main() {
    for (int i = 97; i < 113; i += 3) {
        for (int j = i; j > 60; j -= 4) {
            cout << i << " " << j << endl;
        }
    }
    return 0;
}
```

---