CSci 127: Introduction to Computer Science



hunter.cuny.edu/csci

990

1/43

This lecture will be recorded

CSci 127 (Hunter) Lecture 7 20 October 2020

From email

From email

• Why does Gradescope say program 17 was not graded?

From email

• Why does Gradescope say program 17 was not graded? Don't worry, you did get the reported. It will show as graded soon, we are making some manual adjustments.

From email

- Why does Gradescope say program 17 was not graded?

 Don't worry, you did get the reported. It will show as graded soon, we are making some manual adjustments.
- How do I know the height and width of an image?

From email

- Why does Gradescope say program 17 was not graded? Don't worry, you did get the reported. It will show as graded soon, we are making some manual adjustments.
- How do I know the height and width of an image? When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.

From email

- Why does Gradescope say program 17 was not graded? Don't worry, you did get the reported. It will show as graded soon, we are making some manual adjustments.
- How do I know the height and width of an image? When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.

We will start with that today.

From email

- Why does Gradescope say program 17 was not graded? Don't worry, you did get the reported. It will show as graded soon, we are making some manual adjustments.
- How do I know the height and width of an image?

 When you read an image file using pyplot, you can access the number of rows

 (height) and the number of columns (width) using the shape attribute of a numpy array.
 - We will start with that today.
- Why are we looking at NYC historical population and CUNY enrollment data?

From email

- Why does Gradescope say program 17 was not graded? Don't worry, you did get the reported. It will show as graded soon, we are making some manual adjustments.
- How do I know the height and width of an image? When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.
 - We will start with that today.
- Why are we looking at NYC historical population and CUNY enrollment data? We are showing you how to analyze data. The tools we are exploring can be applied to many different datasets.

2 / 43

CSci 127 (Hunter) Lecture 7 20 October 2020

From email

- Why does Gradescope say program 17 was not graded? Don't worry, you did get the reported. It will show as graded soon, we are making some manual adjustments.
- How do I know the height and width of an image? When you read an image file using pyplot, you can access the number of rows (height) and the number of columns (width) using the shape attribute of a numpy array.
 - We will start with that today.
- Why are we looking at NYC historical population and CUNY enrollment data? We are showing you how to analyze data. The tools we are exploring can be applied to many different datasets.
 - We will explore many more in the programming assignments!

2 / 43

CSci 127 (Hunter) Lecture 7 20 October 2020

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

Crop an image to select the top quarter (upper left corner)



```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = imq.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(imq2)
plt.show()
```

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



7 / 43

CSci 127 (Hunter) Lecture 7 20 October 2020


```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



8 / 43

CSci 127 (Hunter) Lecture 7 20 October 2020

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



• How would you select the lower left corner?

9 / 43


CSci 127 (Hunter) Lecture 7 20 October 2020

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(ima)
plt.show()
heiaht = ima.shape [0]
width = imq.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(ima2)
plt.show()
```



• How would you select the lower left corner? img2 = img[height//2:, :width//2]


```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner?

20 October 2020


```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[:height//2, width//2:]


20 October 2020

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[:height//2, width//2:]
- How would you select the lower right corner?

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge')
plt.imshow(img)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[:height//2, :width//2]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[:height//2, width//2:]
- How would you select the lower right corner? img2 = img[height//2:, width//2:]

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

10 / 43

CSci 127 (Hunter) Lecture 7

 Functions are a way to break code into pieces, that can be easily reused.

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
      says hello to the world!
def main():
     print("Hello, World!")
if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:

```
#Name: your name here
#Date: October 2017
This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions,

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.

"Hello, World!" with Functions

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
#
      says hello to the world!
def main():
     print("Hello, World!")
if __name__ == "__main__":
     main()
```

Python Tutor

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
     says hello to the world!
def main():
    print("Hello, World!")
if __name__ == "__main__":
    main()
```

(Demo with pythonTutor)

Challenge:

Predict what the code will do:

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
ITotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

Python Tutor

```
def totalWithTax(food,tip):
total = 0
tax = 0.8875
total = food + food * tax
total = total * tip
return(clotal)* [Inter lunch total: ')
Ilip= floot(input('Enter lunch total: '))
Ilotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal
dimene= floot(input('Enter dinner total: '))
dimene= floot(input('Enter dinner tipi'))
dfotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

(Demo with pythonTutor)

15 / 43

CSci 127 (Hunter) Lecture 7 20 October 2020

Input Parameters & Return Values

 Functions can have input parameters.

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner total: '))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner total: '))
dTip = float(input('Enter dinner total: '))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).

16 / 43

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)

lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:'))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)

dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:'))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.

16 / 43

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)

lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(Junch, lTip)
print('Lunch total is', lTotal)

dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters

```
def totalWithTax(food,tip):
    total = 0
                        Formal Parameters
    tax = 0.0875
    total = food + food * tax
    total = total + tip
   return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', [[otal)
                           Actual Parameters
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal = totalWithTax dinner, dTip
print('Dinner total is', grocal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters.

```
def totalWithTax(food,tip):
    total = 0
                        Formal Parameters
    tax = 0.0875
    total = food + food * tax
    total = total + tip
   return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', [[otal)
                           Actual Parameters
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal = totalWithTax dinner, dTip
print('Dinner total is', grocal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters.
- Functions can also return
 values to where it was called.

Circle the actual parameters and underline the formal parameters:

```
def prob4():
    verse = "jam tomorrow and jam yesterday,"
    print("The rule is.")
    c = mystery(verse)
    w = enigma(verse.c)
    print(c,w)
def mystery(v):
    print(v)
    c = v.count("jam")
    return(c)
def enigma(v,c):
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
prob4()
```

Circle the actual parameters and underline the formal parameters:

```
def prob4():
    verse "jam tomorrow and jam yesterday,"
    print("The rule is,")
    c = hystery (verse)
    w = enigma (verse,c)
                                   *Actual
    print(c,w)
                                   Parameters
def mystery(v):
    print(v)
    c = v.count(fiam
    return(c)
                                     Formal
def enigma(v,c):
                                      Parameters
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
prob4()
```

Predict what the code will do:

```
def prob4():
    verse = "jam tomorrow and jam yesterday,"
    print("The rule is,")
    c = mystery(verse)
    w = enigma(verse,c)
    print(c,w)
def mystery(v):
    print(v)
    c = v.count("jam")
    return(c)
def enigma(v,c):
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
prob4()
```

Python Tutor

```
def probé():
    verse = "jam tomorrow and jam yesterday,"
    print("The rule is,")
    c = mystery(verse)
    w = enigma(verse,c)
    print(")
    print(")
    c = v.count("jam")
    return(c)
    def enigma(v,c)
    print(")
    print(")
    print(")
    print(")
    print(")
    print(")
    print(")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
    print("jam")
```

prob4()

(Demo with pythonTutor)

21 / 43

Predict what the code will do:

```
#Greet loop example

def greetLoop(person):
    print("Greetings")
    for i in range(5):
        print("Hello", person)

greetLoop("Thomas")
```

```
# From "Teaching with Python" by John Zelle

def happy():
    print("Happy Birthday to you!")

def sing(P):
    happy()
    happy()
    print("Happy Birthday dear " + P + "!")
    happy()

sing("Fred")
sing("Thomas")
sing("Hunter")
```

Python Tutor

```
#Greet loop example
 def greetLoop(person):
      print("Greetings")
     for i in range(5):
          print("Hello", person)
 greetLoop("Thomas")
# From "Teaching with Python" by John Zelle
def happy():
   print("Happy Birthday to you!")
def sing(P):
   happy()
   happy()
   print("Happy Birthday dear " + P + "!")
   happy()
sing("Fred")
sing("Thomas")
sing("Hunter")
```

(Demo with pythonTutor)

Fill in the missing code:

```
def monthString(monthNum):
    Takes as input a number, monthNum, and
    returns the corresponding month name as a string.
    Example: monthString(1) returns "January".
    Assumes that input is an integer ranging from 1 to 12
    monthString = ""
     ********************************
    ### FTLL TN YOUR CODE HERE
                                    ###
    ### Other than your name above, ###
    ### this is the only section
                                    ###
    ### you change in this program. ###
    *************
    return(monthString)
def main():
    n = int(input('Enter the number of the month: '))
    mString = monthString(n)
    print('The month is', mString)
```

IDLE

def main():

n = int(input('Enter the number of the month: '))
mString = monthString(n)
print('The month is', mString)

CSci 127 (Hunter) Lecture 7 20 October 2020 25 / 43

• Used to collaborate on and share code, documents, etc.



26 / 43



Octocat

- Used to collaborate on and share code, documents, etc.
- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.



 Used to collaborate on and share code, documents, etc.

- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.



 Used to collaborate on and share code, documents, etc.

- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.
- Github provides hosting for repositories ('repos') of code.



Octocat

 Used to collaborate on and share code, documents, etc.

- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.
- Github provides hosting for repositories ('repos') of code.
- Also convenient place to host websites (i.e. huntercsci127.github.io).



Octocat

- Used to collaborate on and share code, documents, etc.
- Supporting Open-Source Software: original source code is made freely available and may be redistributed and modified.
- More formally: git is a version control protocol for tracking changes and versions of documents.
- Github provides hosting for repositories ('repos') of code.
- Also convenient place to host websites (i.e. huntercsci127.github.io).
- In Lab6 you set up github accounts to copy ('clone') documents from the class repo. (More in future courses.)

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

 Functions are a way to break code into pieces, that can be easily reused.

27 / 43

```
#Name: your name here
#Date: October 2017
This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
```

main()

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
```

main()

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")

27 / 43

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions,

```
#Name: your name here
#Date: October 2017
This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.

Lecture Quiz

- Log-in to Gradescope
- Find LECTURE 7 Quiz
- Take the quiz
- You have 3 minutes

◆ロト ◆個ト ◆重ト ◆重ト ■ から()

CSci 127 (Hunter) Lecture 7 20 October 2020 28 / 43

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

29 / 43



Freely available source of data.

30 / 43



- Freely available source of data.
- Maintained by the NYC data analytics team.

30 / 43



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.

30 / 43



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.
- Will use pandas, pyplot & folium libraries to analyze, visualize and map the data.



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.
- Will use pandas, pyplot & folium libraries to analyze, visualize and map the data.
- Lab 7 covers accessing and downloading NYC OpenData datasets.



Home Data About V Learn

Film Permits

Permits are generally required when asserting the exclusive use of city property, like a sidewalk, a street, or a park. See http://www1.nyc.gov/site/mome/permits/when-permit-required.page

EventID :	EventType :	StartDateTi	EndDateTime :	EnteredOn ↓ :	EventAg :	ParkingHeld :	Borou
455063	Shooting Permit	12/06/2018 07:00	12/06/2018 09:00	12/05/2018 12:36	Mayor's Offic	STARR AVENUE b	Queens
454967	Shooting Permit	12/06/2018 07:00	12/06/2018 05:00	12/04/2018 09:11	Mayor's Offic	EAGLE STREET be	Brooklyn
454941	Shooting Permit	12/06/2018 07:00	12/06/2018 07:00	12/04/2018 05:44	Mayor's Offic	SOUTH OXFORD	Brooklyn
454920	Shooting Permit	12/06/2018 10:00	12/06/2018 11:59	12/04/2018 03:28	Mayor's Offic	13 AVENUE betw	Queens
454914	Shooting Permit	12/06/2018 08:00	12/06/2018 11:00	12/04/2018 03:05	Mayor's Offic	ELDERT STREET b	Brooklyn
454909	Shooting Permit	12/05/2018 08:00	12/05/2018 06:00	12/04/2018 02:45	Mayor's Offic	ELDERT STREET b	Brooklyn
454905	Shooting Permit	12/06/2018 07:00	12/06/2018 10:00	12/04/2018 02:17	Mayor's Offic	35 STREET betwe	Queens

31 / 43



• What's the most popular street for filming?



- What's the most popular street for filming?
- What's the most popular borough?

CSci 127 (Hunter) Lecture 7 20 October 2020 32 / 43



- What's the most popular street for filming?
- What's the most popular borough?
- How many TV episodes were filmed?

CSci 127 (Hunter) Lecture 7 20 October 2020 32 / 43



Download the data as a CSV file and store on your computer.



- Download the data as a CSV file and store on your computer.
- Python program:

```
#CSci 127 Teaching Staff
#March 2019
#OpenData Film Permits

#Import pandas for reading and analyzing CSV data:
import pandas as pd
csvFile = "filmPermits.csv"  #Name of the CSV file
tickets = pd.read_csv(csvFile)#Read in the file to a dataframe
```



- Download the data as a CSV file and store on your computer.
- Python program:

#CSci 127 Teachina Staff

```
#March 2019
#OpenData Film Permits

#Import pandas for reading and analyzing CSV data:
import pandas as pd
csvFile = "filmPermits.csv"  #Name of the CSV file
tickets = pd.read_csv(csvFile)#Read in the file to a dataframe
print(tickets)  #Print out the dataframe
```



- Download the data as a CSV file and store on your computer.
- Python program:

```
#CSci 127 Teaching Staff
#March 2019
#OpenData Film Permits

#Import pandas for reading and analyzing CSV data:
import pandas as pd
csvFile = "filmPermits.csv"  #Name of the CSV file
tickets = pd.read_csv(csvFile)#Read in the file to a dataframe
print(tickets)  #Print out the dataframe
print(tickets["ParkingHeld"])  #Print out streets (multiple times)
```

35 / 43



- Download the data as a CSV file and store on your computer.
- Python program:

#CSci 127 Teachina Staff




- Download the data as a CSV file and store on your computer.
- Python program:

```
#CSci 127 Teaching Staff
#March 2019
#OpenData Film Permits

#Import pandas for reading and analyzing CSV data:
import pandas as pd
csvFile = "filmPermits.csv"  #Name of the CSV file
tickets = pd.read_csv(csvFile)#Read in the file to a dataframe
print(tickets)  #Print out the dataframe
print(tickets["ParkingHeld"])  #Print out streets (multiple times)
print(tickets["ParkingHeld"].value_counts())  #Print out streets & number of times used
print(tickets["ParkingHeld"].value_counts()[:10])  #Print 10 most popular
```

4 D > 4 A > 4 B > 4 B > B

900



Can approach the other questions in the same way:

- What's the most popular street for filming?
- What's the most popular borough?
- How many TV episodes were filmed?

38 / 43



Design an algorithm that finds the collision that is closest to input location

location.										
DATE	TIME	BOROUGH	ZIP CODE	LATITUDE	LONGITUDE	LOCATION	ON STREET N	CROSS STRE	OFF STREET	NUMBER OF
12/31/16	9:56						2 AVENUE			0
12/31/16	9:55	BRONX	10462	40.83521	-73.85497	(40.8352098	UNIONPORT	OLMSTEAD /	AVENUE	0
12/31/16	9:50						JESUP AVEN	UE		0
12/31/16	9:40	BROOKLYN	11225	40.66911	-73.95335	(40.6691137	ROGERS AVE	UNION STRE	ET	0
12/31/16	20:23	BROOKLYN	11209	40.62578	-74.02415	(40.6257805	80 STREET	5 AVENUE		0
12/31/16	20:20	QUEENS	11375	40.71958	-73.83977	(40.719584,	ASCAN AVEN	QUEENS BO	ULEVARD	0
12/31/16	20:15	BROOKLYN	11204				60 STREET	BAY PARKW	AY	0
12/31/16	20:10			40.66479	-73.82047	(40.6647944	, -73.8204653	3)		0
12/31/16	20:10						69 STREET	37 AVENUE		0
12/31/16	20:05	BRONX	10457	40.85429	-73.90026	(40.8542925	RYER AVENU	EAST 181 ST	REET	0

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

• Create a "To Do" list of what your program has to accomplish.

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:
 - Find data set (great place to look: NYC OpenData).

40 / 43

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:
 - 1 Find data set (great place to look: NYC OpenData).
 - 2 Ask user for current location.

40 / 43

CSci 127 (Hunter) Lecture 7 20 October 2020

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:
 - Find data set (great place to look: NYC OpenData).
 - 2 Ask user for current location.
 - 3 Read the CSV file.

40 / 43

CSci 127 (Hunter) Lecture 7 20 October 2020

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:
 - Find data set (great place to look: NYC OpenData).
 - 2 Ask user for current location.
 - 3 Read the CSV file.
 - 4 Check distance from each collision to user's location.

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:
 - Find data set (great place to look: NYC OpenData).
 - Ask user for current location.
 - Read the CSV file.
 - Check distance from each collision to user's location.
 - Save the location with the smallest distance.

40 / 43

CSci 127 (Hunter) Lecture 7





• **Functions** are a way to break code into pieces, that can be easily reused.





- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:





- **Functions** are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 Example: print("Hello", "World")

41 / 43





- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 Example: print("Hello", "World")
- Can write, or define your own functions,





- **Functions** are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.






- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 - Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.
- Accessing Formatted Data: NYC OpenData

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

```
def totalkiting (Goi, Itp)
total ag S Formal Parameters
total ag S Formal Parameters
total a food a food 'tot
pressure (Inpress of total a food 'total a food 't
```



• Since you must pass the final exam to pass the course, we end every lecture with final exam review.

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
print("Hello, World!")

if __name__ = "__main__":
main()
```

```
eef production and jam yetterday, pring the rule is, )

- system of the is, )

- system of the rule is, 

- system of the rul
```

- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
print("Hello, World!")

if __name__ = "__main__":
main()
```

```
def totalithing (Tool, 197)
total of Por Formal Parameters
total of Por Formal Parameters
total of Tool of Tool of Tool
total of Tool
total
```

```
ref profit) is tomerou and jae yetterday.

Profit in the right in the
```

- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
print("Hello, World!")

if __name__ = "__main__":
main()
```

```
det totalkithe (Tod. IID)

total = 07

parameters

total = 07

tot
```

```
of prodicty
write 1 ja tomorrow and jas yesterday,
yering the rule 1s, 2
c - $strey (Time)
w - $strey (Time)
Parameters
Formal
Forma
```

- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

```
der totalkithe (Tod. IID)

total = 00 Fermal Parameters

total = 00 Fermal Parameters

total = food = food * tos

total = total =
```

```
od production and jan yesterday, principles rate in, in principles rate in, in a special rate in a special r
```

- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - ► followed by answer; and

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

```
def total tit brace (Total Total Tot
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - followed by answer; and
 - ► repeat.

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
     says hello to the world!
def main():
     print("Hello, World!")
if __name__ == "__main__":
     main()
```

```
def totalWithTax food.tip):
    total - 8
                        Formal Parameters
    tax - 0.0875
    total = food + food * tax
    total - total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal - totalWithTax(lunch, lTip)
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', arotal)
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - followed by answer; and
 - repeat.
- Past exams are on the webpage (under Final Exam Information).

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
     says hello to the world!
def main():
     print("Hello, World!")
if __name__ == "__main__":
     main()
```

```
def totalWithTax food.tip):
    total - 8
                        Formal Parameters
    tax = 0.0875
    total = food + food * tax
    total - total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal - totalWithTax(lunch, lTip)
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', arotal)
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - followed by answer; and
 - repeat.
- Past exams are on the webpage (under Final Exam Information).
- Theme: Functions!

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
     says hello to the world!
def main():
     print("Hello, World!")
if __name__ == "__main__":
     main()
```

```
def totalWithTax food.tip):
    total - 8
                        Formal Parameters
   tax - 0.0875
    total = food + food * tax
   total - total + tip
   return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal - totalWithTax(lunch, lTip)
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', arotal)
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - followed by answer; and
 - repeat.
- Past exams are on the webpage (under Final Exam Information).
- Theme: Functions! Starting with Summer 18, #4.

See you next week!



Before next lecture, don't forget to:

- Work on this week's Online Lab
- Optional attend live Lab Review on Wednesday 1-2:30pm
- Take the Lab Quiz on Gradescope by 6pm on Wednesday
- Submit this week's 5 programming assignments (programs 31-35)
- At any point, visit our Drop-In Tutoring 11am-5pm for help!!!