CSci 127: Introduction to Computer Science



hunter.cuny.edu/csci

1/36

This lecture will be recorded

From email

From email

I am not sure how to submit the Lab.

From email

• I am not sure how to submit the Lab.

You don't submit the lab, you read the lab.

From email

I am not sure how to submit the Lab.

You don't submit the lab, you read the lab.

When you are done, start working on this week's 10 programming assignments (this week we will be working on programs 1-10, which is batch 1)

From email

• I am not sure how to submit the Lab.

You don't submit the lab, you read the lab.

When you are done, start working on this week's 10 programming assignments (this week we will be working on programs 1-10, which is batch 1)

Can I work ahead?

From email

I am not sure how to submit the Lab.

You don't submit the lab, you **read the lab.** When you are done, start working on this week's 10 programming assignments (this week we will be working on programs 1-10, which is batch 1)

Can I work ahead?

Absolutely! Submission is open on Gradescope, 3 weeks before the deadline.

From email

I am not sure how to submit the Lab.

You don't submit the lab, you **read the lab.** When you are done, start working on this week's 10 programming assignments (this week we will be working on programs 1-10, which is batch 1)

Can I work ahead?

Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. IMPORTANT: Students who work on the due dates in this class tend to miss deadlines and fall behind. If, instead, you work on programs the week of the associated lecture, you will have time to ask for help if you get stuck and still make the deadline.

From email

I am not sure how to submit the Lab.

You don't submit the lab, you **read the lab**. When you are done, start working on this week's 10 programming assignments (this week we will be working on programs 1-10, which is batch 1)

Can I work ahead?

Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. IMPORTANT: Students who work on the due dates in this class tend to miss deadlines and fall behind. If, instead, you work on programs the week of the associated lecture, you will have time to ask for help if you get stuck and still make the deadline

When is the midterm?

From email

I am not sure how to submit the Lab.

You don't submit the lab, you **read the lab**. When you are done, start working on this week's 10 programming assignments (this week we will be working on programs 1-10, which is batch 1)

Can I work ahead?

Absolutely! Submission is open on Gradescope, 3 weeks before the deadline. IMPORTANT: Students who work on the due dates in this class tend to miss deadlines and fall behind. If, instead, you work on programs the week of the associated lecture, you will have time to ask for help if you get stuck and still make the deadline

When is the midterm?

There is no midterm. Instead there's required class quizzes, programming assignments and the final exam.

Today's Topics



- For-loops
- range()
- Variables
- Characters
- ullet Strings

3/36

In Pairs or Triples...

Some review and some novel challenges:


```
1 #Predict what will be printed:
2 for i in range(4):
       print('The world turned upside down')
  for i in [0,1,2,3,4,5]:
       print(i)
6 for count in range(6):
       print(count)
   for color in ['red', 'green', 'blue']:
       print(color)
   for i in range(2):
10
11
       for j in range(2):
12
           print('Look around,')
13
       print('How lucky we are to be alive!')
```

Python Tutor

```
1 #Predict what will be printed:
2 for i in range(4):
3 print('The world turned upside down')
4 for j in [8,1,2,3,4,5]:
5 print(1)
6 print(1)
7 print(cont)
8 for color in ['rea', 'green', 'blue']:
9 print(color)
10 for i in range(2):
11 for j in range(2):
12 print('Utoka around,')
13 print('Utoka around,')
14 print('Utoka around,')
15 print('Utoka around,')
16 print('Utoka around,')
17 print('Utoka around,')
18 print('Utoka around,')
19 print('Utoka around,')
19 print('Utoka around,')
19 print('Utoka around,')
```

(Demo with pythonTutor)


for-loop



How to Think Like CS, §4.5

for i in list:
 statement1
 statement2
 statement3

for-loop



How to Think Like CS, §4.5

for i in list:
 statement1
 statement2
 statement3

where list is a list of items:

- stated explicitly (e.g. [1,2,3]) or
- generated by a function, e.g. range().

Today's Topics



- For-loops
- range()
- Variables
- Characters
- ullet Strings

7/36

More on range():

```
#Predict what will be printed:
   for num in [2,4,6,8,10]:
 4
        print(num)
 5
 6
    sum = 0
   for x in range(0,12,2):
 8
        print(x)
 9
        sum = sum + x
10
11
   print(sum)
12
13 for c in "ABCD":
14
        print(c)
```

Python Tutor

```
#Predict what will be printed:

for num in [2,4,6,8,10]:
    print(num)


sum = 0
for x in range(0,12,2):
    print(x)
    sum = sum + x

print(sum)

for c in "ABCD":
    print(c)

(Demo with pythonTutor)
```

9/36



• range(stop)





Simplest version:

- range(stop)
- Produces a list: [0,1,2,3,...,stop-1]

10 / 36



Simplest version:

- range(stop)
- Produces a list: [0,1,2,3,...,stop-1]
- For example, if you want the list [0,1,2,3,...,100], you would write:

10 / 36



Simplest version:

- range(stop)
- Produces a list: [0,1,2,3,...,stop-1]
- For example, if you want the list [0,1,2,3,...,100], you would write:

range(101)

10 / 36

What if you wanted to start somewhere else:



What if you wanted to start somewhere else:

• range(start, stop)





What if you wanted to start somewhere else:

- range(start, stop)
- Produces a list: [start,start+1,...,stop-1]



What if you wanted to start somewhere else:

- range(start, stop)
- Produces a list: [start,start+1,...,stop-1]
- For example, if you want the the list [10,11,...,20]
 you would write:



What if you wanted to start somewhere else:

- range(start, stop)
- Produces a list: [start,start+1,...,stop-1]
- For example, if you want the the list [10,11,...,20]
 you would write:

range(10,21)

11 / 36

What if you wanted to count by twos, or some other number:



What if you wanted to count by twos, or some other number:

• range(start, stop, step)



12/36



What if you wanted to count by twos, or some other number:

- range(start, stop, step)
- Produces a list:
 [start,start+step,start+2*step...,last]
 (where last is the largest start+k*step less than stop)

12 / 36



What if you wanted to count by twos, or some other number:

- range(start, stop, step)
- Produces a list: [start,start+step,start+2*step...,last] (where last is the largest start+k*step less than stop)
- For example, if you want the list [5,10,...,50]
 you would write:

12 / 36



What if you wanted to count by twos, or some other number:

- range(start, stop, step)
- Produces a list: [start,start+step,start+2*step...,last] (where last is the largest start+k*step less than stop)
- For example, if you want the list [5,10,...,50]
 you would write:

range(5,51,5)

12 / 36



The three versions:



The three versions:

• range(stop)



The three versions:

- range(stop)
- range(start, stop)



The three versions:

- range(stop)
- range(start, stop)
- range(start, stop, step)

Today's Topics



- For-loops
- range()
- Variables
- Characters
- ullet Strings

14 / 36

• A **variable** is a reserved memory location for storing a value.





- A variable is a reserved memory location for storing a value.
- Different kinds, or types, of values need different amounts of space:
 - ▶ int: integer or whole numbers



- A **variable** is a reserved memory location for storing a value.
- Different kinds, or types, of values need different amounts of space:
 - ► int: integer or whole numbers
 - ► float: floating point or real numbers



- A variable is a reserved memory location for storing a value.
- Different kinds, or types, of values need different amounts of space:
 - ▶ int: integer or whole numbers
 - ► float: floating point or real numbers
 - string: sequence of characters



- A variable is a reserved memory location for storing a value.
- Different kinds, or types, of values need different amounts of space:
 - ► int: integer or whole numbers
 - ► float: floating point or real numbers
 - ► **string**: sequence of characters
 - ► **list**: a sequence of items



- A variable is a reserved memory location for storing a value.
- Different kinds, or types, of values need different amounts of space:
 - ▶ int: integer or whole numbers
 - ► float: floating point or real numbers
 - string: sequence of characters
 - ▶ list: a sequence of items
 e.g. [3, 1, 4, 5, 9] or
 ['violet','purple','indigo']



- A variable is a reserved memory location for storing a value.
- Different kinds, or types, of values need different amounts of space:
 - int: integer or whole numbers
 - float: floating point or real numbers
 - ► **string**: sequence of characters
 - ► list: a sequence of items e.g. [3, 1, 4, 5, 9] or ['violet','purple','indigo']
 - class variables: for complex objects, like turtles.
- In Python (unlike other languages) you don't need to specify the type; it is deduced by its value.

 There's some rules about valid names for variables.





- There's some rules about valid names for variables.
- Can use the underscore ('_'), upper and lower case letters.



- There's some rules about valid names for variables.
- Can use the underscore ('_'), upper and lower case letters.
- Can also use numbers, just can't start a name with a number.



- There's some rules about valid names for variables.
- Can use the underscore ('_'), upper and lower case letters.
- Can also use numbers, just can't start a name with a number.
- Can't use symbols (like '+' or '*') since used for arithmetic.

16 / 36



- There's some rules about valid names for variables.
- Can use the underscore ('_'), upper and lower case letters.
- Can also use numbers, just can't start a name with a number.
- Can't use symbols (like '+' or '*') since used for arithmetic.
- Can't use some words that Python has reserved for itself (e.g. for).
 (List of reserved words in Think CS, §2.5.)

16 / 36

Today's Topics



- For-loops
- range()
- Variables
- Characters
- Strings

17 / 36

Standardized Code for Characters

American Standard Code for Information Interchange (ASCII), 1960.

Standardized Code for Characters

American Standard Code for Information Interchange (ASCII), 1960. (New version called: Unicode).

Standardized Code for Characters

American Standard Code for Information Interchange (ASCII), 1960. (New version called: Unicode).

ASCII TABLE

Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char	Decimal	Hex	Char
0	0	[NULL]	32	20	(SPACE)	64	40	@	96	60	*
1	1	[START OF HEADING]	33	21	1	65	41	A	97	61	a
2	2	[START OF TEXT]	34	22		66	42	В	98	62	b
3	3	[END OF TEXT]	35	23	#	67	43	С	99	63	C
4	4	[END OF TRANSMISSION]	36	24	\$	68	44	D	100	64	d
5	5	[ENQUIRY]	37	25	%	69	45	E	101	65	e
6	6	[ACKNOWLEDGE]	38	26	&	70	46	F	102	66	f
7	7	[BELL]	39	27	1	71	47	G	103	67	g
8	8	[BACKSPACE]	40	28	(72	48	H	104	68	h
9	9	[HORIZONTAL TAB]	41	29)	73	49	1	105	69	1
10	Α	[LINE FEED]	42	2A	*	74	4A	J	106	6A	j
11	В	[VERTICAL TAB]	43	2B	+	75	4B	K	107	6B	k
12	C	[FORM FEED]	44	2C	,	76	4C	L	108	6C	1
13	D	[CARRIAGE RETURN]	45	2D	4	77	4D	M	109	6D	m
14	E	[SHIFT OUT]	46	2E		78	4E	N	110	6E	n
15	F	[SHIFT IN]	47	2F	1	79	4F	0	111	6F	0
16	10	[DATA LINK ESCAPE]	48	30	0	80	50	P	112	70	р
17	11	[DEVICE CONTROL 1]	49	31	1	81	51	Q	113	71	q
18	12	[DEVICE CONTROL 2]	50	32	2	82	52	R	114	72	r
19	13	[DEVICE CONTROL 3]	51	33	3	83	53	S	115	73	S
20	14	[DEVICE CONTROL 4]	52	34	4	84	54	T	116	74	t
21	15	[NEGATIVE ACKNOWLEDGE]	53	35	5	85	55	U	117	75	u
22	16	[SYNCHRONOUS IDLE]	54	36	6	86	56	v	118	76	v
23	17	[ENG OF TRANS. BLOCK]	55	37	7	87	57	w	119	77	w
24	18	[CANCEL]	56	38	8	88	58	X	120	78	X
25	19	[END OF MEDIUM]	57	39	9	89	59	Υ	121	79	У
26	1A	[SUBSTITUTE]	58	ЗА	1	90	5A	Z	122	7A	ž
27	1B	[ESCAPE]	59	3B	;	91	5B	1	123	7B	-{
28	1C	[FILE SEPARATOR]	60	3C	<	92	5C	Ĭ.	124	7C	Ť.
29	1D	[GROUP SEPARATOR]	61	3D	=	93	5D	1	125	7D	}
30	1E	[RECORD SEPARATOR]	62	3E	>	94	5E	^	126	7E	~
31	1F	IUNIT SEPARATORI	63	3F	?	95	5F		127	7F	[DEL]

(wiki)

(There is a link to the ASCII table on the course webpage, under 'Useful Links'.)

ASCII TABLE

(There is a link to the ASCII table on the course webpage, under 'Useful Links'.)



 ord(c): returns Unicode (ASCII) of the character.

19 / 36

(There is a link to the ASCII table on the course webpage, under 'Useful Links'.)



- ord(c): returns Unicode (ASCII) of the character.
- Example: ord('a') returns 97.

(There is a link to the ASCII table on the course webpage, under 'Useful Links'.)



- ord(c): returns Unicode (ASCII) of the character.
- Example: ord('a') returns 97.
- chr(x): returns the character whose Unicode is x.

(There is a link to the ASCII table on the course webpage, under 'Useful Links'.)



- ord(c): returns Unicode (ASCII) of the character.
- Example: ord('a') returns 97.
- chr(x): returns the character whose Unicode is x.
- Example: chr(97) returns 'a'.

(There is a link to the ASCII table on the course webpage, under 'Useful Links'.)



- ord(c): returns Unicode (ASCII) of the character.
- Example: ord('a') returns 97.
- chr(x): returns the character whose Unicode is x.
- Example: chr(97) returns 'a'.
- What is chr(33)?

In Pairs or Triples...

Some review and some novel challenges:

../images/csci127/caesarCipher.png

20 / 36


Python Tutor

```
1 #Predict what will be printed:
     for c in range(65,90):
        print(chr(c))
   6 message - "I love Python"
  7 newMessage =
   8 for c in message:
  9 print(ord(c)) #Print the Unicode of each number
       print(chr(ord(c)+1)) #Print the next character
 11 newMessage = newMessage + chr(ord(c)+1) #add to the new message
12 print("The coded message is", newMessage)
 14 word - "zebra"
 15 codedWord = "
 16 for ch in word:
      offset = ord(ch) - ord('a') + 1 #how many letters past 'a'
       wrap - offset % 26 #if larger than 26, wrap back to 0
 19
       newChar = chr(ord('a') + wrap) #compute the new letter
 28
       print(wrap, chr(ord('a') + wrap)) #print the wrap & new lett
 21
        codedWord - codedWord + newChar #add the newChar to the coded w
23 print("The coded word (with wrap) is", codedWord)
```

(Demo with pythonTutor)

Wrap





wrap: if offset > 26 then wrap around % is the reminder 27 % 26 = 1

CSci 127 (Hunter)

User Input

Covered in detail in Lab 2:

../images/csci127/inputMessage.png

4 D > 4 D > 4 E > 4 E > E 2000



• x = 3 + 5 stores the number 8 in memory location x.



- x = 3 + 5 stores the number 8 in memory location x.



- x = 3 + 5 stores the number 8 in memory location x.
- x = x + 1 increases x by 1.
- s = "hi" + "Mom" stores "hiMom" in memory locations s.



- x = 3 + 5 stores the number 8 in memory location x.
- s = "hi" + "Mom" stores "hiMom" in
 memory locations s.
- s = s + "A" adds the letter "A" to the end of the strings s.

Today's Topics



- For-loops
- range()
- Variables
- Characters
- Strings

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

The first line creates a variable, called s, that stores the string:
 "FridaysSaturdaysSundays"

(ロト 4 個 ト 4 重 ト 4 重 ト) 見) りへの

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called s, that stores the string:
 "FridaysSaturdaysSundays"
- There are many useful functions for strings (more in Lab 2).

(ロト 4 個 ト 4 重 ト 4 重 ト) 見) りへの

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called s, that stores the string:
 "FridaysSaturdaysSundays"
- There are many useful functions for strings (more in Lab 2).
- s.count(x) will count the number of times the pattern, x, appears in s.

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called s, that stores the string:
 "FridaysSaturdaysSundays"
- There are many useful functions for strings (more in Lab 2).
- s.count(x) will count the number of times the pattern, x, appears in s.
 - ▶ s.count("s") counts the number of lower case s that occurs.

More on Strings: String Methods

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called s, that stores the string:
 "FridaysSaturdaysSundays"
- There are many useful functions for strings (more in Lab 2).
- s.count(x) will count the number of times the pattern, x, appears in s.
 - ▶ s.count("s") counts the number of lower case s that occurs.
 - ▶ num = s.count("s") stores the result in the variable num, for later.

4□ > 4□ > 4 = > 4 = > = 900

26 / 36

More on Strings: String Methods

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called s, that stores the string: "FridaysSaturdaysSundays"
- There are many useful functions for strings (more in Lab 2).
- s.count(x) will count the number of times the pattern, x, appears in s.
 - ▶ s.count("s") counts the number of lower case s that occurs.
 - ▶ num = s.count("s") stores the result in the variable num, for later.
 - ➤ What would print(s.count("sS")) output?

More on Strings: String Methods

```
s = "FridaysSaturdaysSundays"
num = s.count("s")
```

- The first line creates a variable, called s, that stores the string:
 "FridaysSaturdaysSundays"
- There are many useful functions for strings (more in Lab 2).
- s.count(x) will count the number of times the pattern, x, appears in s.
 - ▶ s.count("s") counts the number of lower case s that occurs.
 - ▶ num = s.count("s") stores the result in the variable num, for later.
 - ► What would print(s.count("sS")) output?
 - ► What about:

```
mess = "10 20 21 9 101 35"
mults = mess.count("0 ")
print(mults)
```

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

• Strings are made up of individual characters (letters, numbers, etc.)

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

(ロト 4 個 ト 4 분 ト 4 분 ト · 분 · ~ 9 ~ 0

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	а	у	S	S	а	 S	u	n	d	a	у	S

<ロ > < 個 > < 豆 > < 豆 > 豆 の < @

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	а	У	S	S	a	 S	u	n	d	а	у	S
												-4	-3	-2	-1

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	а	у	S	S	а	 S	u	n	d	а	у	S
												-4	-3	-2	-1

● s[0] is

4 ロ ト 4 昼 ト 4 差 ト ま め 4 で

28 / 36

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	а	у	S	S	а	 S	u	n	d	а	у	S
												-4	-3	-2	-1

• s[0] is 'F'.

4 U > 4 🗗 > 4 E > 4 E > E 9 Q C

28 / 36

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	а	У	S	S	а	 S	u	n	d	а	у	S
												-4	-3	-2	-1

s [1] is

4 U > 4 @ > 4 E > 4 E > E 990

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	а	у	S	S	а	 S	u	n	d	а	у	S
												-4	-3	-2	-1

s[1] is 'r'.

4 U > 4 @ > 4 E > 4 E > E 990

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	a	У	S	S	a	 S	u	n	d	а	у	S
												-4	-3	-2	-1

s[-1] is

- 4 ロ ト 4 昼 ト 4 差 ト - 差 - 釣 9 C C

CSci 127 (Hunter) Lecture 2

30 / 36

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	a	У	S	S	a	 S	u	n	d	a	у	S
												-4	-3	-2	-1

• s[-1] is 's'.

4 U > 4 @ > 4 E > 4 E > E 990

30 / 36

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	a	у	S	S	а	 S	u	n	d	а	у	S
												-4	-3	-2	-1

• s[3:6] is

4□ > 4□ > 4 = > 4 = > = 90

31 / 36

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	а	У	S	S	а	 S	u	n	d	а	У	S
												-4	-3	-2	-1

s[3:6] is 'day'.

4ロト 4回ト 4 きト 4 きト き から(*)

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	а	У	S	S	a	 S	u	n	d	а	у	S
												-4	-3	-2	-1

● s[:3] is

- 4 ロ ト 4 昼 ト 4 差 ト - 差 - 釣 9 (で

CSci 127 (Hunter) Lecture 2

32/36

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	а	У	S	S	а	 S	u	n	d	а	у	S
												-4	-3	-2	-1

• s[:3] is 'Fri'.

- 4 ロ ト 4 昼 ト 4 差 ト - 差 - 釣 9 (で

32/36

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	i	d	а	У	S	S	а	 S	u	n	d	а	у	S
												-4	-3	-2	-1

o s[:-1] is

4 U > 4 @ > 4 E > 4 E > E 990

33 / 36

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- Strings are made up of individual characters (letters, numbers, etc.)
- Useful to be able to refer to pieces of a string, either an individual location or a "substring" of the string.

0	1	2	3	4	5	6	7	8	 16	17	18	19	20	21	22
F	r	ij	d	а	у	S	S	а	 S	u	n	d	а	у	S
												-4	-3	-2	-1

s[:-1] is 'FridaysSaturdaysSunday'.
(no trailing 's' at the end)

◆ロト ◆昼 ト ◆ 恵 ト ・ 恵 ・ りへで

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

split() divides a string into a list.

4□ > 4圖 > 4 ≥ > 4 ≥ > ≥ り < ○</p>

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- split() divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

(ロト 4 昼 ト 4 重 ト 4 重 - り 9 0

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- split() divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

"Friday Saturday Sunday"

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- split() divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

```
"Friday XSaturday XSunday"
days = ['Friday', 'Saturday', 'Sunday']
```

34 / 36

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- split() divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

```
"Friday\sectionsSaturday\sectionsSaturday"
days = ['Friday', 'Saturday', 'Sunday']
```

Different delimiters give different lists:

<ロト < @ ト < き > < き > き り < で

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- split() divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

```
"Friday\sectionsSaturday\sectionsSaturday"
days = ['Friday', 'Saturday', 'Sunday']
```

Different delimiters give different lists:

```
days = s[:-1].split("day")
```

<ロト < 個 ト < 重 ト < 重 ト 三 三 り < @

34 / 36

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- split() divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

```
"Friday\sectionsSaturday\sectionsSaturday"
days = ['Friday', 'Saturday', 'Sunday']
```

Different delimiters give different lists:

```
days = s[:-1].split("day")
"FriXXXsSaturXXXsSunXXX"
```

<ロ > < 個 > < 重 > < 重 > < 更 > の Q ⊙

```
s = "FridaysSaturdaysSundays"
days = s[:-1].split("s")
```

- split() divides a string into a list.
- Cross out the delimiter, and the remaining items are the list.

```
"Friday Saturday Sunday"
days = ['Friday', 'Saturday', 'Sunday']
```

Different delimiters give different lists:

```
days = s[:-1].split("day")
"FridxxsSaturdxxsSundxx"
days = ['Fri', 'sSatur', 'sSun']
```

• In Python, we introduced:

```
1 #Predict what will be printed:
 2 for i in range(4):
        print('The world turned upside down')
 4 for j in [0,1,2,3,4,5]:
        print(j)
 6 for count in range(6):
        print(count)
 8 for color in ['red', 'green', 'blue']:
        print(color)
10 for i in range(2):
11
       for j in range(2):
12
          print('Look around,')
13
        print('How lucky we are to be alive!')
```

11

12

13

```
1 #Predict what will be printed:
2 for i in range(4):
3 print("The world turned upside down")
4 for j in [0,1,2,3,4,5]:
5 print([0,1,2,3,4,5]:
5 print(count)
6 for color in ["rad", "green", "blue"]:
9 print(color)
10 for in range(2):
```

print('How lucky we are to be alive!')

for j in range(2):

print('Look around,')

- In Python, we introduced:
 - ▶ For-loops

```
1 #Predict what will be printed:
 2 for i in range(4):
        print('The world turned upside down')
 4 for j in [0,1,2,3,4,5]:
        print(j)
 6 for count in range(6):
        print(count)
 8 for color in ['red', 'green', 'blue']:
        print(color)
10 for i in range(2):
11
       for j in range(2):
12
           print('Look around,')
13
        print('How lucky we are to be alive!')
```

• In Python, we introduced:

- ► For-loops
- ► range()

```
1 #Predict what will be printed:
2 for i in range(4):
3 print('The world turned upside down')
4 for j in (9,1,2,3,4,5):
6 for count in range(6):
7 print(count)
8 for color in ('red', 'green', 'blue']:
9 print(color)
10 for in range(20);
11 print('look around,')
12 print('look around,')
13 print('look ucky we net be a clivel')
```

- In Python, we introduced:
 - ► For-loops
 - ► range()
 - Variables: ints and strings

```
1 #Predict what will be printed:
2 for i in range(4):
3 print("The world turned upside down')
4 for j in (0,1,2,3,4,5):
4 for j in (0,1,2,3,4,5):
5 for count in range(6):
7 print(count)
8 for color in ("red", "green", 'blue"):
9 print(color)
10 for in "in range(0):
11 print("Indo around,")
12 print("Indo lucky are to be alive!")
```

- In Python, we introduced:
 - For-loops
 - ► range()
 - Variables: ints and strings
 - ► Some arithmetic

35/36

```
1 #Predict what will be printed:
2 for i in range(2):
3 print('The world turned upside down')
4 for j in [9,1,2,3,4,5]:
6 for count in range(6):
7 print(count)
8 for color in ['red', 'green', 'blue']:
9 print(color)
10 for i in range(20(2)):
11 print('Look around,')
12 print('tok ulcdy we ret be alive!')
```

- In Python, we introduced:
 - For-loops
 - ► range()
 - Variables: ints and strings
 - ► Some arithmetic
 - ► String concatenation

35/36

```
1 #Predict what will be printed:
2 for i in range(4):
3 parint("The morld turned upside down')
4 print(3,1,3,4,5];
5 print(1);
5 print(1);
6 for count in range(6):
7 print(count)
8 for color in ['red', 'green', 'blue']:
9 print(color)
10 for in range(2);
11 for in range(2);
12 print('look around,')
12 print('look around,')
13 print('look dround,')
14 print('look dround,')
```

• In Python, we introduced:

- For-loops
- ► range()
- Variables: ints and strings
- ► Some arithmetic
- String concatenation
- ► Functions: ord() and chr()

35/36

```
1 #Predict what will be printed:
2 for i in range(4):
5 print(3, 2, 3, 4, 5]:
5 print(3, 2, 3, 4, 5]:
7 print(1, 2, 3, 4, 5]:
9 print(1, 2, 3, 4, 5]:
9 print(count)
9 print(count)
10 for ji in range(6):
11 print(color)
12 print(color)
12 print('look around,')
13 print('look around,')
14 print('look around,')
15 print('look dround,')
15 print('look dround,')
16 print('look dround,')
17 print('look dround,')
18 print('look dround,')
```

- In Python, we introduced:
 - For-loops
 - ► range()
 - Variables: ints and strings
 - Some arithmetic
 - ► String concatenation
 - ► Functions: ord() and chr()
 - ► String Manipulation

35/36

```
1 #Predict what will be printed:
2 for i in range(4):
5 print(3, 2, 3, 4, 5]:
5 print(3, 2, 3, 4, 5]:
7 print(1, 2, 3, 4, 5]:
9 print(1, 2, 3, 4, 5]:
9 print(count)
9 print(count)
10 for ji in range(6):
11 print(color)
12 print(color)
12 print('look around,')
13 print('look around,')
14 print('look around,')
15 print('look dround,')
15 print('look dround,')
16 print('look dround,')
17 print('look dround,')
18 print('look dround,')
```

- In Python, we introduced:
 - For-loops
 - ► range()
 - Variables: ints and strings
 - Some arithmetic
 - ► String concatenation
 - ► Functions: ord() and chr()
 - ► String Manipulation

35/36



Before next lecture, don't forget to:

Read and work through LAB 2!



Before next lecture, don't forget to:

- Read and work through LAB 2!
- Submit this week's 10 programming assignments (programs 1-10)



Before next lecture, don't forget to:

- Read and work through LAB 2!
- Submit this week's 10 programming assignments (programs 1-10)
- If you need help, email cscisummer23@gmail.com with questions or to sign up for Friday online tutoring.



Before next lecture, don't forget to:

- Read and work through LAB 2!
- Submit this week's 10 programming assignments (programs 1-10)
- If you need help, email cscisummer23@gmail.com with questions or to sign up for Friday online tutoring.