```python
# -*- coding: utf-8 -*-

# Form implementation generated from reading ui file 'resources/ui/MainWindow.ui'
#
# Created by: PyQt5 UI code generator 5.15.4
#
# WARNING: Any manual changes made to this file will be lost when pyuic5 is
# run again.  Do not edit this file unless you know what you are doing.


from PyQt5 import QtCore, QtGui, QtWidgets


class Ui_MainWindow(object):
    def setupUi(self, MainWindow):
        MainWindow.setObjectName("MainWindow")
        MainWindow.resize(1000, 800)
        MainWindow.setMinimumSize(QtCore.QSize(1000, 800))
        font = QtGui.QFont()
        font.setFamily("Palatino Linotype")
        font.setPointSize(11)
        font.setBold(True)
        font.setItalic(False)
        font.setWeight(75)
        MainWindow.setFont(font)
        MainWindow.setStyleSheet("font: 75 11pt \"Palatino Linotype\";\n"
"color: rgb(255, 0, 0);\n"
"selection-color: rgb(255, 0, 0);\n"
"font-weight: bold;")
        self.centralwidget = QtWidgets.QWidget(MainWindow)
        self.centralwidget.setObjectName("centralwidget")
        self.layoutWidget = QtWidgets.QWidget(self.centralwidget)
        self.layoutWidget.setGeometry(QtCore.QRect(20, 290, 641, 68))
        self.layoutWidget.setObjectName("layoutWidget")
        self.gridLayout_3 = QtWidgets.QGridLayout(self.layoutWidget)
        self.gridLayout_3.setContentsMargins(0, 0, 0, 0)
        self.gridLayout_3.setObjectName("gridLayout_3")
        self.FinalJudgmentEntryButton_6 = QtWidgets.QPushButton(self.layoutWidget)
        self.FinalJudgmentEntryButton_6.setMinimumSize(QtCore.QSize(120, 30))
        self.FinalJudgmentEntryButton_6.setObjectName("FinalJudgmentEntryButton_6")
        self.gridLayout_3.addWidget(self.FinalJudgmentEntryButton_6, 0, 0, 1, 1)
        self.FinalJudgmentEntryButton_7 = QtWidgets.QPushButton(self.layoutWidget)
        self.FinalJudgmentEntryButton_7.setMinimumSize(QtCore.QSize(120, 30))
        self.FinalJudgmentEntryButton_7.setObjectName("FinalJudgmentEntryButton_7")
        self.gridLayout_3.addWidget(self.FinalJudgmentEntryButton_7, 0, 1, 1, 1)
        self.MinorMisdemeanorTrafficButton_2 = QtWidgets.QPushButton(self.layoutWidget)
        self.MinorMisdemeanorTrafficButton_2.setMinimumSize(QtCore.QSize(120, 30))
        self.MinorMisdemeanorTrafficButton_2.setObjectName("MinorMisdemeanorTrafficButton_2")
        self.gridLayout_3.addWidget(self.MinorMisdemeanorTrafficButton_2, 0, 2, 1, 1)
        self.FinalJudgmentEntryButton_8 = QtWidgets.QPushButton(self.layoutWidget)
        self.FinalJudgmentEntryButton_8.setMinimumSize(QtCore.QSize(120, 30))
        self.FinalJudgmentEntryButton_8.setObjectName("FinalJudgmentEntryButton_8")
        self.gridLayout_3.addWidget(self.FinalJudgmentEntryButton_8, 1, 0, 1, 1)
        self.FinalJudgmentEntryButton_9 = QtWidgets.QPushButton(self.layoutWidget)
        self.FinalJudgmentEntryButton_9.setMinimumSize(QtCore.QSize(120, 30))
        self.FinalJudgmentEntryButton_9.setObjectName("FinalJudgmentEntryButton_9")
        self.gridLayout_3.addWidget(self.FinalJudgmentEntryButton_9, 1, 1, 1, 1)
        self.FinalJudgmentEntryButton_10 = QtWidgets.QPushButton(self.layoutWidget)
        self.FinalJudgmentEntryButton_10.setMinimumSize(QtCore.QSize(120, 30))
        self.FinalJudgmentEntryButton_10.setObjectName("FinalJudgmentEntryButton_10")
        self.gridLayout_3.addWidget(self.FinalJudgmentEntryButton_10, 1, 2, 1, 1)
        self.label_2 = QtWidgets.QLabel(self.centralwidget)
        self.label_2.setGeometry(QtCore.QRect(20, 100, 151, 31))
        font = QtGui.QFont()
        font.setFamily("Palatino Linotype")
        font.setPointSize(11)
        font.setBold(True)
        font.setItalic(False)
        font.setUnderline(True)
        font.setWeight(75)
```

```python
71    self.label_2.setFont(font)
72    self.label_2.setObjectName("label_2")
73    self.label_3 = QtWidgets.QLabel(self.centralwidget)
74    self.label_3.setGeometry(QtCore.QRect(20, 250, 181, 31))
75    font = QtGui.QFont()
76    font.setFamily("Palatino Linotype")
77    font.setPointSize(11)
78    font.setBold(True)
79    font.setItalic(False)
80    font.setUnderline(True)
81    font.setWeight(75)
82    self.label_3.setFont(font)
83    self.label_3.setObjectName("label_3")
84    self.label_4 = QtWidgets.QLabel(self.centralwidget)
85    self.label_4.setGeometry(QtCore.QRect(20, 400, 171, 31))
86    font = QtGui.QFont()
87    font.setFamily("Palatino Linotype")
88    font.setPointSize(11)
89    font.setBold(True)
90    font.setItalic(False)
91    font.setUnderline(True)
92    font.setWeight(75)
93    self.label_4.setFont(font)
94    self.label_4.setObjectName("label_4")
95    self.layoutWidget_2 = QtWidgets.QWidget(self.centralwidget)
96    self.layoutWidget_2.setGeometry(QtCore.QRect(20, 440, 651, 68))
97    self.layoutWidget_2.setObjectName("layoutWidget_2")
98    self.gridLayout_4 = QtWidgets.QGridLayout(self.layoutWidget_2)
99    self.gridLayout_4.setContentsMargins(0, 0, 0, 0)
100   self.gridLayout_4.setObjectName("gridLayout_4")
101   self.FinalJudgmentEntryButton_11 = QtWidgets.QPushButton(self.layoutWidget_2)
102   self.FinalJudgmentEntryButton_11.setMinimumSize(QtCore.QSize(120, 30))
103   self.FinalJudgmentEntryButton_11.setObjectName("FinalJudgmentEntryButton_11")
104   self.gridLayout_4.addWidget(self.FinalJudgmentEntryButton_11, 0, 0, 1, 1)
105   self.FinalJudgmentEntryButton_12 = QtWidgets.QPushButton(self.layoutWidget_2)
106   self.FinalJudgmentEntryButton_12.setMinimumSize(QtCore.QSize(120, 30))
107   self.FinalJudgmentEntryButton_12.setObjectName("FinalJudgmentEntryButton_12")
108   self.gridLayout_4.addWidget(self.FinalJudgmentEntryButton_12, 0, 1, 1, 1)
109   self.MinorMisdemeanorTrafficButton_3 = QtWidgets.QPushButton(self.layoutWidget_2)
110   self.MinorMisdemeanorTrafficButton_3.setMinimumSize(QtCore.QSize(120, 30))
111   self.MinorMisdemeanorTrafficButton_3.setObjectName("MinorMisdemeanorTrafficButton_3")
112   self.gridLayout_4.addWidget(self.MinorMisdemeanorTrafficButton_3, 0, 2, 1, 1)
113   self.FinalJudgmentEntryButton_13 = QtWidgets.QPushButton(self.layoutWidget_2)
114   self.FinalJudgmentEntryButton_13.setMinimumSize(QtCore.QSize(120, 30))
115   self.FinalJudgmentEntryButton_13.setObjectName("FinalJudgmentEntryButton_13")
116   self.gridLayout_4.addWidget(self.FinalJudgmentEntryButton_13, 1, 0, 1, 1)
117   self.FinalJudgmentEntryButton_14 = QtWidgets.QPushButton(self.layoutWidget_2)
118   self.FinalJudgmentEntryButton_14.setMinimumSize(QtCore.QSize(120, 30))
119   self.FinalJudgmentEntryButton_14.setObjectName("FinalJudgmentEntryButton_14")
120   self.gridLayout_4.addWidget(self.FinalJudgmentEntryButton_14, 1, 1, 1, 1)
121   self.FinalJudgmentEntryButton_15 = QtWidgets.QPushButton(self.layoutWidget_2)
122   self.FinalJudgmentEntryButton_15.setMinimumSize(QtCore.QSize(120, 30))
123   self.FinalJudgmentEntryButton_15.setObjectName("FinalJudgmentEntryButton_15")
124   self.gridLayout_4.addWidget(self.FinalJudgmentEntryButton_15, 1, 2, 1, 1)
125   self.layoutWidget1 = QtWidgets.QWidget(self.centralwidget)
126   self.layoutWidget1.setGeometry(QtCore.QRect(20, 140, 961, 68))
127   self.layoutWidget1.setObjectName("layoutWidget1")
128   self.gridLayout_2 = QtWidgets.QGridLayout(self.layoutWidget1)
129   self.gridLayout_2.setContentsMargins(0, 0, 0, 0)
130   self.gridLayout_2.setObjectName("gridLayout_2")
131   self.GreenSheetButton = QtWidgets.QPushButton(self.layoutWidget1)
132   self.GreenSheetButton.setMinimumSize(QtCore.QSize(120, 30))
133   self.GreenSheetButton.setObjectName("GreenSheetButton")
134   self.gridLayout_2.addWidget(self.GreenSheetButton, 0, 1, 1, 1)
135   self.FinalJudgmentEntryButton_5 = QtWidgets.QPushButton(self.layoutWidget1)
136   self.FinalJudgmentEntryButton_5.setMinimumSize(QtCore.QSize(120, 30))
137   self.FinalJudgmentEntryButton_5.setObjectName("FinalJudgmentEntryButton_5")
138   self.gridLayout_2.addWidget(self.FinalJudgmentEntryButton_5, 0, 2, 1, 1)
139   self.MinorMisdemeanorTrafficButton = QtWidgets.QPushButton(self.layoutWidget1)
140   self.MinorMisdemeanorTrafficButton.setMinimumSize(QtCore.QSize(120, 30))
141   self.MinorMisdemeanorTrafficButton.setObjectName("MinorMisdemeanorTrafficButton")
```

```python
141        self.MinorMisdemeanorTrafficButton.setObjectName("MinorMisdemeanorTrafficButton")
142        self.gridLayout_2.addWidget(self.MinorMisdemeanorTrafficButton, 0, 0, 1, 1)
143        self.FinalJudgmentEntryButton_2 = QtWidgets.QPushButton(self.layoutWidget1)
144        self.FinalJudgmentEntryButton_2.setMinimumSize(QtCore.QSize(120, 30))
145        self.FinalJudgmentEntryButton_2.setObjectName("FinalJudgmentEntryButton_2")
146        self.gridLayout_2.addWidget(self.FinalJudgmentEntryButton_2, 1, 0, 1, 1)
147        self.FinalJudgmentEntryButton_3 = QtWidgets.QPushButton(self.layoutWidget1)
148        self.FinalJudgmentEntryButton_3.setMinimumSize(QtCore.QSize(120, 30))
149        self.FinalJudgmentEntryButton_3.setObjectName("FinalJudgmentEntryButton_3")
150        self.gridLayout_2.addWidget(self.FinalJudgmentEntryButton_3, 1, 1, 1, 1)
151        self.FinalJudgmentEntryButton_4 = QtWidgets.QPushButton(self.layoutWidget1)
152        self.FinalJudgmentEntryButton_4.setMinimumSize(QtCore.QSize(120, 30))
153        self.FinalJudgmentEntryButton_4.setObjectName("FinalJudgmentEntryButton_4")
154        self.gridLayout_2.addWidget(self.FinalJudgmentEntryButton_4, 1, 2, 1, 1)
155        self.layoutWidget2 = QtWidgets.QWidget(self.centralwidget)
156        self.layoutWidget2.setGeometry(QtCore.QRect(22, 20, 817, 31))
157        self.layoutWidget2.setObjectName("layoutWidget2")
158        self.gridLayout = QtWidgets.QGridLayout(self.layoutWidget2)
159        self.gridLayout.setContentsMargins(0, 0, 0, 0)
160        self.gridLayout.setObjectName("gridLayout")
161        self.label = QtWidgets.QLabel(self.layoutWidget2)
162        font = QtGui.QFont()
163        font.setFamily("Palatino Linotype")
164        font.setPointSize(11)
165        font.setBold(True)
166        font.setItalic(False)
167        font.setWeight(75)
168        self.label.setFont(font)
169        self.label.setObjectName("label")
170        self.gridLayout.addWidget(self.label, 0, 0, 1, 1)
171        self.hemmeter_radioButton = QtWidgets.QRadioButton(self.layoutWidget2)
172        self.hemmeter_radioButton.setObjectName("hemmeter_radioButton")
173        self.buttonGroup = QtWidgets.QButtonGroup(MainWindow)
174        self.buttonGroup.setObjectName("buttonGroup")
175        self.buttonGroup.addButton(self.hemmeter_radioButton)
176        self.gridLayout.addWidget(self.hemmeter_radioButton, 0, 1, 1, 1)
177        self.rohrer_radioButton = QtWidgets.QRadioButton(self.layoutWidget2)
178        self.rohrer_radioButton.setObjectName("rohrer_radioButton")
179        self.buttonGroup.addButton(self.rohrer_radioButton)
180        self.gridLayout.addWidget(self.rohrer_radioButton, 0, 2, 1, 1)
181        self.pelanda_radioButton = QtWidgets.QRadioButton(self.layoutWidget2)
182        self.pelanda_radioButton.setObjectName("pelanda_radioButton")
183        self.buttonGroup.addButton(self.pelanda_radioButton)
184        self.gridLayout.addWidget(self.pelanda_radioButton, 0, 3, 1, 1)
185        self.bunner_radioButton = QtWidgets.QRadioButton(self.layoutWidget2)
186        self.bunner_radioButton.setObjectName("bunner_radioButton")
187        self.buttonGroup.addButton(self.bunner_radioButton)
188        self.gridLayout.addWidget(self.bunner_radioButton, 0, 4, 1, 1)
189        MainWindow.setCentralWidget(self.centralwidget)
190        self.menubar = QtWidgets.QMenuBar(MainWindow)
191        self.menubar.setGeometry(QtCore.QRect(0, 0, 1000, 31))
192        self.menubar.setObjectName("menubar")
193        self.menuFile = QtWidgets.QMenu(self.menubar)
194        self.menuFile.setObjectName("menuFile")
195        self.menuSettings = QtWidgets.QMenu(self.menubar)
196        self.menuSettings.setObjectName("menuSettings")
197        self.menuView = QtWidgets.QMenu(self.menubar)
198        self.menuView.setObjectName("menuView")
199        MainWindow.setMenuBar(self.menubar)
200        self.statusbar = QtWidgets.QStatusBar(MainWindow)
201        self.statusbar.setObjectName("statusbar")
202        MainWindow.setStatusBar(self.statusbar)
203        self.actionOpen = QtWidgets.QAction(MainWindow)
204        self.actionOpen.setObjectName("actionOpen")
205        self.actionOptions = QtWidgets.QAction(MainWindow)
206        self.actionOptions.setObjectName("actionOptions")
207        self.actionExit = QtWidgets.QAction(MainWindow)
208        self.actionExit.setObjectName("actionExit")
209        self.menu_file_exit = QtWidgets.QAction(MainWindow)
210        self.menu_file_exit.setObjectName("menu_file_exit")
211        self.actionGeneral_Motion_Entry = QtWidgets.QAction(MainWindow)
212        self.actionGeneral_Motion_Entry.setObjectName("actionGeneral_Motion_Entry")
```

```python
212         self.actionGeneral_Motion_Entry.setObjectName("actionGeneral_Motion_Entry")
213         self.actionFail_to_Appear_Minor_Traffic_Offense = QtWidgets.QAction(MainWindow)
214         self.actionFail_to_Appear_Minor_Traffic_Offense.setObjectName("actionFail_to_Appear_Minor_Traffic_Offense")
215         self.actionOmnibus_Motion_Form = QtWidgets.QAction(MainWindow)
216         self.actionOmnibus_Motion_Form.setObjectName("actionOmnibus_Motion_Form")
217         self.actionJury_Instructions = QtWidgets.QAction(MainWindow)
218         self.actionJury_Instructions.setObjectName("actionJury_Instructions")
219         self.actioncontrollers = QtWidgets.QAction(MainWindow)
220         self.actioncontrollers.setObjectName("actioncontrollers")
221         self.actionTemplates = QtWidgets.QAction(MainWindow)
222         self.actionTemplates.setObjectName("actionTemplates")
223         self.menuFile.addAction(self.actionOpen)
224         self.menuFile.addAction(self.actionOptions)
225         self.menuFile.addAction(self.actionExit)
226         self.menuFile.addSeparator()
227         self.menuFile.addAction(self.menu_file_exit)
228         self.menuSettings.addAction(self.actioncontrollers)
229         self.menubar.addAction(self.menuFile.menuAction())
230         self.menubar.addAction(self.menuSettings.menuAction())
231         self.menubar.addAction(self.menuView.menuAction())
232
233         self.retranslateUi(MainWindow)
234         QtCore.QMetaObject.connectSlotsByName(MainWindow)
235
236     def retranslateUi(self, MainWindow):
237         _translate = QtCore.QCoreApplication.translate
238         MainWindow.setWindowTitle(_translate("MainWindow", "MuniEntry - ver 0.2.0 - alpha"))
239         self.FinalJudgmentEntryButton_6.setText(_translate("MainWindow", "Entry"))
240         self.FinalJudgmentEntryButton_7.setText(_translate("MainWindow", "Entry"))
241         self.MinorMisdemeanorTrafficButton_2.setText(_translate("MainWindow", "Entry"))
242         self.FinalJudgmentEntryButton_8.setText(_translate("MainWindow", "Entry"))
243         self.FinalJudgmentEntryButton_9.setText(_translate("MainWindow", "Entry"))
244         self.FinalJudgmentEntryButton_10.setText(_translate("MainWindow", "Entry"))
245         self.label_2.setText(_translate("MainWindow", "Traffic Entries"))
246         self.label_3.setText(_translate("MainWindow", "Criminal Entries"))
247         self.label_4.setText(_translate("MainWindow", "Civil Entries"))
248         self.FinalJudgmentEntryButton_11.setText(_translate("MainWindow", "Entry"))
249         self.FinalJudgmentEntryButton_12.setText(_translate("MainWindow", "Entry"))
250         self.MinorMisdemeanorTrafficButton_3.setText(_translate("MainWindow", "Entry"))
251         self.FinalJudgmentEntryButton_13.setText(_translate("MainWindow", "Entry"))
252         self.FinalJudgmentEntryButton_14.setText(_translate("MainWindow", "Entry"))
253         self.FinalJudgmentEntryButton_15.setText(_translate("MainWindow", "Entry"))
254         self.GreenSheetButton.setText(_translate("MainWindow", "Entry"))
255         self.FinalJudgmentEntryButton_5.setText(_translate("MainWindow", "Entry"))
256         self.MinorMisdemeanorTrafficButton.setText(_translate("MainWindow", "Minor Misdemeanor"))
257         self.FinalJudgmentEntryButton_2.setText(_translate("MainWindow", "Entry"))
258         self.FinalJudgmentEntryButton_3.setText(_translate("MainWindow", "Entry"))
259         self.FinalJudgmentEntryButton_4.setText(_translate("MainWindow", "Entry"))
260         self.label.setText(_translate("MainWindow", "Judicial Officer:"))
261         self.hemmeter_radioButton.setText(_translate("MainWindow", "Judge Hemmeter"))
262         self.rohrer_radioButton.setText(_translate("MainWindow", "Judge Rohrer"))
263         self.pelanda_radioButton.setText(_translate("MainWindow", "Magistrate Pelanda"))
264         self.bunner_radioButton.setText(_translate("MainWindow", "Magistrate Bunner"))
265         self.menuFile.setTitle(_translate("MainWindow", "File"))
266         self.menuSettings.setTitle(_translate("MainWindow", "Settings"))
267         self.menuView.setTitle(_translate("MainWindow", "View"))
268         self.actionOpen.setText(_translate("MainWindow", "Open"))
269         self.actionOptions.setText(_translate("MainWindow", "Options"))
270         self.actionExit.setText(_translate("MainWindow", "Templates"))
271         self.menu_file_exit.setText(_translate("MainWindow", "Exit"))
272         self.actionGeneral_Motion_Entry.setText(_translate("MainWindow", "General Motion Entry"))
273         self.actionFail_to_Appear_Minor_Traffic_Offense.setText(_translate("MainWindow", "Fail to Appear - Minor Traffic Offense"))
274         self.actionOmnibus_Motion_Form.setText(_translate("MainWindow", "Omnibus Motion Form"))
275         self.actionJury_Instructions.setText(_translate("MainWindow", "Jury Instructions"))
276         self.actioncontrollers.setText(_translate("MainWindow", "controllers"))
277         self.actionTemplates.setText(_translate("MainWindow", "Templates"))
```