

笔记本: PHP

创建时间: 2018/10/29 20:39

更新时间: 2018/10/29 20:41





URL: https://blog.csdn.net/m0_37750720/article/details/82595237

一、`cd ~/.ssh`

二、通过下面的命令，依次生成两个平台的key

```
$ ssh-keygen -t rsa -C "xxxxxxx@qq.com" -f "github_id_rsa"
$ ssh-keygen -t rsa -C "xxxxxxx@qq.com" -f "gitee_id_rsa"
```

完成后，.ssh文件夹生成以下文件

 gitee_id_rsa	2018/7/6 20:31	文件	2 KB
 gitee_id_rsa.pub	2018/7/6 20:31	Microsoft Publis...	1 KB
 github_id_rsa	2018/7/6 20:30	文件	2 KB
 github_id_rsa.pub	2018/7/6 20:30	Microsoft Publis...	1 KB

三、把public key复制到gitee和github

执行命令 `cat github_id_rsa.pub` 把第二行到结尾的内容复制到github的ssh中保存

```
$ cat github_id_rsa.pub
ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQDrwjCyCX/X0lQryH2+RtVxN4shie+mj1dAwNuQQVW
xMg1Dy1QLcUnAP8Buj3eItxnE2JsPWLjwXIuVToB5C/K9l0E9Fpr1vD8bMZ8/3QyZJDqNsRZ2BAFup+o
zlwIo7YdfKVjPk53iTq+Bm6uayq03fpE5AgGpnuj/bkFsLw/FLXUCfMZbBf04t1b17mMyVEjmtbJ0ifV
gDd20+bSv0drFy81vnWY1sd37zjM1jLLtD1X8pfgoB/q45kbGgJHNNcht5VoamJUH+TF17RSro3qPeM5
syAk1PPQbYj3lxgTeG6K5xzDWrDZi0iSrY6xVLE6ixVPusFRq3DDDLZX9Qf .@qq.com
```

同样的操作，添加gitee的ssh

四、创建config文件解决ssh冲突

在.ssh文件夹下执行命令 `vi config`

文件中添加以下内容

```
# gitee
Host gitee.com
HostName gitee.com
PreferredAuthentications publickey
```

```
IdentityFile ~/.ssh/gitee_id_rsa

# github
Host github.com
HostName github.com
PreferredAuthentications publickey
IdentityFile ~/.ssh/github_id_rsa
```

五、测试

执行

```
ssh -T git@github.com
```

成功则返回

```
Hi xxx! You've successfully authenticated, but GitHub does not provide shell access.
```

执行

```
ssh -T git@gitee.com
```

成功则返回

```
Hi xxx! You've successfully authenticated, but GITEE.COM does not provide shell access.
```