frbussupport.Rnw: Create Support Files

Gary Young

June 28, 2016

0.1 scripts

Notice that I've had to change underscores in file and directory names when I create them with noweb. I use the "setup.sh" bash script to create the directory structure, and the "check.sh" bash script to compare the renamed Eview files to the originals. I have to ignore white space in the comparison because the original source files are not consistent with using either Microsoft or Linux line ending characters.

0.1.1 setup script

```
2  \( \support/\setup.sh 2 \) \( \support/\
```

This code is written to file support/setup.sh.

0.1. SCRIPTS 3

0.1.2 check script

 $3 \qquad \langle support/check.sh \ 3 \rangle \equiv$

```
cfile=data_only_package/variables.txt; ofile=srcEview/data.only.package/variables.txt; echo "XX cfile=frbus_package/mods/stdver_coeffs.txt; ofile=srcEview/frbus.package/mods/stdver.coeffs.txt cfile=frbus_package/mods/stdver_eqs.txt; ofile=srcEview/frbus.package/mods/stdver.eqs.txt; echo cfile=frbus_package/mods/stdver_varinfo; ofile=srcEview/frbus.package/mods/stdver.varinfo; echo
```

cfile=frbus_package/addins/ld_frbus_cfs/ld_frbus_cfs.prg; ofile=srcEview/frbus.package/addins/l cfile=frbus_package/addins/ld_frbus_eqs/ld_frbus_eqs.prg; ofile=srcEview/frbus.package/addins/l cfile=frbus_package/addins/ld_mce_cfs/ld_mce_cfs.prg; ofile=srcEview/frbus.package/addins/ld.mc cfile=frbus_package/addins/ld_mce_eqs/ld_mce_eqs.prg; ofile=srcEview/frbus.package/addins/ld.mc cfile=frbus_package/addins/ld_some_eqs/ld_some_eqs.prg; ofile=srcEview/frbus.package/addins/ld. cfile=frbus_package/addins/ld_varinfo/ld_varinfo.prg; ofile=srcEview/frbus.package/addins/ld.varinfo.prg; cfile=frbus_package/addins/regadd.prg; ofile=srcEview/frbus.package/addins/regadd.prg; echo "XX cfile=frbus_package/programs/example1.prg; ofile=srcEview/frbus.package/programs/example1.prg; cfile=frbus_package/programs/example2.prg; ofile=srcEview/frbus.package/programs/example2.prg; cfile=frbus_package/programs/example3.prg; ofile=srcEview/frbus.package/programs/example3.prg; cfile=frbus_package/programs/example4.prg; ofile=srcEview/frbus.package/programs/example4.prg; cfile=frbus_package/programs/ocpolicy.prg; ofile=srcEview/frbus.package/programs/ocpolicy.prg; cfile=frbus_package/programs/pings.prg; ofile=srcEview/frbus.package/programs/pings.prg; echo ' cfile=frbus_package/programs/plot_resids.prg; ofile=srcEview/frbus.package/programs/plot.resids cfile=frbus_package/programs/stochsim.prg; ofile=srcEview/frbus.package/programs/stochsim.prg; cfile=frbus_package/subs/master_library.prg; ofile=srcEview/frbus.package/subs/master.library.p cfile=frbus_package/subs/mce_solve_library.prg; ofile=srcEview/frbus.package/subs/mce.solve.lib cfile=mce_solve_package/example1.prg; ofile=srcEview/mce.solve.package/example1.prg; echo "XX \$ cfile=mce_solve_package/example2.prg; ofile=srcEview/mce.solve.package/example2.prg; echo "XX \$ cfile=mce_solve_package/example3.prg; ofile=srcEview/mce.solve.package/example3.prg; echo "XX \$ cfile=mce_solve_package/example4.prg; ofile=srcEview/mce.solve.package/example4.prg; echo "XX \$ cfile=mce_solve_package/example5.prg; ofile=srcEview/mce.solve.package/example5.prg; echo "XX \$ cfile=mce_solve_package/mce_solve_library.prg; ofile=srcEview/mce.solve.package/mce.solve.library.prg; cfile=state_space_package/data_transformations.prg; ofile=srcEview/state.space.package/data.tra cfile=state_space_package/estimation_code.prg; ofile=srcEview/state.space.package/estimation.co cfile=state_space_package/frbus_supply_estimation.prg; ofile=srcEview/state.space.package/frbus cfile=state_space_package/frbus_supply_filter.prg; ofile=srcEview/state.space.package/frbus.sup cfile=state_space_package/initial_values.prg; ofile=srcEview/state.space.package/initial.values

This code is written to file support/check.sh.

Chapter 1

Notes, Bibliography and Indexes

1.1 Chunks

 $\langle support/check.sh \ 3 \rangle$ $\langle support/setup.sh \ 2 \rangle$

1.2 Index