

In [1]:

```
import copy
import numpy as np
import torch
import torch.nn as nn
import torch.nn.functional as F
import torchvision
import torchvision.transforms as transforms
```

PyTorch

In this notebook you will gain some hands-on experience with [PyTorch \(https://pytorch.org/\)](https://pytorch.org/), one of the major frameworks for deep learning. To install PyTorch, follow [the official installation instructions \(https://pytorch.org/get-started/locally/\)](https://pytorch.org/get-started/locally/). Make sure that you select the correct OS & select the version with CUDA if your computer supports it. If you do not have an Nvidia GPU, you can install the CPU version by setting `CUDA` to `None`. However, in this case we recommend using [Google Colab \(https://colab.research.google.com/\)](https://colab.research.google.com/). Make sure that you enable GPU acceleration in `Runtime > Change runtime type`.

You will start by re-implementing some common features of deep neural networks (dropout and batch normalization) and then implement a very popular modern architecture for image classification (ResNet) and improve its training loop.

1. Dropout

Dropout is a form of regularization for neural networks. It works by randomly setting activations (values) to 0, each one with equal probability p . The values are then scaled by a factor $\frac{1}{1-p}$ to conserve their mean.

Dropout effectively trains a pseudo-ensemble of models with stochastic gradient descent. During evaluation we want to use the full ensemble and therefore have to turn off dropout. Use `self.training` to check if the model is in training or evaluation mode.

Do not use any dropout implementation from PyTorch for this!

In [2]:

```
x=torch.rand(4,2,10)
x.var(dim=0,keepdims=True).shape
```

Out[2]:

```
torch.Size([1, 2, 10])
```

In [3]:

```
class Dropout(nn.Module):
    """
    Dropout, as discussed in the lecture and described here:
    https://pytorch.org/docs/stable/nn.html#torch.nn.Dropout

    Args:
        p: float, dropout probability
    """
    def __init__(self, p):
        super().__init__()
        self.p = p

    def forward(self, input):
        """
        The module's forward pass.
        This has to be implemented for every PyTorch module.
        PyTorch then automatically generates the backward pass
        by dynamically generating the computational graph during
        execution.

        Args:
            input: PyTorch tensor, arbitrary shape

        Returns:
            PyTorch tensor, same shape as input
        """
        tmp=torch.tensor((torch.rand(*input.shape)>self.p),dtype=torch.int)

        return tmp*input*1/(1-self.p)
```

In [4]:

```
# Test dropout
test = torch.rand(10_000)
dropout = Dropout(0.2)
test_dropped = dropout(test)

# These assertions can in principle fail due to bad luck, but
# if implemented correctly they should almost always succeed.
assert np.isclose(test_dropped.mean().item(), test.mean().item(), atol=1e-2)
assert np.isclose((test_dropped > 0).float().mean().item(), 0.8, atol=1e-2)
```

c:\users\kashif ai\i2dl_exercises\exercise_01\myenv\lib\site-packages\ipykernel_launcher.py:28: Use
rWarning: To copy construct from a tensor, it is recommended to use sourceTensor.clone().detach() or
sourceTensor.clone().detach().requires_grad_(True), rather than torch.tensor(sourceTensor).

2. Batch normalization

Batch normalization is a trick use to smoothen the loss landscape and improve training. It is defined as the function

$$y = \frac{x - \mu_x}{\sigma_x + \epsilon} \cdot \gamma + \beta$$

, where γ and β and learnable parameters and ϵ is a some small number to avoid dividing by zero. The Statistics μ_x and σ_x are taken separately for each feature. In a CNN this means averaging over the batch and all pixels.

Do not use any batch normalization implementation from PyTorch for this!

In [5]:

```
class BatchNorm(nn.Module):
    """
    Batch normalization, as discussed in the lecture and similar to
    https://pytorch.org/docs/stable/nn.html#torch.nn.BatchNorm1d

    Only uses batch statistics (no running mean for evaluation).
    Batch statistics are calculated for a single dimension.
    Gamma is initialized as 1, beta as 0.

    Args:
        num_features: Number of features to calculate batch statistics for.
    """
    def __init__(self, num_features):
        super().__init__()

        self.gamma = nn.Parameter(torch.ones(num_features))
        self.beta = nn.Parameter(torch.zeros(num_features))

    def forward(self, input):
        """
        Batch normalization over the dimension C of (N, C, L).

        Args:
            input: PyTorch tensor, shape [N, C, L]

        Return:
            PyTorch tensor, same shape as input
        """
        N,C,L=input.shape
        eps = 1e-5
        input=input.permute(1,0,2).reshape(C,-1)
        mean=input.mean(dim=-1,keepdims=True)
        std=input.std(dim=-1,keepdims=True)
        out=(input-mean)/(std+eps)
        out=self.gamma.unsqueeze(dim=-1)*out+self.beta.unsqueeze(dim=-1)
        #print(self.gamma.unsqueeze(dim=0).unsqueeze(dim=-1).shape)
        return out.reshape(C,N,L).permute(1,0,2)
```

In [6]:

```
# Tests the batch normalization implementation
torch.random.manual_seed(42)
test = torch.randn(8, 2, 4)

b1 = BatchNorm(2)
test_b1 = b1(test)

b2 = nn.BatchNorm1d(2, affine=False, track_running_stats=False)
test_b2 = b2(test)

assert torch.allclose(test_b1, test_b2, rtol=0.02)
```

3. ResNet

ResNet is the models that first introduced residual connections (a form of skip connections). It is a rather simple, but successful and very popular architecture. In this part of the exercise we will re-implement it step by step.

Note that there is also an [improved version of ResNet \(https://arxiv.org/abs/1603.05027\)](https://arxiv.org/abs/1603.05027) with optimized residual blocks. Here we will implement the [original version \(https://arxiv.org/abs/1512.03385\)](https://arxiv.org/abs/1512.03385) for CIFAR-10. Your dropout and batchnorm implementations won't help you here. Just use PyTorch's own layers.

This is just a convenience function to make e.g. `nn.Sequential` more flexible. It is e.g. useful in combination with `x.squeeze()`.

In [7]:

```
class Lambda(nn.Module):
    def __init__(self, func):
        super().__init__()
        self.func = func

    def forward(self, x):
        return self.func(x)
```

We begin by implementing the residual blocks. The block is illustrated by this sketch:



Note that we use 'SAME' padding, no bias, and batch normalization after each convolution. You do not need `nn.Sequential` here. The skip connection is already implemented as `self.skip`. It can handle different strides and increases in the number of channels.

In [8]:

```
class ResidualBlock(nn.Module):
    """
    The residual block used by ResNet.

    Args:
        in_channels: The number of channels (feature maps) of the incoming embedding
        out_channels: The number of channels after the first convolution
        stride: Stride size of the first convolution, used for downsampling
    """

    def __init__(self, in_channels, out_channels, stride=1):
        super().__init__()
        if stride > 1 or in_channels != out_channels:
            # Add strides in the skip connection and zeros for the new channels.
            self.skip = Lambda(lambda x: F.pad(x[:, :, ::stride, ::stride],
                                                (0, 0, 0, 0, 0, out_channels - in_channels),
                                                mode="constant", value=0))
        else:
            self.skip = nn.Sequential()

        self.conv1=nn.Conv2d(in_channels,out_channels,3,padding=1,stride=stride,bias=False)
        self.relu=nn.ReLU()
        self.bn1=nn.BatchNorm2d(out_channels)
        self.conv2=nn.Conv2d(out_channels,out_channels,3,padding=1,stride=1,bias=False)

        self.bn2=nn.BatchNorm2d(out_channels)

    def forward(self, input):
        x=self.conv1(input)
        x=self.bn1(x)
        x=self.relu(x)
        x=self.conv2(x)
        x=self.bn2(x)
        x=self.relu(self.skip(input)+x)
        return x
```

Next we implement a stack of residual blocks for convenience. The first layer in the block is the one changing the number of channels and downsampling. You can use `nn.ModuleList` to use a list of child modules.

In [9]:

```
class ResidualStack(nn.Module):
    """
    A stack of residual blocks.

    Args:
        in_channels: The number of channels (feature maps) of the incoming embedding
        out_channels: The number of channels after the first layer
        stride: Stride size of the first layer, used for downsampling
        num_blocks: Number of residual blocks
    """

    def __init__(self, in_channels, out_channels, stride, num_blocks):
        super().__init__()

        self.modules1=nn.ModuleList([ResidualBlock(in_channels,out_channels,stride=stride)])
        self.module_list=self.modules1.extend([ResidualBlock(out_channels,out_channels,stride=1) for i in range(num_blocks-1)])

    def forward(self, input):
        x=input
        for layer in self.module_list:
            x=layer(x)
        return x
```

Now we are finally ready to implement the full model! To do this, use the `nn.Sequential` API and carefully read the following paragraph from the paper (Fig. 3 is not important):



Note that a convolution layer is always convolution + batch norm + activation (ReLU), that each `ResidualBlock` contains 2 layers, and that you might have to squeeze the embedding before the dense (fully-connected) layer.

In [10]:

```
n = 5
num_classes = 10
layers=[nn.Conv2d(3,16,3,1,1,bias=False),nn.BatchNorm2d(16),nn.ReLU()]
in_channel=16
for i in [16,32,64]:
    if i==16:
        layers.append(ResidualStack(in_channel,i,1,n))
    else:
        layers.append(ResidualStack(in_channel,i,2,n))
    in_channel=i
layers=layers+[nn.AdaptiveAvgPool2d(1),nn.Flatten(1),nn.Linear(64,num_classes),nn.Softmax(dim=-1)]

resnet=nn.Sequential(*layers)
# TODO: Implement ResNet via nn.Sequential
```

Next we need to initialize the weights of our model.

In [11]:

```
def initialize_weight(module):
    if isinstance(module, (nn.Linear, nn.Conv2d)):
        nn.init.kaiming_normal_(module.weight, nonlinearity='relu')
    elif isinstance(module, nn.BatchNorm2d):
        nn.init.constant_(module.weight, 1)
        nn.init.constant_(module.bias, 0)

resnet.apply(initialize_weight);
```

4. Training

So now we have a shiny new model, but that doesn't really help when we can't train it. So that's what we do next.

First we need to load the data. Note that we split the official training data into train and validation sets, because you must not look at the test set until you are completely done developing your model and report the final results. Some people don't do this properly, but you should not copy other people's bad habits.

In [12]:

```
class CIFAR10Subset(torchvision.datasets.CIFAR10):
    """
    Get a subset of the CIFAR10 dataset, according to the passed indices.
    """
    def __init__(self, *args, idx=None, **kwargs):
        super().__init__(*args, **kwargs)

        if idx is None:
            return

        self.data = self.data[idx]
        targets_np = np.array(self.targets)
        self.targets = targets_np[idx].tolist()
```

We next define transformations that change the images into PyTorch tensors, standardize the values according to the precomputed mean and standard deviation, and provide data augmentation for the training set.

In [13]:

```
normalize = transforms.Normalize(mean=[0.485, 0.456, 0.406],
                                std=[0.229, 0.224, 0.225])

transform_train = transforms.Compose([
    transforms.RandomHorizontalFlip(),
    transforms.RandomCrop(32, 4),
    transforms.ToTensor(),
    normalize,
])
transform_eval = transforms.Compose([
    transforms.ToTensor(),
    normalize
])
```

In [14]:

```
ntrain = 45_000
train_set = CIFAR10Subset(root='./data', train=True, idx=range(ntrain),
                          download=True, transform=transform_train)
val_set = CIFAR10Subset(root='./data', train=True, idx=range(ntrain, 50_000),
                        download=True, transform=transform_eval)
test_set = torchvision.datasets.CIFAR10(root='./data', train=False,
                                         download=True, transform=transform_eval)
```

Files already downloaded and verified
Files already downloaded and verified
Files already downloaded and verified

In [15]:

```
dataloaders = {}
dataloaders['train'] = torch.utils.data.DataLoader(train_set, batch_size=128,
                                                  shuffle=True, num_workers=0,
                                                  pin_memory=True)
dataloaders['val'] = torch.utils.data.DataLoader(val_set, batch_size=128,
                                                shuffle=False, num_workers=0,
                                                pin_memory=True)
dataloaders['test'] = torch.utils.data.DataLoader(test_set, batch_size=128,
                                                  shuffle=False, num_workers=0,
                                                  pin_memory=True)
```

Next we push the model to our GPU (if there is one).

Next we define a helper method that does one epoch of training or evaluation. We have only defined training here, so you need to implement the necessary changes for evaluation!

In [17]:

```
device = torch.device('cuda') if torch.cuda.is_available() else torch.device('cpu')

resnet.to(device);
print(resnet)
```

```
Sequential(
  (0): Conv2d(3, 16, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
  (1): BatchNorm2d(16, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
  (2): ReLU()
  (3): ResidualStack(
    (modules1): ModuleList(
      (0): ResidualBlock(
        (skip): Sequential()
        (conv1): Conv2d(16, 16, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (relu): ReLU()
        (bn1): BatchNorm2d(16, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv2): Conv2d(16, 16, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (bn2): BatchNorm2d(16, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      )
      (1): ResidualBlock(
        (skip): Sequential()
        (conv1): Conv2d(16, 16, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (relu): ReLU()
        (bn1): BatchNorm2d(16, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv2): Conv2d(16, 16, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (bn2): BatchNorm2d(16, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      )
      (2): ResidualBlock(
        (skip): Sequential()
        (conv1): Conv2d(16, 16, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (relu): ReLU()
        (bn1): BatchNorm2d(16, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv2): Conv2d(16, 16, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (bn2): BatchNorm2d(16, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      )
      (3): ResidualBlock(
        (skip): Sequential()
        (conv1): Conv2d(16, 16, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (relu): ReLU()
        (bn1): BatchNorm2d(16, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv2): Conv2d(16, 16, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (bn2): BatchNorm2d(16, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      )
      (4): ResidualBlock(
        (skip): Sequential()
        (conv1): Conv2d(16, 16, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (relu): ReLU()
```

[illegible]

[illegible]


```

        (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
    )
    (4): ResidualBlock(
      (skip): Sequential()
      (conv1): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (relu): ReLU()
      (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
    )
  )
(module_list): ModuleList(
  (0): ResidualBlock(
    (skip): Lambda()
    (conv1): Conv2d(32, 64, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1), bias=False)
    (relu): ReLU()
    (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
    (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
    (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
  )
  (1): ResidualBlock(
    (skip): Sequential()
    (conv1): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
    (relu): ReLU()
    (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
    (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
    (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
  )
  (2): ResidualBlock(
    (skip): Sequential()
    (conv1): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
    (relu): ReLU()
    (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
    (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
    (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
  )
  (3): ResidualBlock(
    (skip): Sequential()
    (conv1): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
    (relu): ReLU()
    (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
    (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
    (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
  )
  (4): ResidualBlock(
    (skip): Sequential()
    (conv1): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
    (relu): ReLU()
    (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
    (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
    (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
  )
)
)
(6): AdaptiveAvgPool2d(output_size=1)
(7): Flatten(start_dim=1, end_dim=-1)
(8): Linear(in_features=64, out_features=10, bias=True)
(9): Softmax(dim=-1)
)

```

In [19]:

```
def run_epoch(model, optimizer, dataloader, train):
    """
    Run one epoch of training or evaluation.

    Args:
        model: The model used for prediction
        optimizer: Optimization algorithm for the model
        dataloader: Dataloader providing the data to run our model on
        train: Whether this epoch is used for training or evaluation

    Returns:
        Loss and accuracy in this epoch.
    """
    # TODO: Change the necessary parts to work correctly during evaluation (train=False)

    device = next(model.parameters()).device

    # Set model to training mode (for e.g. batch normalization, dropout)

    epoch_loss = 0.0
    epoch_acc = 0.0

    # Iterate over data
    if train:
        model.train()
        for xb, yb in dataloader:
            xb, yb = xb.to(device), yb.to(device)

            # zero the parameter gradients
            optimizer.zero_grad()

            # forward
            with torch.set_grad_enabled(True):
                pred = model(xb)
                loss = F.cross_entropy(pred, yb)
                top1 = torch.argmax(pred, dim=1)
                ncorrect = torch.sum(top1 == yb)

                loss.backward()
                optimizer.step()

            # statistics
            epoch_loss += loss.item()
            epoch_acc += ncorrect.item()
    else:
        model.eval()
        for xb, yb in dataloader:
            xb, yb = xb.to(device), yb.to(device)

            # zero the parameter gradients

            # forward
            with torch.no_grad():
                pred = model(xb)
                loss = F.cross_entropy(pred, yb)
                top1 = torch.argmax(pred, dim=1)
                ncorrect = torch.sum(top1 == yb)

            # statistics
            epoch_loss += loss.item()
            epoch_acc += ncorrect.item()
    epoch_loss /= len(dataloader.dataset)
    epoch_acc /= len(dataloader.dataset)
    return epoch_loss, epoch_acc
```

Next we implement a method for fitting (training) our model. For many models early stopping can save a lot of training time. Your task is to add early stopping to the loop (based on validation accuracy). Early stopping usually means exiting the training loop if the validation accuracy hasn't improved for patience number of steps. Don't forget to save the best model parameters according to validation accuracy. You will need `copy.deepcopy` and the `state_dict` for this.

In [20]:

```
def fit(model, optimizer, lr_scheduler, dataloaders, max_epochs, patience):
    """
    Fit the given model on the dataset.

    Args:
        model: The model used for prediction
        optimizer: Optimization algorithm for the model
        lr_scheduler: Learning rate scheduler that improves training
                     in late epochs with learning rate decay
        dataloaders: Dataloaders for training and validation
        max_epochs: Maximum number of epochs for training
        patience: Number of epochs to wait with early stopping the
                 training if validation loss has decreased

    Returns:
        Loss and accuracy in this epoch.
    """

    best_acc = 0
    curr_patience = 0

    for epoch in range(max_epochs):
        train_loss, train_acc = run_epoch(model, optimizer, dataloaders['train'], train=True)
        lr_scheduler.step()
        print(f"Epoch {epoch + 1: >3}/{max_epochs}, train loss: {train_loss:.2e}, accuracy: {train_acc * 100:.2f}%")

        val_loss, val_acc = run_epoch(model, None, dataloaders['val'], train=False)
        print(f"Epoch {epoch + 1: >3}/{max_epochs}, val loss: {val_loss:.2e}, accuracy: {val_acc * 100:.2f}%")

        # TODO: Add early stopping and save the best weights (in best_model_weights)
        if val_acc > best_acc:
            best_acc = val_acc
            best_model_weights = copy.deepcopy(model.state_dict())
            curr_patience = 0
        else:
            curr_patience = curr_patience + 1
            if curr_patience == patience:
                break

    model.load_state_dict(best_model_weights)
```

In most cases you should just use the Adam optimizer for training, because it works well out of the box. However, a well-tuned SGD (with momentum) will in most cases outperform Adam. And since the original paper gives us a well-tuned SGD we will just use that.

In [21]:

```
optimizer = torch.optim.SGD(resnet.parameters(), lr=0.1, momentum=0.9, weight_decay=1e-4)
lr_scheduler = torch.optim.lr_scheduler.MultiStepLR(optimizer, milestones=[100, 150], gamma=0.1)

# Fit model
fit(resnet, optimizer, lr_scheduler, dataloaders, max_epochs=200, patience=50)
```

```
Epoch 1/200, train loss: 1.73e-02, accuracy: 23.90%
Epoch 1/200, val loss: 1.77e-02, accuracy: 24.40%
Epoch 2/200, train loss: 1.70e-02, accuracy: 28.42%
Epoch 2/200, val loss: 1.74e-02, accuracy: 27.82%
Epoch 3/200, train loss: 1.67e-02, accuracy: 31.39%
Epoch 3/200, val loss: 1.68e-02, accuracy: 35.62%
Epoch 4/200, train loss: 1.65e-02, accuracy: 34.62%
Epoch 4/200, val loss: 1.73e-02, accuracy: 28.70%
Epoch 5/200, train loss: 1.64e-02, accuracy: 36.18%
Epoch 5/200, val loss: 1.64e-02, accuracy: 40.32%
Epoch 6/200, train loss: 1.58e-02, accuracy: 44.15%
Epoch 6/200, val loss: 1.61e-02, accuracy: 44.84%
Epoch 7/200, train loss: 1.56e-02, accuracy: 46.74%
Epoch 7/200, val loss: 1.60e-02, accuracy: 45.38%
Epoch 8/200, train loss: 1.51e-02, accuracy: 52.48%
Epoch 8/200, val loss: 1.61e-02, accuracy: 44.00%
Epoch 9/200, train loss: 1.49e-02, accuracy: 54.80%
Epoch 9/200, val loss: 1.56e-02, accuracy: 51.40%
Epoch 10/200, train loss: 1.48e-02, accuracy: 56.42%
Epoch 10/200, val loss: 1.52e-02, accuracy: 55.92%
Epoch 11/200, train loss: 1.47e-02, accuracy: 57.75%
Epoch 11/200, val loss: 1.51e-02, accuracy: 56.56%
Epoch 12/200, train loss: 1.46e-02, accuracy: 58.99%
Epoch 12/200, val loss: 1.52e-02, accuracy: 55.10%
Epoch 13/200, train loss: 1.46e-02, accuracy: 59.90%
Epoch 13/200, val loss: 1.50e-02, accuracy: 58.26%
Epoch 14/200, train loss: 1.45e-02, accuracy: 60.78%
```

Epoch 14/200, val loss: 1.48e-02, accuracy: 60.54%
Epoch 15/200, train loss: 1.44e-02, accuracy: 61.74%
Epoch 15/200, val loss: 1.51e-02, accuracy: 57.88%
Epoch 16/200, train loss: 1.42e-02, accuracy: 64.69%
Epoch 16/200, val loss: 1.53e-02, accuracy: 54.62%
Epoch 17/200, train loss: 1.41e-02, accuracy: 65.67%
Epoch 17/200, val loss: 1.47e-02, accuracy: 62.40%
Epoch 18/200, train loss: 1.36e-02, accuracy: 72.02%
Epoch 18/200, val loss: 1.43e-02, accuracy: 68.14%
Epoch 19/200, train loss: 1.35e-02, accuracy: 73.74%
Epoch 19/200, val loss: 1.38e-02, accuracy: 73.68%
Epoch 20/200, train loss: 1.34e-02, accuracy: 74.60%
Epoch 20/200, val loss: 1.40e-02, accuracy: 70.78%
Epoch 21/200, train loss: 1.33e-02, accuracy: 75.76%
Epoch 21/200, val loss: 1.38e-02, accuracy: 73.18%
Epoch 22/200, train loss: 1.33e-02, accuracy: 76.70%
Epoch 22/200, val loss: 1.41e-02, accuracy: 69.92%
Epoch 23/200, train loss: 1.32e-02, accuracy: 76.86%
Epoch 23/200, val loss: 1.35e-02, accuracy: 77.56%
Epoch 24/200, train loss: 1.32e-02, accuracy: 77.28%
Epoch 24/200, val loss: 1.37e-02, accuracy: 75.48%
Epoch 25/200, train loss: 1.32e-02, accuracy: 77.67%
Epoch 25/200, val loss: 1.36e-02, accuracy: 76.00%
Epoch 26/200, train loss: 1.31e-02, accuracy: 78.27%
Epoch 26/200, val loss: 1.34e-02, accuracy: 77.96%
Epoch 27/200, train loss: 1.31e-02, accuracy: 78.85%
Epoch 27/200, val loss: 1.35e-02, accuracy: 78.44%
Epoch 28/200, train loss: 1.31e-02, accuracy: 79.12%
Epoch 28/200, val loss: 1.35e-02, accuracy: 77.92%
Epoch 29/200, train loss: 1.30e-02, accuracy: 79.56%
Epoch 29/200, val loss: 1.33e-02, accuracy: 80.14%
Epoch 30/200, train loss: 1.30e-02, accuracy: 80.03%
Epoch 30/200, val loss: 1.39e-02, accuracy: 73.00%
Epoch 31/200, train loss: 1.30e-02, accuracy: 80.08%
Epoch 31/200, val loss: 1.34e-02, accuracy: 78.88%
Epoch 32/200, train loss: 1.30e-02, accuracy: 80.16%
Epoch 32/200, val loss: 1.35e-02, accuracy: 77.98%
Epoch 33/200, train loss: 1.30e-02, accuracy: 80.63%
Epoch 33/200, val loss: 1.33e-02, accuracy: 79.86%
Epoch 34/200, train loss: 1.29e-02, accuracy: 80.94%
Epoch 34/200, val loss: 1.34e-02, accuracy: 79.14%
Epoch 35/200, train loss: 1.29e-02, accuracy: 80.99%
Epoch 35/200, val loss: 1.32e-02, accuracy: 81.40%
Epoch 36/200, train loss: 1.29e-02, accuracy: 81.18%
Epoch 36/200, val loss: 1.36e-02, accuracy: 76.38%
Epoch 37/200, train loss: 1.29e-02, accuracy: 81.72%
Epoch 37/200, val loss: 1.32e-02, accuracy: 81.08%
Epoch 38/200, train loss: 1.29e-02, accuracy: 81.62%
Epoch 38/200, val loss: 1.34e-02, accuracy: 79.46%
Epoch 39/200, train loss: 1.29e-02, accuracy: 81.69%
Epoch 39/200, val loss: 1.42e-02, accuracy: 69.26%
Epoch 40/200, train loss: 1.28e-02, accuracy: 82.06%
Epoch 40/200, val loss: 1.33e-02, accuracy: 80.34%
Epoch 41/200, train loss: 1.28e-02, accuracy: 82.16%
Epoch 41/200, val loss: 1.34e-02, accuracy: 78.56%
Epoch 42/200, train loss: 1.28e-02, accuracy: 82.23%
Epoch 42/200, val loss: 1.34e-02, accuracy: 78.90%
Epoch 43/200, train loss: 1.28e-02, accuracy: 82.51%
Epoch 43/200, val loss: 1.34e-02, accuracy: 79.02%
Epoch 44/200, train loss: 1.28e-02, accuracy: 82.77%
Epoch 44/200, val loss: 1.36e-02, accuracy: 76.74%
Epoch 45/200, train loss: 1.28e-02, accuracy: 82.97%
Epoch 45/200, val loss: 1.33e-02, accuracy: 79.72%
Epoch 46/200, train loss: 1.28e-02, accuracy: 82.88%
Epoch 46/200, val loss: 1.36e-02, accuracy: 76.64%
Epoch 47/200, train loss: 1.27e-02, accuracy: 83.31%
Epoch 47/200, val loss: 1.32e-02, accuracy: 81.88%
Epoch 48/200, train loss: 1.27e-02, accuracy: 83.33%
Epoch 48/200, val loss: 1.33e-02, accuracy: 81.20%
Epoch 49/200, train loss: 1.28e-02, accuracy: 82.82%
Epoch 49/200, val loss: 1.34e-02, accuracy: 79.36%
Epoch 50/200, train loss: 1.27e-02, accuracy: 83.60%
Epoch 50/200, val loss: 1.35e-02, accuracy: 78.74%
Epoch 51/200, train loss: 1.28e-02, accuracy: 83.24%
Epoch 51/200, val loss: 1.36e-02, accuracy: 76.06%
Epoch 52/200, train loss: 1.27e-02, accuracy: 83.53%
Epoch 52/200, val loss: 1.33e-02, accuracy: 80.72%
Epoch 53/200, train loss: 1.27e-02, accuracy: 83.76%
Epoch 53/200, val loss: 1.32e-02, accuracy: 81.30%
Epoch 54/200, train loss: 1.27e-02, accuracy: 83.63%
Epoch 54/200, val loss: 1.34e-02, accuracy: 78.90%
Epoch 55/200, train loss: 1.27e-02, accuracy: 84.07%
Epoch 55/200, val loss: 1.32e-02, accuracy: 81.90%

Epoch 56/200, train loss: 1.27e-02, accuracy: 83.75%
Epoch 56/200, val loss: 1.34e-02, accuracy: 78.34%
Epoch 57/200, train loss: 1.27e-02, accuracy: 84.35%
Epoch 57/200, val loss: 1.31e-02, accuracy: 82.62%
Epoch 58/200, train loss: 1.27e-02, accuracy: 84.39%
Epoch 58/200, val loss: 1.32e-02, accuracy: 81.76%
Epoch 59/200, train loss: 1.27e-02, accuracy: 84.10%
Epoch 59/200, val loss: 1.34e-02, accuracy: 79.54%
Epoch 60/200, train loss: 1.27e-02, accuracy: 84.27%
Epoch 60/200, val loss: 1.31e-02, accuracy: 83.14%
Epoch 61/200, train loss: 1.27e-02, accuracy: 84.02%
Epoch 61/200, val loss: 1.31e-02, accuracy: 82.68%
Epoch 62/200, train loss: 1.26e-02, accuracy: 84.50%
Epoch 62/200, val loss: 1.35e-02, accuracy: 78.06%
Epoch 63/200, train loss: 1.26e-02, accuracy: 84.83%
Epoch 63/200, val loss: 1.34e-02, accuracy: 79.50%
Epoch 64/200, train loss: 1.26e-02, accuracy: 84.60%
Epoch 64/200, val loss: 1.35e-02, accuracy: 77.22%
Epoch 65/200, train loss: 1.26e-02, accuracy: 84.64%
Epoch 65/200, val loss: 1.32e-02, accuracy: 81.72%
Epoch 66/200, train loss: 1.26e-02, accuracy: 84.59%
Epoch 66/200, val loss: 1.33e-02, accuracy: 80.48%
Epoch 67/200, train loss: 1.27e-02, accuracy: 84.49%
Epoch 67/200, val loss: 1.31e-02, accuracy: 82.74%
Epoch 68/200, train loss: 1.27e-02, accuracy: 84.46%
Epoch 68/200, val loss: 1.32e-02, accuracy: 80.54%
Epoch 69/200, train loss: 1.26e-02, accuracy: 84.93%
Epoch 69/200, val loss: 1.31e-02, accuracy: 82.54%
Epoch 70/200, train loss: 1.26e-02, accuracy: 84.86%
Epoch 70/200, val loss: 1.36e-02, accuracy: 75.92%
Epoch 71/200, train loss: 1.26e-02, accuracy: 84.67%
Epoch 71/200, val loss: 1.31e-02, accuracy: 83.04%
Epoch 72/200, train loss: 1.26e-02, accuracy: 85.27%
Epoch 72/200, val loss: 1.32e-02, accuracy: 81.70%
Epoch 73/200, train loss: 1.26e-02, accuracy: 85.10%
Epoch 73/200, val loss: 1.33e-02, accuracy: 80.74%
Epoch 74/200, train loss: 1.26e-02, accuracy: 85.14%
Epoch 74/200, val loss: 1.32e-02, accuracy: 80.96%
Epoch 75/200, train loss: 1.26e-02, accuracy: 85.36%
Epoch 75/200, val loss: 1.32e-02, accuracy: 82.22%
Epoch 76/200, train loss: 1.26e-02, accuracy: 85.50%
Epoch 76/200, val loss: 1.32e-02, accuracy: 81.30%
Epoch 77/200, train loss: 1.26e-02, accuracy: 85.35%
Epoch 77/200, val loss: 1.32e-02, accuracy: 81.94%
Epoch 78/200, train loss: 1.26e-02, accuracy: 85.49%
Epoch 78/200, val loss: 1.32e-02, accuracy: 81.26%
Epoch 79/200, train loss: 1.26e-02, accuracy: 85.36%
Epoch 79/200, val loss: 1.32e-02, accuracy: 81.74%
Epoch 80/200, train loss: 1.26e-02, accuracy: 85.68%
Epoch 80/200, val loss: 1.30e-02, accuracy: 84.22%
Epoch 81/200, train loss: 1.26e-02, accuracy: 85.70%
Epoch 81/200, val loss: 1.30e-02, accuracy: 83.42%
Epoch 82/200, train loss: 1.26e-02, accuracy: 85.75%
Epoch 82/200, val loss: 1.34e-02, accuracy: 78.72%
Epoch 83/200, train loss: 1.26e-02, accuracy: 85.36%
Epoch 83/200, val loss: 1.32e-02, accuracy: 81.20%
Epoch 84/200, train loss: 1.26e-02, accuracy: 85.82%
Epoch 84/200, val loss: 1.33e-02, accuracy: 79.86%
Epoch 85/200, train loss: 1.26e-02, accuracy: 85.66%
Epoch 85/200, val loss: 1.30e-02, accuracy: 83.60%
Epoch 86/200, train loss: 1.26e-02, accuracy: 85.71%
Epoch 86/200, val loss: 1.30e-02, accuracy: 83.72%
Epoch 87/200, train loss: 1.25e-02, accuracy: 85.79%
Epoch 87/200, val loss: 1.31e-02, accuracy: 82.74%
Epoch 88/200, train loss: 1.25e-02, accuracy: 86.05%
Epoch 88/200, val loss: 1.35e-02, accuracy: 77.60%
Epoch 89/200, train loss: 1.25e-02, accuracy: 85.87%
Epoch 89/200, val loss: 1.32e-02, accuracy: 81.98%
Epoch 90/200, train loss: 1.25e-02, accuracy: 85.90%
Epoch 90/200, val loss: 1.30e-02, accuracy: 83.68%
Epoch 91/200, train loss: 1.25e-02, accuracy: 86.47%
Epoch 91/200, val loss: 1.34e-02, accuracy: 79.48%
Epoch 92/200, train loss: 1.26e-02, accuracy: 85.74%
Epoch 92/200, val loss: 1.32e-02, accuracy: 81.06%
Epoch 93/200, train loss: 1.25e-02, accuracy: 86.05%
Epoch 93/200, val loss: 1.31e-02, accuracy: 82.70%
Epoch 94/200, train loss: 1.25e-02, accuracy: 86.01%
Epoch 94/200, val loss: 1.34e-02, accuracy: 78.36%
Epoch 95/200, train loss: 1.25e-02, accuracy: 86.16%
Epoch 95/200, val loss: 1.31e-02, accuracy: 83.08%
Epoch 96/200, train loss: 1.25e-02, accuracy: 85.98%
Epoch 96/200, val loss: 1.32e-02, accuracy: 81.24%
Epoch 97/200, train loss: 1.25e-02, accuracy: 86.47%

Epoch 97/200, val loss: 1.31e-02, accuracy: 82.78%
Epoch 98/200, train loss: 1.25e-02, accuracy: 86.47%
Epoch 98/200, val loss: 1.29e-02, accuracy: 85.34%
Epoch 99/200, train loss: 1.25e-02, accuracy: 86.83%
Epoch 99/200, val loss: 1.33e-02, accuracy: 80.76%
Epoch 100/200, train loss: 1.25e-02, accuracy: 86.17%
Epoch 100/200, val loss: 1.30e-02, accuracy: 83.84%
Epoch 101/200, train loss: 1.23e-02, accuracy: 89.63%
Epoch 101/200, val loss: 1.26e-02, accuracy: 89.02%
Epoch 102/200, train loss: 1.22e-02, accuracy: 90.91%
Epoch 102/200, val loss: 1.26e-02, accuracy: 88.80%
Epoch 103/200, train loss: 1.21e-02, accuracy: 91.63%
Epoch 103/200, val loss: 1.26e-02, accuracy: 89.32%
Epoch 104/200, train loss: 1.21e-02, accuracy: 91.96%
Epoch 104/200, val loss: 1.26e-02, accuracy: 89.34%
Epoch 105/200, train loss: 1.21e-02, accuracy: 92.21%
Epoch 105/200, val loss: 1.26e-02, accuracy: 89.90%
Epoch 106/200, train loss: 1.20e-02, accuracy: 92.59%
Epoch 106/200, val loss: 1.25e-02, accuracy: 90.04%
Epoch 107/200, train loss: 1.20e-02, accuracy: 92.44%
Epoch 107/200, val loss: 1.26e-02, accuracy: 89.72%
Epoch 108/200, train loss: 1.20e-02, accuracy: 92.77%
Epoch 108/200, val loss: 1.25e-02, accuracy: 89.92%
Epoch 109/200, train loss: 1.20e-02, accuracy: 92.74%
Epoch 109/200, val loss: 1.25e-02, accuracy: 90.26%
Epoch 110/200, train loss: 1.20e-02, accuracy: 92.98%
Epoch 110/200, val loss: 1.25e-02, accuracy: 90.04%
Epoch 111/200, train loss: 1.20e-02, accuracy: 93.05%
Epoch 111/200, val loss: 1.25e-02, accuracy: 90.04%
Epoch 112/200, train loss: 1.20e-02, accuracy: 93.24%
Epoch 112/200, val loss: 1.25e-02, accuracy: 89.98%
Epoch 113/200, train loss: 1.20e-02, accuracy: 93.36%
Epoch 113/200, val loss: 1.25e-02, accuracy: 90.24%
Epoch 114/200, train loss: 1.20e-02, accuracy: 93.38%
Epoch 114/200, val loss: 1.25e-02, accuracy: 90.02%
Epoch 115/200, train loss: 1.20e-02, accuracy: 93.39%
Epoch 115/200, val loss: 1.25e-02, accuracy: 90.16%
Epoch 116/200, train loss: 1.20e-02, accuracy: 93.50%
Epoch 116/200, val loss: 1.25e-02, accuracy: 90.26%
Epoch 117/200, train loss: 1.19e-02, accuracy: 93.74%
Epoch 117/200, val loss: 1.25e-02, accuracy: 90.54%
Epoch 118/200, train loss: 1.19e-02, accuracy: 93.73%
Epoch 118/200, val loss: 1.25e-02, accuracy: 90.12%
Epoch 119/200, train loss: 1.19e-02, accuracy: 93.69%
Epoch 119/200, val loss: 1.25e-02, accuracy: 90.26%
Epoch 120/200, train loss: 1.19e-02, accuracy: 93.95%
Epoch 120/200, val loss: 1.25e-02, accuracy: 90.34%
Epoch 121/200, train loss: 1.19e-02, accuracy: 93.96%
Epoch 121/200, val loss: 1.25e-02, accuracy: 90.16%
Epoch 122/200, train loss: 1.19e-02, accuracy: 94.14%
Epoch 122/200, val loss: 1.25e-02, accuracy: 90.36%
Epoch 123/200, train loss: 1.19e-02, accuracy: 94.27%
Epoch 123/200, val loss: 1.25e-02, accuracy: 90.60%
Epoch 124/200, train loss: 1.19e-02, accuracy: 94.25%
Epoch 124/200, val loss: 1.25e-02, accuracy: 90.24%
Epoch 125/200, train loss: 1.19e-02, accuracy: 94.45%
Epoch 125/200, val loss: 1.25e-02, accuracy: 90.60%
Epoch 126/200, train loss: 1.19e-02, accuracy: 94.42%
Epoch 126/200, val loss: 1.25e-02, accuracy: 90.30%
Epoch 127/200, train loss: 1.19e-02, accuracy: 94.30%
Epoch 127/200, val loss: 1.25e-02, accuracy: 90.44%
Epoch 128/200, train loss: 1.19e-02, accuracy: 94.50%
Epoch 128/200, val loss: 1.25e-02, accuracy: 90.34%
Epoch 129/200, train loss: 1.19e-02, accuracy: 94.63%
Epoch 129/200, val loss: 1.25e-02, accuracy: 90.30%
Epoch 130/200, train loss: 1.19e-02, accuracy: 94.55%
Epoch 130/200, val loss: 1.25e-02, accuracy: 90.66%
Epoch 131/200, train loss: 1.19e-02, accuracy: 94.81%
Epoch 131/200, val loss: 1.25e-02, accuracy: 90.08%
Epoch 132/200, train loss: 1.19e-02, accuracy: 94.88%
Epoch 132/200, val loss: 1.25e-02, accuracy: 90.42%
Epoch 133/200, train loss: 1.19e-02, accuracy: 94.78%
Epoch 133/200, val loss: 1.25e-02, accuracy: 90.54%
Epoch 134/200, train loss: 1.18e-02, accuracy: 94.90%
Epoch 134/200, val loss: 1.25e-02, accuracy: 90.74%
Epoch 135/200, train loss: 1.18e-02, accuracy: 94.98%
Epoch 135/200, val loss: 1.25e-02, accuracy: 90.54%
Epoch 136/200, train loss: 1.19e-02, accuracy: 94.79%
Epoch 136/200, val loss: 1.25e-02, accuracy: 90.62%
Epoch 137/200, train loss: 1.18e-02, accuracy: 94.92%
Epoch 137/200, val loss: 1.25e-02, accuracy: 90.78%
Epoch 138/200, train loss: 1.18e-02, accuracy: 95.00%
Epoch 138/200, val loss: 1.25e-02, accuracy: 90.68%

Epoch	139/200,	train loss:	1.18e-02,	accuracy:	95.15%
Epoch	139/200,	val loss:	1.25e-02,	accuracy:	90.32%
Epoch	140/200,	train loss:	1.18e-02,	accuracy:	95.14%
Epoch	140/200,	val loss:	1.25e-02,	accuracy:	90.68%
Epoch	141/200,	train loss:	1.18e-02,	accuracy:	95.20%
Epoch	141/200,	val loss:	1.25e-02,	accuracy:	90.82%
Epoch	142/200,	train loss:	1.18e-02,	accuracy:	95.16%
Epoch	142/200,	val loss:	1.25e-02,	accuracy:	90.44%
Epoch	143/200,	train loss:	1.18e-02,	accuracy:	95.13%
Epoch	143/200,	val loss:	1.24e-02,	accuracy:	91.12%
Epoch	144/200,	train loss:	1.18e-02,	accuracy:	95.34%
Epoch	144/200,	val loss:	1.25e-02,	accuracy:	90.78%
Epoch	145/200,	train loss:	1.18e-02,	accuracy:	95.34%
Epoch	145/200,	val loss:	1.25e-02,	accuracy:	90.70%
Epoch	146/200,	train loss:	1.18e-02,	accuracy:	95.37%
Epoch	146/200,	val loss:	1.25e-02,	accuracy:	90.58%
Epoch	147/200,	train loss:	1.18e-02,	accuracy:	95.34%
Epoch	147/200,	val loss:	1.25e-02,	accuracy:	90.36%
Epoch	148/200,	train loss:	1.18e-02,	accuracy:	95.44%
Epoch	148/200,	val loss:	1.25e-02,	accuracy:	90.56%
Epoch	149/200,	train loss:	1.18e-02,	accuracy:	95.58%
Epoch	149/200,	val loss:	1.25e-02,	accuracy:	91.10%
Epoch	150/200,	train loss:	1.18e-02,	accuracy:	95.54%
Epoch	150/200,	val loss:	1.25e-02,	accuracy:	90.72%
Epoch	151/200,	train loss:	1.18e-02,	accuracy:	95.88%
Epoch	151/200,	val loss:	1.24e-02,	accuracy:	91.32%
Epoch	152/200,	train loss:	1.18e-02,	accuracy:	95.93%
Epoch	152/200,	val loss:	1.24e-02,	accuracy:	91.50%
Epoch	153/200,	train loss:	1.18e-02,	accuracy:	96.12%
Epoch	153/200,	val loss:	1.24e-02,	accuracy:	91.38%
Epoch	154/200,	train loss:	1.17e-02,	accuracy:	96.20%
Epoch	154/200,	val loss:	1.24e-02,	accuracy:	91.44%
Epoch	155/200,	train loss:	1.17e-02,	accuracy:	96.22%
Epoch	155/200,	val loss:	1.24e-02,	accuracy:	91.42%
Epoch	156/200,	train loss:	1.17e-02,	accuracy:	96.26%
Epoch	156/200,	val loss:	1.24e-02,	accuracy:	91.36%
Epoch	157/200,	train loss:	1.17e-02,	accuracy:	96.29%
Epoch	157/200,	val loss:	1.24e-02,	accuracy:	91.42%
Epoch	158/200,	train loss:	1.17e-02,	accuracy:	96.34%
Epoch	158/200,	val loss:	1.24e-02,	accuracy:	91.42%
Epoch	159/200,	train loss:	1.17e-02,	accuracy:	96.28%
Epoch	159/200,	val loss:	1.25e-02,	accuracy:	91.20%
Epoch	160/200,	train loss:	1.17e-02,	accuracy:	96.38%
Epoch	160/200,	val loss:	1.24e-02,	accuracy:	91.38%
Epoch	161/200,	train loss:	1.17e-02,	accuracy:	96.38%
Epoch	161/200,	val loss:	1.24e-02,	accuracy:	91.36%
Epoch	162/200,	train loss:	1.17e-02,	accuracy:	96.34%
Epoch	162/200,	val loss:	1.24e-02,	accuracy:	91.22%
Epoch	163/200,	train loss:	1.17e-02,	accuracy:	96.44%
Epoch	163/200,	val loss:	1.24e-02,	accuracy:	91.22%
Epoch	164/200,	train loss:	1.17e-02,	accuracy:	96.43%
Epoch	164/200,	val loss:	1.24e-02,	accuracy:	91.24%
Epoch	165/200,	train loss:	1.17e-02,	accuracy:	96.54%
Epoch	165/200,	val loss:	1.24e-02,	accuracy:	91.50%
Epoch	166/200,	train loss:	1.17e-02,	accuracy:	96.48%
Epoch	166/200,	val loss:	1.24e-02,	accuracy:	91.30%
Epoch	167/200,	train loss:	1.17e-02,	accuracy:	96.35%
Epoch	167/200,	val loss:	1.24e-02,	accuracy:	91.30%
Epoch	168/200,	train loss:	1.17e-02,	accuracy:	96.54%
Epoch	168/200,	val loss:	1.24e-02,	accuracy:	91.22%
Epoch	169/200,	train loss:	1.17e-02,	accuracy:	96.50%
Epoch	169/200,	val loss:	1.24e-02,	accuracy:	91.44%
Epoch	170/200,	train loss:	1.17e-02,	accuracy:	96.52%
Epoch	170/200,	val loss:	1.24e-02,	accuracy:	91.30%
Epoch	171/200,	train loss:	1.17e-02,	accuracy:	96.44%
Epoch	171/200,	val loss:	1.24e-02,	accuracy:	91.46%
Epoch	172/200,	train loss:	1.17e-02,	accuracy:	96.60%
Epoch	172/200,	val loss:	1.24e-02,	accuracy:	91.28%
Epoch	173/200,	train loss:	1.17e-02,	accuracy:	96.47%
Epoch	173/200,	val loss:	1.24e-02,	accuracy:	91.28%
Epoch	174/200,	train loss:	1.17e		

Epoch 180/200, val loss: 1.24e-02, accuracy: 91.22%
Epoch 181/200, train loss: 1.17e-02, accuracy: 96.60%
Epoch 181/200, val loss: 1.24e-02, accuracy: 91.10%
Epoch 182/200, train loss: 1.17e-02, accuracy: 96.60%
Epoch 182/200, val loss: 1.24e-02, accuracy: 91.24%
Epoch 183/200, train loss: 1.17e-02, accuracy: 96.59%
Epoch 183/200, val loss: 1.24e-02, accuracy: 91.30%
Epoch 184/200, train loss: 1.17e-02, accuracy: 96.61%
Epoch 184/200, val loss: 1.24e-02, accuracy: 91.30%
Epoch 185/200, train loss: 1.17e-02, accuracy: 96.63%
Epoch 185/200, val loss: 1.24e-02, accuracy: 91.24%
Epoch 186/200, train loss: 1.17e-02, accuracy: 96.78%
Epoch 186/200, val loss: 1.24e-02, accuracy: 91.28%
Epoch 187/200, train loss: 1.17e-02, accuracy: 96.63%
Epoch 187/200, val loss: 1.24e-02, accuracy: 91.32%
Epoch 188/200, train loss: 1.17e-02, accuracy: 96.62%
Epoch 188/200, val loss: 1.24e-02, accuracy: 91.30%
Epoch 189/200, train loss: 1.17e-02, accuracy: 96.70%
Epoch 189/200, val loss: 1.24e-02, accuracy: 91.40%
Epoch 190/200, train loss: 1.17e-02, accuracy: 96.80%
Epoch 190/200, val loss: 1.24e-02, accuracy: 91.46%
Epoch 191/200, train loss: 1.17e-02, accuracy: 96.68%
Epoch 191/200, val loss: 1.24e-02, accuracy: 91.44%
Epoch 192/200, train loss: 1.17e-02, accuracy: 96.70%
Epoch 192/200, val loss: 1.24e-02, accuracy: 91.52%
Epoch 193/200, train loss: 1.17e-02, accuracy: 96.72%
Epoch 193/200, val loss: 1.24e-02, accuracy: 91.56%
Epoch 194/200, train loss: 1.17e-02, accuracy: 96.67%
Epoch 194/200, val loss: 1.24e-02, accuracy: 91.54%
Epoch 195/200, train loss: 1.17e-02, accuracy: 96.66%
Epoch 195/200, val loss: 1.24e-02, accuracy: 91.18%
Epoch 196/200, train loss: 1.17e-02, accuracy: 96.84%
Epoch 196/200, val loss: 1.24e-02, accuracy: 91.40%
Epoch 197/200, train loss: 1.17e-02, accuracy: 96.69%
Epoch 197/200, val loss: 1.24e-02, accuracy: 91.42%
Epoch 198/200, train loss: 1.17e-02, accuracy: 96.82%
Epoch 198/200, val loss: 1.24e-02, accuracy: 91.72%
Epoch 199/200, train loss: 1.17e-02, accuracy: 96.75%
Epoch 199/200, val loss: 1.24e-02, accuracy: 91.66%
Epoch 200/200, train loss: 1.17e-02, accuracy: 96.63%
Epoch 200/200, val loss: 1.24e-02, accuracy: 91.64%

Once the model is trained we run it on the test set to obtain our final accuracy. Note that we can only look at the test set once, everything else would lead to overfitting. So you *must* ignore the test set while developing your model!

In [22]:

```
test_loss, test_acc = run_epoch(resnet, None, dataloaders['test'], train=False)
print(f"Test loss: {test_loss:.1e}, accuracy: {test_acc * 100:.2f}%")
```

Test loss: 1.2e-02, accuracy: 90.95%

That's almost what was reported in the paper (92.49%) and we didn't even train on the full training set.

Optional task: Squeeze out all the juice!

Can you do even better? Have a look at [A Recipe for Training Neural Networks \(https://karpathy.github.io/2019/04/25/recipe/\)](https://karpathy.github.io/2019/04/25/recipe/) and some state-of-the-art architectures such as [EfficientNet architecture \(https://ai.googleblog.com/2019/05/efficientnet-improving-accuracy-and.html\)](https://ai.googleblog.com/2019/05/efficientnet-improving-accuracy-and.html). Play around with the possibilities PyTorch offers you and see how close you can get to the [state of the art on CIFAR-10 \(https://paperswithcode.com/sota/image-classification-on-cifar-10\)](https://paperswithcode.com/sota/image-classification-on-cifar-10).