# Machine Learning Techniques for Class Imbalances & Adversaries

Brendan Herger Brendan.Herger@capitalone.com







#### Overview


Sampling
Feature Engineering
Modeling

# Sampling

## Observation Weighting

- Effect cost function by weighting every row at train time
- Some weights become features at predict time
- Weights include
  - Uniform weight
  - Observation age (staleness)
  - Random down-sampling

# Observation Weighting



- (Synthetic Minority Over-sampling Technique)
- Goal: Reduce effect of class imbalance
- Majority class: Down sample, with some probability
- Minority class: Create 'synthetic' observations

- 1. Select minority point
- 2. Select neighbor
- 3. Create new point


- 1. Select minority point
- 2. Select neighbor
- 3. Create new point

- 1. Select minority point
- 2. Select neighbor
- 3. Create new point

1

2

- 1. Select minority point
- 2. Select neighbor
- 3. Create new point



# Observation Weighting SMOTE Sampling




#### Features

#### Outlier Detection

- Goal: Create outlier score
- Train learner to re-create input vector
  - PCA: Reduce dimensionality, increase dimensionality
  - Neural Network: Train auto-encoder
- Measure distance from output vector to input vector

#### Outlier Detection




Outlier score: |X'-X|

## Label Propagation

- Goal: Identify networks of bad-actors
- Create graph (Nodes = actors, Edges = association strength)
- Label nodes (e.g. good actor or bad actor)
- 'Relax' labels through graph

# Label Propagation




http://research.microsoft.com/en-us/people/nicolasl/efficient\_ssl.pdf http://www.amstat.org/publications/jse/v23n2/hardin.pdf

#### Low Rank Models

- Goal: Reduce dimensionality for dataset with many variables
- Reduce dimensionality with generalized PCA
- Model directly on components (latent factors)


#### Low Rank Models



## LDA Topic modeling

- Goal: Reduce dimensionality for variable with many levels
- Method stolen from Natural Language Processing
- Create bags of words w/ maximum separation
- Identify new text by which bag of words was most likely to create it

# LDA Topic modeling



Outlier Detection
Label Propagation
GLRM
LDA Topic Modeling



# Modeling

#### Grid search

- Goal: Find optimal hyper-parameters for given class of models
- Create every possible permutation of hyper-parameters, and compute models until heat death of universe


#### Neural Networks

- See other talks
- Too complicated to cover here

#### Ensemble Modeling

- Goal: Leverage a diverse set of algorithms
- Train multiple classes of algorithms (tree based, linear, neural network), possibly with multiple hyper-parameters, combine scores with meta model

#### Ensemble Modeling



# Genetic Algorithms & Artificial Immune Systems

- Goal: Score how similar a new authorization is to characteristic authorizations
- Train thresholds for likely / unlikely authorizations
- Compare incoming authorization to thresholds

Grid Search Neural Networks Ensemble models Genetic Algorithms



#### Thanks!

Slides:

https://github.com/bjherger/talks/blob/master/strata-ny-2016/Strata-2016-NY.pdf

Brendan.Herger@capitalone.com

