

RM2 Database table structure summary

Phase 1 – Core maintenance

Products

Product is the generic product information table. In a multisite, the product table data is the same at all branches. The primary key of this table is used as a foreign key in many other tables. Each product record can be associated to multiple barcodes and multiple supplier products.

Column	Description	Linked PK	Linked Table
prd_pk	Primary Key		
prd_description	Product description		
prd_size	Product level size description		
prd_supfk	Foreign key for the main supplier linked to the product header.	sup_pk	suppliers
prd_dptfk	Foreign key for the department associated to the product.	dpt_pk	departments
prd_subfk	Foreign key for the sub department associated to the product (optional).	sub_pk	subdepartments
prd_ssbfk	NOT USED		
prd_vatfk	Foreign key for the VAT tax rate associated to the product.	vat_pk	vatrates
prd_seafk	Foreign key for the seasonal date range associated to the product (optional). This is used in ordering procedures.	sea_pk	seasons
prd_prgfk	Foreign key of price group the product belongs to (optional). This is used for bulk price changes of associated products.	prg_pk	pricegroups
prd_manfk	Foreign key for manufacturer associated to product (optional). Reference field with no interactions.	man_pk	manufacturer
prd_owncode	Internal stock code used by the site. Normally only used in multisite warehouse locations.		
prd_stocked	Status flag. Lines not stocked are excluded from ordering procedures.		
prd_stockedfrom	Start date for ordering period.		
prd_stockedto	End date for ordering period.		
prd_weighed	Status flag. Weighed lines have cost prices and quantities calculated based on unit cost when sales are processed.		
prd_labelformat	Foreign key for label format.	laf_pk	labelformats
prd_promlabelformat	Foreign key for label format used for promotion prices.	laf_pk	labelformats
prd_openitem	Status flag. Open item lines trigger a prompt to manually enter a selling price at till.		
prd_labelbatch	Foreign of label batch for most recent label.	lba_pk	labelbatch
prd_reportcode	Text string used to tag products and used as a filter for reports, stock taking, and order procedures.		
prd_pricecheck	Status flag. Indicates if a product is part of a supplier specific scheme (redundant).		
prd_scaleitem	Status flag. Scale item lines trigger weighing on an integrated scale at tills.		
prd_muststock	Status flag. Forces product re-ordering in calculated ordering procedures.		
prd_corerange	Status flag. Indicates if a product is part of a supplier specific scheme (redundant).		
prd_discountable	Status flag. Indicates if a product can have additional discounts applied to it at till. The value of this field is inverted. 0 indicates a product can be discounted. 1 indicates a product can not be discounted.		
PRD_PLRFK	Foreign key for the ploff file processing rule associated to the product. This is used when processing price change downloads from linked suppliers.	plr_pk	ploffrules
PRD_DIFF	Value associated to a specific ploff rule (PLR_CODE D,G). Used when processing supplier price changes.		
prd_timestamp	Timestamp for when the product record was last updated.		

prd_lookup			
prd_efftk	Foreign key for EFT code associated to the product. This is used by fuel sites for fuel card transactions at tills.	eft_pk	eftcodes
prd_downloadseparate	Status flag. Used when processing supplier price changes to segregate items.		
prd_CheckShortDate	Status flag. Triggers a prompt on tills when the product is scanned.		
prd_flag1			
prd_flag2			
prd_flag3			
prd_flag4			
prd_flag5			
prd_flag6			
prd_flag7			
prd_flag8			
prd_flag9			
prd_flag10			
prd_maxtranqty	Max Qty per transaction		
prd_loyalty	Loyalty?		
prd_bonuspoints	Loyalty Points		
prd_notes	Custom Notes Field		
prd_deliScaled	is Item DeliScaled		
prd_pickingOrder	Warehouse function		
prd_deliDptNum			
prd_created	Product Created Date		
prd_deleted	Deleted date		
prd_manualVatRate			
Products_Cloud_Changed_On	Not Used		
Products_Cloud_Updated_On	Not Used		
Products_MasterMergeRequired	Not Used		
Products_TriggerSupress	Not Used		
Products_MasterMergedOn	Not Used		
prd_quickItem			
prd_diet	csv list		
prd_CoA	Country of Origin		
prd_Class	Class of Item (A/B/C)		
Prd_Custom1	Custom Field		
Prd_Custom2	Custom Field		
prd_Security	Security Question		

Barcodes

A barcode is unique to a specific product variant. Multiple barcodes can be grouped together as variants of the same product. The barcode table contains details specific to each barcode within a product.

Column	Description	Linked PK	Linked Table
bar_pk	Primary Key		
bar_prdfk	Foreign key for product barcode is associated with.	prd_pk	products
bar_barcode	Retail barcode		
bar_description	Barcode specific description		
bar_pm	Status flag. Barcode has price marked packaging.		

bar_default	Status flag, Default barcode used for product in display, reports, labels, etc.
bar_size	Barcode specific size description.
bar_pmprice	Price marked value for barcodes with the bar_pm flag enabled.
bar_priceembedded	IBARcode has embedded price value.
bar_labelbatch	???? Last Label Batch
bar_lastsold	Last date a sale for the barcode was processed.
bar_rrp	Recommended retail price for the barcode.
bar_deflabel	Default Number of Labels created when price is changed.
bar_lastchange	Date of last change.
bar_lastprice	Last Sell Price prior to current price.
bar_created	Date the barcode was added to the database.
bar_deleted	Flagged for deletion.
bar_timestamp	Timestamp for when the barcode record was last updated.
bar_qty	Number of units deducted from stock each time the barcode is sold.
bar_excludeProm	Exclude barcode from Promotions
bar_longPLU	Status flag. Long PLU ignores barcode validation checks.
bar_shelfLife	Shelf life is estimated number of days between receiving product and product expiration.
bar_cigPLU	PLU of Cigarette Gantry dispenser.
bar_lastPlofChange	Date when the barcode / price was last updated via the supplier plof download changes.
bar_ESLEnable	Status flag. Is the barcode enabled for electronic shelf edge labels.
Barcodes_Cloud_Changed_On	Not Used
Barcodes_Cloud_Updated_On	Not Used
Barcodes_MasterMergeRequired	Not Used
Barcodes_TriggerSupress	Not Used
Barcodes_MasterMergedOn	Not Used
bar_web	Status flag for web Store Upload
bar_minrrp	Value for minimum RRP value. Currently only used with Morrisons supplier.

SupplierProducts

The SupplierProducts table holds case variant specific information for each supplier. There can be multiple SupplierProduct records for the same supplier within the same product. There can be SupplierProduct records for multiple different suppliers linked to the same product.

Column	Description	Linked PK	Linked Table
spr_pk	Primary Key		
spr_supfk	Foreign key for associated supplier.	sup_pk	suppliers
spr_prdfk	Foreign key for associated product.	prd_pk	products
spr_stkcode	Stock Code use for ordering.		
spr_description	Description		
spr_case	Number of product units per case.		
spr_main	Status flag. Sets the SupplierProduct record as the default variant for the associated supplier.		
spr_inactive	Status flag. Restricts ordering of the variant.		
spr_labelbatch	Foreign key of most recent associated label batch.	lba_pk	labelbatch
spr_disfk	Foreign key for associated discount / surcharge.	dis_pk	discounts
spr_prevcost	Previous Cost price		

spr_lastchange	Date of last Change
spr_outerbarcode	Outer barcode used when scanning in deliveries.
spr_deleted	Flag to mark record for deletion.
spr_timestamp	Timestamp for when the record was last updated.
spr_rebate	Rebate value
spr_splitstckcode	Status flag. Split case size for ordering purposes.
spr_parentcode	Parent Code used to link product variants from specific suppliers.
spr_notes	Custom Notes field
spr_packSize	Pack Size
SupplierProducts_Cloud_Changed_On	Not Used
SupplierProducts_Cloud_Updated_On	Not Used
SupplierProducts_MasterMergeRequired	Not Used
SupplierProducts_TriggerSupress	Not Used
SupplierProducts_MasterMergedOn	Not Used

Prices

Prices are the retail price values associated to each barcode. They have an effective date for when they become live and the most recent effective date that has the released flag active is the current price on till.

Column	Description	Linked PK	Linked Table
prc_pk	Primary Key		
prc_barfk	Foreign key for associated barcode.	bar_pk	barcodes
prc_banfk	Foreign key for relevant price band (multisite functionality).	ban_pk	pricebands
prc_price	Retail selling price value		
prc_effective	Effective Date for when the price change goes live.		
prc_labelbatch	Foreign key for most recent associated label batch.	lba_pk	labelbatch
prc_released	Status flag. Price becomes active on till after it is released.		
prc_timestamp	Timestamp for when price record was last updated.		
prc_cashier	Cashier Name that created / updated.		
prc_preafk	Reason for change	prea_pk	pricechangereasons
prc_accepted	Status flag for price change approval. Mostly redundant multisite option.		
Prices_Cloud_Changed_On	not used		
Prices_Cloud_Updated_On	not used		
Prices_MasterMergeRequired	not used		
Prices_TriggerSupress	not used		
Prices_MasterMergedOn	not used		

Vprices

Vprices is a view and not stored as a table in the database. It returns to current base selling price for each barcode queried.

Column	Description	Linked PK	Linked Table
prc_pk	Prices PK	prc_pk	prices
prc_price	Retail selling price value.		
prc_barfk	Foreign key linking to barcode.	bar_pk	barcodes
prc_banfk	Foreign key linking to price band.	ban_pk	pricebands

CostPrices

Cost prices are the supplier cost charged to the retailer per case and are associated to a supplierproduct. There can be multiple historical costs for each SupplierProduct record. Cost prices have an effective date and the most recent effective date is considered the current cost price.

Column	Description	Linked PK	Linked Table
cst_pk	Primary Key		
cst_sprfk	Foreign key for associated supplierproduct	spr_pk	supplierproducts
cst_price	Cost price value		
cst_effective	Effective date		
cst_timestamp	Timestamp for when record was last updated.		
cst_cashier	Cashier name that added / updated.		
CostPrices_Cloud_Changed_On	not used		
CostPrices_Cloud_Updated_On	not used		
CostPrices_MasterMergeRequired	not used		
CostPrices_TriggerSupress	not used		
CostPrices_MasterMergedOn	not used		

VcostPrices

VcostPrices is a view and not stored as a table in the database. It returns to current base case cost price for each supplierproduct queried.

Column	Description	Linked PK	Linked Table
cst_pk	Costprices PK		
cst_price	Cost price value		
cst_sprfk	Foreign key linking to supplierproducts	spr_pk	supplierproducts

Departments

Departments are compulsory categories that products are sorted into to group them together. A product can only be associated to one department.

Column	Description	Linked PK	Linked Table
dpt_pk	Primary Key		
dpt_number	Department Number		
dpt_description	Department description / name		
dpt_vatfk	Foreign key linked to vat rate	vat_pk	vatrates
dpt_casminage	Cashier Minimum Age. Used at tills.		
dpt_cusminage	Customer Minimum Age. Used at tills.		
dpt_category1			
dpt_category2			
dpt_category3			
dpt_category4			
dpt_section	Section Number		
dpt_allowdisc	Status flag. Allow discount on open department sales at till.		
dpt_labelformat	Foreign key for default label format.	laf_pk	labelformats
dpt_promlabelformat	Foreign key used for promotional labels.	laf_pk	labelformats
dpt_timestamp	Timestamp for when record was last updated.		
dpt_PurchaseCategory	Redundant		
dpt_SalesCategory	Redundant		
dpt_plrfk	Foreign key linking to plof rules used when processing supplier price changes in bulk.	plr_pk	plofrules
dpt_effk	Foreign key linking to EFT codes. Used at till on fuel sites for specific tender type.	eft_pk	eftcodes

dpt_newsdept	Status flag. Defines if a department is set for news and magazines functionality.
dpt_fueldept	Status flag. Defines if department refers to a fuel grade.
dpt_default	Status flag. Defines if the department is the default department. Used when adding new lines without mapping.
dpt_labreq	Status flag. Defines if label are required for this department.
dpt_CheckShortDate	Status flag. Enables check date prompt at till.
dpt_halo	
dpt_lalo	
dpt_changeDefaultPMOnly	
dpt_excludeNineFives	Exclude 9/5 on Updates
dpt_deliScaled	Status flag. Defines if department is set for deli scale functionality.
dpt_sageTaxCode	Sage Tax Code
dpt_sageNominalCode	Sage Nominal Code
dpt_sageExtract	Status flag. Defines if department is included in Sage accounting extract.
dpt_staffDiscount	% value for staff discount. Used at tills.
dpt_sageExpenseCode	Sage Expense code
Departments_Cloud_Changed_On	Not Used
Departments_Cloud_Updated_On	Not Used
Departments_MasterMergeRequired	Not Used
Departments_TriggerSupress	Not Used
Departments_MasterMergedOn	Not Used

SubDepartments

SubDepartments are optional sub-categories within a department. A product can only be associated to one SubDepartment. A SubDepartment is linked to one department.

Column	Description	Linked PK	Linked Table
sub_pk	Primary Key		
sub_number	SubDepartment Number		
sub_description	SubDepartment Description / Name		
sub_dptfk	Foreign key for associated department	dpt_pk	departments
sub_vatfk	Foreign key linked to VAT rate	vat_pk	vatrates
sub_category1			
sub_category2			
sub_category3			
sub_category4			
sub_casminage	Cashier Minimum Age		
sub_cusminage	Customer Minimum Age		
sub_labelformat	Foreign key for label format	laf_pk	labelformat
sub_promlabelformat	Foreign key for promotional label format	laf_pk	labelformat
sub_timestamp	Timestamp for when record was last updated.		
sub_PurchaseCategory	Redundant		
sub_SalesCategory	Redundant		
sub_eftfk	Foreign key for Eft codes used at tills by fuel sites for specific transaction tenders.	eft_pk	eftcodes
sub_newsfreq	not used		
sub_newstime	not used		
sub_default	Status flag. Defines if the SubDepartment is the default		

	within the department.		
sub_CheckShortDate	Status flag. Enables check short date prompt on tills.		
sub_plrfk	Foreign key linking to ploff rules used when processing supplier price changes in bulk.	plr_pk	ploffrules
sub_excludeNineFives	excluded		
sub_staffDiscount	% value for staff discount. Used at tills.		
SubDepartments_Cloud_Changed_On	not Used		
SubDepartments_Cloud_Updated_On	not Used		
SubDepartments_MasterMergeRequired	not Used		
SubDepartments_TriggerSupress	not Used		
SubDepartments_MasterMergedOn	not Used		

BranchProducts

BranchProducts hold additional product level data that can vary between branches in a multi-site. A single site or multisite branch with have one BranchProducts record per Products record but a head office will have one BranchProducts record per branch for each Products record.

Column	Description	Linked PK	Linked Table
bxp_pk	Primary Key		
bxp_brnfk	Foreign key linking the branch	brn_pk	branches
bxp_prdfk	Foreign key linking to product	prd_pk	products
bxp_applies	Applies		
bxp_suspended	is suspended		
bxp_suspendfrom	Date From		
bxp_suspendto	date To		
bxp_banfk	Foreign key linking to price band. Used to set different retail selling price levels across multisite branches.	ban_pk	pricebands
bxp_instock	Current total units in stock of associated product.		
bxp_onorder	Current number of units in outstanding orders that meet configured period criteria.		
bxp_minstk	Minimum Stock quantity. Used in ordering procedures.		
bxp_maxstk	Maximum Stock quantity. Used in ordering procedures.		
bxp_avgcost	Average Cost per unit. Calculate from recent delivery history.		
bxp_facings	Facings in units. Used on labels.		
bxp_inactive	Status flag. An inactive product is restricted in ordering procedures.		
bxp_targetgp	target GP % Used for specific ploff rules when bulk processing supplier price changes.		
bxp_avgsaleswks	Number of Weeks for Average Sales calculation used in ordering procedures.		
bxp_timestamp	Timestamp for when record was last updated.		
bxp_Prom	is Prom?		
bxp_avgSales	Average sales value, calculated from recent sales history.		
bxp_stocked	Status flag. Not stocked lines are restricted in ordering procedures.		
BranchProducts_Cloud_Changed_On	Not Used		
BranchProducts_Cloud_Updated_On	Not Used		
BranchProducts_MasterMergeRequired	Not Used		
BranchProducts_TriggerSupress	Not Used		
BranchProducts_MasterMergedOn	Not Used		

Suppliers

Suppliers are third-parties that provide stock for the retail location. Some suppliers have integrated comms links with RM2.

Column	Description	Linked PK	Linked Table
sup_pk	Primary key		
sup_code	Short supplier reference code used for display.		
sup_name	Full supplier name		
sup_address	Contact details		
sup_address2	Contact details		
sup_address3	Contact details		
sup_postcode	Contact details		
sup_telephone	Contact details		
sup_fax	Contact details		
sup_contact	Contact details		
sup_email	Contact details		
sup_mobile	Contact details		
sup_dasfk	Foreign key to dataschemes for suppliers with integrated comms link.	das_pk	dataschemes
sup_sequence	Supplier list display sequence for handheld terminals (Picco, RM2GO).		
sup_timestamp	timestamp for when record was last updated.		
sup_ordersequece	Display sequence for order lines during order procedures.		
sup_extractsalesdata	Status flag. Enable sales data extract for supplier.		
sup_news	Status flag. Defines if supplier uses news functionality.		
sup_fuel	Status flag. Defines if supplier uses fuel functionality.		
sup_processedi			
sup_sort			
sup_notes	Notes		
sup_WebScan	Status flag. Enables Booker web scan functionality.		
sup_mainelectronic	Status flag. Defines if the supplier is the Main Electronic Supplier used for processing supplier updates.		
sup_warehouse	Status flag. Defines if the supplier is an integrated warehouse in a multisite.		
sup_excludeFromWarehouse	Status flag. Excludes supplier from warehouse supplier grouping in a warehouse enabled multisite.		
sup_hPosUID			
Suppliers_Cloud_Changed_On	not Used		
Suppliers_Cloud_Updated_On	not Used		
Suppliers_MasterMergeRequired	not Used		
Suppliers_TriggerSupress	not Used		
Suppliers_MasterMergedOn	not Used		

PromotionCosts

PromotionCosts contains promotional case cost prices that override the base case cost for the duration of the dates specified.

Column	Description	Linked PK	Linked Table
pcs_pk	primary key		
pcs_pevfk	Foreign key linking to promotion events.	pev_pk	promotionevents
pcs_sprfk	Foreign key linking to supplierproducts	spr_pk	supplierproducts
pcs_price	Promotional case cost price value		

pcs_effective	Start Date of promotional cost price
pcs_expires	End Date of promotional cost price
pcs_promcd	Promotional reference code
pcs_timestamp	timestamp for when record was last updated.
pcs_rebate	Rebate value
pcs_allocated	Flag to denote if the promotion has stock allocation.
PromotionCosts_Cloud_Changed_On	not used
PromotionCosts_Cloud_Updated_On	not used
PromotionCosts_MasterMergeRequired	not used
PromotionCosts_TriggerSupress	not used
PromotionCosts_MasterMergedOn	not used
pcs_ltycost	Loyalty scheme cost price

PromotionPrices

PromotionPrices contains promotional retail selling prices that override the base selling price for the duration of the specified dates.

Column	Description	Linked PK	Linked Table
prm_pk	primary key		
prm_prdfk	Foreign key linking to product	prd_pk	products
prm_pevfk	Foreign key linking to promotion event	pev_pk	promotionevents
prm_schfk	Foreign ket linking to promotion schedule	sch_pk	schedules
prm_price	Promotional retail selling price		
prm_effective	Effective start date for promotional selling price		
prm_expires	Expiry / end date for promotional selling price		
prm_promcd	Promotional reference code		
prm_labelbatch	Foreign key linking to label batch that contains label for the promotional price.	lba_pk	labelbatch
prm_released	Status flag. Released prices are active on till within their effective and expiry dates.		
prm_extendby	Value showing if the promotion has been extended by a number of days.		
prm_extenddate	Date showing extended end of promotional period.		
prm_timestamp	timestamp for when record was last updated.		
prm_comm			
prm_unitssold	Number of units sold at promotional price		
prm_solduntil	Maximum number of units to sell at promotional price		
prm_maxtranqty	Max number of units at promotional price per transaction.		
prm_effPrint			
prm_expPrint			
PromotionPrices_Cloud_Changed_On	not used		
PromotionPrices_Cloud_Updated_On	not used		
PromotionPrices_MasterMergeRequired	not used		
PromotionPrices_TriggerSupress	not used		
PromotionPrices_MasterMergedOn	not used		
prm_ltyprc	Loyalty scheme price		
prm_web	Enable web Store Upload		

PromotionCostPrice

PromotionCostPrice is a table that links together the other pomotional table records.

Column	Description	Linked PK	Linked Table
pcp_pk	primary key		
pcp_prmfk	Foreign key to promotional selling price	prm_pk	promotionprices
pcp_pcsfk	Foreign key to promotional cost price	pcs_pk	promotioncosts
pcp_timestamp	timestamp for when the record was last updated		
PromotionCostPrice_Cloud_Changed_On	not used		
PromotionCostPrice_Cloud_Updated_On	not used		
PromotionCostPrice_MasterMergeRequired	not used		
PromotionCostPrice_TriggerSupress	not used		
PromotionCostPrice_MasterMergedOn	not used		

BranchPromotions

Branch promotions is used in multistes to define if a promotion applies to a specific branch.

Column	Description	Linked PK	Linked Table
bpr_pk	primary key		
bpr_pcpfk	Foreign key linking to promotioncostprice	pcp_pk	promotioncostprice
bpr_brmfk	Foreign key linking to branch	brn_pk	branches
bpr_applies	Flag defining if the promotion applies to this branch		
bpr_timestamp	timestamp for when record was last updated		
BranchPromotions_Cloud_Changed_On	not used		
BranchPromotions_Cloud_Updated_On	not used		
BranchPromotions_MasterMergeRequired	not used		
BranchPromotions_TriggerSupress	not used		
BranchPromotions_MasterMergedOn	not used		

MMHeaders

MMHeaders contains the deal information for multibuy promotions. Each Mmheaders record can have multiple products associated to it in MMDetails.

Column	Description	Linked PK	Linked Table
mmh_pk	Primary Key		
mmh_pevfk	Foreign key for promotional event	pev_pk	promotionevents
mmh_schfk	Foreign key for promotional schedule	sch_pk	schedules
mmh_description	Deal description		
mmh_tilldesc	Short deal description used at till		
mmh_type	Deal type (M = Multibuy / L = Linked)		
mmh_tableno	Table Number		
mmh_trigger1	trigger quantity 1		
mmh_trigger2	trigger quantity 2		
mmh_trigger3	trigger quantity 3		
mmh_trigger4	trigger quantity 4		
mmh_startdate	Deal start date		
mmh_enddate	Deal end date		

mmh_discount	Discount Value, fixed amount		
mmh_package	package Price, fixed amount		
mmh_discperc	Total lines % discount		
mmh_cheapestfree	Get cheapest product free		
mmh_reportno	report number		
mmh_claimable	Flag for if the dealis claimable for reporting.		
mmh_rebate	rebate value per deal triggered on tills		
mmh_dealsold	Number of deals sold		
mmh_qtysoldindeals	Quantity of units sold in deals		
mmh_extendby	Number of days to extend		
mmh_extenddate	date to extend to		
mmh_timestamp	timestamp for when record was last updated		
mmh_SuspendStart	suspended		
mmh_SuspendEnd	suspended stop		
mmh_ontillstocksold	active until amount sold		
mmh_maxdealstran	max deals per transaction		
mmh_change	has changed?		
mmh_laffk	Foreign key of multibuy label format	laf_pk	labelformats
MMHeaders_Cloud_Changed_On	not used		
MMHeaders_Cloud_Updated_On	not used		
MMHeaders_MasterMergeRequired	not used		
MMHeaders_TriggerSupress	not used		
MMHeaders_MasterMergedOn	not used		
mmh_trigger5	trigger quantity 5		
mmh_trigger6	trigger quantity 6		
mmh_loyalty	Is part of a loyalty scheme		
mmh_loyaltydesc	Loyalty description		
mmh_web	Upload to Webstore		

MMDetails

MMDetails contains keys for the barcodes associated to the multibuy deal headers.

Column	Description	Linked PK	Linked Table
mmd_pk	primary Key		
mmd_mmhfk	Foreign key for multibuy header	mmh_pk	mmheaders
mmd_barfk	Foreign key for barcode	bar_pk	barcodes
mmd_triggerno	Trigger Number associated to (1 – 6 from MMHeaders)		
mmd_repprice	Unit price used for reporting		
mmd_timestamp	Timestamp for when record was last updated		
mmd_qtysold	Number of units sold		
MMDetails_Cloud_Changed_On	not used		
MMDetails_Cloud_Updated_On	not used		
MMDetails_MasterMergeRequired	not used		
MMDetails_TriggerSupress	not used		
MMDetails_MasterMergedOn	not used		

MMBranchHeaders

MMBranchheaders contains some deal specific tracking and is used in multisites to control which deals are available on which branches.

Column	Description	Linked PK	Linked Table
mmb_pk	Primary key		
mmb_mmhfk	Foreign key to multibuy header	mmh_pk	mmheaders
mmb_brnfk	Foreign key to branch	brn_pk	branches
mmb_qtysold	Number of units sold in deal		
mmb_deals	Number of deals triggered		
mmb_stdvalue	standard value of products		
mmb_discvalue	discounted value of products		
mmb_timestamp	timestamp for when record was last updated		
mmb_applies	Glag that defines if deal is applied at branch		
MMBranchHeaders_Cloud_Changed_On	not used		
MMBranchHeaders_Cloud_Updated_On	not used		
MMBranchHeaders_MasterMergeReq uired	not used		
MMBranchHeaders_TriggerSupress	not used		
MMBranchHeaders_MasterMergedOn	not used		

ProductSales

Product sales contains a breakdown of units of products sold per date.

Column	Description	Linked PK	Linked Table
psa_pk	Primary Key		
psa_date	Date of sale		
psa_brnfk	Foreign key to branch	brn_pk	branches
psa_prdfk	Foreign key to product	prd_pk	products
psa_dptfk	Foreign key to department	dpt_pk	departments
psa_barfk	Foreign key to barcode	bar_pk	barcodes
psa_quantity	Quantity of units sold		
psa_value	Retail price value of units sold		
psa_cost	Cost value of units sold		
psa_weekno	week number		
psa_timestamp	Timestamp for when record was last updated		
psa_vatrate	Vatrate % value at time of sale		
psa_asafk	Foreign key linking to account sales for reporting.	asa_pk	accountsales
ProductSales_Cloud_Changed_On	not Used		
ProductSales_Cloud_Updated_On	not Used		
ProductSales_MasterMergeRequired	not Used		
ProductSales_TriggerSupress	not Used		
ProductSales_MasterMergedOn	not Used		

PurchaseOrders

PurchaseOrders contains the header records for orders and deliveries created in RM2. Each header can have multiple PurchaseOrderLines linked to it.

Column	Description	Linked PK	Linked Table
ord_pk	Primary key		
ord_number	Order number		
ord_supfk	Foreign key linking to supplier	sup_pk	suppliers

ord_date	Date order created		
ord_deliverydate	Estimated or actual delivery date		
ord_status	Current status number of order		
ord_ref	Text field for reference on order type		
ord_totallines	Total number of lines associated to order		
ord_totalcases	Total number of cases associated to order		
ord_totalcost	Total cost of cases associated to order		
ord_totalsell	Total retail value of cases associated to order		
ord_presell	Flag to define if order is a presell		
ord_preselldate	Presell order date		
ord_notes1			
ord_notes2			
ord_notes3			
ord_suppref	Supplier reference code		
ord_picco	Order picco use status		
ord_edidata	Order EDI download data		
ord_timestamp	Timestamp for when record was last updated		
ord_bookintype	Delivery type		
ord_edl	Flag indicating if EDI data has been processed and attached to the order.		
ord_discrepancy	Flag indicating if a discrepancy note report has been created		
ord_CreatedByEdi	Flag indicating if the order was created from a downloaded EDI file		
ord_invoice	Invoice number from supplier		
ord_dispatch	Dispatch number from supplier		
ord_OrderName			
ord_daily			
ord_brnfk	Foreign key linking to branch	brn_pk	branches
ord_openOnPC			
ord_transmittedDate	Date order was transmitted to supplier		
ord_surcharge	Surcharge value		
PurchaseOrders_Cloud_Changed_On	Not used		
PurchaseOrders_Cloud_Updated_On	Not used		
PurchaseOrders_MasterMergeRequired	Not used		
PurchaseOrders_TriggerSupress	Not used		
PurchaseOrders_MasterMergedOn	Not used		

PurchaseOrderLines

PurchaseOrderLines are the records linking to specific products variants that have been added into a purchase order or delivery.

Column	Description	Linked PK	Linked Table
orl_pk	Primary key		
orl_ordfk	Foreign key linking to order header	ord_pk	purchaseorders
orl_sprfk	Foreign key linking to supplierproduct	spr_pk	supplierproducts
orl_barfk	Foreign key linking to barcode	bar_pk	barcodes
orl_qtyord	Number of cases to order		
orl_qtydel	Number of cases delivered		
orl_price	Retail selling price of barcode		

orl_cost	Case cost price of supplierproduct including discounts / surcharges		
orl_costdel			
orl_freestk	Number of units of free stock		
orl_timestamp	Timestamp of when record was last updated		
ORL_EDIDEL	Flag indicating line is from and EDI delivery download		
orl_scanned	Flag indicating if line has been scanned on handheld terminal delivery		
orl_avgqty			
orl_dayadj			
orl_notes			
orl_scannedQty	Number of cases scanned during handheld terminal delivery		
orl_bulkOrdered			
orl_instock	Number of units currently in stock		
orl_priceDel			
orl_onOrder	Number of units currently in outstanding orders		
orl_case	Case size		
orl_prdfk	Foreign key linking to product	prd_pk	products
orl_grossCost	Case cost of supplierproduct excluding discounts / surcharges		
orl_suggested	Suggested order quantity (legacy)		
orl_leaflet			
orl_Discrepancy			
PurchaseOrderlines_Cloud_Changed_On	Not used		
PurchaseOrderlines_Cloud_Updated_On	Not used		
PurchaseOrderlines_MasterMergeRequired	Not used		
PurchaseOrderlines_TriggerSupress	Not used		
PurchaseOrderlines_MasterMergedOn	Not used		
orl_qtyDifference			

Branches

Branches contains site specific shop information. A single site or branch will have one entry. A multisite head office will have one entry per branch.

Column	Description	Linked PK	Linked Table
brn_pk	Primary Key		
brn_number	Branch number		
brn_name	Contact details		
brn_add1	Contact details		
brn_add2	Contact details		
brn_add3	Contact details		
brn_postcode	Contact details		
brn_telephone	Contact details		
brn_type	Brnch type		
brn_Active	Branch active status		
brn_commspath	Comms path		
brn_timestamp	Timestamp for when record was last updated.		

brn_lastCommunicated	When branch last communicated with head office
brn_warehouse	Flag indicating if the branch is a multisite warehouse
brn_vatNumber	Vat Number
brn_regnumber	
brn_email	Contact details
brn_website	Contact details
brn_fax	Contact details
brn_jhStoreNumber	Not Used
brn_created	Created date
Brn_MD	Managing Director
brn_mobile	Mobile phone number
brn_bacsSort	bacsSort code
brn_bacsAcc	bacs account code
Branches_Cloud_Changed_On	not used
Branches_Cloud_Updated_On	not used
Branches_MasterMergeRequired	not used
Branches_TriggerSupress	not used
Branches_MasterMergedOn	not used
brn_Consl	
brn_logo	Logo
brn_RM2GO	Flag indicating if site is enabled for RM2GO handheld terminal.

Pricebands

Pricebands determine which prices record is used for a barcode. This functionality is only used in multisites.

Column	Description	Linked PK	Linked Table
ban_pk	Primary Key		
ban_description	Description		
ban_priority	priority		
ban_timestamp	timestamp for when record was last updated		
PriceBands_Cloud_Changed_On	not used		
PriceBands_Cloud_Updated_On	not used		
PriceBands_MasterMergeRequired	not used		
PriceBands_TriggerSupress	not used		
PriceBands_MasterMergedOn	not used		

Vatrates

Vatrates are the VAT % levels of sales tax applied to products. This is used in margin and profit calculations.

Column	Description	Linked PK	Linked Table
vat_pk	Primary Key		
vat_code	Vat Code		
vat_description	Description		
vat_rate	Rate as Percentage		
VAT_TIMESTAMP	timestamp for when record was last updated		
vat_newrate	New Rate		
vat_changedate	Date to be changed		
vat_oldrate	Old Rate		

vat_created	Date Created
Vatrates_Cloud_Changed_On	not used
Vatrates_Cloud_Updated_On	not used
Vatrates_MasterMergeRequired	not used
Vatrates_TriggerSupress	not used
Vatrates_MasterMergedOn	not used

PromotionEvents

Promotion events are defined periods when promotional offers will be active. Single price product promotions must be connected to a promotional event. Promotional events are optional for multibuy deals.

Column	Description	Linked PK	Linked Table
pev_pk	Primary Key		
pev_description	Event description		
pev_promcd	Reference code		
pev_sellstart	Sell start date		
pev_sellend	Sell End Date		
pev_coststart	Cost Start Date		
pev_costend	cost End Date		
pev_timestamp	timestamp for when record was last updated		
pev_dasfk	Foreign key for data scheme of suppliers with integrated comms link.	das_pk	dataschemes
pev_period	Period number		
pev_year	Year		
pev_eventConfirmed	Flag indicating if a user has confirmed the promotional period details.		
PromotionEvents_Cloud_Changed_On	not used		
PromotionEvents_Cloud_Updated_On	not used		
PromotionEvents_MasterMergeRequired	not used		
PromotionEvents_TriggerSupress	not used		
PromotionEvents_MasterMergedOn	not used		