Assinment_\	MCQ
Choose the correct Answer;	
1. The format is usually used to store data. a) BCD b) Decimal c) Hexadecimal d) Octal Answer:	
Y. The ^-bit encoding format used to store data in a computer isa) ASCII b) EBCDIC c) ANCI d) USCII Answer:	
r. A source program is usually in a) Assembly language b) Machine level language c) High-level language d) Natural language Answer:	
 ½. Which memory device is generally made of semiconductors? a) RAM b) Hard-disk c) Floppy disk d) Cd disk Answer: 	
o. The small extremely fast, RAM's are called as a) Cache b) Heaps c) Accumulators d) Stacks Answer:	
T. The ALU makes use of to store the intermediate results. a) Accumulators b) Registers c) Heap d) Stack Answer:	
 Y. The control unit controls other units by generating	
 ^ are numbers and encoded characters, generally used as o a) Input b) Data 	perands.

d) Stored Values Answer:
 q. The Input devices can send information to the processor. a) When the SIN status flag is set b) When the data arrives regardless of the SIN flag c) Neither of the cases d) Either of the cases Answer:
 bus structure is usually used to connect I/O devices. Single bus Multiple bus Star bus Rambus Answer:
The I/O interface required to connect the I/O device to the bus consists of Address decoder and registers Control circuits Only Control circuits Answer:
a) Heaps b) Higher capacity RAM's c) SDRAM's d) Cache's Answer:
17 is generally used to increase the apparent size of physical memory. a) Secondary memory b) Virtual memory c) Hard-disk d) Disks Answer:
a) Memory Format Caches b) Memory Function Complete c) Memory Find Command d) Mass Format Command Answer: 10. The time delay between two successive initiations of memory operation
a) Memory access time b) Memory search time c) Memory cycle time d) Instruction delay Answer:

c) Information