

BC

E

		Hazardous CLP content		Rev/ Revision Note		Created by		Checked by		Approved by		Date	
Directive	2014/68/EU	Pipe Class	/I19440-VE16H1A-R00	0		J. Lakka		T. Saarinen		M. Kankkunen		5/5/2026	
Design press. (min)	-1bar	PED Category	I	Site Tervasaari, Valkeakoski		Equipment Type Höyry- ja lauhdejärjestelmä						Equipment ID	
Design temp. (min)	-	Media		Project Key TERPM5_N5265A Ter PM 5 Safe Future		Project Number N5265A						Work	
Max. allow. press. (PS)	-	Standard		Projection Method ISO 2553		Welding Symbols ISO 2553		General Tolerances ISO 13 920-BF ISO 2768-mK-E ISO 2768-mK-E ISO 2768-mK-E		Scale -		Size A1 Weight -	
Operating press.	5.7bar	P&ID	RAU8F00303	 This document is the exclusive intellectual property of Valmet Corporation and/or its subsidiaries (collectively and individually "Valmet") and is furnished solely for executing and maintaining the specific project. Re-use of the document for any other project or purpose is prohibited. The document or the information shall not be reproduced, copied or disclosed to any third party without the prior written consent of Valmet. By accessing this document, you accept these terms of use.									
Operating temp.	164degC	Design press.	6bar										
PED Module	-	Design temp.	220degC	Title 50194-VLA-50-16H1A									
PED Group	-	Test press.	-										
Wind loads	-	Pipe list doc. ID	RAUAF04300	Status CERTIFIED						Document ID			
External loads	-	Valve list doc. ID	RAUAF04301	Security Classification Internal						Sheet 1 / 1 Revision 0			

Welding list see doc	-
----------------------	---