


PIPE SPOOLS

		Hazardous CLP content		Legal protection is to be decided by customer.					
Directive	2014/68/EU	Pipe Class	/119440-VE16C1C-R00	Rev/ Revision Note		Created by	Checked by	Approved by	Date
Design press. (min)	-1bar	PED Category	SEP	0		J. Lakka	T. Saarinen	M. Kankkunen	5/5/2026
Design temp. (min)	-	Media		Site Tervasaari, Valkeakoski		Equipment Type Höyry- ja lauhdejärjestelmä		Project Number NS265A	Equipment ID
Max. allow. press. (PS)	-	Standard		Project Key TERPM5_NS265A		Project Name Ter PM 5 Safe Future			Work
Operating press.	5.9bar	P&ID	RAUF00303	Projection Method  ISO 2553		General Tolerances ISO 2768-mK-E ISO 13 920-BF ISO 2768-mK-E ISO 2768-mK-E		Scale -	Size A1
Operating temp	181degC	Design press.	6bar	 This document is the exclusive intellectual property of Valmet Corporation and/or its subsidiaries (collectively and individually "Valmet") and is furnished solely for executing and maintaining the specific project. Re-use of the document for any other project or purpose is prohibited. The document or the information shall not be reproduced, copied or disclosed to any third party without the prior written consent of Valmet. By accessing this document, you accept these terms of use.					
PED Module	-	Design temp.	220degC	Title 50174-HMP-80-16C1B					
PED Group	-	Test press.	-	Status CERTIFIED					
Wind loads	-	Pipe list doc. ID	RAUAF04300	Document ID					
External loads	-	Valve list doc. ID	RAUAF04301	Security Classification Internal					
				Sheet 1 / 1					
				Revision 0					