



NO	PART DESCRIPTION	DN (MM)	PIPE SPEC	QUANTITY
1	HOSE	50	HOSES	300MM
2	Tube - 60.3 x 2.00 - EN 10217-7 - 1.4307-TC1	50	119440-VE16H1A-R00	2080MM
3	Tube - 60.3 x 2.90 - EN 10216-2 - P235GH-TC1	50	119440-VE16C1C-R00	325MM
4	Elbow - w - EN 10253-4 - type A - Table A.1 - model 3D - 90deg - 60.3 x 2.00 - 1.4307	50	119440-VE16H1A-R00	4
5	HOSE PROVIDED BY KADANT	50	HOSES	1
6	HOSE	50	HOSES	1
7	Loose flange - EN 1092-1 - type 02 - - 60.3/DN50 - PN40 - P265GH HDG	50	119440-VE16H1A-R00	4
8	Weldring neck - EN 1092-1 - type 35 - 60.3/DN50 - PN16 - 1.4307	50	119440-VE16H1A-R00	4
9	Dummy wn flange - DIN 2633 50x60.3 PN16 Delivered with component	50	DUMMY-FLANGES	2
10	Weld-neck flange - EN 1092-1 - type 11 - B1 - 60.3/DN50 - PN40 - P250GH	50	119440-VE16C1C-R00	1
NO	PART DESCRIPTION	DN (MM)	PIPE SPEC	QUANTITY
11	Gasket - EN 1514-1 - type IBC - OD60.3/DN50 - 1.5mm Thk - PN40 Fiber	50	119440-VE16H1A-R00	6
12	80 mm Bolt EN ISO 4014 25CrMo4, EN 10269, mat cert. 3.1, HDG	16		8
13	75 mm Bolt EN ISO 4014 25CrMo4, EN 10269, mat cert. 3.1, HDG	16		8
14	65 mm Bolt EN ISO 4014 25CrMo4, EN 10269, mat cert. 3.1, HDG	16		4
15	Hexagon nut EN ISO 4032 25CrMo4, EN 10269, mat cert. 3.1, HDG	16		20
16	Washer EN ISO 7089 Grade A - S235JR EN10025-2 - HDG	16		40
17	KPK BASIC BALL VALVE FLANGED PN16 RF W/ HAND LEVER 5-0346	50	KBE/VALV01	1
18	Orifice plate, bw ORIFICE 21mm PROVIDED BY KADANT	50	DATACOMP-TEST	1
	<u>SUPPORTS</u>			
19	SLIDE SUPPORT PSK 7303 TYPE 1, LOW See supportlist	50	VOFSUPP-PRIM-PSK-AT TA	1

PIPE SPOOLS

[1] [2] [3] [4]

NOTE:

Site weldings to be added by contractor.

Buildings construction and equipment erection tolerances

to be checked by contractor

Pipe levels and dimensions are according to pipe center line

Isometric drawings for sizes DN 15-25 are approximate.
Piping contractor is responsible for final routing and supporting

Welding factor	Acc. to pipe class
Efficiency of long. weld	Acc. to pipe class
NDT circ. weld %	-
NDT long. weld %	-
Welding list see doc.	-

		Hazardous CLP content		Degree of prehabilitation to be decided by contractor.									
				Rev/ Revision Note		Created by		Checked by		Approved by		Date	
Directive	2014/68/EU	Pipe Class	/119440-VE16H1A-R00	0		J. Lakka		T. Saarinen		M. Kankkunen		5/5/2026	
Design press. (min)	-1bar	PED Category	I	Site Tervasaari, Valkeakoski		Equipment Type Höyry- ja lauhdejärjestelmä						Equipment ID	
Design temp. (min)	-	Media		Project Key TERPMS_NS265A		Project Name Ter PM S Saito Future				Project Number NS265A		Work	
Max. allow. press. (PS)	-	Standard		Projection Method ☐ ⊕		Welding Symbols ISO 5553		General Tolerances ISO 13 920-BF		ISO 2768-mK-E ISO 2768-mK-E ISO 2768-mK-E		Scale -	
Operating press.	5.7bar	P&ID	RAU8F00303	 This document is the exclusive intellectual property of Valmet Corporation and/or its subsidiaries (collectively and individually "Valmet") and is furnished solely for executing and maintaining the specific project. Re-use of the document for any other project or purpose is prohibited. The document or the information shall not be reproduced, copied or disclosed to any third party without the prior written consent of Valmet. By accessing this document, you accept these terms of use.									
Operating temp.	164degC	Design press	6bar	Title		50200-VLA-50-16H1A							
PED Module	-	Design temp.	220degC	Status		CERTIFIED							
PED Group	-	Test press.	-	Document ID									
Wind loads	-	Pipe list doc. ID	RAUAF04300	Security Classification		Internal							
External loads	-	Valve list doc. ID	RAUAF04301	Revision		0							