



|   |                                                                                        |
|---|----------------------------------------------------------------------------------------|
| 1 | Equal Tee - 273 x 6.00 - EN 10217-7 - 1.4307-Tc1                                       |
| 2 | Tube tee - w - EN 10253-4 - type A - Table A.2 - 273 x 6.00 - 1.4307                   |
| 3 | Reduced tee - w - EN 10253-4 - type A - Table A.2 - 273 x 5.00 / 168.3 x 4.00 - 1.4307 |
| 4 | Reduced tee - w - EN 10253-4 - type A - Table A.2 - 273 x 5.00 / 139.7 x 4.00 - 1.4307 |
| 5 | Set on Tee with Bran made of EN 10217-7 Tube 114.3 x 6.00 H=100 - 1.4307-Tc1           |
| 6 | Blind flange - EN 10921 - type 05 - A - 273/DN250 - PN16 P265GH HDG                    |
| 7 | Loose flange - EN 10921 - type 02 - 273/DN250 - PN16 - P265GH HDG                      |
| 8 | Weldring neck - EN 10921 - type 35 - 273/DN250 - PN16 - 1.4307                         |

|    |                                                                      |     |                    |
|----|----------------------------------------------------------------------|-----|--------------------|
| 9  | Gasket - EN 1514-1 - type IBC - OD273/DN250 - 1.5mm Thk - PN16 Fiber | 250 | 119440-VE16H1A-R00 |
| 10 | 110 mm Bolt EN ISO 4014 25CrMo4, EN 10269, mat cert. 3.1, HDG        | 24  |                    |
| 11 | Hexagon nut EN ISO 4032 25CrMo4, EN 10269, mat cert. 3.1, HDG        | 24  |                    |
| 12 | Washer EN ISO 7089 Grade A - S235JR EN10025-2 - HDG                  | 24  |                    |

13 Lisega Spring Support, drwg no S-0049\_1 SPRING SUPPORT TYPE 29 PLACEMENT IN THE MIDDLE  
OF T-PIECE

[1]



| Insulation table (lengths according SSG 7645 Alt2) |           |        |                       |
|----------------------------------------------------|-----------|--------|-----------------------|
| Bore                                               | Thickness | Length | Insulation spec name  |
| 250                                                | 30mm      | 3103mm | /PSK3704-6a-Prot-alum |

|                          |                    |
|--------------------------|--------------------|
| Welding factor           | Acc. to pipe class |
| Efficiency of long. weld | Acc. to pipe class |
| NDT circ. weld %         | -                  |
| NDT long weld %          | -                  |
| Welding list see doc.    | -                  |

Valmet 

This document is the exclusive intellectual property of Valmet Corporation and/or its subsidiaries (collectively and individually "Valmet") and is furnished solely for executing and maintaining the specific project. Re-use of the document for any other project or purpose is prohibited. The document or the information shall not be reproduced, copied or disclosed to any third party without the prior written consent of Valmet. By accessing this document, you accept these terms of use.