



Y	
---	--

Y	

GUIDED SLIDE PSK 7303 TYPE 2, LOW See supportlist

[1] [2] [3]



1		

		Hazardous CLP content			
Directive	2014/68/EU	Pipe Class	/I19440-VE16C1C-R00	Rev Revision Note	
Design press. (min)	-1bar	PED Category	I / SEP	0	
Design temp. (min)	-	Media		Site Tervasaari, Valkeakoski	Equipment Type Hyöty- ja lauhdejärjestelmä
Max. allow. press. (PS)	-	Standard		Project Key TERPM5_N5265A	Project Name Ter PM 5 Safe Future
Operating press.	3.5bar	P&ID	RAUF00303	Projection Method 	General Tolerances ISO 13 920-BF ISO 2768-mK-E ISO 2768-mK-E ISO 2768-mK-E
Operating temp.	156degC	Design press.	6bar	 This document is the exclusive intellectual property of Valmet Corporation and/or its subsidiaries collectively and individually "Valmet") and is furnished solely for executing and maintaining the specific project. Re-use of the document for any other project or purpose is prohibited. The document or the information shall not be reproduced, copied or disclosed to any third party without the prior written consent of Valmet. By accessing this document, you accept these terms of use.	
PED Module	-	Design temp.	220degC	Title	50237-VLA-25-16C1B
PED Group	-	Test press.	-	Status CERTIFIED	Document ID
Wind loads	-	Pipe list doc. ID	RAUAF04300	Security Classification Internal	
External loads	-	Valve list doc. ID	RAUAF04301		