

Lab 1:

```
1  -- lab 1: rbac
2
3  create role cashier_role;
4
5  create user mike with password 'mike123';
6  create user jon with password 'jon123';
7
8  grant cashier_role to mike;
9  grant cashier_role to jon;
10
11 grant select on film, staff to cashier_role;
12 grant select, insert on payment to cashier_role;
13
14
15 grant usage, select
16 on sequence payment_payment_id_seq
17 to cashier_role;
```

Data Output Messages Notifications

GRANT

Query returned successfully in 147 msec.

Lab 2:

```
18
19 -- lab 2: rls
20
21 alter table payment
22 enable row level security;
23
24 create policy isolate_cashier_payments
25 on payment
26 for select
27 to cashier_role
28 using (
29     staff_id = (
30         select staff_id
31         from staff
32         where username = current_user
33     )
34 );
```

Data Output Messages Notifications

CREATE POLICY

Query returned successfully in 87 msec.

Check with mike

```

91 set role mike;
92
93 select current_user as tai_khoan,
94        count(*) as so_payment,
95        min(staff_id) as staff_id_nho_nhat,
96        max(staff_id) as staff_id_lon_nhat
97 from payment;
98
99 reset role;

```

Data Output Messages Notifications

	tai_khoan name	so_payment bigint	staff_id_nho_nhat smallint	staff_id_lon_nhat smallint
1	mike	7293	1	1

Check with jon

```

81 set role jon;
82
83 select current_user as tai_khoan,
84        count(*) as so_payment,
85        min(staff_id) as staff_id_nho_nhat,
86        max(staff_id) as staff_id_lon_nhat
87 from payment;
88
89 reset role;

```

Data Output Messages Notifications

	tai_khoan name	so_payment bigint	staff_id_nho_nhat smallint	staff_id_lon_nhat smallint
1	jon	7304	2	2

