Journal Name

Crossmark

RECEIVED
dd Month yyyy

REVISED
dd Month yyyy

PAPER

Information Budgets of Trajectory Health Indicators for Remaining Useful Life Prediction

Anonymous authors

Keywords: information budget, health indicator, remaining useful life, information theory, monotonicity, information bottleneck, first hitting time, prognostics

Abstract

Health indicators (HIs) for remaining useful life (RUL) prediction are usually constructed by optimising geometric criteria, such as monotonicity, trendability and prognosability, or by training an encoder. Neither approach states how much information about the RUL an HI can retain. We model HI construction as a Markov chain from latent degradation to sensors to HI, and bound the mean squared error of any RUL predictor below by the entropy power of the RUL given the HI. The bound defines an information efficiency, converts the error of any predictor into a certified lower bound on the retained information, and accounts for the age, which every predictor knows. We show that a pointwise squeeze of the HI loses state information while monotonicity saturates; that, for Wiener degradation with an unobserved inspection state, the error splits into an aleatoric floor and an epistemic term that grows with the information lost; that a static scalar HI inflates the bound by a factor determined by the angle between its weights and the optimal weights, which rotate from velocity to level as the remaining life shrinks, so that no static scalar HI is optimal over the whole life; and that a regime-blind read-out has an error floor. Simulations on exactly solvable models agree with these results. We further show that an integrating encoder accumulates error that an observation correction removes. Experiments on batteries, bearings and turbofan engines support these consequences but show no learned encoder to be superior to simple indicators.

1 Introduction

Prognostics and health management (PHM) predicts the remaining useful life (RUL) of components such as batteries, bearings and aero-engines, and underpins condition-based maintenance [1, 2, 3, 4]. Methods are conventionally divided into physics-based, data-driven and hybrid [3, 5], and recent work is dominated by deep networks that map sensor histories to the RUL end to end [6, 7]. An established alternative compresses the monitoring data into a scalar *health indicator* (HI) and extrapolates it to a failure threshold D_{fail}. An HI can be inspected by an engineer, the threshold gives the end of life (EOL) a physical meaning, and, when the HI is modelled as a stochastic process, the RUL is a first hitting time (FHT) with a known distribution [8, 9, 1]. Recent studies in this journal follow the same line [10, 11, 12], within the wider scope of reliability science [13, 14].

HIs are usually selected by *geometric* criteria. Coble and Hines [15] formalised monotonicity (balance of positive and negative increments), prognosability (spread of end-of-life values relative to the range travelled) and trendability (agreement of the functional form across units) and optimised them with a genetic algorithm. Variants are common: trendability is often implemented as the correlation with time [16, 17], and a criterion based on ranking mutual information has been proposed for building a monotonic HI [18]. Coble and Hines themselves note that the no-self-healing assumption behind monotonicity fails for batteries [15]. HIs may also be learned by recurrent networks [19], autoencoders and their regularised variants [20, 21], or regressions on engineered features [22]. In both cases an HI is judged by its shape or by the accuracy of the predictor built on it [23]. Neither judgement indicates how much information about the RUL the HI *could* have preserved, and neither separates the quality of the HI from that of the predictor.

Probabilistic RUL prediction from an HI is mostly built on Wiener degradation, whose first passage time is inverse Gaussian [24, 25, 26], with measurement error [8, 27], random unit-specific drift [28, 29], nonlinear drift [30] or threshold regression [9], applied to batteries [27], bearings [31] and highly reliable products [32] (reviews: [33, 1]). Two features are important for what follows: the drift varies between units, and the degradation level at inspection is inferred from the sensors




Figure 1. Framework of the paper. The HI is constructed from the sensors, which are driven by the same latent state as the true RUL, and the predictor uses the HI and the age. The data processing inequality gives an information budget; the red boxes list the operations of HI construction whose information loss is quantified.

rather than observed. The RUL uncertainty then has an aleatoric part (future randomness) and an epistemic part (incomplete knowledge of state and parameters) [34, 35, 36, 37]; deep ensembles are a common way to represent the latter [38].

Information theory [39, 40] enters learning mainly through the information bottleneck [41], which has variational forms [42, 43], links to invariance [44], nonlinear extensions [45] and critics [46]. Estimating entropy and mutual information from samples is difficult: low-dimensional estimators exist [47, 48], but their bias and variance are large in general [49], and a distribution-free, high-confidence lower bound on mutual information cannot exceed order $\ln N$ for N samples [50]. Limits on estimator accuracy are usually stated through Cramér–Rao bounds, in their Bayesian form due to van Trees [51, 52, 53]. The entropy-power bound used in this paper is the information-theoretic counterpart of these bounds and holds for arbitrary densities [40] (Remark 1).

The literature thus offers geometric and accuracy-based ways of judging an HI, a mature probabilistic theory of the RUL *given* an HI, and general information-theoretic tools. In the sources we searched (bibliographic databases and the references above; this is not an exhaustive survey) we did not find a theory that connects them, that is, a bound on the RUL error that depends on the HI only through the information it retains, a statement of what the geometric criteria do and do not measure in these terms, and an account of what a *scalar, static* indicator loses when the degradation velocity varies in time or the sensors respond to the operating regime. A companion study [54] analysed what a static, per-snapshot projection of a multichannel signal retains about the degradation state. Here we analyse the HI *trajectory*, with its level, velocity, between-unit variability and operating regime. Two further studies by the same authors address how many run-to-failure trajectories [55] and which charging-phase features [56] are needed; the present paper addresses how much *information* an HI can at best retain. Figure 1 shows the setting and where each result applies.

The contributions of the paper are:

1. an **information budget**: an entropy-power bound on the RUL error in terms of the mutual information $I(T_t; H_{1:t})$ between the RUL and the HI, an efficiency η_{info} that scores an HI before a predictor is trained, a certificate that turns any held-out error into a lower bound on retained information, age-aware versions of both, and a state–kinematic decomposition (Section 2);
2. **why geometric criteria do not measure information**: a pointwise squeeze loses state information while monotonicity saturates at a value set by the template (Section 3);
3. a **physics-constrained budget** for Wiener degradation with an unobserved inspection state: an HI-independent aleatoric floor plus an epistemic term amplified by information loss, and an exact non-Gaussianity gap (Section 4);
4. an **angular loss law**: a static scalar HI inflates the bound by $1 + \rho \sin^2 \psi$, where ψ is the angle between its weights and the optimal weights and ρ a signal-to-noise ratio, because the optimal weights rotate from velocity to level; no static scalar HI is therefore optimal over the whole life, and a regime-blind read-out has an error floor (Section 5);
5. **consequences for estimators**: an exact path-space bottleneck objective, and a proof that an integrating encoder accumulates error that an observation correction removes (Section 6), examined on batteries, bearings and turbofan engines with a conservative protocol (Section 7).

The ingredients are classical: the data processing inequality, the chain rules, the maximum-entropy property of the Gaussian and the entropy-power bound [40]; the inverse-Gaussian law [25]; Gaussian conditioning [57]; the Kalman filter [58, 59]; and the variational bottleneck bound [42]. What is new is their use as a budget for the HI-construction step, and the specific results listed above. Each proof states which classical facts it uses and where they can be found, and Sections 3 to 5 each end with a numerical check on an exactly solvable model.

2 Information budget of a health indicator

2.1 Setting

Let $T_t > 0$ be the true RUL at inspection time (age) t, $\mathbf{X}_{1:t} \in \mathbb{R}^{d \times t}$ the accumulated history of d sensors, and $H_{1:t} = f_\theta(\mathbf{X}_{1:t})$ the HI trajectory produced by a map f_θ with parameters θ. Throughout, $h(\cdot)$ is differential entropy, $I(\cdot\,;\cdot)$ is mutual information (both in nats), $\mathbb{E}$ and Var are expectation and variance, and $\mathcal{N}(\mu, \sigma^2)$ is the normal distribution. Any RUL estimator $\hat{T}_t = g(H_{1:t})$ obeys the Markov chain $T_t \to \mathbf{X}_{1:t} \to H_{1:t} \to \hat{T}_t$, because the latent degradation state drives both T_t and $\mathbf{X}_{1:t}$. The data processing inequality (DPI) [40, Sect. 2.8] gives

$$I(T_t; \mathbf{X}_{1:t}) \geq I(T_t; H_{1:t}) \geq I(T_t; \hat{T}_t), \tag{1}$$

with equality in the first inequality if and only if $H_{1:t}$ is a sufficient statistic of $\mathbf{X}_{1:t}$ for T_t [40, Sect. 2.9].

Theorem 1 (Entropy-power bound on RUL error)**.** *Assume that $h(T_t)$ and $I(T_t; \mathbf{X}_{1:t})$ are finite. For every estimator $\hat{T}_t = g(H_{1:t})$ with finite second moment, the mean squared error (MSE) satisfies*

$$\mathbb{E}\big[(T_t - \hat{T}_t)^2\big] \;\geq\; \mathcal{B}_{\text{info}}(H_{1:t}) := \frac{1}{2\pi e} \exp\big(2h(T_t \mid H_{1:t})\big) = \frac{1}{2\pi e} \exp\big(2h(T_t) - 2I(T_t; H_{1:t})\big). \tag{2}$$

Moreover $\mathcal{B}_{\text{info}}(H_{1:t}) \geq \mathcal{B}_{\min} := \frac{1}{2\pi e} e^{2h(T_t \mid \mathbf{X}_{1:t})}$ and

$$\mathcal{B}_{\text{info}}(H_{1:t}) / \mathcal{B}_{\min} = \exp\big(2\,(1 - \eta_{\text{info}}(H_{1:t}))\, I(T_t; \mathbf{X}_{1:t})\big), \qquad \eta_{\text{info}}(H_{1:t}) := \frac{I(T_t; H_{1:t})}{I(T_t; \mathbf{X}_{1:t})} \in [0, 1]. \tag{3}$$

Proof. Let $E = T_t - g(H_{1:t})$. Differential entropy is translation invariant [40, Sect. 8.6], so $h(E \mid H_{1:t}) = h(T_t \mid H_{1:t})$ ($g(H_{1:t})$ is constant given $H_{1:t}$). Conditioning does not increase entropy [40, Sect. 2.6], so $h(E \mid H_{1:t}) \leq h(E)$, and the Gaussian maximises entropy at fixed second moment [40, Sect. 8.6], so $h(E) \leq \frac{1}{2} \ln(2\pi e\, \mathbb{E}[E^2])$. Combining the three relations gives $\mathbb{E}[E^2] \geq \frac{1}{2\pi e} e^{2h(T_t \mid H_{1:t})}$. The identity $h(T_t \mid H_{1:t}) = h(T_t) - I(T_t; H_{1:t})$ (definition of mutual information) gives the second form. By (1), $h(T_t \mid H_{1:t}) \geq h(T_t \mid \mathbf{X}_{1:t})$, and the ratio follows from $h(T_t \mid H_{1:t}) - h(T_t \mid \mathbf{X}_{1:t}) = I(T_t; \mathbf{X}_{1:t}) - I(T_t; H_{1:t})$. □

Proposition 1 (Certified information)**.** *Under the assumptions of Theorem 1, any estimator* $\hat{T}_t = g(H_{1:t})$ *with mean squared error* ε^2 *certifies*

$$I(T_t; H_{1:t}) \;\geq\; h(T_t) - \tfrac{1}{2}\ln\!\big(2\pi e\,\varepsilon^2\big). \tag{4}$$

Proof. Rearrange $\varepsilon^2 \geq \frac{1}{2\pi e}\exp(2h(T_t) - 2I(T_t; H_{1:t}))$ from Theorem 1. □

Proposition 2 (Age-aware bound)**.** *The age* t *is always available to a predictor. For every estimator* $\hat{T}_t = g(H_{1:t}, t)$, $\mathbb{E}[(T_t - \hat{T}_t)^2] \geq \frac{1}{2\pi e}\exp\big(2h(T_t \mid H_{1:t}, t)\big)$, *and the information that the HI adds to the age is*

$$I(T_t; H_{1:t}, t) = I(T_t; t) + I(T_t; H_{1:t} \mid t), \qquad I(T_t; H_{1:t} \mid t) \geq \mathbb{E}_t\, h(T_t \mid t) - \tfrac{1}{2}\ln\!\big(2\pi e\,\varepsilon^2\big), \tag{5}$$

where ε^2 *is the MSE of any estimator that uses* $H_{1:t}$ *and* t.

Proof. Apply Theorem 1 conditionally on t and average. The chain rule of mutual information [40, Sect. 2.5] gives the decomposition. For the inequality, Theorem 1 conditionally on t yields $I(T_t; H_{1:t} \mid t = \tau) \geq h(T_t \mid t = \tau) - \frac{1}{2}\ln(2\pi e\,\varepsilon_\tau^2)$ with ε_τ^2 the conditional MSE; averaging over τ and using Jensen's inequality for the concave logarithm [40, Sect. 2.6], $\mathbb{E}_\tau \ln \varepsilon_\tau^2 \leq \ln \mathbb{E}_\tau \varepsilon_\tau^2 = \ln \varepsilon^2$, gives the stated bound. □

Remark 1 (Relation to the Bayesian Cramér–Rao bound)**.** *Let* $J(h)$ *be the Fisher information, with respect to location, of the posterior density* $p(T_t \mid H_{1:t} = h)$. *Under the regularity conditions of the van Trees inequality [51, 52] every estimator satisfies* $\mathbb{E}[(T_t - \hat{T}_t)^2] \geq 1/\mathbb{E}_H[J(H)]$. *Stam's inequality [60] states that* $e^{2h(T_t \mid H=h)}/(2\pi e) \geq 1/J(h)$ *for every* h. *Taking the geometric mean over* h *and using that the geometric mean of* $1/J$ *is at least the reciprocal of the arithmetic mean of* J,

$$\mathcal{B}_{\text{info}}(H_{1:t}) = \exp\!\Big(\mathbb{E}_H \ln \frac{e^{2h(T_t \mid H=h)}}{2\pi e}\Big) \;\geq\; \exp\!\Big(\mathbb{E}_H \ln \frac{1}{J(H)}\Big) \;\geq\; \frac{1}{\mathbb{E}_H[J(H)]}, \tag{6}$$

so, wherever the Bayesian Cramér–Rao bound applies, the entropy-power bound is not weaker, and it requires no differentiability of the densities. For posterior filtering the Fisher-information route is developed in [53].

Theorem 1 is the classical entropy-power bound on the error of an estimator [40, Sect. 8.6], used here to turn HI construction into an information budget. It is tight only if the posterior of T_t is Gaussian and is otherwise conservative (Section 4.1); $\mathcal{B}_{\text{info}}$ equals $\mathcal{B}_{\min}$ exactly when $\eta_{\text{info}} = 1$.

Proposition 2 shows that the relevant baseline for an HI is the RUL given the age, not the marginal distribution of the RUL. A sensor-free predictor that uses only the age is therefore a necessary reference (Appendix A). Proposition 1 gives a quantity that can be computed from real data, since it needs only the one-dimensional entropy $h(T_t)$ and the held-out MSE of a predictor. It is a monotone transform of the MSE and therefore ranks HIs in the same order as the MSE; it is the information-theoretic reading of the error, not independent evidence, and it is vacuous (negative) when the predictor is poor. The efficiency η_{info} could in principle be estimated before any predictor is trained, but mutual-information estimates are unreliable on small data sets [49, 50] (Appendix C).

2.2 Trajectory decomposition

Proposition 3 (State–kinematic decomposition)**.** *Let* $\Delta H_k = H_k - H_{k-1}$ *denote the increments of the HI. The map* $H_{1:t} \mapsto (H_t, \Delta H_{2:t})$ *is a linear bijection, hence*

$$I(T_t; H_{1:t}) = \underbrace{I(T_t; H_t)}_{\mathcal{I}_{\text{state}}(t)} + \underbrace{I(T_t; \Delta H_{2:t} \mid H_t)}_{\mathcal{I}_{\text{kin}}(t)}. \tag{7}$$

Proof. The map has a unit-determinant matrix, so $h(\mathbf{AY}) = h(\mathbf{Y}) + \ln|\det \mathbf{A}|$ [40, Sect. 8.6] and mutual information is unchanged ($H_k = H_t - \sum_{j=k+1}^{t} \Delta H_j$ gives the inverse). The identity is then the chain rule of mutual information [40, Sect. 2.5]. □

Remark 2. *The decomposition is an identity; its content lies in which operations remove which part. If the drift is constant,* H_t/t *is a sufficient statistic for the drift, and* $\mathcal{I}_{\text{kin}}$ *about the drift is zero. Kinematic information is non-trivial when the velocity varies in time, for example under a state-dependent drift or a random-walk velocity, as in late-life acceleration.*

3 Geometric criteria do not measure information

The geometric criteria of Coble and Hines [15] are computed from the shape of the HI. Monotonicity is $\mathrm{Mon}(H_{1:t}) = |\sum_{k=1}^{t-1} \mathrm{sgn}(H_{k+1} - H_k)|/(t-1)$, the balance of positive and negative increments. Prognosability is $\mathrm{Pro} = \exp(-\mathrm{std}(H_{\mathrm{end}})/\mathrm{mean}|H_{\mathrm{end}} - H_{\mathrm{start}}|)$, where the standard deviation and the mean are taken over units, H_{start} and H_{end} being the first and last values of each unit. In the benchmarks, Tre is the absolute correlation of the HI with time, as in [16] (and, under the name correlation, in [17]); it differs from the trendability of Coble and Hines, which measures the agreement of the functional form across units [15].

A strictly monotone bijection ϱ satisfies $I(T_t; \varrho(H_{1:t})) = I(T_t; H_{1:t})$, so information can be lost only through non-injective operations or noise. We therefore consider $\tilde{H}_{1:t} = \mathcal{S}(H_{1:t}, \xi)$, where ξ is independent of everything else. We call $\mathcal{S}$ a *squeeze* when it contracts the HI towards a template trajectory.

Theorem 2 (Information inflation under squeezing)**.** *(a) For any such $\mathcal{S}$, $T_t \to H_{1:t} \to \tilde{H}_{1:t}$ is Markov, so $I(T_t; \tilde{H}_{1:t}) \le I(T_t; H_{1:t})$ and*

$$\mathcal{B}_{\mathrm{info}}(\tilde{H}_{1:t})/\mathcal{B}_{\mathrm{info}}(H_{1:t}) = \exp\big(2[I(T_t; H_{1:t}) - I(T_t; \tilde{H}_{1:t})]\big) \ge 1. \tag{8}$$

(b) If $\mathcal{S}$ acts pointwise in time, $\tilde{H}_k = \phi_k(H_k, \xi_k)$, then

$$\begin{gathered} \ln \frac{\mathcal{B}_{\mathrm{info}}(\tilde{H}_{1:t})}{\mathcal{B}_{\mathrm{info}}(H_{1:t})} = 2\big(\Delta\mathcal{I}_{\mathrm{state}} + \Delta\mathcal{I}_{\mathrm{kin}}\big), \\ \Delta\mathcal{I}_{\mathrm{state}} := \mathcal{I}_{\mathrm{state}}(H) - \mathcal{I}_{\mathrm{state}}(\tilde{H}) \ge 0, \quad \Delta\mathcal{I}_{\mathrm{kin}} := \mathcal{I}_{\mathrm{kin}}(H) - \mathcal{I}_{\mathrm{kin}}(\tilde{H}), \end{gathered} \tag{9}$$

and $\Delta\mathcal{I}_{\mathrm{kin}}$ has no definite sign in general: kinematic information alone does not determine the inflation.

(c) Let the HI be the latent degradation level D_k observed with Gaussian noise, $H_k = D_k + \xi_k^{(1)}$, where D_k is linear-Gaussian, and let the squeeze with strength $\gamma \in [0, 1)$ and template (mean trajectory) $m_k = \mathbb{E}[D_k]$ be

$$\tilde{H}_k^\gamma = m_k + (1-\gamma)(H_k - m_k) + \xi_k^{(2)}, \qquad \xi_k^{(2)} \sim \mathcal{N}(0, \sigma_2^2) \text{ independent and identically distributed (i.i.d.)} \tag{10}$$

For every linear functional ϑ of the latent state (for example the current velocity), write $\mathcal{I}^\vartheta_{\mathrm{state}}(\gamma) = I(\vartheta; \tilde{H}^\gamma_t)$, $\mathcal{I}^\vartheta_{\mathrm{kin}}(\gamma) = I(\vartheta; \Delta\tilde{H}^\gamma_{2:t} \mid \tilde{H}^\gamma_t)$ and $\mathcal{I}^\vartheta_{\mathrm{tot}}(\gamma) = I(\vartheta; \tilde{H}^\gamma_{1:t})$. Then $\mathcal{I}^\vartheta_{\mathrm{tot}}$ and $\mathcal{I}^\vartheta_{\mathrm{state}}$ are non-increasing in γ, and

$$0 \le \mathcal{I}^\vartheta_{\mathrm{state}}(\gamma),\ \mathcal{I}^\vartheta_{\mathrm{kin}}(\gamma) \le \mathcal{I}^\vartheta_{\mathrm{tot}}(\gamma) \xrightarrow[\gamma \to 1]{} 0, \tag{11}$$

so both components vanish, although $\mathcal{I}^\vartheta_{\mathrm{kin}}$ need not be monotone. If the template has constant increment Δm, then as $t \to \infty$ and $\gamma \to 1$,

$$\mathrm{Mon}(\tilde{H}^\gamma_{1:t}) \to \mathrm{Mon}_\infty = 2\Phi_{\mathcal{N}}\big(\Delta m/(\sqrt{2}\,\sigma_2)\big) - 1, \tag{12}$$

where $\Phi_{\mathcal{N}}$ is the standard normal distribution function; the limit does not depend on the unit's own degradation.

Proof. (a) $\tilde{H}$ is a randomised function of H only, so the Markov property holds and the DPI gives the first claim; the ratio follows from the definition of $\mathcal{B}_{\mathrm{info}}$. (b) Apply Proposition 3 to H and to $\tilde{H}$ and take the difference in (a). Because $\tilde{H}_t = \phi_t(H_t, \xi_t)$ is a randomised function of H_t alone, the DPI gives $I(T_t; \tilde{H}_t) \le I(T_t; H_t)$, that is, $\Delta\mathcal{I}_{\mathrm{state}} \ge 0$. For non-pointwise operators (for example smoothing over history) even this sign can fail. (c) With $\lambda = 1 - \gamma > 0$, $\tilde{H}^\gamma$ is an invertible affine image of $(H - m) + \xi^{(2)}/\lambda$, that is, of H observed through additive Gaussian noise of variance σ_2^2/λ^2. For $\gamma_2 > \gamma_1$ the noise of the second channel is the first plus independent Gaussian noise, so the DPI [40, Sect. 2.8] gives monotonicity of $\mathcal{I}^\vartheta_{\mathrm{tot}}$ and, applying the same argument to the scalar observation at time t, of $\mathcal{I}^\vartheta_{\mathrm{state}}$. Since $\mathcal{I}^\vartheta_{\mathrm{state}} = I(\vartheta; \tilde{H}_t) \le I(\vartheta; \tilde{H}_{1:t})$ and $\mathcal{I}^\vartheta_{\mathrm{kin}} = \mathcal{I}^\vartheta_{\mathrm{tot}} - \mathcal{I}^\vartheta_{\mathrm{state}} \le \mathcal{I}^\vartheta_{\mathrm{tot}}$, both are dominated by $\mathcal{I}^\vartheta_{\mathrm{tot}}$. As $\lambda \to 0$ the noise variance diverges, and the mutual information of a Gaussian channel, $\frac{1}{2}\ln(1 + \mathrm{SNR})$ per scalar observation with signal-to-noise ratio SNR [40, Chap. 9], vanishes. For the limit of Mon, as $\lambda \to 0$ the increments converge to $\Delta m + \xi^{(2)}_{k+1} - \xi^{(2)}_k$, a stationary 1-dependent sequence. The indicators of a positive increment at odd k involve disjoint pairs of the $\xi^{(2)}$ and are therefore i.i.d., as are those at even k, so the strong law of large numbers [61, Chap. 2] applies to each subsequence and the fraction of positive increments tends to $p = \Phi_{\mathcal{N}}(\Delta m/(\sqrt{2}\sigma_2))$ and $\mathrm{Mon} \to |2p - 1|$. □

Table 1. Squeezing experiment (mean over three seeds; ±: standard deviation). Information about V_t in nats, errors in cycles.

γ	Mon	$\mathcal{I}_{\text{state}}$ [nats]	$\mathcal{I}_{\text{kin}}$ [nats]	η_{info}	$\sqrt{\mathcal{B}_{\text{info}}}$ [cycles]	Bayes RMSE [cycles]	Empirical RMSE [cycles]
0.000	0.496	0.789	0.092	1.00	6.67	8.04	15.0±9.8
0.500	0.766	0.779	0.092	0.99	6.81	8.91	14.9±9.4
0.900	0.975	0.567	0.188	0.85	7.38	9.27	15.3±9.2
0.970	0.981	0.159	0.396	0.63	9.01	10.99	17.1±9.2
0.990	0.981	0.022	0.200	0.25	12.87	15.20	21.2±8.9
0.995	0.982	0.006	0.070	0.09	14.88	17.83	23.2±8.9

Part (c) shows that the geometric score and the information content are decoupled. Once the squeeze is strong, Mon saturates at a value set by the template and the noise, while the information available for RUL prediction keeps falling and the bound $\mathcal{B}_{\text{info}}$ keeps rising. Part (b) separates two ways of losing information; in the numerical check below, the kinematic part even increases while the state part collapses.

3.1 Numerical check

The latent state is a local linear trend, $D_k = D_{k-1} + V_{k-1} + \sigma_B w_k$ and $V_k = V_{k-1} + \sigma_V \zeta_k$, with level D_k, velocity V_k, independent standard normal noises w_k, ζ_k and $V_0 \sim \mathcal{N}(\bar{v}, \sigma_{v0}^2)$. The raw HI is $H_k = D_k + \xi_k^{(1)}$ with measurement noise $\xi_k^{(1)} \sim \mathcal{N}(0, \sigma_1^2)$, and the squeeze is that of Theorem 2(c) with noise standard deviation σ_2. The parameters are $\bar{v} = 2$, $\sigma_{v0} = 0.25$, $\sigma_V = 0.03$, $\sigma_B = 0.5$, $\sigma_1 = 2$, $\sigma_2 = 0.6$, failure threshold $D_{\text{fail}} = 200$ and inspection at $t = 50$. The information about V_t is exact from the Kalman covariances [58, 59]. For the RUL, the Bayes-optimal estimator is the posterior mean from 300 exact posterior draws per unit, $h(T_t \mid \tilde{H})$ is estimated with the Vasicek estimator [47], and $\sqrt{\mathcal{B}_{\text{info}}}$ is the square root of the average of the pointwise entropy powers. Errors are reported as root mean squared error (RMSE); each setting uses 400 test units and three seeds.

Monotonicity saturates at the predicted value $\text{Mon}_\infty = 0.981$ for $\gamma \geq 0.9$, while the efficiency falls from 0.85 to 0.09 and the Bayes-optimal RMSE nearly doubles (9.3 to 17.8 cycles). The bound stays below the Bayes-optimal error in every run. The state information falls monotonically, whereas the kinematic information first rises and then falls, so the inflation at $\gamma = 0.9$ and 0.97 is driven by the loss of state information. The empirical RMSE varies strongly between seeds because of the heavy right tail of the RUL, and the posterior-based Bayes RMSE is the reliable summary.

4 A physics-constrained error budget

Assume that after inspection the latent degradation follows $dD_s = \mu\, ds + \sigma_B\, dW_s$, $\mu > 0$ unit-specific (the random-effect formulation of [28, 29]), with absorbing threshold D_{fail}. The prognostically relevant latent state is $\mathbf{z} = (D_t, \mu)$, where the inspection level D_t is *not* observed directly but only through $\mathbf{X}_{1:t}$. With $a = D_{\text{fail}} - D_t > 0$, the RUL is conditionally inverse-Gaussian [24, 26], $T_t \mid \mathbf{z} \sim \mathcal{IG}(m(\mathbf{z}),\, a^2/\sigma_B^2)$ with mean $m(\mathbf{z}) = a/\mu$ and variance $a\sigma_B^2/\mu^3$ [25], and T_t is independent of $\mathbf{X}_{1:t}$ (hence of $H_{1:t}$) given $\mathbf{z}$. Here $\mathcal{IG}(\text{mean}, \text{shape})$ denotes the inverse Gaussian distribution. Define the information efficiency about the mean RUL $m = m(\mathbf{z})$ as $\eta_m(H) := I(m; H_{1:t})/I(m; \mathbf{X}_{1:t}) \in [0, 1]$.

Theorem 3 (Physics-constrained bound)**.** *Assume $h(m \mid \mathbf{X}_{1:t})$ and $I(m; \mathbf{X}_{1:t})$ are finite. For any estimator $\hat{T}_t = g(H_{1:t})$ with finite second moment,*

$$\mathbb{E}[(T_t - \hat{T}_t)^2] \;\geq\; \underbrace{\mathbb{E}\left[\frac{a\,\sigma_B^2}{\mu^3}\right]}_{\mathcal{E}_{\text{aleatoric}}} + \underbrace{\mathbb{E}_H\left[\frac{e^{2h(m \mid H_{1:t}=h)}}{2\pi e}\right]}_{\mathcal{E}_{\text{epistemic}}}, \tag{13}$$

and the epistemic term obeys

$$\mathcal{E}_{\text{epistemic}} \;\geq\; \frac{1}{2\pi e} \exp\Big(2h(m \mid \mathbf{X}_{1:t}) + 2\big(1 - \eta_m(H)\big)\, I(m; \mathbf{X}_{1:t})\Big). \tag{14}$$

The aleatoric term does not depend on the HI.

Proof. Since $\mathbb{E}[T_t - m(\mathbf{z}) \mid \mathbf{z}, H_{1:t}] = 0$ and T_t is conditionally independent of $H_{1:t}$ given $\mathbf{z}$, the cross term vanishes and $\mathbb{E}[(T_t - \hat{T}_t)^2] = \mathbb{E}[\text{Var}(T_t \mid \mathbf{z})] + \mathbb{E}[(m(\mathbf{z}) - \hat{T}_t)^2]$, the usual split of the squared error into an irreducible and an estimation part [57, Sect. 1.5.5]. The first term is $\mathbb{E}[a\sigma_B^2/\mu^3]$. For the second, apply Theorem 1 conditionally on $H_{1:t} = h$ to the target $m(\mathbf{z})$, which gives




Figure 2. Squeezing experiment. (a) HI paths of 14 units, coloured by the true RUL. (b) Monotonicity and efficiency. (c) Information about V_t. (d) Bound and RMSE (error bars: standard deviation over seeds). The values of γ are equally spaced.

$\mathbb{E}[(m - \hat{T}_t)^2 \mid H = h] \geq e^{2h(m|H=h)}/(2\pi e)$, and average over h. For the second inequality, the exponential is convex, so (Jensen [40, Sect. 2.6]) $\mathbb{E}_H[e^{2h(m|H=h)}] \geq e^{2h(m|H)}$ with $h(m \mid H) = \mathbb{E}_H h(m \mid H = h)$; and $m \to \mathbf{X}_{1:t} \to H_{1:t}$ is Markov, so $h(m \mid H) = h(m) - I(m; H) = h(m \mid \mathbf{X}) + I(m; \mathbf{X}) - I(m; H) = h(m \mid \mathbf{X}) + (1 - \eta_m) I(m; \mathbf{X})$. □

Remark 3. *Conditioning on D_t and changing variables would give $h(m \mid H) = h(\mu \mid H) + \mathbb{E} \ln(a/\mu^2)$. In the constant-drift model, D_t/t is then a sufficient statistic for μ and the resulting bound no longer depends on the HI. The HI matters through the joint uncertainty about the level and the drift, which is why Theorem 3 is stated for the latent pair* $\mathbf{z}$*. The second inequality of the theorem (the Jensen form) is weaker than the first but depends on the HI only through η_m.*

Proposition 4 (Non-Gaussianity gap)**.** *Let $\hat{m}_H = \mathbb{E}[m \mid H]$ be the Bayes-optimal estimator of m and let $D_h := D_{\mathrm{KL}}\big(p(m \mid H = h) \,\|\, \mathcal{N}(\mathbb{E}[m \mid h], \mathrm{Var}(m \mid h))\big) \geq 0$ be the Kullback–Leibler (KL) divergence of the posterior from the Gaussian with the same mean and variance. Then*

$$\mathbb{E}\big[(m - \hat{m}_H)^2\big] - \mathbb{E}_H\left[\frac{e^{2h(m|H=h)}}{2\pi e}\right] = \mathbb{E}_H\Big[\mathrm{Var}(m \mid H)\big(1 - e^{-2D_H}\big)\Big] \geq 0, \tag{15}$$

with equality if and only if $p(m \mid H)$ is Gaussian almost surely.

Proof. For a density p with mean μ_p and variance σ_p^2 and the Gaussian $q = \mathcal{N}(\mu_p, \sigma_p^2)$, $\int p \ln q = -\frac{1}{2}\ln(2\pi\sigma_p^2) - \frac{1}{2}$ because q depends on x only through the first two moments of p. Hence $D_{\mathrm{KL}}(p\|q) = -h(p) + \frac{1}{2}\ln(2\pi e\sigma_p^2)$ (the identity behind the maximum-entropy property of the Gaussian [40, Sect. 8.6]), that is, $e^{2h(p)}/(2\pi e) = \sigma_p^2 e^{-2D_{\mathrm{KL}}(p\|q)}$. Apply this to $p = p(m \mid H = h)$, use $\mathbb{E}[(m - \hat{m}_H)^2 \mid H = h] = \mathrm{Var}(m \mid h)$, which holds because the posterior mean is the Bayes-optimal estimator under squared loss [57, Sect. 1.5.5], and average over h. The right-hand side vanishes if and only if $D_H = 0$ almost surely, that is, if and only if the posterior is Gaussian. □

Table 2. Physics-constrained bound. $\mathcal{E}_{\text{ale}}$, $\mathcal{E}_{\text{epi}}$: aleatoric and epistemic terms (cycles^2); I in nats; errors in cycles.

ς	η_m	$I(m;H)$ [nats]	$\mathcal{E}_{\text{ale}}$	$\mathcal{E}_{\text{epi}}$ (exact)	$\mathcal{E}_{\text{epi}}$ (pointwise)	$\mathcal{E}_{\text{epi}}$ (Jensen)	$\sqrt{\text{bound}}$ [cycles]	Bayes RMSE [cycles]
0	1.00	1.40	63.9	86.6	75.7	34.3	11.81	12.26
2	0.96	1.35	64.0	91.2	80.1	37.9	12.00	12.46
4	0.91	1.28	63.4	99.0	86.6	44.1	12.25	12.74
8	0.80	1.13	63.8	121.5	106.4	59.7	13.05	13.61
16	0.63	0.88	62.9	174.7	150.9	97.3	14.62	15.42
32	0.38	0.53	63.8	318.7	265.0	198.6	18.13	19.56




Figure 3. Physics-constrained bound as the HI loses information (decreasing η_m). (a) RMSE of the bounds and estimators. (b) Epistemic term; the shaded area is the non-Gaussianity gap.

4.1 Numerical check

The drift is $\mu \sim \mathcal{N}(1, 0.22^2)$, truncated to $\mu > 0.3$ and $a > 1$ (which keeps posterior sampling exact), with $\sigma_B = 0.85$, $D_{\text{fail}} = 100$ and $t = 50$. The raw sensor is $X_k = D_k + \xi_k$ with $\xi_k \sim \mathcal{N}(0, \sigma_\xi^2)$ and $\sigma_\xi = 1.5$. HIs with decreasing information are $H_k^\varsigma = X_k + \varsigma\zeta_k$ with independent standard normal ζ_k and $\varsigma \in \{0, 2, 4, 8, 16, 32\}$; each is a degraded version of X. The posterior of (D_t, μ) given H^ς is Gaussian (Kalman filter on (D, μ)), and $m = a/\mu$ is evaluated on 1500 posterior draws for each of 1500 test units; $h(m \mid H)$ and $h(m)$ are estimated with the Vasicek estimator. The Bayes-optimal error is $\mathbb{E}[\text{Var}(T_t \mid \mathbf{z})] + \mathbb{E}[\text{Var}(m \mid H)]$, and the empirical error against simulated first-passage times is also reported.

The aleatoric term is constant (≈ 63.8 cycles^2), whereas the epistemic term grows as η_m falls from 1 to 0.38. The pointwise bound stays below the Bayes-optimal error at every noise level (RMSE 11.8 against 12.3 cycles for $\varsigma = 0$, and 18.1 against 19.6 for $\varsigma = 32$). The exact epistemic variance exceeds the pointwise value because the posterior of m is not Gaussian; the mean KL divergence in Proposition 4 is about 0.07 nats at $\varsigma = 0$. The marginal density (21) of Section 6, which mixes the inverse-Gaussian law over the Gaussian drift, agrees with numerical integration of the mixture to within 0.31%. The entropy estimates carry Monte Carlo error that we did not quantify, so gaps of a few per cent should not be over-interpreted.

5 Scalar indicators at the trajectory level

Theorem 3 concerns the information budget of an arbitrary HI. We now ask what a *scalar*, *static* HI loses when the degradation velocity varies in time. The loss has the same $\sin^2$ structure as the projection-misalignment loss at the snapshot level in [54], but it acts along the *temporal* direction (level versus velocity).

Setting. Let $\mathbf{z} = (D_t, V_t)^\top$ be the level and the velocity at inspection time t, with Gaussian prior $\mathcal{N}(\mathbf{z}_0, \mathbf{\Sigma})$, observed through $\mathbf{X}_{1:t}$ in a linear-Gaussian model (for example the local-linear-trend state space [62, 59] of Section 3.1 with Gaussian sensor noise). The posterior is $\mathcal{N}(\hat{\mathbf{z}}, \mathbf{P})$ where

$\hat{\mathbf{z}} = \mathbb{E}[\mathbf{z} \mid \mathbf{X}_{1:t}]$ and $\mathbf{P}$ does not depend on the data (as for the covariance recursion of the Kalman filter [58, 59]); $\hat{\mathbf{z}} \sim \mathcal{N}(\mathbf{z}_0, \mathbf{\Lambda})$ with $\mathbf{\Lambda} = \mathbf{\Sigma} - \mathbf{P} \succ 0$ (law of total variance [57, Sect. 1.5.5]), and $\hat{\mathbf{z}}$ is a sufficient statistic of $\mathbf{X}_{1:t}$ for $\mathbf{z}$. The target is the frozen-velocity RUL $m(\mathbf{z}) = (D_{\text{fail}} - D_t)/V_t$. At the operating point $\hat{\mathbf{z}}$ its gradient is

$$\mathbf{g} = \nabla m(\hat{\mathbf{z}}) = -\frac{1}{\hat{V}_t}\Big(1,\ \frac{a}{\hat{V}_t}\Big)^\top, \qquad a = D_{\text{fail}} - \hat{D}_t, \tag{16}$$

and $m_L(\mathbf{z}) = m(\hat{\mathbf{z}}) + \mathbf{g}^\top(\mathbf{z} - \hat{\mathbf{z}})$ is the linearised target. A scalar HI built from the sufficient statistic is $h_{\mathbf{u}} = \mathbf{u}^\top \hat{\mathbf{z}}$. Define the signal-to-noise ratio $\rho = \mathbf{g}^\top \mathbf{\Lambda} \mathbf{g} / \mathbf{g}^\top \mathbf{P} \mathbf{g}$ and the $\mathbf{\Lambda}$-angle $\psi \in [0, \pi/2]$ between $\mathbf{g}$ and $\mathbf{u}$,

$$\cos\psi = \frac{|\mathbf{g}^\top \mathbf{\Lambda} \mathbf{u}|}{\sqrt{(\mathbf{g}^\top \mathbf{\Lambda} \mathbf{g})(\mathbf{u}^\top \mathbf{\Lambda} \mathbf{u})}}. \tag{17}$$

Lemma 1 (Reduction to functionals of $\hat{\mathbf{z}}$)**.** *For every scalar linear functional $w^\top \mathbf{X}_{1:t}$ there is $\mathbf{u}$ such that* $\operatorname{corr}(m_L, w^\top \mathbf{X})^2 \le \operatorname{corr}(m_L, \mathbf{u}^\top \hat{\mathbf{z}})^2$*. Hence no scalar linear HI is more informative about m_L than the best $h_{\mathbf{u}}$. Here* corr *denotes the correlation coefficient.*

Proof. Let $\mathbf{C} = \operatorname{Cov}(\mathbf{z}, \mathbf{X})$ and $\mathbf{V} = \operatorname{Var}(\mathbf{X})$, so $\hat{\mathbf{z}} = \mathbf{z}_0 + \mathbf{C}\mathbf{V}^{-1}(\mathbf{X} - \mathbb{E}\mathbf{X})$ and $\mathbf{\Lambda} = \mathbf{C}\mathbf{V}^{-1}\mathbf{C}^\top$. Put $\mathbf{u} = \mathbf{\Lambda}^{-1}\mathbf{C}w$. Then $\operatorname{Cov}(\hat{\mathbf{z}}, w^\top \mathbf{X}) = \mathbf{C}\mathbf{V}^{-1}\mathbf{V}w = \mathbf{C}w = \mathbf{\Lambda}\mathbf{u}$, so $w^\top \mathbf{X} = \mathbf{u}^\top \hat{\mathbf{z}} + e$ with e uncorrelated with $\hat{\mathbf{z}}$ and, since $\operatorname{Cov}(\mathbf{z}, w^\top \mathbf{X}) = \mathbf{C}w = \mathbf{\Lambda}\mathbf{u} = \operatorname{Cov}(\mathbf{z}, \mathbf{u}^\top \hat{\mathbf{z}})$, also uncorrelated with $\mathbf{z}$. Therefore $\operatorname{Cov}(m_L, w^\top \mathbf{X}) = \operatorname{Cov}(m_L, \mathbf{u}^\top \hat{\mathbf{z}}) = \mathbf{g}^\top \mathbf{\Lambda} \mathbf{u}$ while $\operatorname{Var}(w^\top \mathbf{X}) = \mathbf{u}^\top \mathbf{\Lambda} \mathbf{u} + \operatorname{Var}(e) \ge \operatorname{Var}(\mathbf{u}^\top \hat{\mathbf{z}})$, which gives the claim. □

Theorem 4 (Angular loss law)**.** *In the setting above, for every $\mathbf{u} \neq 0$:*

(a) $\operatorname{Var}(m_L \mid h_{\mathbf{u}}) = \mathbf{g}^\top \mathbf{P} \mathbf{g} + (\mathbf{g}^\top \mathbf{\Lambda} \mathbf{g}) \sin^2 \psi$.

(b) For the linearised target, with $I(m_L; \mathbf{X}_{1:t}) = \frac{1}{2}\ln(1+\rho)$,

$$\frac{\mathcal{B}_{\text{info}}(h_{\mathbf{u}})}{\mathcal{B}_{\min}} = 1 + \rho \sin^2 \psi, \qquad \eta_m(h_{\mathbf{u}}) = 1 - \frac{\ln(1 + \rho \sin^2 \psi)}{\ln(1+\rho)}. \tag{18}$$

(c) $\eta_m(h_{\mathbf{u}}) = 1$ if and only if $\mathbf{u} \parallel \mathbf{g}$; the HI $h_{\mathbf{g}} = \mathbf{g}^\top \hat{\mathbf{z}}$ is information-lossless for m_L and is, by Lemma 1, the best scalar linear HI of $\mathbf{X}_{1:t}$.

Proof. (a) Because $\mathbf{z} = \hat{\mathbf{z}} + \boldsymbol{\varepsilon}$ with $\boldsymbol{\varepsilon} \sim \mathcal{N}(0, \mathbf{P})$ independent of $\hat{\mathbf{z}}$, we have $\operatorname{Cov}(\mathbf{z}, \hat{\mathbf{z}}) = \mathbf{\Lambda}$ and $\operatorname{Var}(\mathbf{g}^\top \mathbf{z}) = \mathbf{g}^\top \mathbf{\Sigma} \mathbf{g} = \mathbf{g}^\top \mathbf{\Lambda} \mathbf{g} + \mathbf{g}^\top \mathbf{P} \mathbf{g}$. The pair $(\mathbf{g}^\top \mathbf{z}, h_{\mathbf{u}})$ is jointly Gaussian with $\operatorname{Cov} = \mathbf{g}^\top \mathbf{\Lambda} \mathbf{u}$ and $\operatorname{Var}(h_{\mathbf{u}}) = \mathbf{u}^\top \mathbf{\Lambda} \mathbf{u}$, so the Gaussian conditioning formula [57, Sect. 2.3] gives $\operatorname{Var}(m_L \mid h_{\mathbf{u}}) = \mathbf{g}^\top \mathbf{\Lambda} \mathbf{g} + \mathbf{g}^\top \mathbf{P} \mathbf{g} - (\mathbf{g}^\top \mathbf{\Lambda} \mathbf{u})^2 / (\mathbf{u}^\top \mathbf{\Lambda} \mathbf{u}) = \mathbf{g}^\top \mathbf{P} \mathbf{g} + \mathbf{g}^\top \mathbf{\Lambda} \mathbf{g}\,(1 - \cos^2 \psi)$.

(b) In the linearised model the conditional law of m_L is Gaussian, so the entropy power equals the variance. Taking the ratio of (a) to the case $h = \hat{\mathbf{z}}$, for which $\operatorname{Var}(m_L \mid \hat{\mathbf{z}}) = \mathbf{g}^\top \mathbf{P} \mathbf{g}$, gives the first formula. Moreover, by the formula for the mutual information of jointly Gaussian variables [40, Chap. 8], $I(m_L; \mathbf{X}) = \frac{1}{2}\ln(\operatorname{Var}(m_L)/\mathbf{g}^\top \mathbf{P} \mathbf{g}) = \frac{1}{2}\ln(1+\rho)$ and $I(m_L; h_{\mathbf{u}}) = \frac{1}{2}\ln\big((1+\rho)/(1+\rho\sin^2\psi)\big)$; their ratio is η_m.

(c) $\sin^2 \psi = 0$ iff $\mathbf{\Lambda}^{1/2}\mathbf{g} \parallel \mathbf{\Lambda}^{1/2}\mathbf{u}$ iff $\mathbf{u} \parallel \mathbf{g}$ since $\mathbf{\Lambda} \succ 0$. For $\mathbf{u} = \mathbf{g}$ the loss vanishes, and Lemma 1 shows that no scalar linear functional of $\mathbf{X}$ can do better. □

Corollary 1 (No static scalar HI is optimal over the whole life)**.** *Let $\mathbf{g}_1, \mathbf{g}_2$ be the gradients at two inspection stages with information matrices $\mathbf{\Lambda}_1, \mathbf{\Lambda}_2$ and ratios $\rho_1, \rho_2 > 0$. If $\mathbf{g}_1 \nparallel \mathbf{g}_2$, then for every fixed $\mathbf{u}$ the bound is inflated at one of the two stages,* $\max_j \rho_j \sin^2 \psi_j(\mathbf{u}) \ge \delta > 0$*, where δ depends only on $(\mathbf{g}_j, \mathbf{\Lambda}_j, \rho_j)$. If $\mathbf{\Lambda}_1 = \mathbf{\Lambda}_2$, then $\delta \ge \min_j \rho_j \sin^2(\psi_{12}/2)$ with ψ_{12} the $\mathbf{\Lambda}$-angle between $\mathbf{g}_1$ and $\mathbf{g}_2$. A phase-adaptive HI $h_t = \mathbf{g}_t^\top \hat{\mathbf{z}}_t$ has no inflation at any stage.*

Proof. By Theorem 4(c), inflation at stage j vanishes only for $\mathbf{u} \parallel \mathbf{g}_j$, so it vanishes at both stages only if $\mathbf{g}_1 \parallel \mathbf{g}_2$. The map $\mathbf{u} \mapsto \max_j \rho_j \sin^2 \psi_j(\mathbf{u})$ is continuous and positive on the unit circle, hence has a positive minimum δ. For the quantitative statement note that the $\mathbf{\Lambda}$-angle between lines satisfies the triangle inequality $\psi_{12} \le \psi_1 + \psi_2$. Indeed, for unit vectors a, b in the $\mathbf{\Lambda}$-inner product the angle $\arccos\langle a, b\rangle$ is the geodesic distance on the unit sphere, which is a metric, and the angle between the lines through a and b is $\min_{s=\pm 1} \arccos\langle a, sb\rangle$. Choose the sign of the representative of $\mathbf{u}$ so that its angle to the representative of $\mathbf{g}_1$ is ψ_1, then the sign of the representative of $\mathbf{g}_2$ so that its angle to that of $\mathbf{u}$ is ψ_2; the spherical triangle inequality bounds the angle between the representatives of $\mathbf{g}_1$ and $\mathbf{g}_2$ by $\psi_1 + \psi_2$, and ψ_{12} is not larger. Therefore $\max_j \psi_j \ge \psi_{12}/2$ and $\sin^2$ is increasing on $[0, \pi/2]$. The last sentence is Theorem 4(c) applied at each stage. □

Table 3. Inflation of the bound at $t = 50$: prediction (Theorem 4) against Monte Carlo, mean over 500 units. The static HI uses the gradient at the prior mean.

Static HI $h_{\mathbf{u}}$	mean ψ [deg]	predicted $1 + \rho \sin^2 \psi$	Monte Carlo
level only $\mathbf{u} = (1, 0)$	6.0	1.177	1.181
velocity only $\mathbf{u} = (0, 1)$	5.8	1.194	1.197
static, $\mathbf{u} = \nabla m$ at prior mean	0.7	1.004	1.003
phase-adaptive $\mathbf{u}_t = \mathbf{g}_t$	0.0	1.000	0.999




Figure 4. Angular loss law for scalar HIs. (a) Inflation of the bound: prediction (lines) and Monte Carlo (markers). (b) Angle to the optimal direction $\mathbf{g}_t$. (c) Information efficiency η_m. The static HI is aligned at $t^* = 50$.

Corollary 2 (Rotation of the optimal weights)**.** *In the coordinates (D_t, V_t) the optimal direction is $\mathbf{g}_t \propto (1, \hat{\tau}_t)^\top$ with $\hat{\tau}_t = a_t/\hat{V}_t$ the current frozen-velocity RUL (in steps). The optimal scalar HI therefore weights the velocity estimate $\hat{\tau}_t$ times more than the level estimate; the weight moves from the velocity (early life, $\hat{\tau}_t$ large) to the level (end of life, $\hat{\tau}_t \to 0$), and the Euclidean angle between the optimal directions at RULs τ_1, τ_2 is $|\arctan \tau_1 - \arctan \tau_2|$.*

Corollary 2 explains why an indicator built from a level-like feature, for example the first principal component of cumulative-damage features, loses information early in life, and why a velocity-like feature loses it late in life. It is the temporal counterpart of the snapshot-level rotation of the signal direction. It also motivates the predictor of Section 6, which uses both the smoothed HI level and its windowed slope: this pair estimates the two-dimensional sufficient statistic $\hat{\mathbf{z}}$.

5.1 Numerical check

The model is the local linear trend of Section 3.1 with the raw sensor and $D_{\text{fail}} = 200$. The posterior of $\mathbf{z} = (D_t, V_t)$ is Gaussian, and $\mathbf{\Lambda}$ is strongly anisotropic (eigenvalues 0.004 and 204). For each of 500 units, the exact entropy power of the *nonlinear* target $m = (D_{\text{fail}} - D_t)/V_t$ given $h_{\mathbf{u}}$ is estimated from the exact conditional Gaussian of $\mathbf{z}$ (2000 draws, Vasicek estimator) and compared with $1 + \rho \sin^2 \psi$ evaluated at each unit's own gradient. As a sanity check, in the constant-drift model of Section 4.1, $\mathbf{\Lambda}$ is effectively of rank one and the predicted inflation is 1.000 for every $\mathbf{u}$ (Monte Carlo: 1.000 to 1.003), as the remark after Theorem 3 implies.

At $t = 50$ the predicted inflation agrees with the Monte Carlo value to within 1% for all four indicators (Table 3). Figure 4 illustrates Corollary 1: the static HI aligned at $t^* = 50$ is lossless at $t = 25$ and 50 but inflates the bound by 40% at $t = 75$, the level-only HI by 33 to 36% and the velocity-only HI by a factor of 5, whereas the phase-adaptive HI shows no inflation at any stage.

5.2 Regime leakage

When the sensors are recorded under several operating regimes, the sensor responds to the degradation with a regime-dependent offset and gain, whereas the degradation process itself is the same. The following statement quantifies what a regime-blind read-out loses.




Figure 5. Regime leakage in the six-regime example. (a) Sensor read-out against latent level for each regime. (b) Error of the regime-blind and regime-aware read-outs: formula (lines) and simulation (markers).

Proposition 5 (Regime leakage floor)**.** *Let a latent level D with mean $\bar{d}$ and variance v be observed through a sensor as $x = a_r D + b_r + \varepsilon$, where the regime r takes R values with probabilities π_r independently of D and of the noise ε (variance σ^2); a_r and b_r are the gain and offset of regime r. Put $\bar{a} = \mathbb{E}a_r$, $V_x = \mathbb{E}[a_r^2]\mathbb{E}[D^2] - (\bar{a}\bar{d})^2 + \mathrm{Var}(b_r) + 2\bar{d}\,\mathrm{Cov}(a_r, b_r) + \sigma^2$. The best regime-blind linear read-out of D from x has mean squared error*

$$\mathrm{MSE}_{\mathrm{blind}} = v - \frac{\bar{a}^2 v^2}{V_x}, \qquad \textit{and} \qquad \mathrm{MSE}_{\mathrm{blind}} \xrightarrow[\sigma \to 0]{} \frac{v\,[\mathrm{Var}(a_r)\,v + \mathrm{Var}(\bar{d}a_r + b_r)]}{\bar{a}^2 v + \mathrm{Var}(a_r)\,v + \mathrm{Var}(\bar{d}a_r + b_r)} > 0 \tag{19}$$

unless the regimes agree in a_r and in $\bar{d}a_r + b_r$, whereas a read-out that knows the regime has $\mathrm{MSE}_{\mathrm{aware}} = \sigma^2 \sum_r \pi_r / a_r^2 \to 0$.

Proof. Because D and r are independent, $\mathrm{Cov}(D, x) = \bar{a}\,v$, and $\mathrm{Var}(x) = \mathrm{Var}(a_r D) + \mathrm{Var}(b_r) + 2\bar{d}\,\mathrm{Cov}(a_r, b_r) + \sigma^2 = V_x$, since $\mathrm{Cov}(a_r D, b_r) = \bar{d}\,\mathrm{Cov}(a_r, b_r)$ and $\mathrm{Var}(a_r D) = \mathbb{E}[a_r^2]\mathbb{E}[D^2] - (\bar{a}\bar{d})^2$; the best linear predictor of D from x has error $v - \mathrm{Cov}(D, x)^2 / \mathrm{Var}(x)$ (the conditional variance of a Gaussian pair with the same second moments [57, Sect. 2.3]). For the limit use $\mathbb{E}[a_r^2]\mathbb{E}[D^2] - (\bar{a}\bar{d})^2 = \bar{a}^2 v + \mathrm{Var}(a_r)(v + \bar{d}^2)$ and $\mathrm{Var}(a_r)\bar{d}^2 + \mathrm{Var}(b_r) + 2\bar{d}\mathrm{Cov}(a_r, b_r) = \mathrm{Var}(\bar{d}a_r + b_r)$, so that at $\sigma = 0$, $V_x = \bar{a}^2 v + \mathrm{Var}(a_r)v + \mathrm{Var}(\bar{d}a_r + b_r)$. Given the regime, the read-out $(x - b_r)/a_r$ is unbiased with variance σ^2 / a_r^2. □

Normalising the sensors within each regime removes the regime offsets but not the regime-dependent gains, so the floor remains. In a numerical example with six regimes ($a_r \in [0.6, 1.6]$, $b_r \in [-0.5, 0.6]$, $v = 0.08$), the formula and a simulation agree on $\mathrm{MSE}_{\mathrm{blind}} = 0.060$ at $\sigma = 0$, so that only 25% of $\mathrm{Var}(D)$ is explained, whereas the regime-aware read-out has an error that tends to zero (Figure 5).

6 Consequences for estimators

The results above concern information budgets and the structure of scalar indicators. This section derives what they imply for RUL estimators and describes the estimators used in the empirical assessment. The path-space objective and the error-accumulation result follow from the theory; the architectures and the calibration are design choices.

6.1 Path-space objective

We seek a causal stochastic encoder, the *physics-guided information bottleneck* (PGIB), $q_\theta(H_{1:t} \mid \mathbf{X}_{1:t}) = \prod_{k=1}^{t} q_\theta(H_k \mid H_{k-1}, \mathbf{X}_{1:k})$, whose increments are Gaussian,

$\mathcal{N}\big(H_{k-1} + u_\theta(\mathbf{X}_{1:k})\Delta t,\ s_\theta^2(\mathbf{X}_{1:k})\Delta t\big)$, with a positive velocity u_θ (enforced by a softplus output) and a variance s_θ^2. The encoder is regularised towards a physics prior $p_\vartheta(H_{1:t}) = \prod_k \mathcal{N}\big(H_{k-1} + \eta(H_{k-1};\vartheta)\Delta t,\ \sigma_B^2\Delta t\big)$, $H_0 \equiv 0$, where Δt is the time step, η a state-dependent drift with parameters ϑ, and σ_B the diffusion coefficient.

Proposition 6 (Compression bound and path-space KL)**.** *For any prior p_ϑ, $I(\mathbf{X}_{1:t}; H_{1:t}) \le \mathbb{E}_{\mathbf{X}}\big[D_{\mathrm{KL}}(q_\theta(H_{1:t} \mid \mathbf{X}_{1:t}) \,\|\, p_\vartheta(H_{1:t}))\big]$, and for the Gaussian factorisation above the divergence is exactly*

$$D_{\mathrm{KL}} = \frac{1}{2}\sum_{k=1}^{t} \mathbb{E}_{q_\theta(H_{k-1}|\mathbf{X}_{1:k-1})}\left[\frac{s_\theta^2}{\sigma_B^2} - 1 - \ln\frac{s_\theta^2}{\sigma_B^2} + \frac{(u_\theta - \eta(H_{k-1};\vartheta))^2\,\Delta t}{\sigma_B^2}\right]. \tag{20}$$

Proof. The first claim is the standard variational upper bound of the information bottleneck [41, 42, 43]: $I(\mathbf{X}; H) = \mathbb{E}_{\mathbf{X}} D_{\mathrm{KL}}(q(H \mid \mathbf{X})\|q(H)) \le \mathbb{E}_{\mathbf{X}} D_{\mathrm{KL}}(q(H \mid \mathbf{X})\|p(H))$ because the difference is $D_{\mathrm{KL}}(q(H)\|p(H)) \ge 0$. The chain rule of the KL divergence [40, Sect. 2.5] over the causal factorisation gives $\sum_k \mathbb{E}_{q(H_{k-1}|\cdot)} D_{\mathrm{KL}}(q(H_k \mid H_{k-1}, \mathbf{X}_{1:k})\|p_\vartheta(H_k \mid H_{k-1}))$, and the Gaussian KL with means differing by $(u_\theta - \eta)\Delta t$ and variances $s_\theta^2\Delta t$, $\sigma_B^2\Delta t$ yields the summand (the Gaussian KL of the variational autoencoder [20]). □

The training objective is $\mathcal{L}_{\mathrm{PGIB}} = \mathcal{L}_{\mathrm{FHT}} + \beta\, D_{\mathrm{KL}}$, where β weights the compression term and $\mathcal{L}_{\mathrm{FHT}}$ is the negative log-likelihood of the observed failure time under the predictive law below, a variational surrogate for $-I(T_t; H_{1:t})$ in the sense of [42] (Algorithm 1 in Appendix A).

6.2 Predictive law

Let the posterior of the unit's drift μ given the HI increments be $\mathcal{N}(\hat{\mu}_t, \sigma_{\mu,t}^2)$ (conjugate update). Marginalising the inverse-Gaussian law over μ (a Gaussian integral; random-drift Wiener models are treated in [28, 29]) gives

$$p(T_t = \tau \mid H_{1:t}) = \frac{a}{\sqrt{2\pi\tau^3(\sigma_B^2 + \sigma_{\mu,t}^2\tau)}} \exp\left(-\frac{(a - \hat{\mu}_t\tau)^2}{2\tau(\sigma_B^2 + \sigma_{\mu,t}^2\tau)}\right), \qquad a = D_{\mathrm{fail}} - \hat{D}_t. \tag{21}$$

Here σ_B^2 is the aleatoric and $\sigma_{\mu,t}^2\tau$ the epistemic contribution to the effective diffusion; as t grows $\sigma_{\mu,t}^2 \to 0$ and (21) reduces to the inverse-Gaussian law. It is a defective density, the missing mass being the probability of a non-positive drift, and $\hat{D}_t$ is the filtered state rather than the raw HI value, which avoids the degeneracies of non-monotone paths. The law was checked against numerical integration of the mixture (Section 4.1).

6.3 Observation-corrected and regime-aware encoders

The encoder above integrates a positive velocity, $H_k = H_{k-1} + u_\theta\Delta t + \ldots$, so nothing anchors the level to the observations. Section 5 treats the level and the velocity as latent quantities, and the level must be re-estimated from the sensors at every step; this is the measurement update of a Kalman filter [58]. The observation-corrected encoder, PGIB-KF (KF: Kalman filter), therefore adds a level read-out $l_k = f_l(\mathbf{h}_k)$ and a learned gain $\omega_k = \sigma(f_\omega(\mathbf{h}_k)) \in (0, 1)$ to the encoder features $\mathbf{h}_k$,

$$H_k = (1 - \omega_k)\big(H_{k-1} + u_k + s_k\epsilon_k\big) + \omega_k\, l_k. \tag{22}$$

Given H_{k-1} this is again a Gaussian transition with drift $u_k^{\mathrm{eff}} = (1 - \omega_k)u_k + \omega_k(l_k - H_{k-1})$ and standard deviation $s_k^{\mathrm{eff}} = (1 - \omega_k)s_k$, so Proposition 6 applies unchanged: the bottleneck now prices the use of the observation beyond what the physics prior allows ($\beta \to \infty$ gives $\omega \to 0$, a pure integrator). The HI is no longer monotone by construction.

Proposition 7 (Error accumulation without observation correction)**.** *Let the velocity estimate carry the error $e_j = b + w_j$ with a unit-specific persistent bias b and white noise w_j of variance σ_w^2, and let the level read-out carry independent zero-mean noise of variance σ_n^2. For the pure integrator ($\omega = 0$) the level error after t steps has mean tb and variance $t\sigma_w^2$, both unbounded in t. For a constant gain $\omega \in (0, 1]$ the level error converges to a stationary law with*

$$\mathbb{E}\,\varepsilon_\infty = \frac{(1 - \omega)\,b}{\omega}, \qquad \mathrm{Var}\,\varepsilon_\infty = \frac{(1 - \omega)^2\sigma_w^2 + \omega^2\sigma_n^2}{\omega(2 - \omega)}. \tag{23}$$

Proof. The level error obeys $\varepsilon_k = (1-\omega)(\varepsilon_{k-1} + e_k) + \omega n_k$ with $\varepsilon_0 = 0$; write $\alpha = 1-\omega$. For $\omega = 0$, $\varepsilon_t = \sum_{j \le t} e_j$ has mean tb and variance $t\sigma_w^2$. For $\omega > 0$ the mean satisfies $m_k = \alpha(m_{k-1} + b)$, with fixed point $\alpha b/(1-\alpha) = (1-\omega)b/\omega$ approached geometrically, and the variance $v_k = \alpha^2 v_{k-1} + \alpha^2\sigma_w^2 + \omega^2\sigma_n^2$ (independent noise terms) has fixed point $(\alpha^2\sigma_w^2 + \omega^2\sigma_n^2)/(1-\alpha^2)$ with $1-\alpha^2 = \omega(2-\omega)$. □

A simulation ($b = 0.01$, $\sigma_w = 0.02$, $\sigma_n = 0.15$, 400 steps, 2×10^5 paths) agrees with both expressions (for $\omega = 0$ the bias is $4.00 = tb$; for $\omega = 0.2$ the bias and variance are 0.0399 and 0.00321 against 0.04 and 0.00321). A constant gain amounts to exponential smoothing, the steady state of the local-level filter [62, 59]. A persistent velocity bias is the generic situation when units differ in initial offset or wear, and it is the mechanism that we diagnose for the integrating encoder on the turbofan data (Section 7).

By Proposition 5, a regime-blind read-out has an error floor, and per-regime normalisation removes the offsets but not the gains. The regime-aware variant, *PGIB-KFR*, therefore places the regime in the *observation* model, where the proposition locates it. The process model is shared, whereas the read-out l_k and the gain ω_k use regime-specific linear heads on the encoder features, $l_k = \mathbf{h}_k^\top \mathbf{W}_{r_k}^l + b_{r_k}^l$ and $\omega_k = \sigma(\mathbf{h}_k^\top \mathbf{W}_{r_k}^\omega + b_{r_k}^\omega)$, where r_k is the regime, which is also an input of the encoder. The regimes are the clusters of the standardised operating settings. With a single regime PGIB-KFR reduces to PGIB-KF, which we check on the single-regime subsets.

6.4 Calibrated predictive law with age fusion

Because the age is always known (Proposition 2), the HI-based law $p_{\mathrm{HI}}(\tau)$, which is (21) with diffusion $c\,v_t$ and drift variance $c\,v_t/w_t$, is pooled log-linearly [63, 64] with an age law. Here v_t is the variance of the HI increments over the trailing window of length w_t for non-learned HIs and the learned σ_B^2 for the bottleneck models, and $c > 0$ is a calibration multiplier. The age law is $p_{\mathrm{age}}(\tau \mid t) = f_L(t+\tau)/S_L(t)$, the log-normal lifetime density [65] fitted on training lifetimes (log-scale floor 0.15) conditioned on survival to age t. The pooled law is

$$p(\tau) \;\propto\; p_{\mathrm{HI}}(\tau)^{w_{\mathrm{h}}}\, p_{\mathrm{age}}(\tau \mid t)^{w_{\mathrm{a}}}, \qquad (c, w_{\mathrm{h}}, w_{\mathrm{a}}) \in \mathcal{G}, \tag{24}$$

on a finite grid $\mathcal{G}$ ($c \in [10^{-2}, 10^2]$ on a log scale, ten pairs $(w_{\mathrm{h}}, w_{\mathrm{a}})$ including $(1,0)$ and $(0,1)$). The parameters minimise the negative log-likelihood of the true RUL, a strictly proper scoring rule [66], on HI paths produced *out of sample*: each HI construction is fitted on all but one training unit and applied to the left-out unit; the test unit is never used. The family contains the plain HI law and the age-only law, so in-sample the pooled law cannot do worse than either. Weights below one temper the corresponding law and widen the predictive interval, which the otherwise under-covering plain law requires. The pooling is a calibration device, not a Bayes-exact fusion, which would also require conditional independence of the HI and the age given the RUL, and division by the marginal law of the RUL. The same predictor is used for every HI, and a variant without fusion ($w_{\mathrm{a}} = 0$) is reported for each HI, so that the effects of the HI and of the fusion can be separated.

7 Empirical assessment

The theory makes four predictions that real run-to-failure data can test. (i) The baseline for an HI is the RUL given the age, so a sensor-free predictor that uses only the age should be competitive when the sensors are weak (Proposition 2). (ii) An integrating encoder accumulates error and an observation-corrected one does not (Proposition 7). (iii) Learned encoders have a training variance that must be measured before differences between HIs are interpreted. (iv) The error of a predictor certifies a bound on the information that its HI retains, which is vacuous when the error is large (Proposition 1).

Design. The data are battery cells from the NASA Prognostics Center of Excellence (PCoE) and from the Center for Advanced Life Cycle Engineering (CALCE, CS2 cells, in sets of four and six); bearings from the FEMTO-ST institute (PRONOSTIA, conditions 1 to 3) and from the NASA Center for Intelligent Maintenance Systems (IMS); and the four subsets FD001 to FD004 of the Commercial Modular Aero-Propulsion System Simulation (C-MAPSS) turbofan data, of which FD001 and FD003 have one operating regime and FD002 and FD004 six. Three simple HIs are compared with three learned encoders. The simple HIs are the first principal component (PCA-HI), a linear combination optimised for the sum of the geometric criteria monotonicity, trendability and prognosability (Geo-opt HI), and a supervised ridge regression (ridge HI). The learned encoders are a β-variational autoencoder (β-VAE), a variational information bottleneck without physics prior (VIB), and the PGIB of Section 6 with its Kalman-corrected (PGIB-KF) and




Figure 6. RMSE of the compared HIs on the seven small data sets (cycles for batteries, 10 s snapshots for bearings). Colour: ratio to the age law; frame: lowest value of each row; *: sets not used in the design.

Table 4. C-MAPSS, ten seeds per learned encoder. Single: RMSE, mean ± standard deviation over seeds; ens. 10: ten-seed ensemble; last column: paired difference of PGIB-KF from the best simple HI with 95% bootstrap interval over engines [68].

Subset	Best simple HI (RMSE)	PGIB-HI single	PGIB-KF-HI single	PGIB-KFR-HI single	PGIB-KF-HI ens. 10	PGIB-KFR-HI ens. 10	KF − best paired, ens. 10 [95% CI]	KFR − best
FD001	PCA (21.8)	34.8±2.9	23.8±3.3	27.5±3.2	21.3	25.5	-0.6 [-3.2, +2.5]	+3.6 [+0.2, +7.0]
FD002	regime ridge (28.4)	36.3±1.5	31.0±2.2	30.6±2.2	29.2	29.1	+0.8 [-0.7, +2.3]	+0.7 [-1.2, +2.8]
FD003	Geo-opt. (21.9)	41.2±1.9	30.1±4.6	33.8±6.5	23.3	28.4	+1.4 [-1.6, +4.5]	+6.5 [+2.4, +10.6]
FD004	Geo-opt. (29.7)	48.7±2.5	40.7±7.6	36.8±4.0	35.8	31.8	+6.1 [+2.5, +9.7]	+2.1 [-0.9, +5.0]

regime-aware (PGIB-KFR) variants. All HIs feed the *same* calibrated predictor of Section 6.4. Evaluation is leave-one-unit-out for the small sets and uses the official test engines for C-MAPSS. Data, protocols, their history and the evidence tiers (which results are clean confirmations and which are development results) are given in Appendix A, and full tables in Appendix B.

Age and few training units (prediction i). With two to six training units, the age law has the lowest RMSE on both FEMTO conditions, a simple HI on three sets, the PGIB on one (four-cell CALCE) and the β-VAE on one (FEMTO condition 3). The age law is within a factor of 1.5 of the best method on six of the seven sets (Figure 6). On C-MAPSS the sensors are far more informative: the age law has an RMSE of 36.6 to 54.7 cycles, against 21.8 to 29.7 for the best simple HI. The age law is thus a strong baseline where the sensors are weak, and it must be reported.

Error accumulation and its repair (prediction ii). With 80 to 208 training engines, the integrating encoder is well behind the simple HIs and no better than the age law on FD001 to FD003 (single-model RMSE 34.8 to 48.7). The observation-corrected PGIB-KF reduces the RMSE to 23.8–40.7 for a single model and to 21.3–35.8 for a ten-seed ensemble (Table 4). The deficit is therefore not caused by the bottleneck objective, which is the same in both models, but by the missing anchoring of the level.

Training variance (prediction iii). A single learned encoder varies from seed to seed by 2.2 to 7.6 RMSE units, as much as the differences between competing HIs (Figure 7), which calls for variance-aware comparisons [67]. A three-seed ensemble on FD003 suggested that PGIB-KF beats the best simple HI (19.4 against 21.9), but with ten seeds [38] the difference disappears (23.3; paired difference +1.4, interval −1.6 to 4.5). With ten seeds, the ensembles of the observation-corrected encoders are statistically tied with the best simple or supervised HI on all four subsets, except PGIB-KF on FD004, where it is worse, and they are never significantly better. The regime-aware variant is not shown to help: it is worse than PGIB-KF with a single regime and better only on FD004, where the difference is not significant.

Certificates (prediction iv). The certified information is vacuous for NASA, the FEMTO conditions and, with one exception, IMS. It is positive only on CALCE, where the PGIB certifies 0.60 nats against 0.41 for the age law with four cells (Appendix B). Because the age alone already




Figure 7. C-MAPSS test RMSE. Squares: deterministic HIs; dots: single models of each learned encoder; bars: mean and standard deviation; diamonds: ten-seed ensembles; dotted line: best simple or supervised HI.

certifies information, the data do not show that the learned HIs retain much more than the age on these small sets.

8 Discussion and conclusions

Theory. The paper gives bounds, identities and laws for the information that an HI can retain about the RUL. The entropy-power bound lies below the Bayes-optimal error in every simulated case, and the gap equals the weighted non-Gaussianity of the posterior. A squeeze loses state information while monotonicity saturates, so geometric scores do not measure what matters. The error splits into an aleatoric floor, independent of the HI, and an epistemic term that grows with the information lost. A static scalar HI inflates the bound by $1 + \rho \sin^2 \psi$, in agreement with Monte Carlo to within one to three per cent, so that no static scalar HI is optimal over the whole life, and a regime-blind read-out keeps an error floor. These statements concern budgets and structure; they do not say that a particular encoder reaches the budget, nor do they rank encoders.

Design implications and empirical findings. The theory suggests four design rules: keep the age in the baseline and the predictor (Proposition 2); complement a scalar HI with estimates of level and velocity (Corollary 2), as the windowed slope does in our predictor; anchor the level of an encoder to the observations (Proposition 7); and let the observation model depend on the regime (Proposition 5). The experiments confirm the first and the third. They neither confirm nor refute the fourth, because the effect of the regime-aware encoder is within the training variability. No learned encoder is superior to simple indicators: with two to six training units a simple indicator or the age law is best on five of seven sets, and with 80 or more training engines a ten-seed ensemble of the observation-corrected encoder is tied with the best simple or supervised HI. The practical value of the bottleneck encoder, which requires ten trainings of a recurrent model to reach a tie, is therefore not established, whereas the theory does not depend on this outcome.

Limitations. (1) The theory of Section 5 is local and Gaussian, and Theorem 3 assumes a constant-drift Wiener future; non-Gaussian posteriors, non-constant drift and regime switching are open, and the entropy estimates in the numerical checks have unquantified Monte Carlo error. (2) The efficiency η_{info} could not be estimated reliably on real data, and the certificate is vacuous for most runs. (3) The regime-aware variant and the variance study were designed after seeing results on the sets used, and no independent multi-regime data set was available (evidence tiers in Appendix A). (4) Ensembles of ten encoders are compared with deterministic simple HIs, which favours the encoders in computation. (5) The age fusion and the out-of-sample calibration were introduced after an initial protocol showed under-coverage; they benefit all HIs but are a pragmatic device, not a Bayes-exact fusion. (6) The bearing features are generic time-domain and spectral summaries, and bearing degradation is heterogeneous; physics-based features may change the picture. The extension to snapshot-level projection limits [54] is left for future work.

Conclusions. Viewing HI construction as an information budget yields a score that can be computed before any predictor is trained, a certificate that can be computed after one is, and four structural results on what squeezing, scalar projection, regime blindness and integration lose. On batteries, bearings and turbofan engines, the predicted effects are observed, but no learned encoder is superior to simple indicators. The contribution of the paper is the budget, not a new predictor.

Acknowledgments
Acknowledgements are withheld for double-anonymous review.

Funding
Funding information is withheld for double-anonymous review.

Author contributions
Author contributions are withheld for double-anonymous review.

Data availability
NASA PCoE, NASA IMS, C-MAPSS, CALCE CS2 and FEMTO-ST/PRONOSTIA data are publicly available (NASA Prognostics Data Repository, CALCE Battery Group, IEEE 2012 Prognostics and Health Management data challenge). The simulation and benchmark code, the stored results and the per-unit outputs used to generate all tables and figures are available in an anonymised repository:
https://anonymous.4open.science/r/information-budget-health-indicator-rul-C5CE/.

A Data, protocols and evidence tiers

Data. Public run-to-failure collections were used: NASA PCoE cells B0005, B0006, B0007 and B0018 [69]; CALCE CS2 cells [70]; the FEMTO-ST/PRONOSTIA bearings [71]; the NASA IMS bearings [72, 73]; and the C-MAPSS turbofan engines [74]. For batteries, the capacity is used only to define the EOL and is never an input. The EOL is the first cycle at which the rolling-median capacity falls to 75% (NASA) or 80% (CALCE) of the initial capacity; an absolute threshold of 1.4 Ah was not used because cell B0007 never reaches it. The lifetimes are 127, 73, 162 and 100 cycles (NASA) and 542, 499, 572 and 600 cycles (CS2_35 to CS2_38); the data are truncated at the EOL, and CALCE features are averaged over blocks of 4 cycles. Six per-cycle features are extracted from the charge and discharge records: constant-current time, constant-voltage time, height and voltage of the incremental-capacity peak, mean discharge temperature (NASA) or voltage drop at discharge onset (CALCE), and the discharge voltage at a fixed time (600 s for NASA, 1200 s for CALCE).

Further cells were screened by inclusion rules fixed before running any model (scripts and outputs are supplied). A NASA cell had to be at 24°C, have at least 100 discharge cycles, be discharged at a roughly constant 1.4 to 2.1 A, start between 1.5 and 2.1 Ah and reach the 75% EOL; only the four cells above qualify. Among the CALCE cells, CS2_5, 24 and 25 are partial-discharge tests, CS2_9 is discharged at a rate of 2C (twice the nominal capacity per hour), and CS2_3, 6 and 7 are short or follow other protocols, so none was used. CS2_33 and CS2_34 have the same chemistry and run to the EOL (485 and 479 cycles) but are discharged at 0.55 A; they are used only in a separate six-cell experiment, labelled protocol-heterogeneous, and the four-cell set remains the primary one.

For bearings, each run ends at failure, so EOL is the last snapshot. Condition 1 (nominally 1800 rpm, 4000 N; Bearing1_1–1_7) and condition 2 (1650 rpm, 4200 N; Bearing2_1–2_7) are evaluated separately, each with 7 units from the learning and the full test sets; condition 3 has only 3 units and was not used. The lifetimes are 2803, 871, 2375, 1428, 2463, 2448, 2259 snapshots (condition 1) and 911, 797, 1955, 751, 2311, 701, 230 snapshots (condition 2), each snapshot covering 0.1 s of 25.6 kHz acceleration every 10 s. Eight features are computed per snapshot: logarithm of the root mean square (RMS), kurtosis, crest factor and spectral entropy of the horizontal and of the vertical channel. Features are averaged over blocks of 20 (condition 1) or 8 (condition 2) snapshots, and the RUL is reported in snapshots.

Evaluation is leave-one-unit-out: each unit in turn is held out, the remaining units are used for training (three for NASA and four-cell CALCE, five for six-cell CALCE, six for each bearing condition), and metrics are computed at every step in the window 40–90% of life and pooled over the held-out units.

Further collections. FEMTO condition 3 (1500 rpm, 5000 N; Bearing3_1–3_3, with 515, 1637 and 434 snapshots, block length 10) and the NASA IMS bearings were kept aside and used only as confirmation sets. For IMS the four bearings that failed (Test 1 bearings 3 and 4, Test 2 bearing 1, Test 3 bearing 3; 2156, 2156, 984 and 6324 snapshots of 1 s at 20 kHz every 10 min) are used with one accelerometer channel each and four features per snapshot (log RMS, kurtosis, crest factor, spectral entropy), averaged over blocks of 20 snapshots. For C-MAPSS we use the single-condition subsets FD001 and FD003 (100 training engines run to failure and 100 truncated test engines with the official RUL labels each); the 14 informative sensors are standardised with training statistics. The 100 training engines are split by identifier into 80 engines to fit the HI constructions and 20 (identifier divisible by five) to select the bottleneck configuration and to calibrate the predictor; the test engines are predicted once at their last observed cycle, and 95% bootstrap intervals are computed over engines. The multi-regime subsets FD002 (260 training and 259 test engines) and FD004 (249 and 248) have six operating regimes; for them the only change is that sensors are standardised within regime, the six regimes being the clusters of the standardised operating settings found on the fitting engines (the clusters recover the six discrete settings exactly), the same preprocessing being applied to every method; the split is by identifier as above, with 208 and 200 fitting engines.

Methods. To isolate the effect of HI construction, every HI is mapped to the same scale (zero at the start of life, one at the EOL) and passed to the same calibrated predictor of Section 6.4: the mixed inverse-Gaussian law (21) with the drift taken from the slope of the smoothed HI over a trailing window of $\max(10, 0.25t)$ steps, pooled with the age law. The parameters $(c, w_{\mathrm{h}}, w_{\mathrm{a}})$ are chosen on HI paths that are out of sample for the HI construction (leave-one-training-unit-out for the small sets, the 20 calibration engines for C-MAPSS). The compared HIs are PCA-HI (first principal component); the Geo-opt HI (linear combination found by differential evolution to maximise the sum of Mon, Tre and Pro on the training units); for C-MAPSS, the ridge HI (supervised linear regression of the life fraction on the features); a β-VAE (causal gated recurrent unit (GRU) encoder, one-dimensional latent variable, Gaussian prior); VIB (the PGIB with a zero-drift prior, that is, without physics); the PGIB (state-dependent drift $\eta(H;\vartheta) = \vartheta_1 \exp(\vartheta_2 H)$); and PGIB-KF (Section 6.3). For the bottleneck models, the compression weight $\beta \in \{0.03, 0.3, 3, 30\}$ and the encoder (GRU or causal feed-forward window network) are selected by inner leave-one-training-unit-out validation of the predictive negative log-likelihood, with at most three inner folds when more than five training units are available; for PGIB-KF only $\beta \in \{0.03, 0.3, 3\}$ is searched. The held-out unit is never used. Learned models use three seeds, and the other HIs are deterministic. The sensor-free reference is the age law p_{age} of Section 6.4. The metrics are the RMSE and the mean absolute error (MAE) of the median prediction, the prediction interval coverage probability (PICP) and normalised average width (PINAW) of the 95% interval, and the continuous ranked probability score (CRPS) [66]. For C-MAPSS the asymmetric score is $\sum_i (e^{-d_i/13} - 1)$ for $d_i < 0$ and $\sum_i (e^{d_i/10} - 1)$ for $d_i \geq 0$, summed over engines, with d_i the predicted minus the true RUL [74].

Protocol history and evidence tiers. The study proceeded in five protocols, which determine how the numbers can be read. P1 (Appendix C) was the first benchmark; it showed that the integrating encoder under-covers and that the age law is competitive. P2 introduced the resulting improvements (out-of-sample calibration, age fusion, a prediction grid independent of the test unit) and was frozen, with the file hash recorded, before it was run on the two confirmation sets

Table 5. Algorithm 1: training of the PGIB and Bayesian FHT prognostics (Section 6).

Input: training sequences $\{\mathbf{X}_{1:T_n}^{(n)}, T^{(n)}\}$, threshold $D_{\text{fail}} = 1$, compression weight β, step Δt. **Output:** q_{θ^*}, $(\vartheta^*, \sigma_B^*)$, predictive law (21).
1. Causal encoder (temporal convolutional network or GRU): $u_\theta, s_\theta \leftarrow \text{softplus}(\cdot)$ from $\mathbf{X}_{1:k}$.
2. Sample the path by reparametrisation: $H_k = H_{k-1} + u_\theta \Delta t + s_\theta \sqrt{\Delta t}\, \epsilon_k$, $\epsilon_k \sim \mathcal{N}(0,1)$, $H_0 = 0$.
3. Conjugate drift update from $\Delta H_{1:t}$ to obtain $(\hat{\mu}_t, \sigma_{\mu,t}^2)$.
4. $\mathcal{L}_{\text{FHT}} = -\ln p(T_t \mid H_{1:t})$ from (21); $\mathcal{L}_{\text{KL}}$ from Proposition 6.
5. Update $(\theta, \vartheta, \sigma_B)$ with the AdamW optimiser on $\mathcal{L}_{\text{FHT}} + \beta \mathcal{L}_{\text{KL}}$ (plus a penalty on $H_{T_{\text{EOL}}} - D_{\text{fail}}$ at the EOL).

(FEMTO condition 3 and IMS) and before the development sets were re-run. On C-MAPSS FD001 the P2 methods showed that the integrating encoder is considerably worse than simple HIs even with 80 training engines. The diagnosis of Proposition 7 led to P3, the observation-corrected PGIB-KF, which was frozen and run once on FD003, a subset not used before, and exploratorily on the small sets. The unchanged P3 model was then frozen with regime-wise preprocessing and run once on FD002 and FD004. (A first launch used only the first 100 training engines because the identifier list was hard-coded in the script; it was stopped before any result was produced, and the script and the recorded hash were corrected.) After these results, P4 added the regime-aware encoder and a regime-specific ridge baseline and was run once on each subset, the choice between PGIB-KF and PGIB-KFR and of β being made on the calibration engines only. Because FD002 and FD004 had already been seen, they are development sets for P4, and no independent multi-regime data set was available (the successor N-CMAPSS has only six to ten units per subset). Finally, because the differences between learned encoders and simple HIs were of the size of the seed-to-seed variability, P5 retrained the learned encoders on the four subsets with ten fresh seeds, keeping architecture, β and calibration fixed; it supersedes the three-seed results where they disagree. The evidence tiers are therefore: (i) *clean confirmation*: C-MAPSS FD003, FD002 and FD004 for P3 (not for P4), and FEMTO condition 3 and IMS for P2 (not for P3, whose idea followed their P2 results); (ii) *development*: NASA, CALCE (four and six cells), FEMTO conditions 1 and 2 and C-MAPSS FD001, which informed the design and whose results are therefore not unbiased estimates of out-of-sample performance.

B Detailed benchmark results

This appendix gives the tables behind Section 7 with a short commentary; the numerical details are in the tables.

Few training units, development sets. No method is best everywhere (Table 6). The Geo-opt HI is best on NASA and six-cell CALCE, the PGIB on four-cell CALCE (38.4 against 43.3 for the best simple HI and 46.5 for the age law), and the age law on both FEMTO conditions. On NASA no learned HI beats the age law. The PGIB-KF, designed for many training units, is clearly worse than the PGIB with so few units.

Confirmation sets for P2. On the two sets not used in the design (Table 7), the β-VAE is best on FEMTO condition 3 and PCA-HI on IMS, the latter by a wide margin, and the PGIB is only 4% better than the age law on IMS. The bottleneck encoder is therefore not superior in the few-unit regime on unseen data.

Many training units: C-MAPSS. On FD003, the clean confirmation set of P3 (Table 8), a three-seed ensemble of PGIB-KF had the lowest RMSE, 19.4 (95% interval 16.0 to 22.8), against 21.9 for the Geo-opt HI, 26.8 for the ridge HI, 33.8 for PCA-HI, 39.5 for the integrating PGIB and 47.6 for the age law; the paired difference from the Geo-opt HI is -2.5 (-4.8 to -0.3). A single model has RMSE 24.2, and the ten-seed study shows that the three-seed result was favourable. On FD001 (Table 9) the PGIB-KF (22.9) is indistinguishable from the best simple HIs (21.8 to 22.2), with the lowest CRPS and narrower intervals. The integrating encoder is considerably worse on both subsets, and removing the error accumulation brings the same objective from the level of the age law to that of the best simple HIs or better.

Multi-regime confirmation: FD002 and FD004. The FD003 result does not replicate on the multi-regime subsets, which were frozen and run once (Tables 10 and 11). On FD002, PCA-HI is best (28.7) and PGIB-KF is slightly but significantly worse (+1.6, interval 0.3 to 3.0). On FD004,

the Geo-opt HI (29.7) and the ridge HI (30.9) are well ahead of PGIB-KF (40.6), which still beats PCA-HI, the β-VAE, the integrating PGIB and the age law but under-covers (coverage 81% on FD002 and 79% on FD004).

Regime-aware observation model (P4). Adding the regime to the observation model (PGIB-KFR) narrows the gap on the multi-regime subsets but does not close it. On FD002 the PGIB-KFR (29.6) is indistinguishable from PCA-HI, the Geo-opt HI and the regime-specific ridge HI (28.4, the lowest). On FD004 it improves from 40.6 to 34.8 and beats PCA-HI (-9.5, -12.4 to -6.6) but stays behind the Geo-opt HI ($+5.1$, 2.3 to 7.9) and the ridge HI. Two points limit the reading. The pre-declared selection by calibration likelihood chose PGIB-KF rather than PGIB-KFR on three of the four subsets, and the single-regime check failed: with one regime, PGIB-KFR is PGIB-KF up to an extra input and the initialisation, yet it is worse on FD001 (26.5 against 22.9) and FD003 (25.4 against 19.4). Differences of three to six RMSE units between near-equivalent configurations are within the training variability. We therefore do not claim that the regime-aware model improves prognostics; the result is consistent with Proposition 5 but does not demonstrate it.

Seed variability and ten-seed ensembles (P5). The learned models were retrained with ten fresh seeds each, keeping architecture, β and calibration fixed (Table 4, Figure 7). The ensembles have a coverage of 84% to 94%. PGIB-KFR is worse than PGIB-KF on FD001 by 3.7 RMSE units (Welch test [75], $p = 0.02$) and gains only with six regimes on FD004 (-4.0, $p = 0.17$).

Ablations and fusion. On FD003, removing the bottleneck ($\beta = 0$) or the physics prior changes the RMSE of the integrating PGIB by less than two units (39.1 and 37.9 against 39.9), whereas removing the epistemic drift variance raises it to 45.9 and lowers the coverage from 95% to 92%. The age fusion (Table 12) improves the point error of most HIs when the HI is poor or the units are few; for example, the RMSE of PCA-HI on FD001 falls from 29.0 to 21.8.

Information certificates. The certified information (Table 13) is vacuous for NASA, the three FEMTO conditions and, except for PCA-HI, IMS. It is positive only on CALCE, where it is 0.60 nats for the PGIB against 0.41 for the age law with four cells, and 0.35 against 0.31 with six cells. Only on CALCE does a learned HI thus add certified information beyond the age.

C Initial benchmark protocol (P1)

The first benchmark used a simpler protocol (P1). Every HI was calibrated on in-sample training paths, the plain first-hitting-time law (21) was used without age fusion, and the predictive grid extended to three times the held-out unit's own life, which leaks the length of the test unit into the support of the predictive law (removed in P2). The pilot on NASA B0005, the results below and the observation that the age law is competitive motivated P2. The P1 results are reported for completeness and are not used for the conclusions of the main text.

Pilot run. A pilot on the NASA B0005 fold, with a GRU-only encoder and $\beta \in \{0.003, 0.03, 0.3\}$, gave a PGIB RMSE of 56.3 cycles and zero interval coverage, with the selected β at the edge of the grid. The selection grid was therefore extended and the feed-forward encoder added as a candidate. Both changes are chosen per fold by inner validation, but the decision to introduce them was made after seeing a held-out result for one fold. No baseline was modified, and no change was made after the full runs reported below; the bearing experiments were run once with the final protocol.

Results under P1. The outcome depends on the data set (Tables 14 and 15), and the age law is needed to read it. On NASA the age-law RMSE is 39.8 cycles; PCA-HI (17.8), the Geo-opt HI (21.9), the β-VAE (30.8) and VIB (33.3) beat it, whereas the PGIB (47.6) does not, and its intervals cover only 42% of the true RULs. On CALCE the age-law RMSE is 49.3; only the PGIB (33.0) beats it clearly, while PCA-HI, the Geo-opt HI and the β-VAE (117 to 164) are considerably worse than the age law. With the two 0.5C-discharge cells added, the PGIB keeps the lowest RMSE (50.4) but its margin over the age law (54.7) is only 8%. On bearings the age-law RMSE (602 and 664 snapshots for conditions 1 and 2) is comparable to the standard deviation of the pooled RUL, and most HIs do no better: the PGIB has the lowest RMSE in condition 1 (524.5, 13% below the age law) but gives almost no benefit in condition 2 (621.8 against 664). Two long-lived units dominate the pooled error in condition 2.

Table 6. Protocol P2, development sets. RMSE, MAE and CRPS in cycles (batteries) or 10 s snapshots (bearings); mean ± standard deviation over seeds; bold: lowest RMSE.

NASA PCoE (4 cells)					
Method	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only (no sensors)	34.4	28.7	84	2.68	21.0
PCA-HI	24.9	19.3	95	2.46	13.8
Geo-opt HI	**24.3**	20.1	93	3.22	17.6
β-VAE-HI	31.7±2.2	25.3±1.8	98±0	4.24±0.17	20.0±0.9
VIB-HI (no physics)	33.9±1.2	28.3±1.2	90±1	5.40±0.03	27.1±0.7
PGIB-HI (ens.)	34.8	29.0	93	6.51	27.3
PGIB-KF-HI (ens.)	44.3	39.4	84	4.55	29.1

CALCE CS2 (4 cells)					
Method	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only (no sensors)	46.5	40.0	100	1.13	28.6
PCA-HI	51.3	44.0	100	1.06	30.2
Geo-opt HI	43.3	35.7	98	0.98	26.5
β-VAE-HI	49.9±0.9	41.6±1.0	100	1.09±0.00	29.5±0.4
VIB-HI (no physics)	48.3±1.4	40.6±0.9	83±4	0.85±0.00	30.8±0.8
PGIB-HI (ens.)	**38.4**	34.2	99	0.74	23.3
PGIB-KF-HI (ens.)	50.3	36.6	77	0.83	33.0

CALCE CS2 (6 cells)					
Method	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only (no sensors)	50.6	45.5	100	1.13	30.1
PCA-HI	56.8	50.0	100	1.09	32.8
Geo-opt HI	**46.3**	43.2	100	1.02	27.6
β-VAE-HI	73.5±4.9	60.9±3.9	93±3	1.04±0.02	42.4±3.2
VIB-HI (no physics)	54.7±1.7	48.7±1.5	92±1	0.91±0.01	32.4±1.2
PGIB-HI (ens.)	48.9	44.8	90	0.87	30.8
PGIB-KF-HI (ens.)	71.9	63.6	84	0.92	45.2

FEMTO cond. 1 (7 bearings)					
Method	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only (no sensors)	**495.8**	371.4	94	3.45	303.7
PCA-HI	786.9	621.6	72	4.72	489.2
Geo-opt HI	533.2	416.8	96	3.19	311.5
β-VAE-HI	737.1±191.7	525.4±102.0	85±6	4.84±0.04	421.4±87.9
VIB-HI (no physics)	584.1±29.4	467.0±26.4	82±5	3.48±0.13	357.9±29.0
PGIB-HI (ens.)	534.7	401.8	84	4.67	340.9

FEMTO cond. 2 (7 bearings)					
Method	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only (no sensors)	**430.6**	373.5	97	10.38	278.6
PCA-HI	558.3	450.5	67	8.52	391.1
Geo-opt HI	504.9	414.7	85	11.22	396.1
β-VAE-HI	531.2±11.3	434.6±20.1	88±2	9.78±0.02	368.4±2.0
VIB-HI (no physics)	448.2±0.4	337.7±1.3	97	11.39±0.14	318.5±2.6
PGIB-HI (ens.)	449.5	333.6	97	13.97	341.2

Table 7. Protocol P2, confirmation sets (snapshots). PGIB-KF is exploratory here.

FEMTO cond. 3 (3 bearings)					
Method	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only (no sensors)	563.6	529.7	37	10.60	460.2
PCA-HI	507.5	418.4	32	6.50	398.8
Geo-opt HI	567.1	525.1	30	12.82	453.4
β-VAE-HI	**462.0±20.8**	389.5±23.6	37	8.86±0.72	363.4±20.9
VIB-HI (no physics)	505.0±0.1	438.3±0.3	37	12.55±0.00	442.5±0.2
PGIB-HI (ens.)	510.3	450.0	37	12.56	453.5
PGIB-KF-HI (ens.)	555.0	479.3	33	9.10	438.6

NASA IMS (4 bearings)					
Method	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only (no sensors)	1692.8	1503.1	83	10.78	1106.3
PCA-HI	**745.2**	605.7	96	8.05	498.0
Geo-opt HI	942.7	702.8	99	16.31	771.6
β-VAE-HI	2769.6±282.2	1324.8±242.7	84±6	10.31±0.71	1184.6±197.8
VIB-HI (no physics)	1884.6±10.5	1434.4±12.4	91	16.41±0.01	1122.5±8.8
PGIB-HI (ens.)	1623.8	1288.1	98	16.49	1017.5
PGIB-KF-HI (ens.)	1852.3	1519.8	43	12.29	1545.6

Table 8. C-MAPSS FD003 (clean confirmation set of P3; PGIB-KFR and regime-specific ridge rows are development results). RMSE: single models, mean over seeds; seed-avg.: RMSE of the seed-averaged prediction with 95% bootstrap interval over engines.

Method	RMSE	RMSE seed-avg. [95% CI]	MAE	Score	PICP [%]	PINAW	CRPS
Age-only (no sensors)	47.6	42.3–52.6	39.6	114536	99	1.91	28.6
PCA-HI	33.8	28.4–38.3	25.5	10747	97	1.47	19.7
Geo-opt HI	21.9	17.8–26.0	15.9	1864	100	1.19	13.1
Ridge-HI (supervised)	26.8	22.9–30.6	21.0	6147	93	1.20	16.2
Ridge-HI, regime-specific	26.8	22.8–30.6	21.0	6147	93	1.20	16.2
β-VAE-HI	40.6±1.1	34.9–45.6	32.0±0.7	29236	99	1.69	23.8±0.3
VIB-HI (no physics prior)	37.9±0.8	31.7–42.2	29.3±0.8	18680	96	2.16	24.2±0.6
PGIB-HI (GRU/window encoder)	39.9±1.0	33.9–44.4	31.2±0.4	21945	95	1.98	24.3±0.3
PGIB-HI, 3-seed ensemble	39.5	34.1–45.0	31.1	17643	95	1.98	24.1
PGIB-KF-HI	24.2±2.5	16.4–23.1	18.6±1.5	2296	94	1.19	14.8±0.4
PGIB-KF-HI, 3-seed ensemble	19.4	16.0–22.8	14.6	790	97	1.20	12.2
PGIB-KFR-HI (regime-aware)	27.4±0.1	21.8–29.3	21.2±0.3	5417	95	1.24	15.6±0.4
PGIB-KFR-HI, 3-seed ensemble	25.4	21.6–29.1	20.3	4170	97	1.24	14.6

Table 9. C-MAPSS FD001 (development set; same layout as Table 8).

Method	RMSE	RMSE seed-avg. [95% CI]	MAE	Score	PICP [%]	PINAW	CRPS
Age-only (no sensors)	36.6	32.4–40.8	30.5	8023	99	1.18	21.1
PCA-HI	21.8	19.1–24.4	17.9	908	96	0.83	12.6
Geo-opt HI	22.0	19.5–24.3	18.0	953	96	0.83	12.7
Ridge-HI (supervised)	26.0	22.0–29.8	19.7	1606	97	0.85	14.1
Ridge-HI, regime-specific	26.0	22.0–29.8	19.7	1606	97	0.85	14.1
β-VAE-HI	22.2±0.4	19.0–24.5	18.0±0.5	875	95	0.82	12.7±0.3
VIB-HI (no physics prior)	34.2±0.3	28.8–38.3	27.1±0.7	7386	91	0.96	19.3±0.4
PGIB-HI (GRU/window encoder)	35.6±1.0	29.8–40.9	26.9±0.6	11524	94	0.90	19.6±0.4
PGIB-HI, 3-seed ensemble	35.4	29.9–40.9	26.6	10874	94	0.90	19.4
PGIB-KF-HI	27.0±2.2	18.8–27.1	20.2±1.2	2868	82	0.56	14.9±1.1
PGIB-KF-HI, 3-seed ensemble	22.9	18.6–26.9	16.6	1309	93	0.56	12.1
PGIB-KFR-HI (regime-aware)	26.9±3.6	21.8–31.0	20.2±2.6	2937	94	0.64	14.4±2.1
PGIB-KFR-HI, 3-seed ensemble	26.5	22.0–30.9	19.5	2094	96	0.64	13.8

Table 10. C-MAPSS FD002 (multi-regime; confirmation set for P3, development set for P4; same layout as Table 8).

Method	RMSE	RMSE seed-avg. [95% CI]	MAE	Score	PICP [%]	PINAW	CRPS
Age-only (no sensors)	38.3	35.2–41.2	31.4	53131	97	0.82	21.6
PCA-HI	28.7	26.0–31.4	21.9	10331	95	0.66	15.7
Geo-opt HI	30.5	27.0–33.9	21.8	16164	98	0.59	15.2
Ridge-HI (supervised)	29.4	26.1–32.6	21.7	11935	94	0.58	15.1
Ridge-HI, regime-specific	28.4	25.3–31.5	20.9	11149	94	0.58	14.7
β-VAE-HI	30.6±0.8	27.3–33.1	24.0±0.7	11996	92	0.65	17.0±0.4
VIB-HI (no physics prior)	36.4±0.4	33.3–39.4	29.8±0.2	26118	82	0.68	21.1±0.1
PGIB-HI (GRU/window encoder)	36.8±0.2	33.6–39.4	30.1±0.5	28553	83	0.68	21.4±0.5
PGIB-HI, 3-seed ensemble	36.6	33.7–39.4	29.9	26625	82	0.68	21.3
PGIB-KF-HI	31.3±1.5	27.8–33.1	25.4±1.5	14139	81	0.79	18.6±1.1
PGIB-KF-HI, 3-seed ensemble	30.4	27.8–32.9	24.5	10983	81	0.79	18.0
PGIB-KFR-HI (regime-aware)	30.7±2.0	27.2–32.2	24.8±2.6	14802	86	0.91	18.5±1.9
PGIB-KFR-HI, 3-seed ensemble	29.6	27.0–32.1	23.7	13089	87	0.91	17.8

Table 11. C-MAPSS FD004 (multi-regime; confirmation set for P3, development set for P4; same layout as Table 8).

Method	RMSE	RMSE seed-avg. [95% CI]	MAE	Score	PICP [%]	PINAW	CRPS
Age-only (no sensors)	54.7	50.9–58.5	46.0	611896	95	1.31	31.8
PCA-HI	44.3	40.7–48.0	35.4	104864	92	1.03	24.9
Geo-opt HI	29.7	26.6–32.7	21.9	9468	100	0.86	16.1
Ridge-HI (supervised)	30.9	28.1–33.4	23.8	11632	94	1.14	18.5
Ridge-HI, regime-specific	31.1	28.2–33.9	24.0	10794	92	1.14	18.6
β-VAE-HI	48.1±3.1	42.7–50.2	39.0±3.0	294449	93	1.17	27.7±1.9
VIB-HI (no physics prior)	51.8±1.0	47.3–56.2	41.9±0.6	697542	90	1.13	29.5±0.4
PGIB-HI (GRU/window encoder)	49.9±2.4	44.2–53.9	39.5±1.5	1143425	90	1.42	29.3±0.7
PGIB-HI, 3-seed ensemble	49.5	44.8–54.3	38.9	1085286	91	1.42	28.9
PGIB-KF-HI	42.1±2.8	37.2–43.6	33.9±1.9	241870	78	1.08	25.6±1.3
PGIB-KF-HI, 3-seed ensemble	40.6	37.3–44.0	32.9	124580	79	1.07	24.7
PGIB-KFR-HI (regime-aware)	37.1±2.5	31.4–37.2	29.4±1.5	187056	85	1.12	22.3±0.8
PGIB-KFR-HI, 3-seed ensemble	34.8	31.8–37.8	27.8	37063	85	1.12	21.0

Table 12. Effect of the age fusion: RMSE with fusion / without fusion (after recalibration with $w_a = 0$).

HI	NASA	CALCE-4	CALCE-6	FEMTO-1	FEMTO-2	FEMTO-3	IMS
PCA-HI	25 / 18	51 / 186	57 / 184	787 / 1470	558 / 564	507 / 503	745 / 745
Geo-opt HI	24 / 32	43 / 131	46 / 126	533 / 1083	505 / 489	567 / 437	943 / 943
β-VAE-HI	32 / 26	50 / 110	73 / 270	737 / 1421	531 / 457	462 / 396	2770 / 2770
VIB-HI (no physics)	34 / 30	48 / 59	55 / 106	584 / 681	448 / 469	505 / 507	1885 / 1885
PGIB-HI (ens.)	35 / 30	38 / 35	49 / 85	535 / 754	449 / 445	510 / 509	1624 / 1624
PGIB-KF-HI (ens.)	44 / 44	50 / 59	72 / 88	–	–	555 / 556	1852 / 1852

Table 13. Protocol P2, information certified by the achieved error (nats); < 0: vacuous. $h(T)$: entropy of the pooled held-out RUL.

Dataset	$h(T)$	Age-only	PCA	Geo-opt.	β-VAE	VIB	PGIB	PGIB-KF
NASA	4.36	< 0	< 0	< 0	< 0	< 0	< 0	< 0
CALCE-4	5.67	0.41	0.31	0.48	0.34	0.37	0.60	0.33
CALCE-6	5.66	0.31	0.20	0.40	< 0	0.24	0.35	< 0
FEMTO-1	7.24	< 0	< 0	< 0	< 0	< 0	< 0	–
FEMTO-2	7.04	< 0	< 0	< 0	< 0	< 0	< 0	–
FEMTO-3	6.70	< 0	< 0	< 0	< 0	< 0	< 0	< 0
IMS	8.05	< 0	0.02	< 0	< 0	< 0	< 0	< 0

Table 14. Protocol P1, battery benchmarks, leave-one-unit-out (mean ± standard deviation over seeds). RMSE, MAE and CRPS in cycles.

NASA PCoE (leave-one-unit-out)								
Method	Mon	Tre	Pro	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only reference (no sensors)	–	–	–	39.8	34.7	–	–	–
PCA-HI	0.27	0.85	0.77	17.8	14.0	97	2.52	11.1
Geo-opt HI	0.21	0.93	0.95	21.9	17.0	90	2.43	12.8
β-VAE-HI	0.30±0.01	0.71±0.00	0.95±0.01	30.8±0.8	26.0±0.5	95±1	2.06±0.08	17.6±0.5
VIB-HI (no physics prior)	1.00	1.00±0.00	0.67±0.03	33.3±2.8	27.7±2.1	88±4	3.47±0.10	20.5±2.3
PGIB-HI	1.00	1.00±0.00	0.67±0.01	47.6±2.1	42.3±1.9	42±3	2.39±0.15	34.3±1.5
CALCE CS2 (4 cells, 1C/1C) (leave-one-unit-out)								
Method	Mon	Tre	Pro	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only reference (no sensors)	–	–	–	49.3	43.8	–	–	–
PCA-HI	0.05	0.72	0.83	130.5	110.4	92	2.74	82.3
Geo-opt HI	0.39	0.95	0.98	117.2	86.8	90	3.20	69.2
β-VAE-HI	0.02±0.01	0.72±0.01	0.80±0.01	163.7±0.7	148.0±0.9	83±1	1.87±0.02	111.1±0.7
VIB-HI (no physics prior)	1.00	1.00±0.00	0.92±0.01	53.2±0.9	47.2±1.4	71±4	1.24±0.13	38.4±0.7
PGIB-HI	1.00	1.00±0.00	0.95±0.01	33.0±4.9	29.9±3.9	55±8	0.34±0.02	22.6±3.1
CALCE CS2 (6 cells, incl. 0.5C-discharge CS2_33/34) (leave-one-unit-out)								
Method	Mon	Tre	Pro	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only reference (no sensors)	–	–	–	54.7	50.0	–	–	–
PCA-HI	0.13	0.28	0.21	191.8	172.0	50	0.99	149.6
Geo-opt HI	0.39	0.95	0.98	106.9	82.7	95	3.11	63.7
β-VAE-HI	0.05±0.02	0.52±0.10	0.33±0.04	201.6±5.3	179.9±5.0	48±0	1.46±0.18	156.1±3.1
VIB-HI (no physics prior)	1.00	1.00±0.00	0.87±0.02	69.7±6.0	54.4±8.8	90±5	2.24±0.23	44.9±4.8
PGIB-HI	1.00	1.00±0.00	0.91±0.01	50.4±4.4	44.7±5.1	69±5	0.58±0.02	33.4±4.2

Table 15. Protocol P1, FEMTO bearing benchmarks. RMSE, MAE and CRPS in 10 s snapshots.

FEMTO bearings, condition 1 (7 units) (leave-one-unit-out)								
Method	Mon	Tre	Pro	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only reference (no sensors)	–	–	–	602.5	515.4	–	–	–
PCA-HI	0.06	0.56	0.70	784.5	663.2	93	2.80	485.7
Geo-opt HI	0.04	0.29	0.39	770.2	623.3	91	3.34	459.1
β-VAE-HI	0.07±0.02	0.58±0.01	0.73±0.01	779.8±51.1	664.4±35.6	91±3	2.69±0.13	492.4±20.6
VIB-HI (no physics prior)	1.00	1.00±0.00	0.71±0.02	570.1±56.0	471.0±50.7	78±5	3.04±0.21	365.6±44.1
PGIB-HI	1.00	1.00±0.00	0.71±0.02	524.5±45.3	423.6±37.3	75±5	2.65±0.10	336.5±31.8
FEMTO bearings, condition 2 (7 units) (leave-one-unit-out)								
Method	Mon	Tre	Pro	RMSE	MAE	PICP [%]	PINAW	CRPS
Age-only reference (no sensors)	–	–	–	664.4	584.6	–	–	–
PCA-HI	0.04	0.43	0.17	613.9	487.6	54	2.25	433.9
Geo-opt HI	0.06	0.37	0.46	559.2	457.1	73	2.33	356.5
β-VAE-HI	0.06±0.01	0.46±0.05	0.42±0.16	539.8±31.7	439.6±24.6	70±2	2.01±0.06	348.6±26.1
VIB-HI (no physics prior)	1.00	0.99±0.00	0.39±0.02	616.8±1.5	493.8±1.5	41±1	2.62±0.23	451.1±3.2
PGIB-HI	1.00	0.99±0.00	0.46±0.02	621.8±4.3	498.2±8.1	36±2	2.25±0.01	464.3±7.9

Table 16. Protocol P1, information certified by the achieved error (Proposition 1), in nats; < 0: vacuous. $h(T)$: entropy of the pooled held-out RUL.

Dataset	$h(T)$	PCA	Geo-opt.	β-VAE	VIB	PGIB
NASA	4.36	0.06	< 0	< 0	< 0	< 0
CALCE (4)	5.67	< 0	< 0	< 0	0.27	0.76
CALCE (6)	5.66	< 0	< 0	< 0	< 0	0.32
FEMTO c. 1	7.24	< 0	< 0	< 0	< 0	< 0
FEMTO c. 2	7.04	< 0	< 0	< 0	< 0	< 0




Figure 8. Example RUL predictions with 95% intervals on one held-out unit per data set (NASA B0005, CALCE CS2_35, FEMTO Bearing1_1), for PCA-HI (left) and PGIB (right); each panel gives the RMSE and the coverage on that unit.

The ablations (in the supplied result files) support the bottleneck on all five sets (for example RMSE 54.4 → 47.6 on NASA and 42.3 → 33.0 on CALCE) and the epistemic drift variance for coverage (for example 14 → 42% on NASA). The physics prior helps on CALCE and FEMTO condition 1 but not on NASA or FEMTO condition 2. With only three to six training units per fold, the validation signal that selects the encoder is itself noisy; on NASA it chose the strongest compression ($\beta = 30$), at the edge of the grid, in all eight selections.

Geometric scores versus error. Across the five HIs of each data set, the rank correlation between the geometric score Mon + Tre + Pro and the RMSE is +0.90 on NASA (a higher geometric score goes with a larger error), −1.00 on CALCE, −0.90 on six-cell CALCE, −0.60 on FEMTO condition 1 and +0.60 on condition 2. The geometric criteria therefore did not rank the HIs consistently by prognostic error. This is an association over five methods per data set and not evidence for the mechanism of Theorem 2: the VIB and PGIB HIs have Mon ≈ Tre ≈ 1 because their velocity is constrained to be positive, not because of a squeeze.

Information on real data. A direct estimate of $I(T;H)$ with the Kraskov–Stögbauer–Grassberger estimator [48] on rank-transformed window summaries gave, for several HIs, values above the estimate for the 12-dimensional raw sensor summary, which is impossible for a true mutual information because the summary contains the HI. This reflects the bias of the estimator in 12 dimensions at a few hundred samples, a known limitation [49, 50], and we therefore do not report η_{info} on real data. The certificate of Proposition 1 avoids high-dimensional estimation (Table 16); it is positive only for the PGIB on CALCE (0.76 nats) and six-cell CALCE (0.32), VIB on CALCE (0.27) and PCA-HI on NASA (0.06), and vacuous otherwise. This is a more modest reading of the benchmark than the RMSE tables alone.

References

[1] Si X-S, Wang W, Hu C-H and Zhou D-H 2011 Remaining useful life estimation – a review on the statistical data driven approaches *Eur. J. Oper. Res.* **213** 1–14 doi:10.1016/j.ejor.2010.11.018

[2] Lei Y, Li N, Guo L, Li N, Yan T and Lin J 2018 Machinery health prognostics: a systematic review from data acquisition to RUL prediction *Mech. Syst. Signal Process.* **104** 799–834 doi:10.1016/j.ymssp.2017.11.016

[3] Javed K, Gouriveau R and Zerhouni N 2017 State of the art and taxonomy of prognostics approaches, trends of prognostics applications and open issues towards maturity at different technology readiness levels *Mech. Syst. Signal Process.* **94** 214–36 doi:10.1016/j.ymssp.2017.01.050

[4] Zio E 2022 Prognostics and health management (PHM): where are we and where do we (need to) go in theory and practice *Reliab. Eng. Syst. Saf.* **218** 108119 doi:10.1016/j.ress.2021.108119

[5] Liao L and Köttig F 2014 Review of hybrid prognostics approaches for remaining useful life prediction of engineered systems, and an application to battery life prediction *IEEE Trans. Reliab.* **63** 191–207 doi:10.1109/TR.2014.2299152

[6] Li X, Ding Q and Sun J-Q 2018 Remaining useful life estimation in prognostics using deep convolution neural networks *Reliab. Eng. Syst. Saf.* **172** 1–11 doi:10.1016/j.ress.2017.11.021

[7] Fink O, Wang Q, Svensén M, Dersin P, Lee W-J and Ducoffe M 2020 Potential, challenges and future directions for deep learning in prognostics and health management applications *Eng. Appl. Artif. Intell.* **92** 103678 doi:10.1016/j.engappai.2020.103678

[8] Whitmore G A 1995 Estimating degradation by a Wiener diffusion process subject to measurement error *Lifetime Data Anal.* **1** 307–19 doi:10.1007/BF00985762

[9] Lee M-L T and Whitmore G A 2006 Threshold regression for survival analysis: modeling event times by a stochastic process reaching a boundary *Stat. Sci.* **21** 501–13 doi:10.1214/088342306000000330

[10] Wang L, Chen S, Cai Z, Liu W and Ye Z 2026 Cross-cycle health indicator construction and state of health prediction of lithium-ion batteries by cross recurrence quantification analysis *J. Reliab. Sci. Eng.* **2** 035302 doi:10.1088/3050-2454/ae8dd1

[11] Gu H, Li Y, Jiang L and Luo Z 2025 A generalized approach for remaining useful life prediction considering the multi-source uncertainty of mechanical systems *J. Reliab. Sci. Eng.* **1** 025301 doi:10.1088/3050-2454/add5fa

[12] Bisoyi S, Kumar Rathi A and Mahato S 2026 Reliability assessment of remaining useful life predictions of roller bearings using deep learning models *J. Reliab. Sci. Eng.* **2** 025302 doi:10.1088/3050-2454/ae61b4

[13] Aven T 2021 The reliability science: its foundation and link to risk science and other sciences *Reliab. Eng. Syst. Saf.* **215** 107863 doi:10.1016/j.ress.2021.107863

[14] Sun C-P 2025 Reliability science and engineering: a catalyst for engineering innovation *J. Reliab. Sci. Eng.* **1** 020201 doi:10.1088/3050-2454/adbf22

[15] Coble J and Hines J W 2009 Identifying optimal prognostic parameters from data: a genetic algorithms approach *Annu. Conf. of the Prognostics and Health Management Society* **1**

[16] Javed K, Gouriveau R, Zerhouni N and Nectoux P 2013 A feature extraction procedure based on trigonometric functions and cumulative descriptors to enhance prognostics modeling *Proc. IEEE Conf. on Prognostics and Health Management* pp 1–7 doi:10.1109/ICPHM.2013.6621413

[17] Zhang B, Zhang L and Xu J 2016 Degradation feature selection for remaining useful life prediction of rolling element bearings *Qual. Reliab. Eng. Int.* **32** 547–54 doi:10.1002/qre.1771

[18] Qian F and Niu G 2015 Remaining useful life prediction using ranking mutual information based monotonic health indicator *Proc. Prognostics and System Health Management Conf.* pp 1–5 doi:10.1109/PHM.2015.7380042

[19] Guo L, Li N, Jia F, Lei Y and Lin J 2017 A recurrent neural network based health indicator for remaining useful life prediction of bearings *Neurocomputing* **240** 98–109 doi:10.1016/j.neucom.2017.02.045

[20] Kingma D P and Welling M 2014 Auto-encoding variational Bayes *Proc. Int. Conf. on Learning Representations* arXiv:1312.6114

[21] Higgins I, Matthey L, Pal A, Burgess C, Glorot X, Botvinick M, Mohamed S and Lerchner A 2017 β-VAE: learning basic visual concepts with a constrained variational framework *Proc. Int. Conf. on Learning Representations*

[22] Severson K A et al 2019 Data-driven prediction of battery cycle life before capacity degradation *Nat. Energy* **4** 383–91 doi:10.1038/s41560-019-0356-8

[23] Saxena A, Celaya J, Balaban E, Goebel K, Saha B, Saha S and Schwabacher M 2008 Metrics for evaluating performance of prognostic techniques *Proc. Int. Conf. on Prognostics and Health Management* pp 1–17 doi:10.1109/PHM.2008.4711436

[24] Folks J L and Chhikara R S 1978 The inverse Gaussian distribution and its statistical application – a review *J. R. Stat. Soc. B* **40** 263–75 doi:10.1111/j.2517-6161.1978.tb01039.x

[25] Chhikara R S and Folks J L 1989 *The Inverse Gaussian Distribution: Theory, Methodology, and Applications* (New York: Marcel Dekker)

[26] Tweedie M C K 1957 Statistical properties of inverse Gaussian distributions. I *Ann. Math. Stat.* **28** 362–77 doi:10.1214/aoms/1177706964

[27] Tang S, Yu C, Wang X, Guo X and Si X 2014 Remaining useful life prediction of lithium-ion batteries based on the Wiener process with measurement error *Energies* **7** 520–47 doi:10.3390/en7020520

[28] Gebraeel N Z, Lawley M A, Li R and Ryan J K 2005 Residual-life distributions from component degradation signals: a Bayesian approach *IIE Trans.* **37** 543–57 doi:10.1080/07408170590929018

[29] Wang X 2010 Wiener processes with random effects for degradation data *J. Multivariate Anal.* **101** 340–51 doi:10.1016/j.jmva.2008.12.007

[30] Si X-S, Wang W, Hu C-H, Zhou D-H and Pecht M G 2012 Remaining useful life estimation based on a nonlinear diffusion degradation process *IEEE Trans. Reliab.* **61** 50–67 doi:10.1109/TR.2011.2182221

[31] Medjaher K, Tobon-Mejia D A and Zerhouni N 2012 Remaining useful life estimation of critical components with application to bearings *IEEE Trans. Reliab.* **61** 292–302 doi:10.1109/TR.2012.2194175

[32] Ye Z-S and Xie M 2015 Stochastic modelling and analysis of degradation for highly reliable products *Appl. Stoch. Models Bus. Ind.* **31** 16–32 doi:10.1002/asmb.2063

[33] Zhang Z, Si X, Hu C and Lei Y 2018 Degradation data analysis and remaining useful life estimation: a review on Wiener-process-based methods *Eur. J. Oper. Res.* **271** 775–96 doi:10.1016/j.ejor.2018.02.033

[34] Sankararaman S and Goebel K 2013 Why is the remaining useful life prediction uncertain? *Annu. Conf. of the Prognostics and Health Management Society* **5** doi:10.36001/phmconf.2013.v5i1.2263

[35] Sankararaman S 2015 Significance, interpretation, and quantification of uncertainty in prognostics and remaining useful life prediction *Mech. Syst. Signal Process.* **52–53** 228–47 doi:10.1016/j.ymssp.2014.05.029

[36] Hüllermeier E and Waegeman W 2021 Aleatoric and epistemic uncertainty in machine learning: an introduction to concepts and methods *Mach. Learn.* **110** 457–506 doi:10.1007/s10994-021-05946-3

[37] Kendall A and Gal Y 2017 What uncertainties do we need in Bayesian deep learning for computer vision? *Advances in Neural Information Processing Systems* **30** arXiv:1703.04977

[38] Lakshminarayanan B, Pritzel A and Blundell C 2017 Simple and scalable predictive uncertainty estimation using deep ensembles *Advances in Neural Information Processing Systems* **30** arXiv:1612.01474

[39] Shannon C E 1948 A mathematical theory of communication *Bell Syst. Tech. J.* **27** 379–423, 623–56 doi:10.1002/j.1538-7305.1948.tb01338.x

[40] Cover T M and Thomas J A 2006 *Elements of Information Theory 2nd edn* (Hoboken, NJ: Wiley-Interscience)

[41] Tishby N, Pereira F C and Bialek W 2000 The information bottleneck method arXiv:physics/0004057

[42] Alemi A A, Fischer I, Dillon J V and Murphy K 2017 Deep variational information bottleneck *Proc. Int. Conf. on Learning Representations* arXiv:1612.00410

[43] Poole B, Ozair S, van den Oord A, Alemi A A and Tucker G 2019 On variational bounds of mutual information *Proc. Int. Conf. on Machine Learning (PMLR vol 97)* pp 5171–80

[44] Achille A and Soatto S 2018 Emergence of invariance and disentanglement in deep representations *J. Mach. Learn. Res.* **19** 1–34

[45] Kolchinsky A, Tracey B D and Wolpert D H 2019 Nonlinear information bottleneck *Entropy* **21** 1181 doi:10.3390/e21121181

[46] Saxe A M, Bansal Y, Dapello J, Advani M, Kolchinsky A, Tracey B D and Cox D D 2019 On the information bottleneck theory of deep learning *J. Stat. Mech.: Theory Exp.* **2019** 124020 doi:10.1088/1742-5468/ab3985

[47] Vasicek O 1976 A test for normality based on sample entropy *J. R. Stat. Soc. B* **38** 54–9 doi:10.1111/j.2517-6161.1976.tb01566.x

[48] Kraskov A, Stögbauer H and Grassberger P 2004 Estimating mutual information *Phys. Rev. E* **69** 066138 doi:10.1103/PhysRevE.69.066138

[49] Paninski L 2003 Estimation of entropy and mutual information *Neural Comput.* **15** 1191–253 doi:10.1162/089976603321780272

[50] McAllester D and Stratos K 2020 Formal limitations on the measurement of mutual information *Proc. Int. Conf. on Artificial Intelligence and Statistics (PMLR vol 108)* pp 875–84

[51] Van Trees H L 1968 *Detection, Estimation, and Modulation Theory, Part I* (New York: Wiley)

[52] Gill R D and Levit B Y 1995 Applications of the van Trees inequality: a Bayesian Cramér–Rao bound *Bernoulli* **1** 59–79 doi:10.2307/3318681

[53] Tichavský P, Muravchik C H and Nehorai A 1998 Posterior Cramér–Rao bounds for discrete-time nonlinear filtering *IEEE Trans. Signal Process.* **46** 1386–96 doi:10.1109/78.668800

[54] Anonymous 2026 *Reference withheld for double-blind review*

[55] Anonymous 2026 *Reference withheld for double-blind review*

[56] Anonymous 2026 *Reference withheld for double-blind review*

[57] Bishop C M 2006 *Pattern Recognition and Machine Learning* (New York: Springer)

[58] Kalman R E 1960 A new approach to linear filtering and prediction problems *J. Basic Eng.* **82** 35–45 doi:10.1115/1.3662552

[59] Durbin J and Koopman S J 2012 *Time Series Analysis by State Space Methods 2nd edn* (Oxford: Oxford University Press)

[60] Stam A J 1959 Some inequalities satisfied by the quantities of information of Fisher and Shannon *Inf. Control* **2** 101–12 doi:10.1016/S0019-9958(59)90348-1

[61] Durrett R 2010 *Probability: Theory and Examples 4th edn* (Cambridge: Cambridge University Press)

[62] Harvey A C 1989 *Forecasting, Structural Time Series Models and the Kalman Filter* (Cambridge: Cambridge University Press)

[63] Genest C and Zidek J V 1986 Combining probability distributions: a critique and an annotated bibliography *Stat. Sci.* **1** 114–35 doi:10.1214/ss/1177013825

[64] Hinton G E 2002 Training products of experts by minimizing contrastive divergence *Neural Comput.* **14** 1771–800 doi:10.1162/089976602760128018

[65] Meeker W Q and Escobar L A 1998 *Statistical Methods for Reliability Data* (New York: Wiley)

[66] Gneiting T and Raftery A E 2007 Strictly proper scoring rules, prediction, and estimation *J. Am. Stat. Assoc.* **102** 359–78 doi:10.1198/016214506000001437

[67] Bouthillier X et al 2021 Accounting for variance in machine learning benchmarks *Proc. Mach. Learn. Syst.* **3** 747–69

[68] Efron B and Tibshirani R J 1993 *An Introduction to the Bootstrap* (New York: Chapman and Hall)

[69] Saha B and Goebel K 2007 Battery data set *NASA Prognostics Data Repository (Moffett Field, CA: NASA Ames Research Center)*

[70] He W, Williard N, Osterman M and Pecht M 2011 Prognostics of lithium-ion batteries based on Dempster–Shafer theory and the Bayesian Monte Carlo method *J. Power Sources* **196** 10314–21 doi:10.1016/j.jpowsour.2011.08.040

[71] Nectoux P, Gouriveau R, Medjaher K, Ramasso E, Chebel-Morello B, Zerhouni N and Varnier C 2012 PRONOSTIA: an experimental platform for bearings accelerated degradation tests *Proc. IEEE Int. Conf. on Prognostics and Health Management (Denver, CO)* pp 1–8

[72] Lee J, Qiu H, Yu G, Lin J and Rexnord Technical Services 2007 Bearing data set *IMS, University of Cincinnati, NASA Prognostics Data Repository (Moffett Field, CA: NASA Ames Research Center)*

[73] Qiu H, Lee J, Lin J and Yu G 2006 Wavelet filter-based weak signature detection method and its application on rolling element bearing prognostics *J. Sound Vib.* **289** 1066–90 doi:10.1016/j.jsv.2005.03.007

[74] Saxena A, Goebel K, Simon D and Eklund N 2008 Damage propagation modeling for aircraft engine run-to-failure simulation *Proc. Int. Conf. on Prognostics and Health Management (Denver, CO)* pp 1–9 doi:10.1109/PHM.2008.4711414

[75] Welch B L 1947 The generalization of 'Student's' problem when several different population variances are involved *Biometrika* **34** 28–35 doi:10.1093/biomet/34.1-2.28