


C28 updated
 Released for discussion
 Preliminary Design
Raw Matter IO Pty Ltd

Sheet: /12V/
 File: 12V.kicad_sch

Title:

Size: A4 Date: 2025-08-26
 KiCad E.D.A. 9.0.2

Rev: 1
 Id: 2/3



Output Voltage

 $R_{FB_H} = R_{FB_L}(V_{out} - V_{fb})/V_{fb}$
 R_{FB_H} - Resistor feedback High
 R_{FB_L} - Resistor feedback Low
 V_{out} - Desired output voltage
 V_{fb} - feedback voltage (0.6)

$R_{FB_H} = 10000(5 - 0.6)/0.6$
 $R_{FB_H} = 73.2k$

MODE selection

MODE1
 100K to VDD for forced CCM
 $f_{sw} = 500kHz$

MODE2

OC limit of 14A
 200K to AGND = 78% of I_{max} (18A - SIC437x)

AGND and PGND connected inside SIC437

C28 updated
 Released for discussion
 Preliminary Design
Raw Matter IO Pty Ltd

Sheet: /5V/
 File: 5V.kicad_sch

Title:

Size: A4
 KiCad E.D.A. 9.0.2

Date: 2025-08-26

Rev: 1
 Id: 6/3