TestSuite1

Execution Environment

Host name	nthuyen5 - nthuyen5.tma.com.vn
Local OS	Windows 10 64bit
Katalon version	8.6.5.208
Browser	Chrome 114.0.0.0

Summary

ID	Test Suites/TestSuite1		
Description			
Total	2		
Passed	1	Failed	1
Error	0	Incomplete	0
Skipped	0		
Start	2023-06-27 16:53:26	End	2023-06-27 16:53:37
Elapsed	11.438s		

#	ID	Description	Status
1	Test Cases/LoginSwag		FAILED
2	Test Cases/TestVariables		PASSED

LoginSwag

Information

ID   Test Cases/LoginSwag

Description

Tag

Start   2023-06-27 16:53:34   End   2023-06-27 16:53:37

Elapsed   2.289s

Status   FAILED

Details

#	Description	Elapsed	Status
1	Start listener action : sampleBeforeTestCase	0.001s	PASSED
2	Start setup action : setupTestCase Method 'setupTestCase' complete successfully	0.001s	PASSED
3	openBrowser("") Browser is opened with url: ''	2.177s	PASSED

LoginSwag

#	Description	Elapsed	Status
4	navigateToUrl(url_swag)	0.100s	FAILED

Unable to navigate to 'null' (Root cause: com.kms.katalon.core.exception.
StepFailedException: Unable to navigate to 'null'
        at com.kms.katalon.core.webui.keyword.internal.WebUIKeywordMain.stepFailed
(WebUIKeywordMain.groovy:64)
        at com.kms.katalon.core.webui.keyword.internal.WebUIKeywordMain.runKeyword
(WebUIKeywordMain.groovy:26)
        at com.kms.katalon.core.webui.keyword.builtin.NavigateToUrlKeyword.
navigateToUrl(NavigateToUrlKeyword.groovy:83)
        at com.kms.katalon.core.webui.keyword.builtin.NavigateToUrlKeyword.execute
(NavigateToUrlKeyword.groovy:67)
        at com.kms.katalon.core.keyword.internal.KeywordExecutor.
executeKeywordForPlatform(KeywordExecutor.groovy:74)
        at com.kms.katalon.core.webui.keyword.WebUiBuiltInKeywords.navigateToUrl
(WebUiBuiltInKeywords.groovy:187)
        at com.kms.katalon.core.webui.keyword.WebUiBuiltInKeywords$navigateToUrl$0.
call(Unknown Source)
        at LoginSwag.run(LoginSwag:23)
        at com.kms.katalon.core.main.ScriptEngine.run(ScriptEngine.java:194)
        at com.kms.katalon.core.main.ScriptEngine.runScriptAsRawText(ScriptEngine.
java:119)
        at com.kms.katalon.core.main.TestCaseExecutor.runScript(TestCaseExecutor.
java:448)
        at com.kms.katalon.core.main.TestCaseExecutor.doExecute(TestCaseExecutor.
java:439)
        at com.kms.katalon.core.main.TestCaseExecutor.processExecutionPhase
(TestCaseExecutor.java:418)
        at com.kms.katalon.core.main.TestCaseExecutor.accessMainPhase
(TestCaseExecutor.java:410)
        at com.kms.katalon.core.main.TestCaseExecutor.execute(TestCaseExecutor.
java:285)
        at com.kms.katalon.core.main.TestCaseExecutor.execute(TestCaseExecutor.
java:369)
        at com.kms.katalon.core.main.TestCaseExecutor.execute(TestCaseExecutor.
java:369)
        at com.kms.katalon.core.main.TestCaseExecutor.execute(TestCaseExecutor.
java:369)
        at com.kms.katalon.core.common.CommonExecutor.accessTestCaseMainPhase
(CommonExecutor.java:65)
        at com.kms.katalon.core.main.TestSuiteExecutor.accessTestSuiteMainPhase
(TestSuiteExecutor.java:148)
        at com.kms.katalon.core.main.TestSuiteExecutor.execute(TestSuiteExecutor.java:
106)
        at com.kms.katalon.core.main.TestCaseMain.startTestSuite(TestCaseMain.java:
187)
        at com.kms.katalon.core.main.TestCaseMain$startTestSuite$0.call(Unknown
Source)
        at TempTestSuite1687859596030.run(TempTestSuite1687859596030.groovy:36)
Caused by: java.lang.IllegalArgumentException: Url cannot be null or empty
        at com.kms.katalon.core.webui.keyword.builtin.
NavigateToUrlKeyword$_navigateToUrl_closure1.doCall(NavigateToUrlKeyword.groovy:75)
        at com.kms.katalon.core.webui.keyword.builtin.
NavigateToUrlKeyword$_navigateToUrl_closure1.call(NavigateToUrlKeyword.groovy)
        at com.kms.katalon.core.webui.keyword.internal.WebUIKeywordMain.runKeyword
(WebUIKeywordMain.groovy:20)
        at com.kms.katalon.core.webui.keyword.builtin.NavigateToUrlKeyword.
navigateToUrl(NavigateToUrlKeyword.groovy:83)

#	Description	Elapsed	Status
	at com.kms.katalon.core.webui.keyword.builtin.NavigateToUrlKeyword.execute (NavigateToUrlKeyword.groovy:67) at com.kms.katalon.core.keyword.internal.KeywordExecutor. executeKeywordForPlatform(KeywordExecutor.groovy:74) at com.kms.katalon.core.webui.keyword.WebUiBuiltInKeywords.navigateToUrl (WebUiBuiltInKeywords.groovy:187) at com.kms.katalon.core.webui.keyword.WebUiBuiltInKeywords$navigateToUrl$0. call(Unknown Source) at Script1687851710133.run(Script1687851710133.groovy:23) ... 16 more)		
5	Start tear down : tearDownTestCase Method 'tearDownTestCase' complete successfully	0.001s	PASSED
6	Start listener action : sampleAfterTestCase	0.000s	PASSED

TestVariables

Information

ID   Test Cases/TestVariables

Description

Tag

Start   2023-06-27 16:53:37   End   2023-06-27 16:53:37

Elapsed   0.322s

Status   PASSED

Details

#	Description	Elapsed	Status
1	Start listener action : sampleBeforeTestCase	0.001s	PASSED
2	Start setup action : setupTestCase Method 'setupTestCase' complete successfully	0.001s	PASSED
3	str = "Print this text"	0.001s	PASSED
4	i = 2	0.000s	PASSED
5	j = 5	0.000s	PASSED
6	sum = i + j	0.001s	PASSED
7	println(str)	0.000s	PASSED

TestVariables

#	Description	Elapsed	Status
8	println(sum)	0.000s	PASSED
9	Start tear down : tearDownTestCase Method 'tearDownTestCase' complete successfully	0.000s	PASSED
10	Start listener action : sampleAfterTestCase	0.001s	PASSED