7900 809 719

REV.	DATE		DESCRIPTIO	N		REF.No.	DWN.	CHKD.	CUTTING TOLE	PANCE	
init.	2016/02/2	3		,		112,110.	 	Ho_Shou_Rsuan	0.5 ≦, ≦ 6	± 0.1	
\wedge	-						United Head	TIN_CHIQU_HAGGII	6 < ,≦ 30	± 0.2	
쉿			., -						30 < , ≦ 120	± 0.3	
쉬									120 < , ≦ 400	± 0.5	
\triangle					- · · · · · · · · · · · · · · · · · · ·				TOLERANCES NOT O SPECIFIED APPLIES JIS B 0401		
			 13						FINISH MAR		
		A (8	o:1)								
_)	12 30	7.27 A	Ø								
\propto	\mathcal{O}	, Vec 17 . 04+1	0.005					/	1.6 0.8	0.4	
	18	GC TE	<u> </u>		HỦY SÁU K DO M	CHI HOÀN TÁI DT COPY		\vee (\sim	\vee /	
	(_		`		08.03			全Q0.2(SC-1	36)	
			SR0.8()	±1)		SX VDM			(1)		
		İ		GP .			icia wil		9		
			K M ,					_			
			X 1 Y	<u>></u> + 4.\	(D)		GI	?	(14)		
R1.5(注1) R2(注1) R2(注1) T											
	বে	\ /	230	GP	<u> </u>		<u>← K2(</u>	<u>注1)</u>			
	U	△	GC GC				1				
GC	-GP	4	8.0		GP	l		5	= •		
		, l i	, O						_		
							C (10:1)				
			C					-	•		
							Α				
	<i>~</i>		ĺ	3 3	<u></u>		, k				
			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	aung	sai đầu-	Ar.	/ [[A		
	Ď.			y)		€C	\		€C .		
<u> </u>	7		Ø4.020a	5.006.1	0.002 1	\mathcal{D}	\\\\	1/7			
10.5)-GP											
			C0.2	2 🕒		`		22			
				2							
			٥	SP.		(1)		٨			
	·	_		,	⊿刻印Ø4.0	20			<u> </u>	•	
	G	C. T	ž	AL		Ø8±	.0.1	T'	1		
	<u> </u>	Ø5.6-0	0.002				 <	GS2	2		
	LE	3	>			GR					
					,						
	注:										
1、标记处的寸法不须严守,但必须是光滑曲面,不可有任何段差与锐角;											
2、Ø4.020的寸法公差及形位公差的适用范围如图之10mm区间; S CHUÂN											
					,		- Agranding and	2) 6	TILIMIY		
					A SAME AND ADDRESS OF THE PROPERTY OF THE PROP						
DS	GND.	CHKD.				PARTS NAME					
CHEN	YING_FUH	Ho_Shou_Hsuan	lo Shou Hsuan 部品図			サイジングピン					
	H&TEMPER	SURFACE	PART DRAWING			SIZING PIN					
HRC 0 °~ 0 °			部品図			整形銷					
			部品図			整形销					
		DATE	SCALE	A				DWG.N	~~		
W(C(D30)	2016/02/23	1:1	Ψ			RO	71	442		

SNO: R071442 SỐ PCS TỐI THIỂU/1 LẦN ĐẶT HÀNG:									
DIỄN GIẢI	THỜI GIAN CHUẨN 1P								