MV

V3			. )						
•			100000000000000000000000000000000000000	TION .		REF.No.	DWN.	CHKD.	
REV	, DAYE		DEWZRII	JION			K,Kamakura	T.Yajima	0.00
init	2015/11/23	新规渗计					<del> </del>		0.00
<u>                                   </u>							<del> </del>	<del> </del>	0.00
4		<i><b>├</b>#</i>						<u> </u>	0.0
									0.
						<u> </u>			
1	•	7							1
-									-
- 1					(M12)				1

\*Ø3

(36)

CUTTING TOLERANCE					
0.0000 ± 0.002		0.000 +0	+0 -0.005		
0.000	±0.005	0.000 _0	+0.005		
0.00	± 0.01	0.00 +0	+0 -0.01		
0.0	±0.1	0.00 -0	+0.01		
	± 0.2	0.0 +0	+0		
0.		0.0 -0	+0.1		
TOLERANCES NOT					
OTHERWISE SPECIFIED					

FINISH MARKS

 $\nabla \nabla$ 

MISUMI CB12-220 \*印記寸法部追加工

128	
/120	

			PARTS NAME
DSGND.	CHKD.	TITLE	ボルト
K.Kamakura	T.Yajima	部品図 PART DRAWING	BOLT
QUENCH&TEMPER		部品図	螺拴
		部品図	螺栓
HRC 0 °~ 0 °	DATE	SCALE _	DWG.No.
MATERIAL		1:1	R029040
······································	2015/11/23		MABUCH MOTOR CO.LTD.

(Ø18)

SNO: R029040			
SỐ PCS TỐI THIỂU/1 LẦN ĐẶT HÀNG:			
NGƯỜI THIẾT LẬP: 10197			
DIỄN GIẢI	THỜI GIAN CHUẨN 1P		
1.VẬT LIỆU: Xuất hàng K2 Quy cách:CB12-220	ED:90		