

Workflow Notes

Hwan Goh

17th May 2020

1 Vim Tips and Tricks

Some good references are [5, 31]. A more advanced tutorial that I haven't watched yet is [4]. A document on effective text editing written by the creator of Vim can be found at [23].

- In Linux based systems, put 'setxkbmap -option "caps:escape' into ~/.bashrc to map the caps lock key to escape.
- To set Vim as your default text editor, use 'sudo update-alternatives --config editor'.
- Suppose the cursor is in the middle of a word. Whilst 'cw' and 'dw' will change/delete until the end of the word, 'ciw' and 'diw' to change or delete the whole word, thereby not requiring you to move the cursor to the beginning of the word first.
- To reformat a paragraph, use 'gq'. Reformatting includes enforcing the wrap limit which can be set in your vimrc with 'set tw=<number>'. Other options can be seen such as indentation. Note that this command requires a minimum of two lines, so you'll need to at least use 'gqj' and at most use 'gjG' for the rest of the document under the line currently under the cursor.
- Use 'm<key>' to set a mark to <key> then <key> to jump to it. Note that if you set it to the capitalized version of <key> then the jumping can occur between buffers. To see your list of marks, use ':mark'.
- Use '"<key>' then an action like 'y' or 'd' to store text in the *register* <key>. Then use '"<key>p' to paste it. Note that using 'd' will automatically store it in the register at register x and 'p' will automatically paste whatever is in register 'x'. Use ':reg' to see the register list.
- Use 'f<key>' to forward search for <key>. To backwards search, use 'F<key>'. To repeat the search, use ';', ','.
- The 't' stands for 'til'. For example, 'dt=' will delete up to and not including an = sign.
- The '*' can be used to search for the word under cursor.
- 'J' is used to join the line below to the line currently under the cursor. This is useful for reformatting improperly wrapped lines but in general 'gq' is more useful for this purpose.
- 'zt' or 'z!CR_l' will put the line under the cursor to the top of the window. 'z.' will put the line to the center of the window and 'z-' will put it to the bottom of the window.
- 'z=' will give spelling suggestions for the word under the cursor.
- '[s' and ']s' to cycle backwards and forwards through misspelled words.
- Use 'g\$' to go to the end of an unwrapped line.
- If you type a long line of text in insert mode, this counts as one action. Therefore, if you press undo, the whole line will be deleted. To break the undo chain, use <c-g>u while in insert mode. Alternatively, you could map space to <c-g>u so that the undo chain is broken whenever a space is added in insert mode:
inoremap <Space><Space><c-g>u
- Use the accent '<shift+6>' in insert mode to move to the first non-white space character in the line.
- Use '%' while your cursor is over a parenthesis, square or curly bracket to move to the corresponding open/-closing parenthesis or bracket.
- Use ':ls' to see the list of buffers then ':b' and the number to select one. A useful mapping for this process is:
nnoremap <leader>b:ls<cr>:b<space>

2 Version Controlling Your Vim Configuration

This section follows [24]. First, we work towards turning `/.vim` into a git repository:

1. Move `/.vimrc` into `/.vim`.
2. When vim boots, it's still going to look for `.vimrc` in the home directory. To ensure that it looks for `vimrc` in the `/.vim` directory, we can create a symbolic link to that file using `'ln -s /.vim/vimrc /.vimrc'`.
3. Make `/.vim` into a git repository.

An issue now is if you install a plugin that itself is a git repository, you lose the version-control capabilities of that plugin. To circumvent this issue, we use a plugin manager; in this case *Pathogen*.

2.1 Pathogen: the Plugin Manager

The pathogen plugin makes it possible to cleanly install plugins as a bundle. Rather than having to place all of your plugins side by side in the same directory, you can keep all of the files for each individual plugin together in one directory (see video from first link for example). This makes installation more straightforward, and also simplifies the tasks of upgrading and even removing a plugin if you decide you no longer need it since they are carefully segregated from each other. For a good tutorial on Pathogen, see [19].

Following the readme on the repo at [25], to install Pathogen do the following:

1. Run in terminal:
`mkdir -p /.vim/autoload /.vim/bundle &&`
`curl -LSso /.vim/autoload/pathogen.vim https://tpo.pe/pathogen.vim`
2. Add the following to your vimrc: `execute pathogen#infect()`

Now any plugins you wish to install can be extracted to a subdirectory under `/.vim/bundle`, and they will be added to the `'runtimepath'`. For example, to install "sensible.vim", simply run: `"cd /.vim/bundle && git clone https://github.com/tpope/vim-sensible.git"`.

2.2 Submodules: Installing Git Repositories Within Git Repositories

This section follows [24]. Now that we can install plugins via Pathogen, let's see how we preserve the version control capabilities of our plugins. As a worked example, let us install the *Vimtex* plugin:

1. `cd /.vim`
2. Now to clone a git repository into the bundle directory, use:
`git submodule add https://github.com/lervag/vimtex.git bundle/vimtex`

Now, to upgrade this plugin, use:

1. `cd /.vim/bundle/vimtex`
2. `git pull origin master`

To upgrade ALL of your plugins, use:

1. `cd /.vim`
2. `git submodule foreach git pull origin master`

2.3 Importing Your Vim Configuration and Plugins To a New Machines

One of the main benefits of version controlling your Vim configuration and plugins is the ease of which they can be imported into a new machine. To fo so, use the following:

1. `cd`
2. `git clone <git repo url> /.vim`
3. `ln -s /.vim/vimrc /.vimrc`
4. `cd /.vim`
5. `git submodule init`
6. `git submodule update`

3 Vimtex

3.1 Installing and Running Vimtex

Assuming you are using the Pathogen plugin manager and version controlling your `./vim` directory, follow the steps used in Section 2.2. Then use ‘:Helptags’ which is Pathogen’s method for generating help tags. With this, we can use ‘:h vimtex’ to see the manual for Vimtex. To confirm that the plugin works, type “:VimtexInfo” to see a summary of the tex file.

3.2 Compiling a Tex File

The following commands are useful:

- `:VimtexCompile` # this is a continuous compiler meaning that everytime you save with “:w” it will automatically compile
- `:VimtexStop` # this stops the continuous compiler
- `:VimtexCompileSS` # this is a single shot compiler. Note that you have to save your file first
- `:VimtexClean` # Cleans auxiliary files generated in compilation process

I set the following mappings in my vimrc:

```
autocmd FileType tex noremap <F5> :VimtexView<Enter>
autocmd FileType tex inoremap <F5> <Esc> :VimtexView<Enter>
autocmd FileType tex noremap <F6> :w! <bar> :VimtexCompileSS<Enter>
autocmd FileType tex inoremap <F6> <Esc> :w! <bar> :VimtexCompileSS<Enter>
```

3.3 Forward and Backwards Searching with SyncTex

This section follows [8]. For this, you will need a Vimtex server which allows you to do forward and backward to navigate between corresponding sections of the tex file and the pdf. You will also need the pdf viewer *Zathura*. To install, simply use ‘sudo apt-get install zathura’. Then, in your vimrc, add the following line ‘let g:vimtex_view_method = ‘zathura’.

Following [20], to install just use ‘sudo apt-get install vim-gnome’. Finally, to edit a tex file with navigation capabilities:

1. In the directory containing the tex file, use:
`vim -servername <servername><texfile>.tex`
2. While in tex file, to jump to the text on the pdf corresponding to the line under your cursor, use:
`<leader>lv`
3. Move your mouse cursor over some text on the pdf. Then, to jump to corresponding text on the tex file, use:
`Ctrl + left-click`

Note that `<leader>lv` forward search works without the Vim server; it’s the backwards search that requires the Vim server.

3.4 Other Useful References

- Nice compilation of Vimtex commands [8]
- Quick guide on the basics of Vimtex [12]
- For a comparison with other Vim LaTeX plugins [21]
- Note-taking using Vim and LaTeX for math lectures [3]
- Vim and LaTeX on MacOS [6]
- Some useful mappings such as the teleportation trick [28, 29].

4 Python

The following mapping may prove useful for starting an IPython terminal:

```
nnoremap <leader>p :botright vertical terminal ipython -no-autoindent<cr>
```

4.1 sendtosplit Plugin

When coding in Python with a Vim terminal on the side running IPython, I use the *sendtwindow* plugin [17] to send lines of code to the terminal. See [16] for a Reddit post from the author discussing the plugin. It's a very simple plugin that allows the use of vim motions to move lines of text to terminals left, right, above or below the Vim window.

Some notes on installation: notice that this repository only has one file called *sendtosplit.vim* which contains a couple of functions. Unless you are using a plugin manager like vim-plug or put all these functions into your vimrc, we can install this plugin in a slightly different way. All we need to do is create a directory `./vim/plugin` and copy *sendtosplit.vim* into that directory. However, unlike the method with pathogen detailed in Section 2.1, your plugin won't be version controlled and so any updates added by the coder cannot be retrieved via git. More details about this type of plugin management can be found in [27].

This plugin is simple and elegant in use. I use the following maps:

```
let g:sendtwindow_use_defaults=0
nmap ,sr <Plug> SendRight
xmap ,srv <Plug> SendRightV
nmap ,sl <Plug> SendLeft
xmap ,slv <Plug> SendLeftV
nmap ,su <Plug> SendUp
xmap ,suv <Plug> SendUpV
nmap ,sd <Plug> SendDown
xmap ,sdv <Plug> SendDownV
```

Any one of these mappings will specify to either send some text in normal mode or in visual mode. When in normal mode, to specify which text to send, use the usual Vim movements. For example, `'sr$'` will send from the cursor to the end of the line to the window on the right. However, if you are in the middle of a line, it may become tedious having to first go to the beginning of the line and having to type `'$'`. Therefore, we can define line objects using the following maps:

```
onoremap <silent> <expr> _ v:count==0 ? " :<c-u>normal! 0V$h<cr>" : " :<c-u>normal! V" . (v:count) . "jk<cr>"
vnoremap <silent> <expr> _ v:count==0 ? " :<c-u>normal! 0V$h<cr>" : " :<c-u>normal! V" . (v:count) . "jk<cr>"
onoremap <silent> <expr> i_ v:count==0 ? " :<c-u>normal! ^vg-<cr>" : " :<c-u>normal! ^v" . (v:count) . "jkg-<cr>"
vnoremap <silent> <expr> i_ v:count==0 ? " :<c-u>normal! ^vg-<cr>" : " :<c-u>normal! ^v" . (v:count) . "jkg-h<cr>"
```

With `'_'` alone the indentation is left intact and `'i_'` is without indentation. So, for example, `'sr_'` will send the line under the cursor to the window on the right with indentation and `'sr8_'` will send four lines under the cursor to the window on the right. Note that this is important for Python as if you try send a for loop with `'i_'` and leave out the indentation, then it may not run.

4.2 With tmux

There are many plugins that allow interaction between Vim and tmux. For example, there is Vim-Slime [13] and Vimux [1]. The one I use is Slimux [7]. There is a blog post about it here [30]. As discussed in the blog post, Slimux differs from Vimux in that it is more disjoint from tmux. In particular, Vimux will create a pane on which you must run your commands whereas slimux allows you to select the pane you wish to use. Also, unlike Vim-Slime, you do not need to manually type in the pane to select it; in Slimux an interactive prompt is given. It's also worth noting that Vim-Slime supports many terminal multiplexers such as GNU Screen, kitty and Vim's native terminal.

However, there is an issue with sending commands to IPython where the indentation is constantly carried over [18]. There are three proposed fixes [22, 15, 32]. The first modifies *python.vim*, the second modifies both *slimux.vim* and *python.vim* by implementing IPython's *cpaste* function and the third modifies a single line of *slimux.vim*. Since the repo owner hasn't pulled any of these fixes, I opted for the third fix which requires changing line 328 of *slimux.vim* to:

```
let b:code_packet["text"] = "\e[200~" . a:text . "\e[201~\r\r.
```

4.3 Other Useful References

- Another lightweight workflow can be found in [9]. For this, you will need three plugins: Vimux [1], vim-pyShell [10] and vim-cellmode [14]. However, I have trouble getting this to work. Starting and stopping a pyShell session works fine as well as sending one line of code, but I have issues sending over cells.

i++i

References

- [1] benmills. vimux. <https://github.com/benmills/vimux>.
- [2] M. Cantor. How to do 90% of what plugins do (with just vim). <https://www.youtube.com/watch?v=E-ZbrtoSuzw>.
- [3] G. Castel. How i'm able to take notes in mathematics lectures using latex and vim. <https://castel.dev/post/lecture-notes-1/#vim-and-latex>.
- [4] L. Chang. Vim: Tutorial on customization and configuration (2020). <https://www.youtube.com/watch?v=JFr28K65-5E&list=FLVuBBjy7NC7Q0xVUm8SEjrw&index=3&t=3083s>.
- [5] L. Chang. Vim: Tutorial on editing, navigation, and file management (2018). <https://www.youtube.com/watch?v=E-ZbrtoSuzw>.
- [6] J. V. Dyke. Getting started with latex and vim. https://web.ma.utexas.edu/users/vandyke/notes/tex/getting_started/getting_started.pdf.
- [7] esamattis. Slimux. <https://github.com/esamattis/slimux/blob/master/README.md>.
- [8] M. Gunther. Vimtex tool for working vim, tex and zathura. <https://wikimatze.de/vimtex-the-perfect-tool-for-working-with-tex-and-vim/>.
- [9] G. Hornung. Boosting your data science workflow with vim+tmux. <https://towardsdatascience.com/boosting-your-data-science-workflow-with-vim-tmux-14505c5e016e>.
- [10] G. Hornung. vim-pyshell. <https://github.com/greghor/vim-pyShell>.
- [11] P. Ivanov. vim-ipython. <https://github.com/ivanov/vim-ipython>.
- [12] jdhao. A complete guide on writing latex with vimtex in neovim. https://jdhao.github.io/2019/03/26/nvim_latex_write_preview/.
- [13] jpalardy. vim-slime. <https://github.com/jpalardy/vim-slime>.
- [14] julienr. vim-cellmode. <https://github.com/julienr/vim-cellmode>.
- [15] karadaharu. Add an option to use cpaste for ipython #68. <https://github.com/esamattis/slimux/pull/68>.
- [16] KKPMW. 'sendtowindow' - a small plugin with operator for sending text to repls (or any other vim window). https://www.reddit.com/r/vim/comments/au8eo5/sendtowindow_a_small_plugin_with_operator_for/.
- [17] KKPMW. vim-sendtowindow. <https://github.com/KKPMW/vim-sendtowindow>.
- [18] kmARC. Python repl indentationerror: unexpected indent # 38. <https://github.com/esamattis/slimux/issues/38>.
- [19] R. Lafourcade. How to use tim pope's pathogen. <https://gist.github.com/romainl/9970697>.
- [20] Y. Lerner. Enable servername capability in vim/xterm. https://vim.fandom.com/wiki/Enable_servername_capability_in_vim/xterm.
- [21] K. Lervag. What are the differences between latex plugins? <https://vi.stackexchange.com/questions/2047/what-are-the-differences-between-latex-plugins>.
- [22] lotabout. remove indent for selected blocks #74. <https://github.com/esamattis/slimux/pull/74>.
- [23] B. Moolenaar. Seven habits of effective text editing. <https://www.moolenaar.net/habits.html>.

- [24] D. Neil. Synchronizing plugins with git submodules and pathogen. <http://vimcasts.org/episodes/synchronizing-plugins-with-git-submodules-and-pathogen/>.
- [25] T. Pope. pathogen.vim. <https://github.com/tpope/vim-pathogen>.
- [26] princker. Is it possible to skip over :terminal buffers when using :bn and :bp in vim 8? https://www.reddit.com/r/vim/comments/8njgul/is_it_possible_to_skip_over_terminal_buffers_when/.
- [27] T. Ryder. Attack of the 5000-line vimrc. <https://vimways.org/2018/from-vimrc-to-vim/>.
- [28] L. Smith. My dank vim & latex setup (wordcucks btfo once again). https://www.youtube.com/watch?v=Mphdtdv2_xs.
- [29] L. Smith. Start turning vim into a /comfy/ ide! <https://www.youtube.com/watch?v=Q4I-Ft-VLA&list=FLVuBBjy7NC7Q0xVUm8SEjrw&index=3&t=462s>.
- [30] E.-M. Suuronen. Slimux - tmux plugin for vim. <http://esa-matti.suuronen.org/blog/2012/04/19/slimux-tmux-plugin-for-vim/>.
- [31] C. Toomey. Mastering the vim language. <https://www.youtube.com/watch?v=w1R5gYd6um0>.
- [32] zcesur. Fix ipython issues when sending multiple lines #80. <https://github.com/esamattis/slimux/pull/80>.