

Daymo ERD · 계정 · 인증

법례
PK 기본키 · FK 외래키 · UK 고유키 · IDX 단일 컬럼 인덱스 · ? NULL 허용
CASCADE · SET NULL · RESTRICT · 회색 NO ACTION
target_type + target_id 같은 다형 참조는 DB FK가 아니므로 관계선에서 제외

계정 · 인증

throttle_counters		
id	UUID	PK
scope	VARCHAR(20)	
key_hash	VARCHAR(64)	
attempts	INTEGER	
window_started_at	DATETIME	IDX
last_attempt_at	DATETIME?	
blocked_until	DATETIME?	

refresh_tokens		
id	UUID	PK
user_id	UUID	FK
device_id	UUID?	FK
token_family_id	UUID	IDX
token_hash	VARCHAR(64)	IDX
last_used_at	DATETIME?	
expires_at	DATETIME	
replaced_by	UUID?	FK
revoked_at	DATETIME?	
revoke_reason	VARCHAR(20)?	
created_at	DATETIME	
updated_at	DATETIME	

oauth_pending_logins		
id	UUID	PK
provider	VARCHAR(20)	
provider_subject	VARCHAR(255)	
provider_email	VARCHAR(320)?	
email_verified	BOOLEAN	
display_name	VARCHAR(50)?	
code_hash	VARCHAR(64)	IDX
code_challenge	VARCHAR(128)	
expires_at	DATETIME	IDX
used_at	DATETIME?	
link_token_hash	VARCHAR(64)?	IDX
link_expires_at	DATETIME?	
linked_at	DATETIME?	
created_at	DATETIME	
updated_at	DATETIME	

oauth_states		
id	UUID	PK
provider	VARCHAR(20)	
state_hash	VARCHAR(64)	IDX
nonce	VARCHAR(64)	
app_redirect_uri	VARCHAR(200)	
app_state	VARCHAR(128)	
code_challenge	VARCHAR(128)	
expires_at	DATETIME	IDX
used_at	DATETIME?	
created_at	DATETIME	
updated_at	DATETIME	

reauth_proofs		
id	UUID	PK
user_id	UUID	FK
action	VARCHAR(20)	
nonce	VARCHAR(64)	
token_hash	VARCHAR(64)	IDX
expires_at	DATETIME	
used_at	DATETIME?	
created_at	DATETIME	
updated_at	DATETIME	

email_change_tokens		
user_id	UUID	FK · IDX
new_email	VARCHAR(320)	
id	UUID	PK
token_hash	VARCHAR(64)	IDX
expires_at	DATETIME	
used_at	DATETIME?	
revoked_at	DATETIME?	
created_at	DATETIME	
updated_at	DATETIME	

password_reset_tokens		
user_id	UUID	FK · IDX
id	UUID	PK
token_hash	VARCHAR(64)	IDX
expires_at	DATETIME	
used_at	DATETIME?	
revoked_at	DATETIME?	
created_at	DATETIME	
updated_at	DATETIME	

email_verification_tokens		
user_id	UUID	FK · IDX
id	UUID	PK
token_hash	VARCHAR(64)	IDX
expires_at	DATETIME	
used_at	DATETIME?	
revoked_at	DATETIME?	
created_at	DATETIME	
updated_at	DATETIME	

devices		
id	UUID	PK
user_id	UUID	FK
installation_id	VARCHAR(64)	
platform	VARCHAR(20)	
app_version	VARCHAR(20)?	
display_name	VARCHAR(40)?	
last_seen_at	DATETIME	
revoked_at	DATETIME?	
created_at	DATETIME	
updated_at	DATETIME	

oauth_accounts		
id	UUID	PK
user_id	UUID	FK · IDX
provider	VARCHAR(20)	
provider_subject	VARCHAR(255)	
provider_email	VARCHAR(320)?	
created_at	DATETIME	
updated_at	DATETIME	

users		
id	UUID	PK
email	VARCHAR(320)	UK
email_verified_at	DATETIME?	
password_hash	VARCHAR(255)?	
display_name	VARCHAR(50)	
terms_version	VARCHAR(20)?	
terms_agreed_at	DATETIME?	
avatar_path	VARCHAR(500)?	
timezone	VARCHAR(64)	
status	VARCHAR(20)	
deletion_requested_at	DATETIME?	
deletion_scheduled_at	DATETIME?	IDX
deleted_at	DATETIME?	
created_at	DATETIME	
updated_at	DATETIME	

calendar_notes		
id	UUID	PK
created_by	UUID?	FK
... 11개 컬럼		

checklist_items		
id	UUID	PK
created_by	UUID?	FK
... 12개 컬럼		

checklists		
id	UUID	PK
created_by	UUID?	FK
... 5개 컬럼		

diaries		
id	UUID	PK
created_by	UUID?	FK
... 8개 컬럼		

expenses		
id	UUID	PK
created_by	UUID?	FK
... 14개 컬럼		

external_links		
id	UUID	PK
created_by	UUID?	FK
... 7개 컬럼		

feedback		
id	UUID	PK
user_id	UUID?	FK
... 5개 컬럼		

ingredients		
id	UUID	PK
created_by	UUID?	FK
... 10개 컬럼		

memberships		
id	UUID	PK
user_id	UUID	FK
removed_by	UUID?	FK
created_by	UUID?	FK
... 7개 컬럼		

memos		
id	UUID	PK
created_by	UUID?	FK
... 9개 컬럼		

payments		
id	UUID	PK
deleted_by	UUID?	FK
created_by	UUID?	FK
... 8개 컬럼		

recipes		
id	UUID	PK
created_by	UUID?	FK
... 9개 컬럼		

reports		
id	UUID	PK
reporter_user_id	UUID?	FK
... 8개 컬럼		

reservations		
id	UUID	PK
created_by	UUID?	FK
... 15개 컬럼		

schedule_items		
id	UUID	PK
created_by	UUID?	FK
... 12개 컬럼		

spaces		
id	UUID	PK
owner_id	UUID	FK
created_by	UUID?	FK
... 8개 컬럼		

stays		
id	UUID	PK
created_by	UUID?	FK
... 11개 컬럼		

tags		
id	UUID	PK
created_by	UUID?	FK
... 6개 컬럼		

transports		
id	UUID	PK
created_by	UUID?	FK
... 16개 컬럼		

trip_cards		
id	UUID	PK
created_by	UUID?	FK
... 10개 컬럼		

trip_participants		
id	UUID	PK
created_by	UUID?	FK
... 6개 컬럼		

trip_places		
id	UUID	PK
created_by	UUID?	FK
... 9개 컬럼		

trips		
id	UUID	PK
created_by	UUID?	FK
... 24개 컬럼		

user_blocks		
id	UUID	PK
blocker_user_id	UUID	FK
blocked_user_id	UUID	FK · IDX
... 2개 컬럼		