

Hy Pham

Student ID: 3644179

```
f1 = @(x) x.^2;
#This line declares an anonymous function that takes 1 input variable x and applies power of two to it.
".^2" applies to all elements if the input is either a vertex or a matrix.

f2 = @(x) idivide (int32(abs(x - (x/2)))), 100, "fix");
#This line declares an anonymous function that takes 1 input variable x. The anonymous function first
calculates the absolute value of x minus x divides by 2 (effectively halving it), converts the output to 32-
bit integer, before dividing all its elements by 100. "fix" indicates that the fractional part of the result will
be rounded towards 0.

f3 = @(x, y) x != y;
# This line declares an anonymous function that takes 2 input variables x and y. It returns boolean true
if x is not the same as y, boolean false if they are the same.

function retval = f4(f1, f2, f3, value1, value2)
retval = f3(f1(value1), f2(value2));
End
# This section declares a named function f4 that takes 5 arguments f1, f2, f3, value1, value2, with a
return value retval (1st line). The function then performs f3 on the output of f1 with value1 as argument
and f2 with value2 as argument. In this case, it compares value1 to the power of 2 and the integer
division of half of value2 by 100. If they are not the same, the function returns boolean true. If not, it
returns boolean false.

f4(f1, f2, f3, 5, 130);
#This line calls function f4, passing in the 3 anonymous functions above, along with 5 for value1 and 130
for value2. In this case, the function compares 5^2 and (int32 (abs (130 - (130 - 2)))), 100, "fix"). The
output will be boolean true.
```