


Relational Database Management System 116U01C403

Module 2 .4 Mapping EER to Relational Model
Jan 2024-May 2024

ER-to-Relational Mapping

- **ER-to-Relational Mapping Algorithm**
 - Step 1: Mapping of Regular Entity Types
 - Step 2: Mapping of Weak Entity Types
 - Step 3: Mapping of Binary 1:1 Relation Types
 - Step 4: Mapping of Binary 1:N Relationship Types.
 - Step 5: Mapping of Binary M:N Relationship Types.
 - Step 6: Mapping of Multivalued attributes.
 - Step 7: Mapping of N-ary Relationship Types.
- **Mapping EER Model Constructs to Relations**
 - Step 8: Options for Mapping Specialization or Generalization.
 - Step 9: Mapping of Union Types (Categories).



ER-to-Relational Mapping Algorithm

- Step 1: Mapping of Regular Entity Types.
 - For each regular (strong) entity type E in the ER schema, create a relation R that includes all the simple attributes of E.
 - Choose one of the key attributes of E as the primary key for R.
 - If the chosen key of E is composite, the set of simple attributes that form it will together form the primary key of R.

Example:

- We create the relations EMPLOYEE, DEPARTMENT, and PROJECT in the relational schema corresponding to the regular entities in the ER diagram.
 - SSN, DNUMBER, and PNUMBER are the primary keys for the relations EMPLOYEE, DEPARTMENT, and PROJECT as shown.

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary
-------	-------	-------	------------	-------	---------	-----	--------

DEPARTMENT

Dname	<u>Dnumber</u>
-------	----------------

PROJECT

Pname	<u>Pnumber</u>	Plocation
-------	----------------	-----------

ER-to-Relational Mapping Algorithm (contd.)

- **Step 2: Mapping of Weak Entity Types**
 - For each weak entity type *W* in the ER schema with owner entity type *E*, create a relation *R* & include all simple attributes (or simple components of composite attributes) of *W* as attributes of *R*.
 - Also, include as foreign key attributes of *R* the primary key attribute(s) of the relation(s) that correspond to the owner entity type(s).
 - The primary key of *R* is the *combination* of the primary key(s) of the owner(s) and the partial key of the weak entity type *W*, if any.

- **Example:** Create the relation DEPENDENT in this step to correspond to the weak entity type DEPENDENT.
 - Include the primary key SSN of the EMPLOYEE relation as a foreign key attribute of DEPENDENT (renamed to ESSN).
 - The primary key of the DEPENDENT relation is the combination {ESSN, DEPENDENT_NAME} because DEPENDENT_NAME is the partial key of DEPENDENT.

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------


DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------

Primary Key

ER-to-Relational Mapping Algorithm (contd.)

- **Step 3: Mapping of Binary 1:1 Relation Types**
 - For each binary 1:1 relationship type R in the ER schema, identify the relations S and T that correspond to the entity types participating in R.
- There are three possible approaches:
 1. **Foreign Key approach:** Choose one of the relations-say S-and include a foreign key in S the primary key of T. It is better to choose an entity type with total participation in R in the role of S.
 - Example: 1:1 relation MANAGES is mapped by choosing the participating entity type DEPARTMENT to serve in the role of S, because its participation in the MANAGES relationship type is total.
 2. **Merged relation option:** An alternate mapping of a 1:1 relationship type is possible by merging the two entity types and the relationship into a single relation. This may be appropriate when both participations are total.
 3. **Cross-reference or relationship relation option:** The third alternative is to set up a third relation R for the purpose of cross-referencing the primary keys of the two relations S and T representing the entity types.



DEPARTMENT

Dname	<u>Dnumber</u>
-------	----------------

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

ER-to-Relational Mapping Algorithm (contd.)

- Step 4: Mapping of Binary 1:N Relationship Types.
 - For each regular binary 1:N relationship type R, identify the relation S that represent the participating entity type at the N-side of the relationship type.
 - Include as foreign key in S the primary key of the relation T that represents the other entity type participating in R.
 - Include any simple attributes of the 1:N relation type as attributes of S.
- Example: 1:N relationship types WORKS_FOR, CONTROLS, and SUPERVISION in the figure.
 - For WORKS_FOR we include the primary key DNUMBER of the DEPARTMENT relation as foreign key in the EMPLOYEE relation and call it DNO.

- We have three 1:N relations, Works_for ,controls and supervision.
- Find an entity of N participation ,modify it with primary key of another entity.(such as modify Employee, Project,)

- **EMPLOYEE**

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary
-------	-------	-------	------------	-------	---------	-----	--------

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

PROJECT

Pname	<u>Pnumber</u>	Plocation
-------	----------------	-----------

PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

ER-to-Relational Mapping Algorithm (contd.)

- **Step 5: Mapping of Binary M:N Relationship Types.**
 - For each regular binary M:N relationship type R, *create a new relation S* to represent R.
 - Include as foreign key attributes in S the primary keys of the relations that represent the participating entity types; *their combination will form the primary key* of S.
 - Also include any simple attributes of the M:N relationship type (or simple components of composite attributes) as attributes of S.
- **Example: The M:N relationship type WORKS_ON from the ER diagram is mapped by creating a relation WORKS_ON in the relational database schema.**
 - The primary keys of the PROJECT and EMPLOYEE relations are included as foreign keys in WORKS_ON and renamed PNO and ESSN, respectively.
 - Attribute HOURS in WORKS_ON represents the HOURS attribute of the relation type. The primary key of the WORKS_ON relation is the combination of the foreign key attributes {ESSN, PNO}.

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----



PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------


WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------



ER-to-Relational Mapping Algorithm (contd.)

- **Step 6: Mapping of Multivalued attributes.**
 - For each multivalued attribute A, create a new relation R.
 - This relation R will include an attribute corresponding to A, plus the primary key attribute K-as a foreign key in R-of the relation that represents the entity type of relationship type that has A as an attribute.
 - The primary key of R is the combination of A and K. If the multivalued attribute is composite, we include its simple components.
- **Example:** The relation DEPT_LOCATIONS is created.
 - The attribute DLOCATION represents the multivalued attribute LOCATIONS of DEPARTMENT, while DNUMBER-as foreign key-represents the primary key of the DEPARTMENT relation.
 - The primary key of R is the combination of {DNUMBER, DLOCATION}.



DEPT_LOCATIONS


<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

ER-to-Relational Mapping Algorithm (contd.)

- **Step 7: Mapping of N-ary Relationship Types.**
 - For each n-ary relationship type R, where $n > 2$, create a new relationship S to represent R.
 - Include as foreign key attributes in S the primary keys of the relations that represent the participating entity types.
 - Also include any simple attributes of the n-ary relationship type (or simple components of composite attributes) as attributes of S.
- **Example:** The relationship type SUPPY in the ER on the next slide.
 - This can be mapped to the relation SUPPLY shown in the relational schema, whose primary key is the combination of the three foreign keys {SNAME, PARTNO, PROJNAME}

Ternary relationship types. (a) The SUPPLY relationship.

(a)



SUPPLIER

<u>SNAME</u>	...
--------------	-----

PROJECT

<u>PROJNAME</u>	...
-----------------	-----

PART

<u>PARTNO</u>	...
---------------	-----

SUPPLY

<u>SNAME</u>	PROJNAME	<u>PARTNO</u>	QUANTITY
--------------	----------	---------------	----------

Mapping the n -ary relationship type SUPPLY from Figure 4.11a.

SUPPLIER

<u>SNAME</u>	...
--------------	-----

PROJECT

<u>PROJNAME</u>	...
-----------------	-----

PART

<u>PARTNO</u>	...
---------------	-----

SUPPLY

<u>SNAME</u>	PROJNAME	<u>PARTNO</u>	QUANTITY
--------------	----------	---------------	----------

Result of mapping the COMPANY ER schema into a relational schema

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

PROJECT

Pname	<u>Pnumber</u>	<u>Plocation</u>	Dnum
-------	----------------	------------------	------

WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------




Figure 7.2
Result of mapping the COMPANY ER
schema into a relational database schema.

Example

