


# Low-energy communication backup system for hydrogen racecar

**Jarno Mechele  
Joey De Smet  
Robijn Ameye**

Begeleider:  
Begeleider:

Sammy Verslype  
Anton Lintermans

Academic year 2024–2025





## **Abstract**

lorem ipsum this has to be filled with something

# **1 Firmware Design and Implementation**

In this section, we present the design and implementation of the firmware for the STM32U5, which enables two-way raw LoRa communication, real time speech synthesis,

## **1.1 System Overview**

[Describe the overall system architecture. Mention hardware components, communication methods, and high-level software structure. Include a figure if possible.]

## **1.2 Firmware Design**

[Describe the structure of the firmware. Mention FreeRTOS (if used), key modules/tasks, inter-process communication, power handling, interrupt strategies, etc.]

## **1.3 Testing and Results**

[Discuss how you verified the system. Include relevant metrics: timing, memory usage, communication robustness, etc. Optionally describe test setups.]

## **1.4 Conclusion**

[Summarize what you built, how well it works, and potential areas for improvement or future work.]

## References

[1] Author Name, *Title of the Book or Article*, Publisher or Journal, Year.

FACULTY OF ENGINEERING TECHNOLOGY  
KU LEUVEN - BRUGES  
Spoorwegstraat 12  
8200 BRUGES, België  
tel. + 32 50 66 48 00  
fet.bruges@kuleuven.be  
[www.fet.kuleuven.be](http://www.fet.kuleuven.be)

