

via_015_35

Date/Time: 2026/04/22 21:24:57

Type: Via

Units: mm

Decimal places: 4

Hole Data

Hole type: Circle

Finished Hole

- Diameter: 0.1500
- Tolerance: positive=0.0000, negative=0.0000

Drilled Hole

- Drilled Diameter: 0.2000
- Tolerance: positive=0.0000, negative=0.0000

Offset: (0.0000, 0.0000)

Plating: Plated

Drill Symbol Data

Geometry: Circle

Width: 0.7000

Height: 0.7000

Characters:

Design Layer Pads

Layer: BEGIN LAYER

Pad	Geometry	Width	Height	X offset	Y offset
Regular	Round	0.3500	0.3500	0.0000	0.0000
Thermal	Round	0.3500	0.3500	0.0000	0.0000
Anti	Round	0.6000	0.6000	0.0000	0.0000
Keep Out	None				

Layer: DEFAULT INTERNAL

Pad	Geometry	Width	Height	X offset	Y offset
Regular	Round	0.3500	0.3500	0.0000	0.0000
Thermal	Round	0.3500	0.3500	0.0000	0.0000
Anti	Round	0.6000	0.6000	0.0000	0.0000
Keep Out	None				

Layer: END LAYER

Pad	Geometry	Width	Height	X offset	Y offset
Regular	Round	0.3500	0.3500	0.0000	0.0000
Thermal	Round	0.3500	0.3500	0.0000	0.0000
Anti	Round	0.6000	0.6000	0.0000	0.0000
Keep Out	None				

Layer: ADJACENT LAYER

Pad	Geometry	Width	Height	X offset	Y offset
Regular	None				
Thermal	None				
Anti	None				
Keep Out	None				

Mask Layer Pads

Layer	Geometry	Width	Height	X offset	Y offset
SOLDERMASK_TOP	None				
SOLDERMASK_BOTTOM	None				
PASTEMASK_TOP	None				
PASTEMASK_BOTTOM	None				
FILMMASK_TOP	None				
FILMMASK_BOTTOM	None				
COVERLAY_TOP	None				
COVERLAY_BOTTOM	None				

Usage Options

Suppress unconnected internal pads: Yes

Lock layer span: No

Poly via: No