

CS 228 : Logic in Computer Science

S. Krishna

MSO on Words

- ▶ Signature $\tau = (Q_\Sigma, <, S)$, domain or universe = set of positions of a word
- ▶ MSO over words: Atomic formulae


$$X(x) \mid Q_\Sigma(x) \mid x = y \mid x < y \mid S(x, y)$$

- ▶ Given a MSO sentence φ , $L(\varphi)$ defined as usual
- ▶ A language $L \subseteq \Sigma^*$ is MSO definable iff there is an MSO formula φ such that $L = L(\varphi)$
- ▶ Given an MSO sentence φ , is it satisfiable/valid?


MSO Expressiveness

- ▶ Clearly, $FO \subseteq MSO$
- ▶ $FO \subset \text{Regular}$
- ▶ $MSO = \text{Regular}$


Regular Languages to MSO



Regular Languages to MSO



Regular Languages to MSO




Runs of words:

a	a	a	a
q_0	q_1	q_0	q_1

a	a	b	a
-----	-----	-----	-----

Regular Languages to MSO



Runs of words:

a	a	a	a	
q_0	q_1	q_0	q_1	q_0

a	a	b	a	
q_0	q_1	q_0	q_2	q_2

Regular Languages to MSO

Given a regular language L , and a DFA such that $L = L(A)$,

- ▶ Run of a word : at every position of the word, we are in some unique state

Regular Languages to MSO

Given a regular language L , and a DFA such that $L = L(A)$,

- ▶ Run of a word : at every position of the word, we are in some unique state

Position x	:	0	1	2	3
		a	a	b	a
		q_0	q_1	q_0	q_2

Regular Languages to MSO

Given a regular language L , and a DFA such that $L = L(A)$,

- ▶ Run of a word : at every position of the word, we are in some unique state

Position x	:	0	1	2	3
		a	a	b	a
		q_0	q_1	q_0	q_2

- ▶ For a state $q \in Q$, let X_q =the set of positions of the word where the state is q in the run

Regular Languages to MSO

Given a regular language L , and a DFA such that $L = L(A)$,

- ▶ Run of a word : at every position of the word, we are in some unique state

Position x	:	0	1	2	3
		a	a	b	a
		q_0	q_1	q_0	q_2

- ▶ For a state $q \in Q$, let X_q =the set of positions of the word where the state is q in the run
- ▶ $X_{q_0} = \{0, 2\}$, $X_{q_1} = \{1\}$, $X_{q_2} = \{3\}$

Regular Languages to MSO

Given a regular language L , and a DFA such that $L = L(A)$,

- ▶ Run of a word : at every position of the word, we are in some unique state

Position x	:	0	1	2	3
		a	a	b	a
		q_0	q_1	q_0	q_2

- ▶ For a state $q \in Q$, let X_q = the set of positions of the word where the state is q in the run
- ▶ $X_{q_0} = \{0, 2\}$, $X_{q_1} = \{1\}$, $X_{q_2} = \{3\}$
- ▶ The initial position of any word must belong to X_{q_0} : $0 \in X_{q_0}$

Regular Languages to MSO

- ▶ If a word wa is accepted, then
 - ▶ The last position x of the word satisfies $Q_a(x)$
 - ▶ For some state q , we have $X_q(x)$ and there is a transition $\delta(q, a) = q_f \in F$

Regular Languages to MSO

- ▶ If a word wa is accepted, then
 - ▶ The last position x of the word satisfies $Q_a(x)$
 - ▶ For some state q , we have $X_q(x)$ and there is a transition $\delta(q, a) = q_f \in F$

Position x	:	0	1	2	3	
		a	a	b	a	
		q_0	q_1	q_0	q_2	q_2

Regular Languages to MSO

- ▶ If a word wa is accepted, then
 - ▶ The last position x of the word satisfies $Q_a(x)$
 - ▶ For some state q , we have $X_q(x)$ and there is a transition $\delta(q, a) = q_f \in F$

Position x	:	0	1	2	3	
		a	a	b	a	
		q_0	q_1	q_0	q_2	q_2

- ▶ $Q_a(3)$ and $3 \in X_{q_2}$. $\delta(q_2, a) = q_2 \notin F$
- ▶ If x, y are consecutive positions in the word, and if $X_q(x) \wedge Q_a(x)$, then it must be that $X_t(y)$ such that $\delta(q, a) = t$

Regular Languages to MSO

- ▶ If a word wa is accepted, then
 - ▶ The last position x of the word satisfies $Q_a(x)$
 - ▶ For some state q , we have $X_q(x)$ and there is a transition $\delta(q, a) = q_f \in F$

Position x	:	0	1	2	3	
		a	a	b	a	
		q_0	q_1	q_0	q_2	q_2

- ▶ $Q_a(3)$ and $3 \in X_{q_2}$. $\delta(q_2, a) = q_2 \notin F$
- ▶ If x, y are consecutive positions in the word, and if $X_q(x) \wedge Q_a(x)$, then it must be that $X_t(y)$ such that $\delta(q, a) = t$
- ▶ $X_{q_0}(0)$, $X_{q_1}(1)$ and $Q_a(0)$. $\delta(q_0, a) = q_1$.
- ▶ $X_{q_1}(1)$, $X_{q_0}(2)$ and $Q_a(1)$. $\delta(q_1, a) = q_0$.

Regular Languages to MSO

Given a DFA $A = (Q, \Sigma, \delta, q_0, F)$, a word w is accepted iff it satisfies

$$\exists X_0 \exists X_1 \dots \exists X_n \{ [\forall x (X_0(x) \vee \dots \vee X_n(x)) \wedge \forall x \bigwedge_{i \neq j} \neg (X_i(x) \wedge X_j(x))] \wedge$$

Regular Languages to MSO

Given a DFA $A = (Q, \Sigma, \delta, q_0, F)$, a word w is accepted iff it satisfies

$$\begin{aligned} \exists X_0 \exists X_1 \dots \exists X_n \{ & [\forall x (X_0(x) \vee \dots \vee X_n(x)) \wedge \forall x \bigwedge_{i \neq j} \neg (X_i(x) \wedge X_j(x))] \wedge \\ & [\exists x (\text{first}(x) \wedge X_0(x))] \wedge \end{aligned}$$

Regular Languages to MSO

Given a DFA $A = (Q, \Sigma, \delta, q_0, F)$, a word w is accepted iff it satisfies

$$\exists X_0 \exists X_1 \dots \exists X_n \{ [\forall x (X_0(x) \vee \dots \vee X_n(x)) \wedge \forall x \bigwedge_{i \neq j} \neg (X_i(x) \wedge X_j(x))] \wedge$$

$$[\exists x (\text{first}(x) \wedge X_0(x))] \wedge$$

$$\forall x \forall y [S(x, y) \rightarrow \bigvee_{\delta(i, a)=j} [X_i(x) \wedge Q_a(x) \wedge X_j(y)]] \wedge$$

Regular Languages to MSO

Given a DFA $A = (Q, \Sigma, \delta, q_0, F)$, a word w is accepted iff it satisfies

$$\exists X_0 \exists X_1 \dots \exists X_n \{ [\forall x (X_0(x) \vee \dots \vee X_n(x)) \wedge \forall x \bigwedge_{i \neq j} \neg (X_i(x) \wedge X_j(x))] \wedge$$


$$[\exists x (\text{first}(x) \wedge X_0(x))] \wedge$$

$$\forall x \forall y [S(x, y) \rightarrow \bigvee_{\delta(i, a)=j} [X_i(x) \wedge Q_a(x) \wedge X_j(y)]] \wedge$$

$$\exists x [\text{last}(x) \wedge \bigvee_{\delta(i, a)=j \in F} [X_i(x) \wedge Q_a(x)]] \}$$


► $w \in L(A)$ iff $w \models \varphi$

Example : Regular to MSO




$$\exists X_0 \exists X_1 \exists X_2 \{ [\forall x (X_0(x) \vee X_1(x) \vee X_2(x)) \wedge \forall x [\neg (X_0(x) \wedge X_1(x)) \wedge \neg (X_0(x) \wedge X_2(x)) \wedge \neg (X_1(x) \wedge X_2(x))] \wedge$$

Example : Regular to MSO



$$\exists X_0 \exists X_1 \exists X_2 \{ [\forall x (X_0(x) \vee X_1(x) \vee X_2(x)) \wedge \forall x [\neg (X_0(x) \wedge X_1(x)) \wedge \neg (X_0(x) \wedge X_2(x)) \wedge \neg (X_1(x) \wedge X_2(x))] \wedge [\exists x (\text{first}(x) \wedge X_0(x))] \wedge$$


Example : Regular to MSO



$$\exists X_0 \exists X_1 \exists X_2 \{ [\forall x (X_0(x) \vee X_1(x) \vee X_2(x)) \wedge \forall x [\neg (X_0(x) \wedge X_1(x)) \wedge \neg (X_0(x) \wedge X_2(x)) \wedge \neg (X_1(x) \wedge X_2(x))] \wedge [\exists x (\text{first}(x) \wedge X_0(x))] \wedge$$

$$\forall x \forall y [S(x, y) \rightarrow [(X_0(x) \wedge Q_a(x) \wedge X_1(y)) \vee (X_0(x) \wedge Q_b(x) \wedge X_2(y)) \vee (X_1(x) \wedge Q_a(x) \wedge X_0(y)) \vee (X_1(x) \wedge Q_b(x) \wedge X_2(y)) \vee (X_2(x) \wedge Q_a(x) \wedge X_2(y)) \vee (X_2(x) \wedge Q_b(x) \wedge X_2(y))]]$$

Example : Regular to MSO



$$\exists X_0 \exists X_1 \exists X_2 \{ [\forall x (X_0(x) \vee X_1(x) \vee X_2(x)) \wedge \forall x [\neg (X_0(x) \wedge X_1(x)) \wedge \neg (X_0(x) \wedge X_2(x)) \wedge \neg (X_1(x) \wedge X_2(x))] \wedge [\exists x (\text{first}(x) \wedge X_0(x))] \wedge$$

$$\forall x \forall y [S(x, y) \rightarrow [(X_0(x) \wedge Q_a(x) \wedge X_1(y)) \vee (X_0(x) \wedge Q_b(x) \wedge X_2(y)) \vee (X_1(x) \wedge Q_a(x) \wedge X_0(y)) \vee (X_1(x) \wedge Q_b(x) \wedge X_2(y)) \vee (X_2(x) \wedge Q_a(x) \wedge X_2(y)) \vee (X_2(x) \wedge Q_b(x) \wedge X_2(y))]]$$

$$\wedge \exists x [\text{last}(x) \wedge (X_1(x) \wedge Q_a(x))]] \}$$

MSO to Regular Languages

- ▶ Every MSO sentence φ over words can be converted into a DFA A_φ such that $L(\varphi) = L(A_\varphi)$.
- ▶ Start with atomic formulae, construct DFA for each of them.
- ▶ Conjunctions, Disjunctions, Negation easily handled via union, intersection and complementation of respective DFA
- ▶ Handling quantifiers?

Atomic Formulae to DFA

- ▶ $Q_a(x)$: All words which have an a . Need to fix a position for x , where a holds.

Atomic Formulae to DFA

- ▶ $Q_a(x)$: All words which have an a . Need to fix a position for x , where a holds.
- ▶ Think of a word $baab$ which satisfies $Q_a(x)$ as $\begin{array}{c} baab \\ 0010 \end{array}$ or $\begin{array}{c} baab \\ 0100 \end{array}$

Atomic Formulae to DFA


- ▶ $Q_a(x)$: All words which have an a . Need to fix a position for x , where a holds.
- ▶ Think of a word $baab$ which satisfies $Q_a(x)$ as $\begin{array}{c} baab \\ 0010 \end{array}$ or $\begin{array}{c} baab \\ 0100 \end{array}$
- ▶ The first row is over Σ , and the second row captures a possible assignment to x

Atomic Formulae to DFA

- ▶ $Q_a(x)$: All words which have an a . Need to fix a position for x , where a holds.
- ▶ Think of a word $baab$ which satisfies $Q_a(x)$ as $\begin{array}{cc} baab & baab \\ 0010 & 0100 \end{array}$ or
- ▶ The first row is over Σ , and the second row captures a possible assignment to x
- ▶ Think of an extended alphabet $\Sigma' = \Sigma \times \{0, 1\}$, and construct an automaton over Σ' .

Atomic Formulae to DFA

- ▶ $Q_a(x)$: All words which have an a . Need to fix a position for x , where a holds.
- ▶ Think of a word $baab$ which satisfies $Q_a(x)$ as $\begin{matrix} baab \\ 0010 \end{matrix}$ or $\begin{matrix} baab \\ 0100 \end{matrix}$
- ▶ The first row is over Σ , and the second row captures a possible assignment to x
- ▶ Think of an extended alphabet $\Sigma' = \Sigma \times \{0, 1\}$, and construct an automaton over Σ' .
- ▶ Deterministic, not complete.



Simple Formulae to DFA

- ▶ $Q_a(x) \wedge X(x)$ means that the position x is in the set X , and letter a is true when $x = 1$.

Simple Formulae to DFA

- ▶ $Q_a(x) \wedge X(x)$ means that the position x is in the set X , and letter a is true when $x = 1$.
- ▶ Think of a word *baab* which satisfies $Q_a(x) \wedge X(x)$ as

baab *baab*

0010 or 0100

DD1D *D1DD*


where D stands for *dont care*. X can have value 0 or 1 at D .

Simple Formulae to DFA

- ▶ $Q_a(x) \wedge X(x)$ means that the position x is in the set X , and letter a is true when $x = 1$.
- ▶ Think of a word *baab* which satisfies $Q_a(x) \wedge X(x)$ as
 baab *baab*
 0010 or 0100
 DD1D *D1DD*
 where D stands for *dont care*. X can have value 0 or 1 at D .
- ▶ However, the position where $x = 1$ must belong to X .


Simple Formulae to DFA

- ▶ The first row is over Σ , and the second row captures a possible assignment to x , and the third row captures a possible assignment to X .
- ▶ Think of an extended alphabet $\Sigma' = \Sigma \times \{0, 1\} \times \{0, 1\}$, and construct an automaton over Σ' .
- ▶ $Q_a(x) \wedge X(x)$: deterministic, not complete




Simple Formulae to DFA

► $X(x)$



Simple Formulae to DFA

- ▶ $X(x) \wedge \neg Y(x)$
- ▶ $\Sigma' = \Sigma \times \{0, 1\} \times \{0, 1\} \times \{0, 1\}$



Formulae to DFA


- ▶ Given $\varphi(x_1, \dots, x_n, X_1, \dots, X_m)$, an MSO formula over Σ , consider the extended alphabet

$$\Sigma' = \Sigma \times \{0, 1\}^{m+n}$$

- ▶ Assign values to x_i, X_j at every position as seen in the cases of atomic formulae
- ▶ Keep in mind that every x_i can be assigned 1 at a unique position

Handling Quantifiers

- $\exists X \exists Y \forall x [X(x) \rightarrow Y(x)]$



Points to Remember

- ▶ Given $\varphi(x_1, \dots, x_n, X_1, \dots, X_m)$, construct automaton for atomic MSO formulae over the extended alphabet $\Sigma \times \{0, 1\}^{m+n}$
- ▶ Intersect with the regular language where every x_i is assigned 1 exactly at one position
- ▶ Given a sentence $Q_{x_1} \dots Q_{x_n} Q_{X_1} \dots Q_{X_m} \varphi$, first construct the automaton for the formula $\varphi(x_1, \dots, x_n, X_1, \dots, X_m)$
- ▶ Replace \forall in terms of \exists

Points to Remember

- ▶ Given the automaton for $\varphi(x_1, \dots, x_n, X_1, \dots, X_n)$, the automaton for $\exists X_i \varphi(x_1, \dots, x_n, X_1, \dots, X_n)$ is obtained by **projecting out** the row of X_i
- ▶ This may result in an NFA
- ▶ Determinize it and complement it to get a DFA for $\neg \exists X_i \varphi(x_1, \dots, x_n, X_1, \dots, X_n)$
- ▶ Intersect with the regular language where each of $x_1, \dots, x_{i-1}, x_{i+1}, \dots, x_n$ are assigned 1 exactly at one position

The Automaton-Logic Connection

Given any MSO sentence φ , one can construct a DFA A_φ such that $L(\varphi) = L(A_\varphi)$. If a language L is regular, one can construct an MSO sentence φ such that $L = L(\varphi)$.