

Отчёт по работе с GIT.

Шаг 1. Создание локального репозитория

```
PS C:\Users\Admin\Documents\git_practice> git init
Initialized empty Git repository in C:/Users/Admin/Documents/git_practice/.git/
```

Шаг 2. Создание файлов и первый коммит

```
PS C:\Users\Admin\Documents\git_practice> git status
>> git add .
On branch master

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        file1.txt
        file2.txt

nothing added to commit but untracked files present (use "git add" to track)
PS C:\Users\Admin\Documents\git_practice> git commit -m "First commit: initial files"
[master (root-commit) 7dd4eff] First commit: initial files
2 files changed, 2 insertions(+)
create mode 100644 file1.txt
create mode 100644 file2.txt
```

Шаг 3. Добавление файла .gitignore

```
❖ .gitignore
1 *.log
2 temp/
```

```
PS C:\Users\Admin\Documents\git_practice> git status
On branch master
Untracked files:
  (use "git add <file>..." to include in what will be committed)
        .gitignore

nothing added to commit but untracked files present (use "git add" to track)
PS C:\Users\Admin\Documents\git_practice> █
```

```
PS C:\Users\Admin\Documents\git_practice> git status
On branch master
nothing to commit, working tree clean
PS C:\Users\Admin\Documents\git_practice> █
```

Шаг 4. Изменение файла и второй коммит

```

PS C:\Users\Admin\Documents\git_practice> git diff
>> git add file1.txt
>> git commit -m "Update file1.txt"
diff --git a/file1.txt b/file1.txt
index 0a97240..1852c1f 100644
--- a/file1.txt
+++ b/file1.txt
@@ -1,2 @@
-beleberda
\ No newline at end of file
+beleberda
+гыыы 67 бегите я конченый
\ No newline at end of file
[master a906049] Update file1.txt
1 file changed, 2 insertions(+), 1 deletion(-)
PS C:\Users\Admin\Documents\git_practice>

```

Шаг 5. Создание новой ветки и изменение файла

```

PS C:\Users\Admin\Documents\git_practice> git checkout -b feature
Switched to a new branch 'feature'
PS C:\Users\Admin\Documents\git_practice> git add file2.txt
>> git commit -m "Change file2 in feature branch"
[feature e20c80a] Change file2 in feature branch
1 file changed, 2 insertions(+), 1 deletion(-)
PS C:\Users\Admin\Documents\git_practice>

```

Шаг 6. Возврат в основную ветку и Fast-Forward слияние

```

PS C:\Users\Admin\Documents\git_practice> git merge feature
Updating a906049..e20c80a
Fast-forward
 file2.txt | 3 ++-
1 file changed, 2 insertions(+), 1 deletion(-)
PS C:\Users\Admin\Documents\git_practice>

```

Шаг 7. Изменение в основной ветке

```

file1.txt
1  beleberda
2  гыыы 67 бегите я конченый
3  Изменение из ветки master

PS C:\Users\Admin\Documents\git_practice> git add file1.txt
>> git commit -m "Edit file1 in master"
[master d9cfaac] Edit file1 in master
1 file changed, 2 insertions(+), 1 deletion(-)
PS C:\Users\Admin\Documents\git_practice>

```

Шаг 8. Вызов и разрешение конфликта слияния

```
PS C:\Users\Admin\Documents\git_practice> git checkout master
>> git merge feature
Switched to branch 'master'
Auto-merging file1.txt
CONFLICT (content): Merge conflict in file1.txt
Automatic merge failed; fix conflicts and then commit the result.
```

```
file1.txt
1  beleberda
2  гыыы 67 бегите я кончный
   Accept Current Change | Accept Incoming Change | Accept Both Changes | Compare C
3  <<<<<<< HEAD (Current Change)
4  Изменение из ветки master
5  =====
6  Изменение их ветки feature
7  >>>>>> feature (Incoming Change)
8
```

```
file1.txt
1  beleberda
2  ∨ гыыы 67 бегите я кончный
3  | HEAD
4  | Изменение из ветки master
5
6  ∨ Изменение их ветки feature
7  | feature
8
```

```
PS C:\Users\Admin\Documents\git_practice> git add file1.txt
>> git commit -m "Resolve merge conflict"
[master b6bed5c] Resolve merge conflict
PS C:\Users\Admin\Documents\git_practice>
```

Шаг 9. Просмотр истории коммитов с графом

```
PS C:\Users\Admin\Documents\git_practice> git log --oneline --graph --a
*   b6bed5c (HEAD -> master) Resolve merge conflict
| \
| * 60a754c (feature) Edit file1 in feature
* | d9cfaac Edit file1 in master
|/
* e20c80a Change file2 in feature branch
* a906049 Update file1.txt
* aa9e07b Add .gitignore
* 7dd4eff First commit: initial files
PS C:\Users\Admin\Documents\git_practice>
```

Шаг 10: Создание удалённого репозитория на GitHub и push

```
Please make sure you have the correct access rights
and the repository exists.
PS C:\Users\Admin\Documents\git_practice> git remote add origin https://github.co
m/Hyperoid8/git-practice
PS C:\Users\Admin\Documents\git_practice> git branch -M main
>> git push -u origin main
info: please complete authentication in your browser...
Enumerating objects: 22, done.
Counting objects: 100% (22/22), done.
Delta compression using up to 16 threads
Compressing objects: 100% (19/19), done.
Writing objects: 100% (22/22), 2.27 KiB | 774.00 KiB/s, done.
Total 22 (delta 5), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/Hyperoid8/git-practice
 * [new branch]      main -> main
branch 'main' set up to track 'origin/main'.
PS C:\Users\Admin\Documents\git_practice> 
```

 Hyperoid8 / **git-practice** 

       

[Code](#) [Issues](#) [Pull requests](#) [Agents](#) [Actions](#) [Projects](#) [Wiki](#) [More](#) 

 **git-practice** Public  Pin  Watch 0  Fork 0  Star 0 



Start coding with Codespaces

Add a README file and start coding in a secure, configurable, and dedicated development environment.

[Create a codespace](#)



Add collaborators to this repository

Search for people using their GitHub username or email address.

[Invite collaborators](#)

Quick setup — if you've done this kind of thing before

 [Set up in GitHub Desktop](#) or [HTTPS](#) [SSH](#) <https://github.com/Hyperoid8/git-practice.git> 

Get started by [creating a new file](#) or [uploading an existing file](#). We recommend every repository include a [README](#), [LICENSE](#), and [.gitignore](#).

...or create a new repository on the command line

```
echo "# git-practice" >> README.md
git init
git add README.md
git commit -m "first commit"
git branch -M main
git remote add origin https://github.com/Hyperoid8/git-practice.git
git push -u origin main
```



...or push an existing repository from the command line

```
git remote add origin https://github.com/Hyperoid8/git-practice.git
git branch -M main
git push -u origin main
```



Шаг 11. Создание README.md на GitHub

 Hyperoid8 Add README with project title in Russian	4f1710b · now	
 .gitignore	Add .gitignore	44 minutes ago
 README.md	Add README with project title in R...	now
 file1.txt	Resolve merge conflict	19 minutes ago
 file2.txt	Change file2 in feature branch	40 minutes ago

Шаг 12: Скачивание изменений через git pull

```
PS C:\Users\Admin\Documents\git_practice> git pull
remote: Enumerating objects: 4, done.
remote: Counting objects: 100% (4/4), done.
remote: Compressing objects: 100% (2/2), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (3/3), 1.02 KiB | 130.00 KiB/s, done.
From https://github.com/Hyperoid8/git-practice
   b6bed5c..4f1710b  main      -> origin/main
Updating b6bed5c..4f1710b
Fast-forward
 README.md | 1 +
 1 file changed, 1 insertion(+)
 create mode 100644 README.md
PS C:\Users\Admin\Documents\git_practice>
```